

+
TL
589
U58

RESTRICTED

+
TL
589
U58

ARMY

INDEX OF
**AERONAUTICAL
EQUIPMENT**

NAVY

NOTICE—This document contains information affecting the national defense of the United States within the meaning of the Espionage Act, 50 U. S. C., 31 and 32, as amended. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

ARMAMENT



INDEX OF ARMY AERONAUTICAL EQUIPMENT

**WITH NAVY AND BRITISH
EQUIVALENTS**



Volume 5

ARMAMENT



**Compiled and published
by authority of

The Commanding General
Army Air Forces Materiel Command
Wright Field, Dayton, Ohio**

***Accepted by*

The Air Council of
The United Kingdom

Air Publication 2599E**

Book Number:

177124

815055

A COMPLETE

INDEX OF ARMY AERONAUTICAL EQUIPMENT

WITH NAVY AND BRITISH EQUIVALENTS

CONSISTS OF:

Volume 1 Turbosuperchargers, Pumps and Accessories	AERDEXONE
Volume 2 Landing Gear	AERDEXTWO
Volume 3 Oxygen and Miscellaneous	AERDEXTHREE
Volume 4 Electrical Equipment	AERDEXFOUR
Volume 5 Armament	AERDEXFIVE
Volume 6 Instruments	AERDEXSIX

For cable or teletype transmission use the code words AERDEXONE or AERDEXTWO, etc.

Compiled and Published

By

ARMY AIR FORCES
MATERIEL COMMAND
WRIGHT FIELD, DAYTON, OHIO

All Technical Reference to the Above Publications
Should Be Addressed as Indicated Below

COMMANDING GENERAL
ARMY AIR FORCES MATERIEL COMMAND
WRIGHT FIELD, DAYTON, OHIO

DISTRIBUTION

ARMY AIR FORCES
MATERIEL COMMAND
AERONAUTICAL EQUIPMENT
BRANCH
WRIGHT FIELD, DAYTON, OHIO

Distributed in Original Form to All Materiel Command Activities and Block Distribution to Bureau of Aeronautics.

ARMY AIR FORCES
AIR SERVICE COMMAND
HEADQUARTERS
MAINTENANCE DATA SECTION
MAINTENANCE DIVISION
PATTERSON FIELD, OHIO

Reproduced as Technical Order 00-25-10 and Distributed to United Nations and All AAF Activities Except Materiel Command.

BUREAU OF AERONAUTICS
PUBLICATIONS SECTION
WASHINGTON, D. C.
Distribution to All Navy Activities.



GUIDE

to

Volume Five

Armament Equipment

	Page Numbers
Alphabetical Index	V to XXIV
Numerical Index	XXV to LXXXVIII
Gunnery	1-227
Gun Mount Adapters and Accessories	3-28
Containers	29-37
Gun Chargers and Feed Units	38-46
Mounts	53-73
Gun Sights	74-95
Gun Synchronizers	96-100
Gun Solenoids	101-120
Switches	123-126
Machine Gun Turrets and Fire Control Systems	130-227
Bombing	229-292
Bomb Arming and Bomb Release Interval	
Controls	235-243
Torpedo Directors	247-249
Release Handles	250-254
Bomb Hoists	259-263
Automatic Pilot	268-271
Bomb Racks and Bomb Releases	272-280
Bomb Shackles and Bomb Hoist Slings	281-291
Ordnance	293-330
Automatic Guns and Adapters	296-303
Aircraft Machine Guns and Accessories	304-319
Tool Rolls	320-323
Pyrotechnic Projectors	324-330



ALPHABETICAL INDEX

Name	Type, Drawing or Designation	Page
A. F. C. E. cover.....	PK1A1	246
Adapter—box.....	A	231
Adapter—box end.....	L-2	27
Adapter—gun end.....	L-1	26
Adapter—gun mount.....		4
Adapter—gun mount.....	C-12	6
Adapter—gun mount.....	C-16	7
Adapter—gun mount.....	C-17	8
Adapter—gun mount.....	C-18	9
Adapter—gun mount.....	C-19	10
Adapter—gun mount.....	E-5	12
Adapter—gun mount.....	E-5A	11
Adapter—gun mount.....	E-8	14
Adapter—gun mount.....	E-10	15
Adapter—gun mount.....	E-11	16
Adapter—gun mount.....	E-12	18
Adapter—gun mount, BAM—30, M2, flexible, single (Navy).....	C-12	6
“ “ “ “ —30, M2, flexible, single (Navy).....	C-16	7
“ “ “ “ —30, M2, flexible, twin (Navy).....		4
“ “ “ “ —50, M2, flexible, single (Navy).....	E-5	12
“ “ “ “ —50, M2, flexible, single (Navy).....	E-11	16
“ “ “ “ —50, M2, turret type (Navy).....	E-5A	11
“ “ “ “ —50, M2, turret type (Navy).....	E-10	15
“ “ “ “ trigger backplate.....	E-11	16
“ —machine gun (British).....		4
“ “ “ “	C-12	6
“ “ “ “	C-16	7
“ “ “ “	C-17	8
“ “ “ “	C-18	9
“ “ “ “	C-19	10
“ “ “ “	E-5	12
“ “ “ “	E-5A	11
“ “ “ “	E-8	14
“ “ “ “	E-10	15
“ “ “ “	E-11	16
“ “ “ “	E-12	18
“ —30 caliber.....	C-16	7
“ —50 caliber machine gun—spade grip.....	E-5	12
“ —50 caliber M2 machine gun.....	E-5	12
“ assembly—gun mount.....	E-9	Not catalogued
“ “ —gun mount—50 caliber with yoke.....	E-5	Not catalogued
“ “ —20-mm.....	AN-M6	302
“ “ —20-mm. recoil absorption.....	AN-M1	300
“ “ —20-mm. “ “	AN-M6	302
Adapter assembly, 20-mm., AN-M1.....		300
Adapter assembly, 20-mm., AN-M6.....		302
Adapter, gun mount, AG—20-mm. (M-1 and M-2).....	AN-M1	300
“ “ “ “ —20-mm. (M-1 and M-2).....	AN-M6	302
“ ring.....	43B15328	256
“ yoke.....	41D6865	129
Adapters—gun mounts and gun mount.....		3
Adjustable bomb hoist.....	AN-Mark 7 Mod. 1	259
Aircraft automatic gun, 20-mm.....	M1 and AN-M2	297
“ “ 20-mm. cannon.....	M1 and AN-M2	297
Aircraft machine guns.....		304
Aircraft navigation box B-285 flame floats.....	Mk 2	Not catalogued
“ power rheostat.....	D-1	123
Airplane automatic 37-mm. gun.....	M4	296
Airplane gun mount, 75-mm.....	M6	318
Altitude and air speed hand set.....	T-8252908	173, 188
Aluminum sea marker.....	Mk 5	Not catalogued
Ammunition box.....	L-4	21
Ammunition box.....	L-7	22
Ammunition box.....	O-1	23



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Ammunition box—15-round, 37-mm.	M2	312
" " —30 caliber.	L-4	21
" " " "	L-7	22
Ammunition box holder	A-1	47
Ammunition box holder—30 caliber	A-1	47
Ammunition box mount	A-3	53
Ammunition box mount	C-2	54, 55
" " " "	C-3	56, 57
" " " assembly—L.H.	C-4	Not catalogued
" " " " —R.H.	C-5	Not catalogued
" " " " " —	C-6	Not catalogued
" " box, 15-round, 37-mm.	M2	312
" " feeder, 20-mm.	AN-M1	316, 317
Amplidyne	5AM31NJ9	189, 211, 220
Amplidyne	5AM31NJ18	50
Amplidyne local control motor—generator	5AM31NJ18	50
Amplidyne motor—generator		173, 206, 215
Amplidyne remote control motor—generator	5AM31NJ9	189, 211, 220
Amplidyne remote control motor—generator	5AM61NJ1C	190
Amplifier		269
Amplifier—servo	2CV1C1	174
Anti-vibration bombsight mount	B-7	263
Aperture disc	No. 2, Mk 1	329
Arm lock—directional		270
Armorer's tool kit	A-28	320
" " " "	A-38	322
Armorer's tool roll complete w/contents	A-28	320
Armorer's tool roll complete w/contents	A-38	322
Armorer's tool .30 and .50 caliber roll		Not catalogued
Articulated link belt magazine, 15-round	M2	312
Automatic and control signal discharger	Mk 2	Not catalogued
Automatic compensating gun sight	K-3	92
Automatic compensating gun sight	K-4	93
Automatic compensating sight	K-8	94
" " " assembly	K-10	Not catalogued
" " " " "	K-11	Not catalogued
" " flight control equipment	M-5	Not catalogued
Automatic gun, 37-mm., M4	M4	296
Automatic pilot	B-1	Not catalogued
" " "	C-1	268
" " 20-mm. cannon	M1 and AN-M2	297
Autopilot control panel	A-6A	232
Autopilot control panel		269
Auxiliary arming mechanism	AN-A-1	236
" " " "	AN-A-2	237
" " " "	B-2	238
" " ring and bead sight assembly		Not catalogued
" " switch box	A-1	277
Axisimuth turret drive motor	5BA50LJ1	51
Ball-grip bomb and flare release handle	A-3A	251
" " " " " "	A-3B	252
Ball and socket gun mount	K-2	63
Ball and socket gun mount	K-2A	64
Ball and socket gun mount	K-3	65
Ball and socket gun mount	K-4	66
Ball and socket gun mount	K-5	67
" " " " " assembly	K-1	62
" " " " " mount	K-1	62
" " " " " "	K-2	63
" " " " " "	K-2A	64
" " " " " "	K-3	65
" " " " " "	K-4	66
" " " " " "	K-5	67
Band—bomb adapter	80-1	Not catalogued
" " " " " "	80-2	Not catalogued



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Band—bomb adapter	80-3	Not catalogued
" " "	80-4	Not catalogued
" " "	80-5	Not catalogued
" " "	80-6	Not catalogued
" " "	80-7	Not catalogued
Barrel—gun charging control turnbuckle		19
Barrel—gun charging turnbuckle		19
Bead sight	A-4	76
" "	A-5	77
" "	A-11	78
Bell turret	M-6	70
Belly turret—ball type	A-2	156
Belt feed mechanism—20-mm.	AN-M1	316, 317
Bendix chin turret	A-16	168
" lower gun turret	A-5	160
" " "	A-10	162
" nose "	A-16	168
" upper "	A-4	148
" " "	A-9	150
" " "	A-9A	152
Bolt and bracket—gun trunnion	A-3	20
Bolt and bracket assembly—gun trunnion	A-3	20
Bolt stud	A13424	319
Bolt, trunnion, BAM—.30 and .50 caliber, M2, (Navy)	A-3	20
Bomb adapter band	80-1	Not catalogued
" " "	80-2	Not catalogued
" " "	80-3	Not catalogued
" " "	80-4	Not catalogued
" " "	80-5	Not catalogued
" " "	80-6	Not catalogued
" " "	80-7	Not catalogued
" adjustable hoist	AN Mk 7 Mod. 1	258
Bomb and flare release handle	A-3A	251
Bomb and flare release handle	A-3B	252
Bomb and flare release handle assembly	A-3A	251
" " " " " "	A-3B	252
Bomb arming control	AN-A-1	236
Bomb arming control	AN-A-2	237
Bomb arming control	B-2	238
Bomb arming control assembly	B-1	Not catalogued
" " " box	AN-A-1	236
" " " "	AN-A-2	237
" " " "	B-2	238
Bomb arming control mount	A-1	262
Bomb arming control mount assembly	A-1	262
Bomb arming controls		235
Bomb box adapter	A	231
" carrier receptacle		291
" fusing control	AN-A-1	236
" " "	AN-A-2	237
" " "	B-2	238
" " " box slide	A-1	262
Bomb hoist	C-3	260
Bomb hoist assembly	C-3	260
Bomb hoist sling	A-1	289
Bomb hoist sling	A-2	290
Bomb hoist sling assembly	A-1	289
" " " "	A-2	290
" portable hoist	AN-Mk 7, Mod. 1	258
Bomb rack	AN-Mk. 51, Mod. 7	272
Bomb rack	D-3	285
" "	D-5	286
Bomb rack	Mk. 43, Mod. 1	274
Bomb rack	N-5	275
Bomb rack	Q-2	276
Bomb rack assembly	AN-Mk. 51 Mod. 7	272



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Bomb rack assembly.....	Mk. 43 Mod. 1.....	274
" " " ".....	N-5.....	275
" " " ".....	Q-2.....	276
" " handle.....	L-21A.....	253
Bomb rack left hand release.....	A-2.....	278
Bomb rack release.....	A-2.....	278, 279
" " " ".....	A-3.....	280
" " " " —L.H.	A-4.....	Not catalogued
" " " " —R.H.	A-4.....	Not catalogued
" " " " assembly.....	A-2.....	278, 279
" " " " " ".....	A-3.....	280
" " " " " " —L.H.—(12-volt)	A-3.....	Not catalogued
" " " " handle.....	Mk. 4, Mod. 2.....	254
Bomb rack right hand release.....	A-2.....	279
Bomb rack right hand release.....	A-3.....	280
Bomb release control.....	AN-B-3.....	242
" " " ".....	B-2.....	240
" " " ".....	B-2A.....	241
Bomb release handle.....	A-3.....	250
Bomb release handle.....	L-21A.....	253
Bomb release handle.....	Mk. 4, Mod. 2.....	254
Bomb release handle assembly.....	A-3.....	250
" " " " " ".....	L-21A.....	253
" " " " " ".....	Mk. 4 Mod. 2.....	254
Bomb release interval control.....		239
Bomb release interval control.....	AN-B-3.....	242
Bomb release interval control.....	B-2.....	240
Bomb release interval control.....	B-2A.....	241
Bomb release interval control assembly.....	A-1.....	Not catalogued
Bomb release receptacle.....	A-1.....	277
Bomb release receptacle assembly.....	A-1.....	277
Bomb shackle.....		281
Bomb shackle.....	AN-B-9.....	283
Bomb shackle.....	B-7.....	282
Bomb shackle.....	H-10.....	284
Bomb shackle.....	D-3.....	285
Bomb shackle.....	D-5.....	286
Bomb shackle.....	D-6.....	287
Bomb shackle.....	D-7.....	288
Bomb shackle assembly.....	AN-B-9.....	283
" " " ".....	B-7.....	282
" " " ".....	B-10.....	284
" " " ".....	D-3.....	285
" " " ".....	D-5.....	286
" " " ".....	D-6.....	287
" " " ".....	D-7.....	288
" " " ".....	D-8.....	Not catalogued
" " release.....	A-2.....	278, 279
" " " ".....	A-3.....	280
" " " " mechanism.....	A-2.....	278, 279
" " " " " ".....	A-3.....	280
" " 1000 pounds.....	AN-B-9.....	283
" " 1100 pounds.....	B-7.....	282
" " 1600 pounds.....	B-10.....	284
" " 2000 pounds.....	D-3.....	285
" " " ".....	D-5.....	286
" " " ".....	D-6.....	287
" " 4000 pounds.....	D-7.....	288
" sling.....	A-2.....	290
" socket.....		291
Bomb socket—5 way.....		291
Bombsight blanket.....	A-1.....	244
" " " ".....	A-2.....	245
" " cover.....	A-1.....	244
" " " ".....	A-2.....	245
Bombsight disc speed tachometer.....	4050 & 4050A.....	292

ALPHABETICAL INDEX
ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Bombight mount	B-7	263
Bombight mount assembly		Not catalogued
" " " "	B-7	263
" pilot director indicator		Not catalogued
" " " "	Mk 15 Mod. 3	266
" " " "	Mk 15 Mod. 6	264
" roto speed tachometer		Not catalogued
" shock mount	B-7	263
Box—adapter and terminal	A	231
Box—ammunition	L-4	22
Box—ammunition	L-7	22
Box—ammunition	O-1	23
Box—ammunition .50 caliber	O-1	23
Box—control	T-8007519	208, 173
Box—control	T-8252925	217
Box—junction	T-8007523	209, 173
Box—junction	T-8252853	218
Box—left blister auxiliary control	P-8242380	175, 173
Box—nose system control	W-8258868	176, 173
Box—right blister auxiliary control	P-8242380	173, 177
Box—side blister selector switch	T-8252890	173, 179
Box—side blister system control	W-8258874	173, 178
Box—tail system control	W-8258881	173, 180
Box—upper blister system control	W-8258865	173, 181
Box adapter	A	231
Box assembly—machine gun electric synchronizer control	A-3	Not catalogued
Box end adapter	L-2	27
Box feedway adapter	L-2	27
Bracket—gun trunnion	A-1	Not catalogued
Briggs retractable ball turret	A-13	198
British bomb carrier	No. 1 Mk 3	233
" signal pistol	No. 4 Mk. 1	228
Browning aircraft fixed machine gun, caliber .30, M2		306
Browning aircraft flexible machine gun, caliber .30, M2		308
Browning aircraft, flexible with fixed back plate machine gun, caliber .30, M2		307
Browning machine gun, caliber .30, M2, aircraft, flexible with fixed back plate		307
Browning machine gun, caliber .30, M2, aircraft, fixed		306
Browning machine gun, caliber .50, M2, aircraft basic		309
Cable ends—impulse, BAM—.30 and .50 caliber (Navy)	E-3	98
Cannon—20-mm.	M1 and AN-M2	297
" —37-mm.	M4	296
" firing switch	B-5A	197
Capsules—fuse		Not catalogued
Carbon dioxide charger	T-8252878	182, 213, 226
Carrier—universal bomb	No. 1, Mk. 3	233
Carrier—universal bomb No. 1	Mk 2	Not catalogued
" " " " No. 2	Mk 2	Not catalogued
Cartridge—1 1/2 inch green		Not catalogued
" — " " and red		Not catalogued
" — " red		Not catalogued
" — " yellow		Not catalogued
" — " " and green		Not catalogued
" — " " red		Not catalogued
Case ejection container	A-4	29
" " "	A-5	30
Central station fire control system	A-26	215
Central station fire control system	B-29	173
Central station fire control system	P-61	206
Chain—type bomb hoist sling	A-2	290
Charger—CO ₂	T-8252878	182, 213, 226
Charger—gun	T-8252878	173, 182, 213, 226
Charger—gun, hydraulic BAM .50, M2 (Navy)	D-2	41
" — " " " " " "	D-3	39
Charger—20-mm. hydraulic gun	D-3	39
Charger—.30 caliber hydraulic gun	D-1	40
Charger—.50 caliber hydraulic gun	D-2	41



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Charger; manual, M2		38
Charging valve	A-1	128
Chin turret	A-16	168
Chute—flexible feed	A	28
Chute—flexible feed	B	25
Chutes—flexible feed		24
Chuting assembly—flexible ammunition, .60 caliber	A	28
“ “ “ “ “ “	B	25
Collector ring	T-8252833	191
Compensating gun sight assembly	K-9	Not catalogued
Compensating sight	K-8	94
Compressed air gun charger	T-8252878	182, 213, 226
Computer—double parallax	2CH1D1	173, 183
Computer—single parallax	Mod. No. 2 CH1C1 G. E.	173, 184
Computer voltage regulator		Not catalogued
Computing sight	K-3	92
“ “	K-4	93
“ “	K-8	94
Consolidated tail turret	A-6	164
Container—case ejection	A-4	29
Container—ejected case	A-4	29
Container—ejected case	A-5	30
Container—ejected link	A-3	31
Container—ejected link	A-4	32
Container—ejected link	A-5	33
Container—ejection case	A-5	30
“ —link ejection	A-3	31
“ “ “	A-4	32
Container—signal flare	A-1	34
Container—signal flare	A-5	35
Container—signal flare	A-6	36
Container—signal flare	A-7	37
Container assembly—signal flare	A-3	Not catalogued
“ “ “ “	A-4	Not catalogued
“ “ “ “	A-8	Not catalogued
“ , ejected case, BAM—30, M2 (Navy)	A-4	29
Continuous feed units		42
Control—bomb arming	AN-A-1	236
Control—bomb arming	AN-A-2	237
Control—bomb arming	B-2	238
Control—bomb release interval	AN-B-3	242
Control—bomb release interval	B-2	240
Control—bomb release interval	B-2A	241
Control—gun charger	M2	38
Control—pilot director indicator	A-1	243
Control—turn		271
“ —vertical gyro		269
Controls—bomb arming		235
Control assembly—bomb arming	B-1	Not catalogued
“ “ — “ release interval	A-1	Not catalogued
“ box	A-6A	232
Control box	T-8007519	208, 206
Control box	T-8252925	217
Control panel	A-6A	232
“ rheostat	D-1	123
Control stick gun switch	H-1A	124
Control stick gun switch	B-5	125
Control stick switch	B-1A	124
“ “ “	B-5	125
Cover	No. 2, Mk 1	329
Cover—electrically heated automatic pilot	PK 1A1	246
Cover—electrically heated bombsight	A-1	244
Cover—electrically heated bombsight	A-2	245
Crocker—Wheeler training turret	A-8	134
Cylinder—hydraulic gun charger—20-mm. cannon	D-3	39
“ — “ “ “ —30 caliber	D-1	40



Name	Type, Drawing or Designation	Page
Cylinder—hydraulic gun charger—.50 caliber	D-2	41
Deck turret	A-3	136
Deck turret—Bendix	A-4	148
“ “ —Bendix	A-9	150
“ “ —Bendix	A-9A	152
“ “ —Martin	A-3A	138-139
“ “ —Martin	A-3B	140
“ “ —Martin	A-3C	142
“ “ —Martin	A-11	144
“ “ —Martin	A-14	146
“ “ —Sperry	A-1	132-133
“ “ —Sperry	A-1A	134-135
Destructor, AN-M3		295
Detonator	AN-M3	295
Directional arm lock		270
“ panel		270
“ stabilizer		269
Director—torpedo	B-1	Not catalogued
Director—torpedo	B-2	249
Director—torpedo	Mk. 28, Mod. 2	248
Director assembly—torpedo	B-2	249
“ “ “	Mk 28 Mod. 2	248
Disc, aperture, No. 2, Mk 1	No. 2, Mk 1	329
Discharger—automatic and control signal	Mk 2	Not catalogued
Discharger, pyrotechnic, AN-M5		326
Disk speed indicator	4050 & 4050A	292
“ “ “ —B.S. Mk 15	4050 & 4050A	292
Double parallax computer	2CH1D1	183, 173
Double power hydraulic unit	AA-16801	169
Double power hydraulic unit	AA-16804	170
Double power unit	AA-16804	170
Drive—tail gun mount azimuth	W-8258810	173, 185
Drive—tail gun mount elevation	W-8258807	173, 186
Drive motor	5BA50GJ1	52
“ “	5BA50LJ2A	227
“ “	5BA50LJ1	51
Drum type magazine	M1	313
Dynamotor	5D21FJ2A	210, 206
Dynamotor	5D21NJ3	173, 187, 219, 215
Dynamotor—400 cycle		Not catalogued
Edgewater 20-mm. recoil adapter	M1	300
“ “ “	AN-M6	302
Ejected case container	A-4	29
Ejected case container	A-5	30
Ejected link container	A-3	31
Ejected link container	A-4	32
Ejected link container	A-5	33
Electric trigger AN-M1		120
Electric trigger control	AN-M1	120
“ “ “ (Navy)	C-4B	106, 108
“ “ “ (Navy)	C-4C	110, 112
“ “ “ (Navy)	E-6	102
“ “ “ (Navy)	G-4A	114
“ “ “ (Navy)	G-9	116
“ “ “ (Navy)	G-10	104
“ “ “ (Navy)	G-11	117
Electrical destructor	AN-M3	295
“ detonator	AN-M3	295
Electrically heated A.F.C.E. cover	PK 1A1	246
“ “ automatic pilot blanket	PK 1A1	246
“ “ “ cover	PK 1A1	246
“ “ bombsight blanket	A-1	244
“ “ bombsight blanket	A-2	245
Electrically heated bombsight cover	A-1	244
Electrically heated bombsight cover	A-2	245
Electrically heated cover	PK 1A1	246



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Elevation turret drive motor	5BA50GJ1	52
Emergency repair kit	A	Not catalogued
" " "	B	Not catalogued
Emerson nose turret	A-15	166
Endless belt magazine—30 round	M6	314
Endless belt magazine, 37-mm., M7		315
Endless belt magazine, 37-mm., M6		314
Ends—impulse unit	E-3	98
Equipment—automatic flight control	M-5	Not catalogued
External bomb rack	N-5	275
" " "	Q-2	276
Fairchild compensating sight	K-8	94
Feed—left hand upper continuous	CF-3L	43
Feed—lower continuous	CF-5	45
Feed—right hand upper continuous	CF-3R	44
Feed—.30 caliber lower continuous	CF-5	45
" mechanism—20-mm., L.H.	AN-M1	318
" " —20-mm., R.H.	AN-M1	317
Firing solenoid	C-4B	106, 108
" "	C-4C	110, 112
" "	E-4	101
" "	E-6	102
" "	E-8	103
" "	G-4A	114
" "	G-8	115
" "	G-9	116
" "	G-10	104
" "	G-11	117
" "	G-13	118
" "	G-15	119
" "	G-16	105
Fixed gun sight	Mark 8	83
Fixed gun sight	N-3A	84
Fixed gun sight	N-3B	86
Fixed gun sight assembly	N-2A	Not catalogued
" " " "	N-3	Not catalogued
" " " "	N-5	Not catalogued
" " " "	N-7	Not catalogued
Flame floats—aircraft navigation box B 285	Mark 2	Not catalogued
Flare—reconnaissance 4 1/2 inch	Mark 2	Not catalogued
" pistol	AN-M8	330
" pistol	M2	327
" rack assembly	A-4	Not catalogued
Flexible ammunition chute	A	28
" " "	B	25
Flexible feed chute	A	28
Flexible feed chutes	B	25
Flexible feed chutes		24
" " chute adapter	L-1	26
" " " "	L-2	27
Flexible feed chuting	A	28
" " chuting	B	25
" gun—machine .50 caliber—Browning	M2	Not catalogued
" " ammunition box mount—.50 caliber	C-2	54, 55
" " ammunition box mount—.50 caliber	C-3	56, 57
" " mount	G-1A	59
" " mount	G-5	60
" " mount	H-1	61
Flexible gun post sight	A-4	76
Flexible gun post sight	A-5	77
Flexible gun post sight	A-11	78
Flexible gun post sight assembly	A-6	Not catalogued
" " " "	A-8	Not catalogued
" " " "	A-10	Not catalogued
" " " "	A-12	Not catalogued
" " " .30 caliber sight assembly	A-9	Not catalogued



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Flexible gun ring sight.....	B-10.....	79
Flexible gun ring sight.....	B-11.....	80
Flexible gun ring sight.....	B-13.....	81
Flexible gun ring sight assembly.....	B-14.....	Not catalogued
" " " " " ".....	B-15.....	Not catalogued
" " " " " ".....	L-2.....	Not catalogued
" " sight.....	Mark 9.....	90
Flexible gun sight.....	N-6.....	87
Flexible gun sight.....	N-6A.....	88
Flexible gun sight.....	N-8.....	91
Flexible gun sight mount.....	C-4.....	58
Flexible machine gun, caliber .30, Browning M2 aircraft.....	M2.....	308
Fore lower gun turret.....	2CGD50LRC4.....	200
" upper turret.....	2CGD50URC3.....	204
Fuse capsules.....		Not catalogued
Fusing unit.....	AN-A-1.....	236
" ".....	AN-A-2.....	237
" ".....	B-2.....	238
Generator—gun synchronizer impulse.....	E-8.....	97
Green and red cartridge, 1 1/2 inch.....		Not catalogued
" cartridge, 1 1/2 inch.....		Not catalogued
Grenade mount.....	A-1.....	261
Grenade mount assembly.....	A-1.....	261
Group assembly—operating slide.....	D28200.....	310
Group assembly—retracting slide.....	D28300A.....	311
Gun—aircraft, 37-mm.....	M4.....	296
" —automatic, 20-mm.....	M1.....	298
" —automatic, 20-mm. cannon.....	M1 and AN-M2.....	297, 298
Gun—machine, caliber .50—Browning M-2 aircraft—basic.....	M2.....	309
Gun—machine, .30 caliber—Browning aircraft—fixed.....	M2.....	306
" —machine, .30 caliber—Browning aircraft—flexible.....	M2.....	308
" —machine, .30 caliber—Browning aircraft—flexible with fixed back plate.....	M2.....	307
" —machine, .50 caliber—Browning aircraft—basic.....	M2.....	309
" —machine, .50 caliber—Browning—flexible.....	M-2.....	Not catalogued
Gun, 20-mm., aircraft automatic.....		297
Gun, aircraft automatic, 20-mm., M1 and AN-M2 (all types).....		297, 298
Gun, automatic, 37-mm., M4.....		296
Gun, .30 caliber, BAM-30 (M-2) flexible.....	M2.....	308
" .50 caliber, BAM-50 (M2) basic.....	M2.....	309
Gun charger.....	T-8252878.....	173, 206, 182, 213, 226, 215
Gun charger control.....	M2.....	38
" charger valve.....	A-1.....	128
Gun charging handle.....	A-2.....	46
Gun charging turnbuckle barrel.....		19
Gun control stick switch.....	B-1A.....	124
" " " " " ".....	B-4.....	Not catalogued
" " " " " ".....	B-1A.....	124
" " " " " ".....	B-5.....	125
Gun end adapter.....	L-1.....	26
Gun feedway adapter.....	L-1.....	26
" firing solenoid.....	AN-M1.....	120
" " " " " ".....	C-4B.....	106, 108
" " " " " ".....	C-4C.....	110, 112
" " " " " ".....	E-4.....	101
" " " " " ".....	E-6.....	102
" " " " " ".....	E-8.....	103
" " " " " ".....	G-4A.....	114
" " " " " ".....	G-8.....	115
" " " " " ".....	G-9.....	116
" " " " " ".....	G-10.....	104
" " " " " ".....	G-11.....	117
" " " " " ".....	G-13.....	118
" " " " " ".....	G-15.....	119
" " " " " ".....	G-16.....	105
Gun heater—L.H.....	J-1.....	Not catalogued
" " —R.H.....		Not catalogued



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Gun, machine, caliber .30 Browning, M2 aircraft, fixed		306
Gun, machine, caliber .30 Browning, M2 aircraft, flexible		308
Gun, machine, caliber .30 Browning, M2 aircraft, flexible with fixed back plate		307
Gun, machine, caliber .50 Browning, M2 aircraft, basic		309
Gun, machine, .30 caliber Browning aircraft, flexible with fixed back plate		307
Gun mount	G-1A	59
Gun mount	G-5	60
Gun mount	H-1	61
Gun mount	K-1	62
" "	K-2	63
Gun mount	M-1	68
Gun mount	M-5	72
Gun mount	M-6	70
Gun mount	M-7	Not catalogued
" " —75-mm.		Not catalogued
Gun mount adapter		4
Gun mount adapter	C-12	6
Gun mount adapter	C-16	7
Gun mount adapter	C-17	8
Gun mount adapter	C-18	9
Gun mount adapter	C-19	10
Gun mount adapter	E-5	12
Gun mount adapter	E-5A	11
Gun mount adapter	E-8	14
Gun mount adapter	E-10	15
Gun mount adapter	E-11	16
Gun mount adapter	E-12	18
Gun mount adapter assembly	E-9	Not catalogued
" " " " —.50 caliber with yoke	E-5	Not catalogued
Gun mount adapter yoke	41D6865	129
Gun mount assembly	G-4	Not catalogued
" " post	A-4	73
" " 75-mm., airplane		318
Gun mounting post	A-4	73
Gun mounts and gun mount adapters		3
Gun post sight	A-4	76
" " "	A-5	77
" " "	A-11	78
" " " —.50 caliber	A-5	77
" " " —.50 caliber	A-11	78
" ring "	B-10	79
" " "	B-11	80
" " "	B-13	81
" " " —.30 caliber	B-10	79
" " " —.50 caliber	B-11	80
" " " —.50 caliber	B-13	81
Gun sight image reflector support	41D3024	122
Gun sight image reflector support	41D4892	121
Gun sight image reflector support	N-2	Not catalogued
" " reflector support	41D4892	121
Gun sight		74
Gun solenoid	AN-M1	120
Gun solenoid	E-4	101
Gun solenoid	E-6	102
Gun solenoid	E-8	103
Gun solenoid	G-4A	114
Gun solenoid	G-8	115
Gun solenoid	G-9	116
Gun solenoid	G-10	104
Gun solenoid	G-11	117
Gun solenoid	G-13	118
Gun solenoid	G-15	119
Gun solenoid	G-16	105
Gun solenoid (24-volt)	G-4	Not catalogued
" " assembly	E-2A	Not catalogued
" " " (12-volt)	E-5	Not catalogued



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Gun solenoid assembly (12-volt)	E-7	Not catalogued
" " " (12-volt)	E-9	Not catalogued
" " " (24-volt)	G-1	Not catalogued
" " " (24-volt)	G-2	Not catalogued
" " " (24-volt)	G-3	Not catalogued
" " " —R.H. (24-volt)	G-12	Not catalogued
" synchronizer control plunger assembly	A-1	Not catalogued
Gun synchronizer impulse generator	E-8	97
Gun trunnion bolt and bracket	A-3	20
Gun trunnion bracket	A-1	Not catalogued
Gun, 20-mm. aircraft automatic	AN-M2	297, 298
Hand grenade mount	A-1	261
Hand set—altitude and air speed	T-8252908	73, 188
Handheld tachometer	4050 & 4050A	292
Handle—bomb and flare release	A-3A	251
Handle—bomb and flare release	A-3B	252
Handle—bomb release	A-3	250
Handle—bomb release	L-21A	253
Handle—bomb release	MK 4 Mod. 2	254
Handle—gun charging	A-2	46
Head—pilot's bombsight	A-1	255
Head—pilot's bombsight	A-2	257
Hemmer—gun—L.H.	J-1	Not catalogued
" —gun—R.H.	J-1	Not catalogued
Heavy bomb hoist	A-1	289
Hispano-Suiza cannon	M1 & AN-M2	297
Hoist—bomb	C-3	260
Hoist—portable bomb	AN-MK 7 Mod. 1	258
Holder—ammunition box	A-1	47
Holder—pyrotechnic pistol	A-1	48
Holder—pyrotechnic pistol	A-2	49
Hydraulic charger—30 caliber	D-1	40
Hydraulic gun charger—20-mm.	D-3	39
Hydraulic gun charger—30 caliber	D-1	40
Hydraulic gun charger—50 caliber	D-2	41
Hydraulic gun charger cylinder	D-1	40
" " " " "	D-2	41
" " " " "	D-3	39
Hydraulic gun charging valve	A-1	128
Hydraulic gun mount	M-1	68
" " " " "	M-5	72
" " " " "	M-6	70
" swivel gun mount	M-1	68
" " " " "	M-5	72
" " " " "	M-6	70
Illuminated gun sight	MK 8	83
" " " " "	MK 9	90
" " " " "	N-3A	84
" " " " "	N-3B	86
" " " " "	N-6	87
" " " " "	N-6A	88
" " " " "	N-8	91
Illuminated sight	MK 8	83
Illuminated sight	MK 9	90
Illuminated sight	N-3A	84
" " " " "	N-3B	86
" " " " "	N-6	87
" " " " "	N-6A	88
" " " " "	N-8	91
Impulse tube and wire ends	E-3	98
Impulse unit ends	E-5	98
Incendiary grenade mount	A-1	261
Indicator—bombsight pilot		Not catalogued
Indicator—pilot director		Not catalogued
" " " " "		269
Indicator—pilot director	MK 15 Mod. 3	266



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Indicator—pilot director	MK 15 Mod. 5	264
Indicator—resistance unit		Not catalogued
" —steering	MK 1	Not catalogued
Interval control	AN-B-3	242
" "	B-2	240
" "	B-2A	241
Interval control—bomb release		239
Intervalometer (Navy and British Type)	AN-B-3	242
" (Navy)	B-2	240
" "	B-2A	241
Inverters—rotary		270
Junction box	T-8007523	209, 206, 173
Junction box	T-8252853	218, 215
Kit—emergency repair	A	Not catalogued
" "	B	Not catalogued
Left blister auxiliary control box	P-8242380	175, 173
Left blister sighting station	2CSR3R2	173, 192
Left hand ammunition box mount	C-2	54
Left hand ammunition box mount	C-3	56
Left hand bomb rack release	A-2	278
Left hand feed mechanism, 20-mm.	AN-M1	316
Left hand gun solenoid	C-4B	106
Left hand gun solenoid	C-4C	110
Left hand upper continuous feed	CF-3L	43
Left hand .30 caliber upper continuous feed	CF-3L	43
Lewis-Larson flexible chuting	B	25
Link ejection container	A-3	31
" "	A-4	32
" "	A-5	33
Links—20-mm. for feed mechanism	M-1	Not catalogued
Lock—directional arm	C-1	270
Low altitude bombsight	A-1	255
" "	A-2	257
Lower aft gun turret	2CGD50LRC5	198, 173
Lower ball local control turret—retractable	A-13	158
" " turret—local control	A-2	156
Lower continuous feed	CF-5	45
Lower forward gun turret	2CGD50LRC4	200, 173
Lower gun turret	2CGD50LRC1	222, 215
Lower gun turret	A-2	136
Lower gun turret	A-5	160
Lower gun turret	A-10	162
Lower gun turret—local control (British)	A-2	156
" " —local control retractable (British)	A-13	158
" " assembly	A-10A	Not catalogued
" remote control turret assembly	B-1	Not catalogued
" turret—Bendix	A-10	162
Machine gun adapter—.50 caliber M2	E-5A	11
" " —.50 caliber M2	E-8	14
" " —.50 caliber M2	E-11	16
" " .30 caliber—Browning, aircraft, fixed	M2	306
" " caliber .30, Browning, M2, aircraft, flexible	M2	308
" " caliber .30, Browning, M2, aircraft, flexible with fixed back plate	M2	307
" " electric synchronizer control box assembly	A-3	Not catalogued
" " timer assembly	A-4	Not catalogued
" " trigger motor assembly	A-1	Not catalogued
Machine gun synchronizers		96
Machine gun turrets		130
Machine guns—aircraft		304
Magazine (Navy)	L-4	21
" "	L-7	22
" endless belt, 30-round	M6	314
Magazine, endless belt, 37-mm., M6		314
Magazine, endless belt, 37-mm., M7		315
Magazine, 15-round, 37-mm., M2		312
Magazine, 30-round	M7	315

ALPHABETICAL INDEX
ARMAMENT SECTION

(RESTRICTED)
XVII



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Mount assembly—bombsight		Not catalogued
" " —gun	G-4	Not catalogued
" " —75-mm. cannon	M6	318
Mount, gun, airplane, 75-mm., M6		318
Mount, 75-mm.	M6	318
Mounting sleeve	No. 2, Mk 1	329
Nose gun turret	A-15	166
Nose gun turret	A-16	168
Nose gun turret assembly	A-6	Not catalogued
Nose sighting station	2CSR3C1	173, 193
Nose system control box	W-8258468	176, 173
Operating slide group assembly	D28200	310
" " lever stud	A13424	319
Optical sight	MK 8	83
" " "	MK 9	90
" " "	N-3A	84
" " "	N-3B	85
" " "	N-6	87
" " "	N-6A	88
" " "	N-8	91
P.D.I.	MK 15 Mod. 3	266
" " control	MK 15 Mod. 5	264
" " "	A-1	243
Panel—autopilot control	A-6A	232
Panel—autopilot control		269
" —directional		270
" —pilot's control		271
Periscopic sighting station	2CSD1C1	221
Pilot—automatic	B-1	Not catalogued
Pilot—automatic	C-1	268
Pilot director dash switch		Not catalogued
" " indicator		Not catalogued
" " "		258
Pilot director indicator	MK 15 Mod. 3	266
Pilot director indicator	MK 15 Mod. 5	269
Pilot director indicator control	A-1	243
Pilot's bombsight adapter ring	43B15328	256
Pilot's bombsight head	A-1	255
Pilot's bombsight head	A-2	257
Pilot's bombsight head adapter ring	43B15328	256
" control box	A-6A	232
" " panel		271
" " "	A-6A	232
Pistol holder	A-1	48
" " "	A-2	49
" mount	No. 2, MK. 1	329
" " cover	No. 2, MK. 1	329
Pistol, pyrotechnic, AN-M8, w/mount		330
Pistol, pyrotechnic, M2		327
Pistol, signal, No. 4 MK 1	No. 4, MK. 1	328
Plug container assembly	A	291
Plunger assembly—gun synchronizer control	A-1	Not catalogued
Portable bomb hoist	AN-MK. 7 Mod. 1	258
Portable tachometer—1000 R.P.M.	4050 & 4050A	292
Post—gun mounting	A-4	73
Post sight	A-4	76
" " "	A-5	77
" " "	A-11	78
Power operated lower gun turret	A-5	160
" " " " "	A-10	162
" unit	AA-16801	169
" " "	AA-16804	170
Pyrotechnic discharger	AN-M5	326
" " AN-M5 and remote controller M2		326
Pyrotechnic pistol	AN-M8	330
Pyrotechnic pistol	M2	327



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Pyrotechnic pistol.....	No. 4, MK 1.....	328
Pyrotechnic pistol holder.....	A-1.....	48
Pyrotechnic pistol holder.....	A-2.....	49
Pyrotechnic pistol mount.....	M1.....	Not catalogued
" projector.....	AN-M5.....	326
" projectors and signals.....		324
" signal pistol.....	AN-M8.....	330
" " ".....	M2.....	327
Rack—bomb.....	MK 43 Mod. 1.....	274
Rack—bomb.....	AN-MK 51 Mod. 7.....	272
Rack—bomb.....	N-5.....	275
Rack—bomb.....	Q-2.....	276
Rack assembly—flare.....	A-4.....	Not catalogued
Rear lower gun turret.....	2CGD50LRC5.....	198
" mounting post (Navy).....	A-4.....	73
" upper gun turret.....	2CGD50URC4.....	202
Receptacle—bomb release.....	A-1.....	277
Recoil absorption adapter.....	AN-M1.....	300
" " ".....	AN-M6.....	302
Reconnaissance flare—4 1/2 inch.....	MK 2.....	Not catalogued
Red cartridge—1 1/2 inch.....		Not catalogued
Reflector support.....	41D4892.....	121
Regulator—computer voltage.....		Not catalogued
Release—bomb rack left hand.....	A-2.....	278
Release—bomb rack—L.H.....	A-4.....	Not catalogued
Release—bomb rack—R.H.....	A-2.....	279
Release—bomb rack right hand.....	A-3.....	280
Release—bomb rack—R.H.....	A-4.....	Not catalogued
" assembly—bomb rack—L.H. (12-volt).....	A-3.....	Not catalogued
Resistance unit indicator.....		Not catalogued
" " transmitter.....		Not catalogued
Reticle reflecting sight.....	N-6.....	87
Retiflector sight.....	N-8.....	91
Retractable lower gun turret.....	A-10.....	162
Retractable lower gun turret.....	A-13.....	158
Retractable lower gun turret—Bendix.....	A-5.....	160
Retracting slide group assembly.....	D28300A.....	311
" " lever stud.....	A-13424.....	319
Rheostat.....	D-1.....	123
Rheostat—variable resistance.....	D-1.....	123
Right blister auxiliary control box.....	P-8242380.....	177, 173
Right blister sighting station.....	2CSR3H1.....	194, 173
Right hand ammunition box mount.....	C-2.....	55
Right hand ammunition box mount.....	C-3.....	57
Right hand bomb rack release.....	A-2.....	279
" " " ".....	A-3.....	280
Right hand feed mechanism, 20-mm.....	AN-M1.....	317
Right hand feed mechanism, 20-mm., AN-M1.....		317
Right hand gun solenoid.....	C-4B.....	108
Right hand gun solenoid.....	C-4C.....	112
Right hand upper continuous feed.....	CF-3R.....	44
Ring—pilot's bombsight adapter.....	43H15328.....	256
Ring assembly—upper sight collector.....	T-8252833.....	173, 191
Ring sight.....	B-10.....	79
" ".....	B-11.....	80
" ".....	B-13.....	81
" sighting station.....	2CSR3A1.....	196
" spring cartridge—20-mm. gun adapter.....	M1.....	300
" " " —20-mm. gun adapter.....	AN-M6.....	302
Roll—armourer's tool 30 and .50 caliber.....		Not catalogued
Roll, tool, armourer's w/contents, complete.....	A-28.....	320
Roll, tool, armourer's w/contents, complete.....	A-38.....	322
Rotary inverters.....		270
Selective fusing control.....	AN-A-1.....	236
" " ".....	AN-A-2.....	237
" " ".....	B-2.....	238

Name	Type, Drawing or Designation	Page
Selsyn		206
Selsyn	2JIGI	212, 206
Servo—amplifier.....	2CVIBI.....	206, 207, 216, 215
Servo—amplifier.....	2CVICI.....	174, 173
Servomotor.....		278
Shackle—bomb.....		281
Shackle—bomb.....	AN-B-9.....	283
Shackle—bomb.....	B-7.....	282
Shackle—bomb.....	B-10.....	284
Shackle—bomb.....	D-3.....	285
Shackle—bomb.....	D-5.....	286
Shackle—bomb.....	D-6.....	287
Shackle—bomb.....	D-7.....	288
Shackle assembly—bomb.....	D-8.....	Not catalogued
Side blister selector switch box.....	T-8252A90.....	179, 173
Side blister system control box.....	W-8258874.....	178, 173
Sight—automatic compensating gun.....	K-3.....	92
Sight—automatic compensating gun.....	K-4.....	93
Sight—compensating.....	K-8.....	94
Sight—fixed gun.....	N-3A.....	84
Sight—flexible gun.....	N-3B.....	86
Sight—flexible gun.....	N-6.....	87
Sight—flexible gun.....	N-6A.....	88
Sight—flexible gun.....	N-8.....	91
Sight—flexible gun post.....	A-4.....	76
Sight—flexible gun post.....	A-5.....	77
Sight—flexible gun post.....	A-11.....	78
Sight—flexible gun ring.....	B-10.....	79
Sight—flexible gun ring.....	B-11.....	80
Sight—flexible gun ring.....	B-13.....	81
Sight—gun.....		74
Sight—illuminated.....	Mk 8.....	83
Sight—illuminated.....	Mk 9.....	90
Sight—telescopic gun.....	E-5.....	82
Sight assembly—automatic compensating.....		Not catalogued
" " ————— "	K-11.....	Not catalogued
" " —auxiliary ring and bead.....		Not catalogued
" " —compensating gun.....	K-9.....	Not catalogued
" " —fixed gun.....	N-2A.....	Not catalogued
" " ————" "	N-3.....	Not catalogued
" " ————" "	N-5.....	Not catalogued
" " ————" "	N-7.....	Not catalogued
" " ——flexible gun post.....	A-6.....	Not catalogued
" " —————" " "	A-8.....	Not catalogued
" " —————" " "	A-10.....	Not catalogued
" " —————" " "	A-12.....	Not catalogued
" " —————.30 caliber.....	A-9.....	Not catalogued
" " ——ring.....	B-14.....	Not catalogued
" " —————" "	B-15.....	Not catalogued
" " ——tail gun telescopic model 323.....	L-2.....	Not catalogued
" " ——telescopic (ordnance M-7) .30 and .50 caliber.....	Q-3.....	Not catalogued
Sight, open fore post (Navy).....	A-5.....	77
" " rear ring (Navy).....	B-10.....	79
" " ——"	B-11.....	80
Sights—gun.....		74
Sighting station.....	2CSDIC1.....	221, 215
Signal flare container.....	A-1.....	34
Signal flare container.....	A-5.....	35
Signal flare container.....	A-6.....	36
Signal flare container.....	A-7.....	37
Signal flare container assembly.....	A-3.....	Not catalogued
" " " ".....	A-4.....	Not catalogued
" " " ".....	A-8.....	Not catalogued
" pistol.....	AN-M8.....	330
" ".....	M2.....	322



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Signal pistol	No. 4, Mk 1	328
Single gun mount adapter	C-12	6
" " "	C-16	7
" parallax computer	2CH1C1	184, 173
" pole toggle switch	B-5A	197
Single pole toggle switch	AN3022-2	126
Sleeve, mounting, No. 2, Mk 1	No. 2, Mk 1	329
Slide, operating, BAM .50 (M-2), group assembly	D28200	310
Slide, operating, group assembly	D28200	310
Slide, retracting, BAM .50 (M-2), group assembly	D28300A	311
Slide, retracting, group assembly	D28300A	311
Sling—bomb hoist	A-1	289
Sling—bomb hoist	A-2	290
Socket—5-way bomb		291
Socket—7-way	U	Not catalogued
Solenoid	C-4B	106, 108
"	C-4C	110, 112
"	E-4	101
"	E-6	102
"	E-8	103
"	G-4A	114
"	G-8	115
"	G-9	116
"	G-10	104
"	G-11	117
"	G-13	118
"	G-15	119
"	G-16	105
Solenoid—cannon	AN-M1	120
Solenoid—gun	E-4	101
Solenoid—gun	E-6	102
Solenoid—gun	E-8	103
Solenoid—gun	G-4A	114
Solenoid—gun	G-8	115
Solenoid—gun	G-9	116
Solenoid—gun	G-10	104
Solenoid—gun	G-11	117
Solenoid—gun	G-13	118
Solenoid—gun	G-15	119
Solenoid—gun	G-16	105
Solenoid—left hand gun	C-4B	106
Solenoid—left hand gun	C-4C	110
Solenoid—right hand gun	C-4B	108
Solenoid—right hand gun	C-4C	112
Solenoid assembly—gun	E-2A	Not catalogued
" " —	E-5	Not catalogued
" " — (12-volt)	E-7	Not catalogued
" " — (12-volt)	E-9	Not catalogued
" " — (24-volt)	G-1	Not catalogued
" " — (24-volt)	G-2	Not catalogued
" " — (24-volt)	G-3	Not catalogued
" " — (24-volt)	G-4	Not catalogued
" " — R.H.—(24-volt)	G-12	Not catalogued
Sperry computer	K-3	92
" " "	K-4	93
" computing sight	K-3	92
" " "	K-4	93
" lower ball turret	A-2	156
" upper turret	A-1	132, 133
" " "	A-1A	134, 135
Stabilizer—directional		269
Station—left blister sighting	2CSR3B2	173, 192
Station—nose sighting	2CSR3C1	173, 193
Station—right blister sighting	2CSR3B1	173, 194
Station—sighting	2CSD1C1	215, 221
Station—tail sighting	2CSR3B3	173, 195



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Station—upper ring sighting	2CSR3A1	173, 196
Steering indicator	Mk 1	Not catalogued
Strap—torpedo hoisting	Mk 13	Not catalogued
Stud—bolt	A13424	319
Support—gun sight image reflector	41D3024	122
Support—gun sight image reflector	41D4H92	121
Support—gun sight image reflects	N-2	Not catalogued
Switch	AN3022-2	126
Switch—control stick gun	B-1A	124
Switch—control stick gun	B-5	125
Switch—gun control stick	B-4	Not catalogued
—pilot director dash		Not catalogued
—single pole toggle	AN3022-2	126
Switch—tail cannon selector	B-5A	173, 197
Switch—three hole mounting single pole toggle	B-5A	126
box	T-8252925	217
trigger gun firing and bomb release (Navy)		125
Swivel gun mount	K-5	67
Synchronizer—gun impulse generator	E-8	97
trigger motor	E-3, Mk 1	99
" " "	E-3A, Mk 1 Mod 1	100
Synchronizers—machine gun		96
System—A-26 central station fire control		215
System—B-29 central station fire control		173
System—P-61 central station fire control		206
Tachometer—bombsight disc speed	4050 & 4050A	292
Tachometer—bombsight roto speed		Not catalogued
Tail cannon selector switch	B-5A	173, 197
Tail gun mount azimuth drive	W-8258810	173, 185
Tail gun mount elevation drive	W-8258807	173, 186
Tail gun telescopic model 323 sight assembly	Q-3	Not catalogued
Tail gun turret	A-6	164
Tail gun turret assembly	A-15A	Not catalogued
Tail sighting station	2CSR3B3	195, 173
Tail system control box	W-8258881	180, 173
Tee-grip bomb release handle	A-3	250
Telescopic gun sight	E-5	82
Telescopic (ordnance M-7) .30 and .50 caliber sight assembly		Not catalogued
sight mount	C-4	58
Timer assembly—machine gun electric synchronizer	A-4	Not catalogued
Toggle switch	AN3022-2	126
" " "	B-5A	197
Tool roll	A-28	320
" " —.30 caliber	A-38	322
" " —.50 "	A-28	320
" " —.50 "	A-38	322
Torpedo director	B-1	Not catalogued
Torpedo director	B-2	249
Torpedo director	Mk 28 Mod. 2	248
Torpedo directors		247
hoisting strap	Mk 13	Not catalogued
Training turret	A-8	154
Transmitter—resistance unit		Not catalogued
Trigger—electric AN-M1		120
Trigger—manual	A-1	127
Trigger assembly—gun firing	A-1	127
Trigger motor	E-3	99
Trigger motor	E-3A	100
Turn control		271
type remote control unit (British)	A-6A	232
Turnbuckle harrel		19
Turret—double power unit	AA-16801	169
— Emerson	A-15	166
Turret—lower aft gun	2CGD50LRC5	173, 198
Turret—lower forward gun	2CGD50LRC4	173, 200
Turret—lower gun	2CGD50LRC1	215, 222



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Turret—lower gun	A-2	156
Turret—lower gun	A-5	160
Turret—lower gun	A-10	162
Turret—lower gun—retractable	A-5	160
“ “ “ “	A-10	162
“ “ “ “ —44 inch ball	A-13	158
“ “ local control	A-2	156
Turret—nose	A-16	168
Turret—nose gun	A-15	166
Turret—nose gun	A-16	168
Turret—retractable lower gun	A-13	158
Turret—tail gun	A-6	164
Turret—tail gun—consolidated	A-6	164
Turret—upper aft gun	2CGD50URC4	173, 202
Turret—upper forward gun	2CGD50URC3	173, 204
Turret—upper gun	2CGD50URC1	224
Turret—upper gun	2CGQ50URA4	215, 214
Turret—upper gun	A-1	132-133
Turret—upper gun	A-1A	134-135
Turret—upper gun	A-3	136
Turret—upper gun	A-3A	138-139
Turret—upper gun	A-3B	140
Turret—upper gun	A-3C	142
Turret—upper gun	A-4	148
Turret—upper gun	A-9	150
Turret—upper gun	A-9A	152
Turret—upper gun	A-9B	Not catalogued
Turret—upper gun	A-11	144
Turret—upper gun	A-14	146
Turret—upper gun—Martin	A-3	136
“ “ “ “	A-3A	138-139
“ “ “ “	A-3B	140
“ “ “ “	A-3C	142
“ “ “ “	A-11	144
“ “ “ “	A-14	146
“ “ local control	A-1	132-133
“ “ local control	A-1A	134-135
Turret—upper training	A-8	154
Turret assembly—lower gun	A-10A	Not catalogued
“ “ “ remote control	B-1	Not catalogued
“ “ —nose gun	A-6	Not catalogued
“ “ —tail gun	A-15A	Not catalogued
“ drive motor	5BA50GJ1	52
Turret drive motor	5BA50LJ2A	227
Turret drive motor	5BA50LJ1	51
Turrets—machine gun		130
Twin adapter—30 caliber		4
“ gun mount adapter		4
Unit—double power hydraulic	AA-16801	169
Unit—double power hydraulic	AA-16804	170
United shoe gun mount	M-1	68
Units—continuous feed		42
Universal bomb carrier	No. 1 Mk 3	233
Universal bomb carrier—No. 1	Mk 2	Not catalogued
“ “ “ —No. 2	Mk 2	Not catalogued
“ “ “ adapter box	A	231
“ turret drive motor	5BA50LJ2A	227
Upper aft gun turret	2CGD50URC4	173, 202
Upper blister system control box	W-8258865	181, 173
Upper forward turret	2CGD50URC3	204, 173
Upper gun turret	2CGD50URC1	224, 215
Upper gun turret	2CGQ50URA4	214, 206
Upper gun turret	A-1	132-133
Upper gun turret	A-1A	134-135
Upper gun turret	A-3	136
Upper gun turret	A-3A	138-139



ALPHABETICAL INDEX ARMAMENT SECTION

Name	Type, Drawing or Designation	Page
Upper gun turret	A-3B	140
Upper gun turret	A-3C	142
Upper gun turret	A-4	148
Upper gun turret	A-9	150
Upper gun turret	A-9A	152
Upper gun turret	A-9B	Not catalogued
Upper gun turret	A-11	144
Upper gun turret	A-14	146
Upper gun turret—local control (British)	A-3	136
" " " " " "	A-3A	138-139
" " " " " "	A-3B	140
" " " " " "	A-3C	142
" " " " " "	A-11	144
" " " " " "	A-14	146
" " " " " "—Sperry	A-1	132-133
" " " " " "	A-1A	134-135
Upper ring sighting station	2CSR3A1	196, 173
Upper sight collector ring assembly	T-8252833	173, 191
Upper training turret	A-8	154
Upper turret—local control (British)	A-4	148
" " " " " "	A-9	150
" " " " " "	A-9A	152
Valve	A-1	128
Valve—hydraulic gun charging	A-1	128
Variable bombing reflector	A-1	255
" " " " " "	A-2	257
" " reflector	A-1	255
" " " " " "	A-2	257
Variable resistance rheostat	D-1	123
Vertical gyro control		269
Vickers unit	AA-16801	169
" " " " " "	AA-16804	170
Wing bomb rack	N-5	275
" " " " " "	Q-2	276
Yellow and green cartridge—1 1/4 inch		Not catalogued
" " red cartridge—1 1/4 inch		Not catalogued
" " cartridge—1 1/4 inch		Not catalogued
Yoke	41D6865	129
Yoke—gun mount adapter	41D6865	129



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used In Connection with	Type, Drawing or Designation	Page
1-S-9423	A.O.S.L.	Slide, operating, group assembly	D23200	310
1-S-9428	" "	" retracting, group assembly	D23300A	311
1-S-22240	" "	Stud—bolt	A13424	319
1-T-2880	" "	Trigger—electric, AN-M1		120
1-V-430	" "	Valve—hydraulic gun charging	A-1	128
2-B-1900	" "	Cover—electrically heated bombsight	A-1	244
2-D-155	" "	Director—torpedo	Mk 28 Mod 2	248
2-D-176	" "	" — " "	B-1	249
2-D-180	" "	Discharger, pyrotechnic, AN-M5		326
2-I-105	" "	Indicator—pilot director	Mk 15 Mod 3	267
2-I-115	" "	" — " "	Mk 15 Mod 5	265
2-P-3485	" "	Pistol, pyrotechnic, M2		327
2-P-3499	" "	" " AN-M8, w/mount		330
2-S-335	" "	Panel—autopilot control	A-6A	232
2-S-335	" "	Pilot—automatic	C-1	268
2-S-3090	" "	Sight—flexible gun post	A-1	76
2-S-3091	" "	" — " " "	A-5	77
2-S-3106	" "	" — " " " ring	B-0	79
2-S-3107	" "	" — " " " "	B-1	80
2-S-3114	" "	" — illuminated	Mk 8	83
2-S-3115	" "	" — " "	Mk 9	90
2-S-3117	" "	" — fixed gun	N-3A	83
2-T-20	" "	Tachometer—bombsight disc speed	4050 & 4050A	292
2CFR12A3	Mfr's Model	Central station fire control system—P-61		206
2CFR21B3	" "	" " " " —A-26		215
2CGD50LRC1	" "	Turret—lower aft gun	2CGD50LRC5	199
2CGD50LRC1	" "	" — " forward gun	2CGD50LRC4	201
2CGD50LRC1	" "	" — " gun	2CGD50LRC1	222, 223
2CGD50LRC4	" "	" — " aft gun	2CGD50LRC5	199
2CGD50LRC4	" "	" — " forward gun	2CGD50LRC4	200, 201
2CGD50LRC4	" "	" — " gun	2CGD50LRC1	223
2CGD50LRC5	" "	" — " aft gun	2CGD50LRC5	198, 199
2CGD50LRC5	" "	" — " forward gun	2CGD50LRC4	201
2CGD50LRC5	" "	" — " gun	2CGD50LRC1	223
2CGD50URC1	" "	" —upper aft gun	2CGD50URC4	203
2CGD50URC1	" "	" — " forward gun	2CGD50URC3	203
2CGD50URC1	" "	" — " gun	2CGD50URC1	224, 225
2CGD50URC3	" "	" — " aft gun	2CGD50URC4	203
2CGD50URC3	" "	" — " forward gun	2CGD50URC3	204, 205
2CGD50URC3	" "	" — " gun	2CGD50URC1	225
2CGD50URC4	" "	" — " aft gun	2CGD50URC4	202, 203
2CGD50URC4	" "	" — " forward gun	2CGD50URC3	203
2CGD50URC4	" "	" — " gun	2CGD50URC1	225
2CGQ50URA4	" "	" — " "	2CGQ50URA4	214
2CH1C1	" "	Computer—single parallax	2CH1C1	184
2CH1D1	" "	" —double parallax	2CH1D1	183
2CSD1C1	" "	Station—sighting	2CSD1C1	221
2CSR3A1	" "	" —upper ring sighting	2CSR3A1	196
2CSR3B1	" "	" —right blister sighting	2CSR3B1	194
2CSR3B2	" "	" —left blister sighting	2CSR3B2	192
2CSR3B3	" "	" —tail sighting	2CSR3B3	195
2CSR3C1	" "	" —nose sighting	2CSR3C1	193
2CV1B1	" "	Servo—amplifier	2CV1B1	207, 216
2CV1C1	" "	" — " "	2CV1C1	174
2J1F1	" "	Station—left blister sighting	2CSR3B2	192
2J1F1	" "	" —nose sighting	2CSR3C1	193
2J1F1	" "	" —right blister sighting	2CSR3B1	194
2J1F1	" "	" —tail sighting	2CSR3B3	195
2J1F1	" "	" —upper ring sighting	2CSR3A1	196
2J1G1	" "	Drive—tail gun mount azimuth	W-8258810	185
2J1G1	" "	" — " " " elevation	W-8258807	186
2J1G1	" "	Selsyn	2J1G1	212
2, Mk 1	Army, Brit. Type	Disc, aperture	2, Mk 1	328, 329
2, Mk 1	" "	Pistol, signal	No. 4, Mk 1	328
2, Mk 1	" "	Sleeve, mounting	2, Mk 1	329
3-B-1401	A.O.S.L.	Receptacle—bomb release	A-1	277



NUMERICAL INDEX
ARMAMENT SECTION

Number	Number Identification	Used In Connection with	Type, Drawing or Designation	Page
3-B-1969	A.O.S.L.	Control—bomb arming	AN-A-1	236
3-B-1969	" "	" " " "	AN-A-2	237
3-B-1970	" "	" " " "	AN-A-1	236
3-B-1970	" "	" " " "	AN-A-2	237
3-B-1977	" "	" " " "	B-2	238
3-C-1805	" "	" " " "	AN-A-1	236
3-C-1805	" "	" " " "	AN-A-2	237
3-C-1810	" "	" " " "	AN-A-1	236
3-C-1810	" "	" " " "	AN-A-2	237
3-C-1875	" "	" " release interval	B-2A	242
3-C-1880	" "	" " " "	AN-B-3	242
3-H-627	" "	Handle—bomb release	Mk 4 Mod 2	254
3-H-635	" "	" " " "	A-3	250
3-H-645	" "	" " " "	L-21A	253
3-H-1035	" "	Hoist—portable bomb	AN-Mk 7 Mod 1	259
3-I-495	" "	Control—bomb release interval	AN-B-3	242
3-R-167	" "	Rack—bomb	Mk 43 Mod 1	274
3-R-176-70	" "	" " " "	AN-Mk 51 Mod 7	273
3-R-176-73	" "	" " " "	AN-Mk 51 Mod 7	273
3-R-176-75	" "	" " " "	AN-Mk 51 Mod 7	273
3-R-519-25	" "	Release—bomb rack right hand	A-3	280
3-S-1904	" "	Shackle—bomb	B-7	282
3-S-1905	" "	" " " "	AN-B-9	283
3-S-1906	" "	" " " "	AN-B-10	284
3-S-1908	" "	" " " "	D-6	287
4, Mk 1	Army, Brit. Type	Disc, aperture	2, Mk 1	329
4, Mk 1	" " "	Pistol, signal	4, Mk 1	329
4, Mk 1	" " "	Sleeve, mounting	2, Mk 1	329
5AM31NJ9	Mfr's Model	Motor—turret drive	5BA50LJ2A	227
5AM31NJ9	" "	" generator—amplidyne remote control	5AM31NJ9	189, 211, 220
5AM31NJ18	" "	" —azimuth turret drive	5BA50LJ1	51
5AM31NJ18	" "	" —elevation turret drive	5BA50GJ1	52
5AM31NJ18	" "	" generator—amplidyne local control	5AM31NJ18	50
5AM61NJ1C	" "	Drive—tail gun mount azimuth	W-8258810	185
5AM61NJ1C	" "	" " " " elevation	W-8258807	186
5AM61NJ1C	" "	Motor generator—amplidyne remote control	5AM61NJ1C	190
5BA50GJ1	" "	" —elevation turret drive	5BA50GJ1	52
5BA50GJ1	" "	" generator—amplidyne local control	5AM31NJ18	50
5BA50LJ1	" "	" —azimuth turret drive	5BA50LJ1	51
5BA50LJ1	" "	" generator—amplidyne local control	5AM31NJ18	50
5BA50LJ2	" "	" —turret drive	5BA50LJ2A	227
5BA50LJ2A	" "	" " " "	5BA50LJ2A	227
5BC31NJ65	" "	Drive—tail gun mount azimuth	W-8258810	185
5BC31NJ65	" "	" " " " elevation	W-8258807	186
5D/517	Brit. Ref.	Adapter—box	A	231
5D/525	" "	Socket—5 way bomb	A	291
5D/526	" "	Adapter—box	A	231
5D/529	" "	Socket—5 way bomb	A	291
5D/610	" "	Adapter—box	A	231
5D1NJ3A	Mfr's Model	Dynamotor	5D21NJ3	187, 219
5D21FJ2A	" "	" " " "	5D21FJ2A	210
7B/810	Brit. Ref.	Pistol, signal	No. 4, Mk 1	328
7B/811	" "	Sleeve, mounting	No. 2, Mk 1	329
7B/812	" "	Disc, aperture	No. 2, Mk 1	329
9-205	War Dept. tech. list no.	Gun, machine, caliber .30 Browning M2, aircraft fixed		306
9-205	War Dept. tech. man. no.	" " " " " " M2, aircraft flexible		308
9-205	War Dept. tech. man. no.	" " " " " " " " " "		307
9-205	Ord. TM	Roll, tool armorer's w/contents, complete	A-28	321
9-225	War Dept. tech. man. no.	Gun, machine, caliber .50 Browning M2, aircraft basic		309
9-225	" "	Roll, tool, armourer's w/contents, complete	A-38	323
9-225	" "	Slide, operating, group assembly	D28200	310
9-225	" "	" retracting, group assembly	D28300A	311



NUMERICAL INDEX
ARMAMENT SECTION

Number	Number Identification	Used In Connection with	Type, Drawing or Designation	Page
9-225	War Dept. tech. man. no.	Stud—bolt	A13424	319
9-227	" "	Adapter assembly, 20-mm., AN-M1		316
9-227	" "	" " " " AN-M6		303
9-227	" "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		299
9-227	" "	Magazine, 60 RD, 20-mm., M1		313
9-227	" "	Mechanism, feed, left hand, 20-mm., AN-M1		316
9-227	" "	" " " " right hand, 20-mm., AN-M1		317
9-240	" "	Gun, automatic, 37-mm., M4		296
9-240	" "	Magazine, endless belt, 37-mm., M6		314
9-240	" "	" " " " 15 round, 37-mm., M2		312
9-290	" "	Discharger, pyrotechnic, AN-M5		326
9-290	" "	Pistol, pyrotechnic, AN-M8, w/mount		338
9-290	" "	" " " " M2		327
9-1205	" "	Gun, machine, caliber .30 Browning, aircraft fixed	M2	386
9-1205	" "	" " " " " " " " M2, aircraft flexible		308
9-1206	" "	" " " " " " " " " " " "		
		with fixed back plate		307
9-1206	" "	Roll, tool, armorer's w contents, complete	A-28	321
9-1225	" "	Gun, machine, caliber .50, Browning M2, aircraft basic		309
9-1225	" "	" " " " " " " " flexible		309
9-1225	" "	Roll, tool, armorer's w/contents, complete	A-38	323
9-1227	" "	Gun, aircraft, automatic 20-mm., M1 and AN-M2 (all types)		299
9-1240	" "	" " " " " " " " " " " "		296
9-1900	" "	Destructor, AN-M3		295
10C/40	Brit. ref.	Rheostat—variable resistance	D-1	123
11-1-8	Army T.O.	Gun, machine, caliber .50, Browning, M2 aircraft flexible		309
11-1-8	" "	Roll, tool, armorer's w contents, complete	A-38	323
11-1-8	" "	Slide, operating, group assembly	D28200	310
11-1-8	" "	" " " " " " " " " " " "	D28300A	311
11-1-8	" "	Stud—bolt	A13424	319
11-1-14	" "	Valve—hydraulic gun charging	A-1	128
11-1-15	" "	Gun, automatic, 37-mm., M4		296
11-1-15	" "	Magazine, 15 round, 37-mm., M2		312
11-1-16	" "	Adapter assembly, 20-mm., AN-M1		301
11-1-16	" "	" " " " " " " " " " " "		303
11-1-16	" "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		299
11-1-16	" "	Magazine, 60 RD, 20-mm., M1		313
11-1-16	" "	Mechanism, feed, left hand, 20-mm., AN-M1		316
11-1-16	" "	" " " " " " " " " " " "		317
11-1-17	" "	Gun, automatic, 37-mm., M4		296
11-1-17	" "	Magazine, endless belt, 37-mm., M6		314
11-1-17	" "	" " " " " " " " " " " "		312
11-1-18	" "	Gun, automatic, 37-mm., M4		296
11-1-18	" "	Magazine, endless belt, 37-mm., M6		314
11-1-18	" "	" " " " " " " " " " " "		312
11-1-21	" "	Charger—20-mm., hydraulic gun	D-3	39
11-1-28	" "	Gun, machine, caliber .30 Browning, M2, aircraft fixed		306
11-1-28	" "	" " " " " " " " " " " "		308
11-1-28	" "	" " " " " " " " " " " "		
		with fixed back plate		307
11-1-28	" "	Gun, machine, caliber .50 Browning, M2 aircraft basic		309
11-1-30	" "	Solenoid—gun	E-3	101
11-1-30	" "	" " " " " " " " " " " "	E-6	102
11-1-30	" "	" " " " " " " " " " " "	E-8	103
11-1-30	" "	" " " " " " " " " " " "	G-4A	114
11-1-30	" "	" " " " " " " " " " " "	G-8	115
11-1-30	" "	" " " " " " " " " " " "	G-9	116
11-1-30	" "	" " " " " " " " " " " "	G-10	104
11-1-30	" "	" " " " " " " " " " " "	G-11	117
11-1-30	" "	" " " " " " " " " " " "	G-13	118
11-1-30	" "	" " " " " " " " " " " "	G-15	119
11-1-30	" "	" " " " " " " " " " " "	G-16	105
11-1-30	" "	" " " " " " " " " " " "	C-4B	107
11-1-30	" "	" " " " " " " " " " " "	C-4C	111
11-1-30	" "	" " " " " " " " " " " "	C-4B	109



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
11-1-30	Army T.O.	Solenoid—right hand gun	C-4C	113
11-1-30	" "	Trigger—electric AN-M1		120
11-1-36	" "	Control—bomb release interval	B-2	240
11-1-36	" "	" — " " " "	B-2A	241
11-1-37	" "	Solenoid—gun	G-8	115
11-1-37	" "	Trigger—electric AN-M1		120
11-1-41	" "	Feed—left hand upper continuous	CF-3L	43
11-1-41	" "	" —lower continuous	CF-5	45
11-1-41	" "	" —right hand upper continuous	CF-3R	44
11-1-44	" "	Handle—bomb release	Mk 4 Mod 2	254
11-5-7	" "	Rack—bomb	AN-Mk 51 Mod 7	273
11-5-10	" "	Shackle—bomb	D-6	287
11-5-10	" "	" — " "	D-7	288
11-5-13	" "	" — " "	D-3	285
11-5-13	" "	" — " "	D-5	286
11-5-14	" "	Control—bomb release interval	B-2	240
11-5-14	" "	" — " " " "	B-2A	241
11-5-18	" "	Rack—bomb	Mk 43 Mod 1	274
11-5-26	" "	Hoist—bomb	C-9	260
11-5-27	" "	Shackle—bomb	B-7	282
11-5-28	" "	Release—bomb rack left hand	A-2	278
11-5-28	" "	" — " " right hand	A-2	279
11-5-29	" "	Control—bomb release interval	AN-B-3	242
11-5-29	" "	" — " " " "	B-2	240
11-5-29	" "	" — " " " "	B-2A	241
11-5-30	" "	Release—bomb rack right hand	A-3	280
11-5-33	" "	Control—bomb arming	AN-A-1	236
11-5-33	" "	" — " " " "	AN-A-2	237
11-5-33	" "	Mount—bomb arming control	A-1	262
11-5-35	" "	Shackle—bomb	AN-B-9	283
11-5-38	" "	Release—bomb rack left hand	A-2	278
11-5-38	" "	" — " " right hand	A-2	279
11-5-43	" "	Carrier—universal bomb	No. 1 Mk 3	233
11-5-46	" "	Release—bomb rack left hand	A-2	278
11-5-46	" "	" — " " right hand	A-2	279
11-5-47	" "	Control—bomb arming	AN-A-1	236
11-5-47	" "	" — " " " "	AN-A-2	237
11-5-49	" "	Hoist—portable bomb	AN-Mk 7 Mod 1	259
11-10-5	" "	Adapter—gun mount	E-10	15
11-10-6	" "	" — " " " "	E-5A	11
11-10-7	" "	" — " " " "	E-5	13
11-10-7	" "	" — " " " "	E-8	14
11-10-7	" "	" — " " " "	E-11	17
11-10-7	" "	" — " " " "	E-12	18
11-10-8	" "	" — " " " "	E-5	13
11-10-8	" "	" — " " " "	E-8	14
11-10-8	" "	" — " " " "	E-11	17
11-10-8	" "	" — " " " "	E-12	18
11-10-9	" "	" — " " " "	C-12	6
11-10-9	" "	" — " " " "	C-17	8
11-10-9	" "	" — " " " "	C-18	9
11-10-9	" "	" — " " " "	E-5	13
11-10-9	" "	" — " " " "	E-8	14
11-10-9	" "	" — " " " "	E-11	17
11-10-9	" "	" — " " " "	E-12	18
11-10-10	" "	" — " " " "		5
11-10-13	" "	Mount—gun	G-1A	59
11-10-13	" "	" — " " " "	G-5	60
11-10-14	" "	Adapter—gun mount	C-16	7
11-15-1	" "	Pistol, pyrotechnic, AN-M8, w/mount		330
11-15-8	" "	Container—signal flare	A-5	35
11-15-8	" "	" — " " " "	A-6	36
11-15-8	" "	" — " " " "	A-7	37
11-15-8	" "	Holder—pyrotechnic pistol	A-2	49
11-15-9	" "	Pistol, pyrotechnic, M2		327
11-20-11	" "	Motor—trigger	E-3	99



NUMERICAL INDEX
ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
11-20-11	Army T.O.	Motor—trigger	E-3A	100
11-20-12	" "	Solenoid—gun	G-4A	114
11-20-12	" "	" — " "	G-9	116
11-20-13	" "	Ends—impulse unit	E-3	98
11-20-13	" "	Generator—gun synchronizer impulse	E-8	97
11-20-15	" "	Motor—trigger	E-3	99
11-20-15	" "	" — " "	E-3A	100
11-20-16	" "	Solenoid—gun	G-4A	114
11-20-16	" "	" — " "	G-9	116
11-30-1	" "	Cover—electrically heated bombsight	A-1	244
11-30-9	" "	" — " "	A-1	244
11-30-10	" "	" — " "	A-2	245
11-30-11	" "	" — " " automatic pilot	PK 1A1	246
11-30-12	" "	Head—pilot's bombsight	A-1	255
11-30-12	" "	" — " "	A-2	257
11-30-12	" "	Ring—pilot's bombsight adapter	43B15328	256
11-35-5	" "	Sight—fixed gun	N-3A	85
11-35-5	" "	" — " "	N-3B	86
11-35-5	" "	Support—gun sight image reflector	41D3024	122
11-35-5	" "	" — " "	41D4892	121
11-35-12	" "	Sight—flexible gun	N-6	87
11-35-12	" "	" — " "	N-6A	89
11-35-12	" "	" — " "	N-8	91
11-35-13	" "	" — " " post	A-11	78
11-35-13	" "	" — " " ring	B-13	81
11-35A-1	" "	" — automatic compensating gun	K-3	92
11-35A-1	" "	" — " "	K-4	93
11-35B-1	" "	" — flexible gun	N-6	87
11-35B-1	" "	" — " "	N-6A	89
11-35B-1	" "	" — " "	N-8	91
11-45A-1	" "	Turret—lower gun	A-5	161
11-45A-1	" "	" — " "	A-10	163
11-45A-3	" "	" — upper gun	A-4	149
11-45A-3	" "	" — " "	A-9	151
11-45A-3	" "	" — " "	A-9A	153
11-45B-1	" "	" — " "	A-3	137
11-45B-1	" "	" — " "	A-3A	139
11-45B-1	" "	" — " "	A-3B	141
11-45B-1	" "	" — " "	A-3C	143
11-45B-1	" "	" — " "	A-11	145
11-45B-1	" "	" — " "	A-14	147
11-45B-2	" "	" — " "	A-3	137
11-45B-2	" "	" — " "	A-3A	139
11-45B-2	" "	" — " "	A-3B	141
11-45B-2	" "	" — " "	A-3C	143
11-45B-2	" "	" — " "	A-11	145
11-45B-2	" "	" — " "	A-14	147
11-45BA-1	" "	" — " "	A-3	137
11-45BA-1	" "	" — " "	A-3A	139
11-45BA-1	" "	" — " "	A-3B	141
11-45BA-1	" "	" — " "	A-3C	143
11-45BA-1	" "	" — " "	A-11	145
11-45BA-1	" "	" — " "	A-14	147
11-45BB-1	" "	" — " "	A-3	137
11-45BB-1	" "	" — " "	A-3A	139
11-45BB-1	" "	" — " "	A-3B	141
11-45BB-1	" "	" — " "	A-3C	143
11-45BB-1	" "	" — " "	A-11	145
11-45BB-1	" "	" — " "	A-14	147
11-45BC-1	" "	" — " "	A-3	137
11-45BC-1	" "	" — " "	A-3A	139
11-45BC-1	" "	" — " "	A-3B	141
11-45BC-1	" "	" — " "	A-3C	143
11-45BC-1	" "	" — " "	A-11	145
11-45BC-1	" "	" — " "	A-14	147
11-45BD-1	" "	" — " "	A-3	137



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
11-45BD-1	Army T.O.	Turret—upper gun	A-3A	139
11-45BD-1			A-3B	141
11-45BD-1			A-3C	143
11-45BD-1			A-11	145
11-45BD-1			A-14	147
11-45C-1		Turret—lower gun	A-2	137
11-45C-1		" — retractable lower gun	A-13	139
11-45C-1		" — upper gun	A-1	133
11-45C-1			A-1A	135
11-45C-1		Unit—double power hydraulic	AA-16801	169
11-45C-1			AA-16801	171
11-45D-1		Turret—tail gun	A-6	165
11-45F-1		" —upper training	A-8	155
11-50-1		Director—torpedo	Mk 28, Mod. 2	248
11-50-2			Mk 28, Mod. 2	248
11-50-3			H-2	249
11-60-1		Pilot—automatic	C-1	268
11-60-1		Panel—autopilot control	A-6A	232
11-60AA-1		Indicator—pilot director	Mk 15, Mod. 5	265
11-60AA-1		Pilot—automatic	C-1	268
12	Navy Type	Solenoid—gun	E-6	102
12-12	Ord C.re. Letter	Slide, retracting, group assembly	D28,500A	311
14D1G1	Mfr's Dwg.	Solenoid—gun	G-1A	114
14D1G1			G-9	116
14D2G1			G-8	115
14D2G1		Trigger—electric AN-M1		120
14D3G1		Solenoid—gun	G-10	104
14D3G4			E-4	101
14D3G4			E-6	102
14D5G3			G-11	117
14D8	Mfr's Model	Trigger—manual	A-1	127
14D11G1	Mfr's Dwg.	Solenoid—gun	G-16	105
14D14G1			G-13	118
14D14G1			G-15	119
14D22G3			G-8	115
14D22G3	" "	Trigger—electric AN-M1		120
14D26G1	Mfr's Dwg. & Mod.	Control—bomb arming	AN-A-1	236
14D26G1			AN-A-2	237
14D26G4			B-2	238
14D27G1	Mfr's Dwg.	Mount—bomb arming control	A-1	262
14DG1		Solenoid—gun	G-10	104
17-1-44	Army T.O.	Tachometer—bombsight disc speed	4050 and 4050A	292
18-2-1	Ord. Dwg.	Mount, gun, airplane, 75-mm., M6		318
18T22	Navy Spec.	Tachometer—bombsight disc speed	4050 and 4050A	292
19-G	Mfr's Model	Adapter—gun mount		5
19-G	" "	Mount—gun	H-1	61
24	Navy Type	Solenoid—gun	G-10	104
29F4824	Mfr's Dwg.	Turret—tail gun	A-6	165
30-616*	Army & Mfr's Dwg.	Box—ammunition	L-4	21
30-616*	" " "		L-7	22
31-808*	" " " "	Barrel—gun charging turnbuckle		19
31B1184	" Dwg.	Handle—gun charging	A-2	46
32B1644	" "	Bolt and bracket—gun trunnion	A-3	20
32F5800	Mfr's Spec.	Turret—tail gun	A-6	165
32F5800-3	Mfr's Dwg.		A-6	165
33B2523	Army Part	Shackle—bomb	D-3	285
33B2523	" "		D-5	286
33D5226	" Dwg.		B-7	282
33K2512*	" & Mfr's Dwg.		D-3	285
33K2512*	" " " "		D-5	286
34B6051	" Dwg.	Solenoid—left hand gun	C-4B	106
34B6051	" "	" —right hand gun	C-4B	108
35A2539	" "	Rack—bomb	N-5	275
35A2539	" "		Q-2	276
35A5243	" Part	Solenoid—gun	E-4	101

Note* Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
36D3891*	Army & Mfr's Dwg.	Box—ammunition	O-1	23
36-6108	Mfr's Dwg.	" — "	L-4	21
36-6108	" "	" — "	L-7	22
36H5311*	Army & Mfr's Dwg.	Hoist—bomb	C-3	260
37A5810*	" " " "	Sight—flexible gun post	A-5	77
37A5811*	" " " "	" — " " ring	B-11	80
37B2301*	" " " "	Solenoid—left hand gun	C-4B	106, 107
37B2301*	" " " "	" — " " "	C-4C	111
37B2301*	" " " "	" —right hand gun	C-4B	108, 109
37B2301*	" " " "	" — " " "	C-4C	113
37B2301-1*	A. Part-Mfr. Dwg	" —left hand gun	C-4B	107
37B2301-1*	" " " "	" —left hand gun	C-4C	111
37B2301-1*	" " " "	" —right hand gun	C-4B	108, 109
37B2301-1*	" " " "	" — " " "	C-4C	113
37B2675*	Army & Mfr's Dwg.	Mount—left hand ammunition box	C-2	54
37B2675*	" " " "	" — " " "	C-3	56
37B2675	" Dwg.	Mount—right hand ammunition box	C-2	55
37B2675-1*	A. Part-Mfr. Dwg.	" — " " "	C-3	57
37B3574*	Army & Mfr's Dwg.	Sight—flexible gun ring	B-10	79
37B2578*	" " " "	" — " " post	A-4	76
37B3675-1*	" " " "	Mount—right hand ammunition box	C-2	55
37D2077*	" " " "	Container—ejected link	A-3	31
37D2077*	" " " "	" — " " "	A-4	32
37D2077*	" " " "	" — " " "	A-5	33
37D4929*	" " " "	Adapter—gun mount	C-12	6
37D5641	" Dwg.	Container—ejected case	A-4	29
37D5641*	" & Mfr's Dwg.	" — " " "	A-5	30
37D5642*	" " " "	Container—ejected link	A-3	31
37D5642*	" " " "	" — " " "	A-4	32
37D5642*	" " " "	" — " " "	A-5	33
37E5013*	" " " "	Shackle—bomb	D-6	287
37G4926	" Dwg.	Adapter—gun mount	C-12	6
37G6581*	" & Mfr's Dwg.	Mount—gun	G-1A	59
37G6581*	" " " "	" — " " "	G-5	60
37K4961	" Dwg.	Hoist—bomb	C-3	260
38A1782	" Part	Sight—fixed gun	N-3A	85
38B1942	" Dwg.	Post—gun mounting	A-4	73
38B5990	" " " "	Handle—bomb release	L-21A	253
38D4829*	" & Mfr's Dwg.	Generator—gun synchronizer	E-8	97
38D5089	" Dwg.	Handle—bomb release	L-21A	253
39A2389	" Part	Sight—fixed gun	N-3A	85
39A2389	" " " "	Solenoid—gun	E-4	101
39B3829	" " " "	Shackle—bomb	D-3	285
39B3829	" " " "	" — " " "	D-5	286
39B3905	" Dwg.	Mount—left hand ammunition box	C-3	56
39B3905	" " " "	" —right hand ammunition box	C-3	57
39B3905-L*	" & Mfr's Dwg.	" —left hand ammunition box	C-2	54
39B3905-L*	" " " "	" — " " "	C-3	56
39B3905-R*	" " " "	" —right hand ammunition box	C-2	55
39B3905-R*	" " " "	" — " " "	C-3	57
39G4407*	" " " "	Rack—bomb	N-6	275
39G4427*	" " " "	" — " " "	Q-2	276
39G5016	" Dwg.	Adapter—gun mount	E-5	12
39K3828*	" & Mfr's Dwg.	Shackle—bomb	D-3	285
39K3828*	" " " "	" — " " "	D-5	286
40A6792	" Part	Hoist—bomb	C-3	260
40B7830*	" & Mfr's Dwg.	Sight—telescopic gun	E-5	82
40D585R	" Dwg.	Mount—ammunition box	A-3	53
40D6090*	" & Mfr's Dwg.	" —flexible gun sight	C-4	58
40G6567*	" " " "	Adapter—gun mount	C-17	8
40G6567*	" " " "	Mount—ball and socket gun	K-2	63
40G6567*	" " " "	" —ball and socket gun	K-2A	64
40G6567*	" " " "	" —ball and socket gun	K-3	65
40G6567	" Dwg.	Mount assembly—ball and socket gun	K-1	62
40G7385*	" & Mfr's Dwg.	Container—ejected case	A-4	29

Note* Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
40G7385*	Army & Mfr's Dwg.	Container—ejected case	A-5	30
40G7402	" Dwg.	Holder—ammunition box	A-1	47
40K3852	" "	Adapter—gun mount	C-16	7
41A9227	" Part	Solenoid—gun	G-4A	114
41A9227	" "	"	G-13	118
41B2679*	Army & Mfr's Dwg.	Adapter—gun mount	E-10	15
41B3718*	" " " "	Solenoid—gun	G-4A	114
41B3718*	" " " "	"	G-9	116
41B5099L*	" " " "	" —left hand gun	C-4B	107
41B5099L*	" " " "	" —right hand gun	C-4C	110, 111
41B5099L*	" " " "	" — " " "	C-4B	109
41B5099L*	" " " "	" — " " "	C-4C	113
41B5099R*	" " " "	" —left hand gun	C-4B	107
41B5099R*	" " " "	" — " " "	C-4C	111
41B5099R*	" " " "	" —right hand gun	C-4B	109
41B5099R*	" " " "	" — " " "	C-4C	113
41B5641*	" " " "	Mount—ball and socket gun	K-2	63
41B5641*	" " " "	"	K-2A	64
41B5641*	" " " "	"	K-3	65
41B5641*	" " " "	Mount assembly—ball and socket gun	K-1	62
41B8946*	" " " "	Switch—control stick gun	B-6	125
41B10360*	" " " "	Mount—ball and socket gun	K-2	63
41B10360*	" " " "	"	K-2A	64
41B10360*	" " " "	"	K-3	65
41B10360*	" " " "	Mount assembly—ball and socket gun	K-1	62
41B10395*	" " " "	Handle—bomb and flare release	A-3A	251
41B10395*	" " " "	" — " and flare release	A-3B	252
41B10395*	" " " "	Handle—bomb release	A-3	250
41D1831	" Dwg.	Control—bomb release interval	B-2	240
41D3024*	& Mfr's Dwg.	Support—gun sight image reflector	41D3024	122
41D3024*	" " " "	"	41D4892	121
41D4892*	" " " "	"	41D3024	122
41D4892*	" " " "	"	41D4892	121
41D5642*	" " " "	Adapter—gun mount	C-17	8
41D5642*	" " " "	"	C-18	9
41D6865*	" " " "	Yoke—gun mount adapter	41D6865	129
41D9625*	" " " "	Sight—flexible gun	N-6	87
41D9625*	" " " "	"	N-6A	89
41D9625*	" " " "	"	N-8	91
41D10395*	" " " "	Handle—bomb release	A-3	250
41D10802	" Dwg.	Control—bomb release interval	B-2A	241
41D11020*	& Mfr's Dwg.	Adapter—gun mount	C-17	8
41D11020*	" Dwg.	" — " "	C-18	9
41D11038*	& Mfr's Dwg.	Container—ejected link	A-3	31
41D11038*	" " " "	" — " "	A-4	32
41D11038*	" " " "	" — " "	A-5	33
41E4555	" Dwg.	Shackle—bomb	D-6	287
41G1742	" " "	Release—bomb rack left hand	A-2	278
41G1742-1	" " "	" — " right hand	A-2	279
41G6410*	& Mfr's Dwg.	Mount—gun	H-1	61
41G6436*	" " " "	Sight—fixed gun	N-3A	85
41G6436*	" " " "	"	N-3B	86
41G8920	" Dwg.	Holder—pyrotechnic pistol	A-1	48
41G9233*	& Mfr's Dwg.	Container—signal flare	A-1	34
41G10752*	" " " "	Mount—gun	G-1A	59
41G10752*	" " " "	"	G-5	60
41K3850*	" " " "	Adapter—gun mount	E-8	14
42-39	Ord. Dwg.	Discharger, pyrotechnic, AN-M5		326
42-44	" " "	Pistol, pyrotechnic, AN-M8, w/mount		330
42A8317*	Army & Mfr's Dwg.	Sight—flexible gun post	A-11	78
42B3980*	" " " "	Motor—trigger	E-3	99
42B3980*	" " " "	"	E-3A	100
42B7343*	" " " "	Solenoid—gun	G-13	118
42B7343*	" " " "	"	G-15	119
42B8318*	" " " "	Sight—flexible gun ring	B-13	81

Note* Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used In Connection with	Type, Drawing or Designation	Page
42B12323	Army Dwg.	Mount—ball and socket gun.	K-3	65
42B19084	" "	" " " "	K-4	66
42C10439	" "	Charger, manual, M2.	B-6	3A
42D3116	" "	Control—bomb release interval	AN-B-3	242
42D6433	" "	Sling—bomb hoist.	A-2	290
42D6859*	Army & Mfr's Dwg.	Box—ammunition	L-4	21
42D6859*	" " " "	" " " "	L-7	22
42D7807*	" " " "	Shackle—bomb	AN-B-9	283
42D19090	" Dwg.	Adapter—gun mount	C-19	10
42E7219	" "	Shackle—bomb	D-7	28H
42G2343	" "	Sling—bomb hoist.	A-1	289
42G2343-6	" Part	" " " "	A-1	289
42G11966*	Army & Mfr's Dwg.	Container—signal flare	A-5	35
42G11967	" Dwg.	" " " "	A-6	36
42G14292*	" & Mfr's Dwg.	Sight—flexible gun.	N-6	87
42G14292	" " " "	" " " "	N-6A	89
42G14292*	" " " "	" " " "	N-8	91
42G20092*	" Dwg.	" —fixed gun	N-3A	85
42G20092*	Army & Mfr's Dwg.	" " " "	N-3B	86
42H11968	" Dwg.	Container—signal flare	A-7	37
42J11770	" "	Mount—bombsight	B-7	263
42K0078	" "	Adapter—gun mount	E-12	1H
42M16384	" "	Cover—electrically heated bombsight.	A-1	244
43A3886	" "	Mount—bomb arming control.	A-1	262
43A15180	" "	Trigger—manual	A-1	127
43A20361	" "	Adapter—box end.	L-2	27
43A20362	" "	" —gun end.	L-1	26
43A20364	" "	Chute—flexible feed	B	25
43B7513	" & Mfr's Dwg.	Rack—bomb	AN-Mk 51 Mod 7	272, 273
43B9887	" Dwg.	Control—bomb arming.	AN-A-2	237
43B11200*	" & Mfr's Dwg.	Receptacle—bomb release.	A-1	277
43B11390*	" " " "	Handle—bomb and flare release	A-3A	251
43B11390*	" " " "	" " " " " "	A-3B	252
43B11390*	" " " "	Handle—bomb release	A-3	250
43B11958	" Dwg.	Control—bomb arming.	B-2	23H
43B15328	" Part	Ring—pilot's bombsight adapter.	43B15328	256
43D10157*	" & Mfr's Dwg.	Shackle—bomb	B-10	284
43D10279	" Dwg.	Mount—grenade	A-1	261
43D12264*	" & Mfr's Dwg.	Head—pilot's bombsight	A-1	255
43D12264*	Mfr's Dwg.	" " " "	A-2	257
43D19996*	" "	" " " "	A-1	255
43D19996*	Army & Mfr's Dwg.	" " " "	A-2	257
43G7044*	" " " "	Holder—pyrotechnic pistol.	A-2	49
43G7095*	Army & Mfr's Dwg.	Director—torpedo	B-2	249
43G10872	" Dwg.	Mount—swivel gun.	K-5	67
43G16373	" "	Director—torpedo	B-2	249
48-22	" Spec.	Handle—bomb release	A-3	250
51-57-3	Ord. Dwg.	Gun, machine, caliber .30 Browning, M2, aircraft fixed.		305
51-57-3A	" "	" " " " " " " "		305
51-76-1	" "	" " " " " " M2, aircraft flexible		30H
51-76-1A	" "	" " " " " " " "		30H
51-82-1	" "	" " " " " " 50 Browning M2, aircraft, basic		309
51-82-1A	" "	" " " " " " " "		309
51-92	" "	" automatic, 37-mm., M4.		296
51-105-4	" "	" aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		299
51-107-1	" "	" " " " " " " "		299
51-122-1	" "	" machine, caliber .30 Browning M2, aircraft flexible,		
		with fixed back plate.		307
51-122-1A	" "	Gun, machine, caliber .30 Browning M2, aircraft flexible,		
		with fixed back plate.		307
52-243-1	Ord. Dwg. No.	Mount, gun, airplane, 75-mm., M6.		31H
52-400	A.E. Ref. No.	Adapter—gun mount		5
52-100	A.E. Ref. No.	Mount—gun	H-1	61
52-500	A.E. Ref. No.	Adapter—gun mount	C-12	6
52-500	A.E. Ref. No.	Container—ejected case	A-4	29

Note: Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
52-600	A.E. Ref. No.	Adapter—gun mount	C-12	6
52-600	A.E. Ref. No.	Adapter—gun mount	C-16	7
52-600	A.E. Ref. No.	Mount—gun	G-1A	59
52-600	" " "	" " "	G-5	60
52-700	A.E. Ref. No.	Adapter—gun mount	G-17	8
52-700	A.E. Ref. No.	Mount—ball and socket gun	K-2	63
52-700	" " "	" " " " "	K-2A	64
52-700	" " "	" " " " "	K-3	65
52-800	A.E. Ref. No.	Adapter—gun mount	C-18	9
52-800	A.E. Ref. No.	Mount—ball and socket gun	K-2	63
52-800	" " "	Mount—ball and socket gun	K-3	65
52-850	A.E. Ref. No.	Adapter—gun mount	C-19	10
52-850	A.E. Ref. No.	Mount—ball and socket gun	K-4	66
52-875	A.E. Ref. No.	Adapter—gun mount	E-5	12
52-875	A.E. Ref. No.	Mount—flexible gun sight	C-4	58
52-900	" " "	Adapter assembly—gun mount—50 cal. with yoke	E-5	Not catalogued
52-1000	A.E. Ref. No.	Adapter—gun mount	E-5A	11
52-1100	A.E. Ref. No.	Adapter—gun mount	E-8	14
52-1100	A.E. Ref. No.	Adapter—gun mount	E-10	15
52-1100	" " "	Box—ammunition	O-1	23
52-1100	" " "	Mount—flexible gun sight	C-4	58
52-1100	" " "	Sight—flexible gun post	A-11	78
52-1100	" " "	" " " " ring	B-13	81
52-1100	" " "	Yoke—gun mount adapter	41D6865	129
52-1150	" " "	Adapter assembly—gun mount		Not catalogued
52-1200	A.E. Ref. No.	Adapter—gun mount	E-10	15
52-1300	A.E. Ref. No.	Adapter—gun mount	C-19	10
52-1300	" " "	" " " "	E-5	12
52-1300	A.E. Ref. No.	Adapter—gun mount	E-11	16
52-1300	A.E. Ref. No.	Box—ammunition	O-1	23
52-1300	" " "	Mount—ball and socket gun	K-4	66
52-1300	" " "	" —gun	H-1	61
52-1300	" " "	" —swivel gun	K-5	67
52-1325	" " "	Adapter—gun mount	E-8	14
52-1325	" " "	" " " "	E-10	15
52-1325	A.E. Ref. No.	Adapter—gun mount	E-12	18
52-1325	A.E. Ref. No.	Mount—gun	H-1	61
52-1400	A.E. Ref. No.	Barrel—gun charging turnbuckle		19
52-1450	A.E. Ref. No.	Bolt and bracket—gun trunnion	A-3	20
52-1450	A.E. Ref. No.	Post—gun mounting	A-4	73
52-1500	A.E. Ref. No.	Box—ammunition	L-4	21
52-1500	A.E. Ref. No.	Holder—ammunition box	A-1	47
52-1550	" " "	Box—ammunition	L-4	21
52-1550	A.E. Ref. No.	Box—ammunition	L-7	22
52-1550	A.E. Ref. No.	Holder—ammunition box	A-1	47
52-1600	A.E. Ref. No.	Box—ammunition	O-1	23
52-1600	A.E. Ref. No.	Mount—left hand ammunition box	C-2	54
52-1600	" " "	" " " " " "	C-3	56
52-1600	" " "	" —right hand ammunition box	C-2	55
52-1600	" " "	" " " " " "	C-3	57
52-1650	" " "	Box assembly—machine gun electric synchronizer control	A-3	Not catalogued
52-1685	" " "	Bracket—gun trunnion	A-1	Not catalogued
52-1720	" " "	Central station fire control system—A-26		215
52-1720	" " "	" " " " " " —B-29		173
52-1720	" " "	" " " " " " —P-61		206
52-1720	A.E. Ref. No.	Charger—gun	T-8252878	182, 213, 226
52-1720	A.E. Ref. No.	Turret—lower aft gun	2CGD50LRC5	199
52-1720	" " "	" — " forward gun	2CGD50LRC4	201
52-1720	" " "	" — " gun	2CGD50LRC1	223
52-1720	" " "	" —upper aft gun	2CGD50URC4	203
52-1720	" " "	" — " forward gun	2CGD50URC3	203
52-1720	" " "	" — " gun	2CGD50URC1	225
52-1722	" " "	Adapter—box end	L-2	27
52-1722	" " "	" —gun end	L-1	26
52-1722	" " "	Chute—flexible feed	A	28
52-1722	A.E. Ref. No.	Chute—flexible feed	B	25



NUMERICAL INDEX
ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
52-1723	A.E. Ref. No.	Adapter—box end	B	27
52-1723	A.E. Ref. No.	Adapter—gun end	L-1	26
52-1723	A.E. Ref. No.	Chute—flexible feed	B	25
52-1724	A.E. Ref. No.	Adapter—box end	L-2	27
52-1724	A.E. Ref. No.	Adapter—gun end	L-1	26
52-1724	" " "	Chute—flexible feed	B	25
52-1730	A.E. Ref. No.	Chute—flexible feed	A	28
52-1730	A.E. Ref. No.	Chute—flexible feed	B	25
52-1750	A.E. Ref. No.	Chute—flexible feed	A	28
52-1750	A.E. Ref. No.	Chute—flexible feed	B	25
52-1760	A.E. Ref. No.	Chute—flexible feed	A	28
52-1760	A.E. Ref. No.	Chute—flexible feed	B	25
52-1770	A.E. Ref. No.	Chute—flexible feed	A	28
52-1770	A.E. Ref. No.	Chute—flexible feed	B	25
52-1790	A.E. Ref. No.	Chute—flexible feed	A	28
52-1790	A.E. Ref. No.	Chute—flexible feed	B	25
52-1800	A.E. Ref. No.	Chute—flexible feed	A	28
52-1800	A.E. Ref. No.	Chute—flexible feed	B	25
52-1810	A.E. Ref. No.	Chute—flexible feed	A	28
52-1810	A.E. Ref. No.	Chute—flexible feed	B	25
52-1950	A.E. Ref. No.	Container—ejected case	A-1	29
52-2000	A.E. Ref. No.	Container—ejected case	A-1	29
52-2000	A.E. Ref. No.	Container—ejected case	A-5	30
52-2100	A.E. Ref. No.	Container—ejected link	A-3	31
52-2150	A.E. Ref. No.	Container—ejected link	A-1	32
52-2200	A.E. Ref. No.	Container—ejected link	A-3	31
52-2200	" " "	" " " "	A-4	32
52-2200	A.E. Ref. No.	Container—ejected link	A-5	33
52-2250	A.E. Ref. No.	Container—signal flare	A-1	34
52-2250	A.E. Ref. No.	Holder—pyrotechnic pistol	A-1	48
52-2252	" " "	Container assembly—signal flare	A-3	Not catalogued
52-2253	" " "	" " " "	A-4	Not catalogued
52-2254	A.E. Ref. No.	Container—signal flare	A-5	35
52-2254	A.E. Ref. No.	Holder—pyrotechnic pistol	A-2	49
52-2255	A.E. Ref. No.	Container—signal flare	A-6	36
52-2255	A.E. Ref. No.	Holder—pyrotechnic pistol	A-2	49
52-2256	" " "	Container—signal flare	A-1	34
52-2256	A.E. Ref. No.	Container—signal flare	A-7	37
52-2256	A.E. Ref. No.	Holder—pyrotechnic pistol	A-2	49
52-2257	" " "	Container assembly—signal flare	A-8	Not catalogued
52-2275	" " "	Charger—20-mm. hydraulic gun	D-3	39
52-2275	A.E. Ref. No.	Charger, manual, M2	B-6	38
52-2275	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298
52-2275	" " "	Handle—gun charging	A-2	46
52-2300	A.E. Ref. No.	Charger—20-mm. hydraulic gun	D-3	39
52-2300	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298
52-2300	" " "	Valve—hydraulic gun charging	A-1	128
52-2400	A.E. Ref. No.	Charger—.30 caliber hydraulic gun	D-1	40
52-2400	A.E. Ref. No.	Valve—hydraulic gun charging	A-1	128
52-2500	A.E. Ref. No.	Charger—.50 caliber hydraulic gun	D-2	41
52-2500	A.E. Ref. No.	Valve—hydraulic gun charging	A-1	128
52-2575	" " "	Central station fire control system—P-61		206
52-2575	A.E. Ref. No.	Dynamotor	5D21FJ2A	210
52-2580	A.E. Ref. No.	Central station fire control system—A-26		215
52-2580	" " "	" " " " " " —B-29		173
52-2580	A.E. Ref. No.	Dynamotor	5D21NJ3	187, 219
52-2600	A.E. Ref. No.	Ends—impulse unit	E-3	98
52-2600	A.E. Ref. No.	Generator—gun synchronizer impulse	E-8	97
52-2600	" " "	Motor—trigger	E-3	99
52-2600	" " "	" " " "	E-1A	100
52-2680	A.E. Ref. No.	Feed—left hand upper continuous	CF-3L	43
52-2680	A.E. Ref. No.	Feed—lower continuous	CF-5	45
52-2681	" " "	" " " "	CF-5	45
52-2681	A.E. Ref. No.	Feed—right hand upper continuous	CF-3R	44
52-2682	A.E. Ref. No.	Feed—left hand upper continuous	CF-3L	43
52-2682	A.E. Ref. No.	Feed—lower continuous	CF-5	45



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
52-2682	A.E. Ref. No.	Feed—right hand upper continuous.	CF-3R	44
52-2700	" " "	Ends—impulse unit	E-3	98
52-2700	A.E. Ref. No.	Generator—gun synchronizer impulse	E-8	97
52-2700	A.E. Ref. No.	Motor—trigger	M-3 Mk 1	99
52-2700	" " "	" " "	E-3A	100
52-2700	" " "	Solenoid—gun	G-10	104
52-2750	A.E. Ref. No.	Handle—gun charging	A-2	46
52-2765	A.E. Ref. No.	Heater—gun L.H.	J-1	Not catalogued
52-2766	" " "	Heater—gun R.H.	J-1	Not catalogued
52-2800	" " "	Box—ammunition	L-4	21
52-2800	" " "	" " "	L-7	22
52-2800	A.E. Ref. No.	Holder—ammunition box	A-1	47
52-2800	A.E. Ref. No.	Mount—ammunition box	A-3	53
52-2825	A.E. Ref. No.	Holder—pyrotechnic pistol	A-1	48
52-2825	A.E. Ref. No.	Pistol, pyrotechnic, M2		327
52-2826	" " "	Container—signal flare	A-5	35
52-2826	" " "	" " "	A-6	36
52-2826	" " "	" " "	A-7	37
52-2826	A.E. Ref. No.	Holder—pyrotechnic pistol	A-2	49
52-2850	A.E. Ref. No.	Motor assembly—machine gun electric synchronizer trigger	A-1	Not catalogued
52-2900	A.E. Ref. No.	Motor—trigger	E-3	99
52-3000	A.E. Ref. No.	Ends—impulse unit	E-3	98
52-3000	" " "	Generator—gun synchronizer impulse	E-8	97
52-3000	" " "	Motor trigger	E-3	99
52-3000	A.E. Ref. No.	Motor trigger	E-3A	100
52-3030	A.E. Ref. No.	Motor—azimuth turret drive	5BA50LJ1	51
52-3030	" " "	" — elevation turret drive	5BA60GJ1	52
52-3030	A.E. Ref. No.	Motor generator—amplidyne local control	5AM31NJ18	50
52-3040	A.E. Ref. No.	Central station fire control system—A-26		215
52-3040	" " "	" " " " " —B-29		173
52-3040	" " "	" " " " " —P-61		206
52-3040	" " "	Motor—turret drive	5BA50IJ2A	227
52-3040	A.E. Ref. No.	Motor generator—amplidyne remote control	5AM31NJ9	189, 211, 220
52-3040	A.E. Ref. No.	Turret—lower aft gun	2CGD50LRC5	199
52-3040	" " "	" — " forward gun	2CGD50LRC4	201
52-3040	" " "	" — " gun	2CGD50LRC1	223
52-3040	" " "	" —upper aft gun	2CGD50URC4	203
52-3040	" " "	" — " forward gun	2CGD50URC3	205
52-3040	" " "	" — " gun	2CGD50URC1	225
52-3045	" " "	Central station fire control system—B-29		173
52-3045	" " "	Drive—tail gun mount azimuth	W-8258810	185
52-3045	" " "	" — " " " elevation	W-8258807	186
52-3045	A.E. Ref. No.	Motor—generator—amplidyne remote control	5AM61NJ1C	190
52-3060	A.E. Ref. No.	Motor—azimuth turret drive	5BA50LJ1	51
52-3060	A.E. Ref. No.	Motor generator—amplidyne local control	5AM31NJ18	50
52-3065	A.E. Ref. No.	Motor—turret drive	5BA50IJ2A	227
52-3065	A.E. Ref. No.	Turret—lower aft gun	2CGD50LRC5	199
52-3065	" " "	" — " forward gun	2CGD50LRC4	201
52-3065	" " "	" — " gun	2CGD50LRC1	223
52-3065	" " "	" —upper aft gun	2CGD50URC4	203
52-3065	" " "	" — " forward gun	2CGD50URC3	205
52-3065	" " "	" — " gun	2CGD50URC1	225
52-3070	A.E. Ref. No.	Motor—elevation turret drive	5BA50GJ1	52
52-3070	A.E. Ref. No.	Motor generator—amplidyne local control	5AM31NJ18	50
52-3100	A.E. Ref. No.	Mount—ammunition box	A-3	53
52-3200	A.E. Ref. No.	Box—ammunition	O-1	23
52-3200	" " "	Chute—flexible feed	A	28
52-3200	A.E. Ref. No.	Mount—left hand ammunition box	C-2	54
52-3300	A.E. Ref. No.	Box—ammunition	O-1	23
52-3300	" " "	Chute—flexible feed	A	28
52-3300	A.E. Ref. No.	Mount—right hand ammunition box	C-2	55
52-3360	A.E. Ref. No.	Box—ammunition	O-1	23
52-3350	" " "	Chute—flexible feed	A	28
52-3350	" " "	Mount—left hand ammunition box	C-2	54
52-3350	A.E. Ref. No.	Mount—left hand ammunition box	C-3	56
52-3350	A.E. Ref. No.	Mount—right hand ammunition box	C-2	55



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
52-3360	A.E. Ref. No.	Box—ammunition	O-1	23
52-3360	" " "	Chute—flexible feed	A	28
52-3360	A.E. Ref. No.	Mount—right hand ammunition box	C-3	57
52-3380	A.E. Ref. No.	Mount assembly—ammunition box L.H.	C-4	Not catalogued
52-3381	" " "	" " " " R.H.	C-4	Not catalogued
52-3390	" " "	" " " " L.H.	C-5	Not catalogued
52-3391	" " "	" " " " R.H.	C-5	Not catalogued
52-3400	A.E. Ref. No.	" —flexible gun sight	C-4	58
52-3400	A.E. Ref. No.	Sight—telescopic gun	E-5	82
52-3500	A.E. Ref. No.	Mount—gun	G-1A	59
52-3550	A.E. Ref. No.	Mount assembly—gun	G-4	Not catalogued
52-3600	" " "	Mount—gun	G-1A	59
52-3600	A.E. Ref. No.	Mount—gun	G-5	60
52-3700	A.E. Ref. No.	Mount—gun	H-1	61
52-3800	A.E. Ref. No.	Mount—ball and socket gun	K-2	63
52-3800	A.E. Ref. No.	Mount assembly—ball and socket gun	K-1	62
52-3850	A.E. Ref. No.	Adapter—gun mount	C-17	8
52-3850	" " "	" " " "	C-18	9
52-3850	A.E. Ref. No.	Mount—ball and socket gun	K-2	63
52-3900	A.E. Ref. No.	Adapter—gun mount	C-17	8
52-3900	" " "	" " " "	C-18	9
52-3900	A.E. Ref. No.	Mount—ball and socket gun	K-2A	64
52-3950	A.E. Ref. No.	Adapter—gun mount	C-17	8
52-3950	" " "	" " " "	C-18	9
52-3950	" " "	Mount—ball and socket gun	K-2	63
52-3950	" " "	" " " "	K-2A	64
52-3950	A.E. Ref. No.	Mount—ball and socket gun	K-3	65
52-3950	A.E. Ref. No.	Mount assembly—ball and socket gun	K-1	62
52-3960	" " "	Adapter—gun mount	C-19	10
52-3960	A.E. Ref. No.	Mount—ball and socket gun	K-4	66
52-3966	A.E. Ref. No.	Mount—swivel gun	K-5	67
52-3975	A.E. Ref. No.	Mount—gun	M-1	69
52-3978	A.E. Ref. No.	Mount—gun	M-5	72
52-3980	A.E. Ref. No.	Mount—gun	M-6	71
52-3985	A.E. Ref. No.	Mount—gun	M-7	Not catalogued
52-4000	" " "	Plunger assembly—gun synchronizer control	A-1	Not catalogued
52-4100	A.E. Ref. No.	Post—gun mounting	A-4	73
52-4125	A.E. Ref. No.	Regulator—computer voltage		Not catalogued
52-4150	A.E. Ref. No.	Rheostat—variable resistance	D-1	123
52-4210	A.E. Ref. No.	Central station fire control system—P-61		206
52-4210	" " "	Drive—tail gun mount azimuth	W-8258810	185
52-4210	" " "	" " " " elevation	W-8258807	186
52-4210	A.E. Ref. No.	Selsyn	2J161	212
52-4210	A.E. Ref. No.	Turret—lower aft gun	2CGD50LRC5	199
52-4210	" " "	" " " forward gun	2CGD50LRC4	201
52-4210	" " "	" " " gun	2CGD50LRC1	223
52-4210	" " "	" " " upper aft gun	2CGD50URC4	203
52-4210	" " "	" " " forward gun	2CGD50URC3	205
52-4210	" " "	" " " gun	2CGD50URC1	225
52-4250	A.E. Ref. No.	Sight—automatic compensating gun	K-3	92
52-4260	A.E. Ref. No.	Sight—automatic compensating gun	K-4	93
52-4263	A.E. Ref. No.	Sight assembly—auxiliary ring and bead		Not catalogued
52-4264	" " "	" " " " " " " "		Not catalogued
52-4270	A.E. Ref. No.	Sight—compensating	K-8	93
52-4272	A.E. Ref. No.	Sight assembly—compensating	K-9	Not catalogued
52-4273	" " "	" " " —automatic compensating	K-10	Not catalogued
52-4274	" " "	" " " " " " " "	K-11	Not catalogued
52-4275	" " "	" " " —fixed gun	N-2A	Not catalogued
52-4300	" " "	" " " " " " " "	N-3	Not catalogued
52-4400	" " "	Head—pilot's bombsight	A-1	255
52-4400	" " "	" " " " " " " "	A-2	257
52-4400	A.E. Ref. No.	Sight—fixed gun	N-3A	85
52-4400	A.E. Ref. No.	Support—gun sight image reflector	41D3024	122
52-4400	" " "	" " " " " " " "	41D4892	121
52-4425	" " "	Head—pilot's bombsight	A-1	255
52-4425	" " "	" " " " " " " "	A-2	257



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
52-4425	A.E. Ref. No.	Sight—fixed gun	N-3A	85
52-4425	A.E. Ref. No.	Sight—fixed gun	N-3B	86
52-4425	A.E. Ref. No.	Support—gun sight image reflector	41D3024	122
52-4425	" " "	" " " "	41D4892	121
52-4450	" " "	Sight assembly—fixed gun	N-5	Not catalogued
52-4500	" " "	Head—pilot's bombsight	A-1	255
52-4500	" " "	Head—pilot's bombsight	A-2	257
52-4500	" " "	Mount—gun	M-1	69
52-4500	" " "	Rheostat—variable resistance	D-1	123
52-4500	" " "	Ring—pilot's bombsight adapter	43B15328	256
52-4500	A.E. Ref. No.	Sight—flexible gun	N-6	87
52-4525	A.E. Ref. No.	Head—pilot's bombsight	A-1	255
52-4525	" " "	" " " "	A-2	257
52-4525	" " "	Rheostat—variable resistance	D-1	123
52-4525	" " "	Ring—pilot's bombsight adapter	43B15328	256
52-4525	" " "	Sight—flexible	N-6	87
52-4525	A.E. Ref. No.	Sight—flexible gun	N-6A	89
52-4530	A.E. Ref. No.	Sight assembly—fixed gun	N-7	Not catalogued
52-4550	" " "	Mount—gun	M-6	71
52-4550	A.E. Ref. No.	Sight—flexible gun	N-8	91
52-4550	A.E. Ref. No.	Sight—illuminated	Mark 9	90
52-4600	A.E. Ref. No.	Sight—flexible gun post	A-4	76
52-4600	A.E. Ref. No.	Sight—flexible gun ring	B-10	79
52-4700	" " "	Mount—gun	M-5	72
52-4700	A.E. Ref. No.	Sight—flexible gun post	A-5	77
52-4700	A.E. Ref. No.	Sight—flexible gun ring	B-11	80
52-4725	" " "	" assembly—flexible gun post	A-6	Not catalogued
52-4750	" " "	" " " " " "	A-8	Not catalogued
52-4800	" " "	" " " " " " .30 caliber	A-9	Not catalogued
52-4825	" " "	" " " " " " " "	A-10	Not catalogued
52-4850	A.E. Ref. No.	Sight—flexible gun post	A-11	78
52-4850	A.E. Ref. No.	Sight—flexible gun ring	B-13	81
52-4852	" " "	" assembly—flexible gun post	A-12	Not catalogued
52-4900	" " "	" —flexible gun post	A-4	76
52-4900	A.E. Ref. No.	Sight—flexible gun ring	B-10	79
52-5000	A.E. Ref. No.	Mount—gun	M-5	72
52-5000	" " "	Sight—flexible gun post	A-5	77
52-5000	A.E. Ref. No.	Sight—flexible gun ring	B-11	80
52-5050	A.E. Ref. No.	Sight—flexible gun post	A-11	78
52-5050	A.E. Ref. No.	Sight—flexible gun ring	B-13	81
52-5100	A.E. Ref. No.	Sight assembly—flexible gun ring	B-14	Not catalogued
52-5110	" " "	" —flexible gun ring	B-11	80
52-5110	" " "	" assembly—flexible gun ring	B-15	Not catalogued
52-5200	" " "	" " " " " "	L-2	Not catalogued
52-5300	" " "	Mount—flexible gun sight	C-4	58
52-5300	" " "	Sight assembly—telescopic (ordnance M-7) .30 and .50 caliber		Not catalogued
52-5350	" " "	Mount—flexible gun sight	C-4	58
52-5350	A.E. Ref. No.	Sight—telescopic gun	E-5	87
52-5370	A.E. Ref. No.	Sight—illuminated	Mk 8	83
52-5375	A.E. Ref. No.	Mount—gun	M-6	71
52-5375	A.E. Ref. No.	Sight—illuminated	Mk 9	90
52-5385	A.E. Ref. No.	Sight assembly—tail gun telescopic model 323	Q-3	Not catalogued
52-5390	A.E. Ref. No.	Solenoid—left hand gun	C-4B	106
52-5395	A.E. Ref. No.	Solenoid—right hand gun	C-4B	108
52-5400	A.E. Ref. No.	Solenoid—left hand gun	C-4B	106
52-5400	A.E. Ref. No.	Solenoid—left hand gun	C-4C	110
52-5450	A.E. Ref. No.	Solenoid—right hand gun	C-4B	108
52-5450	A.E. Ref. No.	Solenoid—right hand gun	C-4C	112
52-5500	A.E. Ref. No.	Solenoid—gun	E-8	103
52-5500	" " "	" assembly—gun	E-2A	Not catalogued
52-5600	A.E. Ref. No.	Solenoid—gun	E-4	101
52-5625	A.E. Ref. No.	Solenoid assembly—gun (12 volt)	E-5	Not catalogued
52-5650	" " "	" —gun	E-4	101
52-5650	A.E. Ref. No.	Solenoid—gun	E-6	102
52-5660	A.E. Ref. No.	Solenoid assembly—gun (12 volt)		Not catalogued
52-5670	A.E. Ref. No.	Solenoid—gun	E-8	103



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used In Connection with	Type, Drawing or Designation	Page
52-5680	A.E. Ref. No.	Solenoid assembly—gun (12 volt)	E-9	Not catalogued
52-5700	" " "	" " " (24 volt)	G-1	Not catalogued
52-5800	" " "	" " " gun	G-10	184
52-5800	" " "	" " assembly—gun (24 volt)	G-2	Not catalogued
52-5850	" " "	" " " " " "	G-3	Not catalogued
52-5900	" " "	" " " " " "	G-4	Not catalogued
52-6000	A.E. Ref. No.	Solenoid—gun	G-4A	114
52-6100	A.E. Ref. No.	Solenoid—gun	G-8	115
52-6200	A.E. Ref. No.	Solenoid—gun	G-9	116
52-6300	A.E. Ref. No.	Generator—gun synchronizer impulse	E-8	97
52-6300	A.E. Ref. No.	Solenoid—gun	G-10	184
52-6350	" " "	Solenoid—gun	G-11	117
52-6350	A.E. Ref. No.	Trigger—manual	A-1	127
52-6353	" " "	Support—gun sight image reflects	N-2	Not catalogued
52-6357	" " "	Solenoid assembly—gun R.H. (24 volt)	G-12	Not catalogued
52-6360	A.E. Ref. No.	Solenoid—gun	G-13	118
52-6370	A.E. Ref. No.	Solenoid—gun	G-13	118
52-6370	A.E. Ref. No.	Solenoid—gun	G-15	119
52-6375	A.E. Ref. No.	Solenoid—gun	G-16	105
52-6380	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298, 299
52-6380	" " "	Solenoid—gun	G-8	115
52-6380	A.E. Ref. No.	Trigger—electric AN-M1	G-17	120
52-6390	A.E. Ref. No.	Support—gun sight image reflects	N-2	Not catalogued
52-6400	" " "	Sight—fixed gun	N-3A	85
52-6400	" " "	" " " "	N-3B	86
52-6400	A.E. Ref. No.	Support—gun sight image reflector	41D4892	121
52-6450	A.E. Ref. No.	Support—gun sight image reflector	41D3024	122
52-6475	A.E. Ref. No.	Switch—control stick gun	B-1A	124
52-6500	A.E. Ref. No.	Switch—control stick gun	B-4	Not catalogued
52-6600	" " "	Rack—bomb	N-6	275
52-6600	" " "	" " "	Q-2	276
52-6600	" " "	Switch—control stick gun	B-1A	124
52-6600	A.E. Ref. No.	Switch—control stick gun	B-5	125
52-6650	A.E. Ref. No.	Central station fire control system—B-29		173
52-6650	" " "	Rack—bomb	N-5	275
52-6650	" " "	" " "	Q-2	276
52-6650	A.E. Ref. No.	Switch—single pole toggle	AN3022-2	126
52-6650	A.E. Ref. No.	Switch—tail cannon selector	B-5A	197
52-6701	A.E. Ref. No.	Box—control	T-8252925	217
52-6701	A.E. Ref. No.	Central station fire control system—A-26		215
52-6702	A.E. Ref. No.	Box—junction	T-8252853	218
52-6702	A.E. Ref. No.	Central station fire control system—A-26		215
52-6703	" " "	" " " " " " " " " "		215
52-6703	A.E. Ref. No.	Station—sighting	2CSD1C1	221
52-6704	A.E. Ref. No.	Central station fire control system—A-26		215
52-6704	A.E. Ref. No.	Turret—lower gun	2CGD50LRC1	223
52-6705	A.E. Ref. No.	Central station fire control system—A-26		215
52-6705	A.E. Ref. No.	Turret—upper gun	2CGD50URC1	225
52-6801	A.E. Ref. No.	Central station fire control system—A-26		215
52-6801	" " "	" " " " " " " " " " —P-61		206
52-6801	A.E. Ref. No.	Servo—amplifier	2CVB1B1	207, 216
52-6802	A.E. Ref. No.	Box—control	T-8007519	208
52-6802	A.E. Ref. No.	Central station fire control system—P-61		206
52-6803	A.E. Ref. No.	Box—junction	T-8007523	209
52-6803	A.E. Ref. No.	Central station fire control system—P-61		206
52-6804	" " "	" " " " " " " " " "		206
52-6804	A.E. Ref. No.	Turret—upper gun	2CGQ50URA4	214
52-6851	A.E. Ref. No.	Central station fire control system—B-29		173
52-6851	A.E. Ref. No.	Servo—amplifier	2CV1C1	174
52-6852	A.E. Ref. No.	Box—left blister auxiliary control	P-8242340	175
52-6852	A.E. Ref. No.	Central station fire control system—B-29		173
52-6853	A.E. Ref. No.	Box—nose system control	W-8258868	176
52-6853	A.E. Ref. No.	Central station fire control system—B-29		173
52-6854	A.E. Ref. No.	Box—right blister auxiliary control	P-8242340	177
52-6854	A.E. Ref. No.	Central station fire control system—B-29		173
52-6855	A.E. Ref. No.	Box—side blister system control	W-8258871	178

**NUMERICAL INDEX
ARMAMENT SECTION**

(RESTRICTED)



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
52-7476	A.E. Ref. No.	Turret—upper gun	A-3A	139
52-7475	" " "	" " "	A-3B	141
52-7475	A.E. Ref. No.	Turret—upper gun	A-3C	143
52-7475	A.E. Ref. No.	Turret—upper gun	A-14	147
52-7500	A.E. Ref. No.	Turret—upper gun	A-4	149
52-7600	A.E. Ref. No.	Sight—automatic compensating gun	K-3	92
52-7600	A.E. Ref. No.	Turret—upper gun	A-1	133
52-7600	A.E. Ref. No.	Unit—double power hydraulic	AA-16801	169
52-7625	" " "	Sight—automatic compensating gun	K-3	92
52-7625	" " "	Turret—upper gun	A-1	133
52-7625	A.E. Ref. No.	Turret—upper gun	A-1A	135
52-7625	A.E. Ref. No.	Unit—double power hydraulic	AA-16801	169
52-7700	A.E. Ref. No.	Turret—upper training	A-8	153
52-7790	A.E. Ref. No.	Motor—azimuth turret drive	5BA50LJ1	51
52-7790	" " "	" —elevation turret drive	5BA50GJ1	52
52-7790	" " "	" generator—amplidyne local control	5AM31NJ18	50
52-7790	" " "	Turret assembly—tail gun	A-15A	Not catalogued
52-7795	A.E. Ref. No.	Turret—nose gun	A-15	167
52-7800	A.E. Ref. No.	Turret—tail gun	A-6	165
52-7805	A.E. Ref. No.	Turret assembly—nose gun	A-6	Not catalogued
52-7900	" " "	Motor—azimuth turret drive	5BA50LJ1	51
52-7900	" " "	Motor—elevation turret drive	5BA50GJ1	52
52-7900	" " "	" generator—amplidyne local control	5AM31NJ18	50
52-7900	A.E. Ref. No.	Turret—upper gun	A-9	151
52-7910	A.E. Ref. No.	Motor—azimuth turret drive	5BA50LJ1	51
52-7910	" " "	" —elevation turret drive	5BA50GJ1	52
52-7910	" " "	" generator—amplidyne local control	5AM31NJ18	50
52-7910	" " "	Turret—upper gun	A-4	149
52-7910	" " "	" " "	A-9	151
52-7910	A.E. Ref. No.	Turret—upper gun	A-9A	153
52-7911	A.E. Ref. No.	Turret—upper gun	A-9B	Not catalogued
52-7950	" " "	Motor—azimuth turret drive	5BA50LJ1	51
52-7950	" " "	" —elevation turret drive	5BA50GJ1	52
52-7950	" " "	" generator—amplidyne local control	5AM31NJ18	50
52-7950	" " "	Turret—lower gun	A-5	161
52-7950	A.E. Ref. No.	Turret—lower gun	A-10	163
52-7960	A.E. Ref. No.	Turret assembly—lower gun	A-10A	Not catalogued
52-8000	" " "	Motor—azimuth turret drive	5BA50LJ1	51
52-8000	" " "	" —elevation turret drive	5BA50GJ1	52
52-8000	A.E. Ref. No.	Turret—upper gun	A-11	145
52-8050	A.E. Ref. No.	Sight—automatic compensating gun	K-4	93
52-8050	A.E. Ref. No.	Turret—retractable lower gun	A-13	159
52-8050	A.E. Ref. No.	Unit—double power hydraulic	AA-16804	171
52-8100	A.E. Ref. No.	Turret—upper gun	A-11	147
52-8325	A.E. Ref. No.	Timer assembly—machine gun electric synchronizer	A-4	Not catalogued
52-8350	A.E. Ref. No.	Unit—double power hydraulic	AA-16801	169
52-8375	A.E. Ref. No.	Unit—double power hydraulic	AA-16804	171
52-8450	A.E. Ref. No.	Charger—.30 caliber hydraulic gun	D-1	40
52-8450	" " "	" —.50 caliber hydraulic gun	D-2	41
52-8450	" " "	" —20-mm. hydraulic gun	D-3	39
52-8450	A.E. Ref. No.	Valve—hydraulic gun charging	A-1	128
52-9000	A.E. Ref. No.	Yoke—gun mount adapter	41D6865	129
56-11A	Mfr's Dwg.	Rheostat—variable resistance	D-1	123
64-110	A.E. Ref. No.	Adapter—box	A	231
64-110	A.E. Ref. No.	Carrier—universal bomb	No. 1, Mark 3	233
64-150	" " "	Band—bomb adapter	80-1	Not catalogued
64-155	" " "	" " "	80-2	Not catalogued
64-160	" " "	" " "	80-3	Not catalogued
64-175	" " "	" " "	80-4	Not catalogued
64-180	" " "	" " "	80-5	Not catalogued
64-185	" " "	" " "	80-6	Not catalogued
64-190	" " "	" " "	80-7	Not catalogued
64-195	A.E. Ref. No.	Panel—autopilot control	A-6A	232
64-195	A.E. Ref. No.	Pilot—automatic	C-1	268, 269
64-197	" " "	Adapter—box	A	231
64-197	" " "	Carrier—universal bomb No. 1	Mk 2	Not catalogued



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
64-198	A.E. Ref. No.	Adapter—box	A	231
64-198	A.E. Ref. No.	Carrier—universal bomb	No. 1, Mk 3	233
64-198	A.E. Ref. No.	Socket—5 way bomb	A	291
64-199	" " "	Adapter—box	A	231
64-199	" " "	Carrier—universal bomb No. 2	Mk 2	Not catalogued
64-200	A.E. Ref. No.	Control—bomb arming	AN-A-1	236
64-220	A.E. Ref. No.	Control—bomb arming	AN-A-2	237
64-220	A.E. Ref. No.	Mount—bomb arming control	A-1	262
64-250	" " "	Control assembly—bomb arming	B-1	Not catalogued
64-275	A.E. Ref. No.	Control—bomb arming	B-2	238
64-275	A.E. Ref. No.	Mount—bomb arming control	A-1	262
64-400	" " "	Control assembly—bomb release interval	A-1	Not catalogued
64-600	A.E. Ref. No.	Control—bomb release interval	B-2	240
64-800	A.E. Ref. No.	Control—bomb release interval	B-2	240
64-800	A.E. Ref. No.	Control—bomb release interval	B-2A	241
64-825	A.E. Ref. No.	Control—bomb release interval	AN-B-3	242
64-835	A.E. Ref. No.	Control—pilot director indicator	A-1	243
64-835	A.E. Ref. No.	Indicator—pilot director	Mark 15, Mod. 3	266
64-835	" " "	" " "	Mark 15, Mod. 5	264
64-850	A.E. Ref. No.	Cover—electrically heated bombsight	A-1	244
64-852	A.E. Ref. No.	Cover—electrically heated bombsight	A-2	245
64-855	A.E. Ref. No.	Cover—electrically heated automatic pilot	PK 1A1	246
64-900	A.E. Ref. No.	Director—torpedo	Mk 28, Mod. 2	248
64-925	A.E. Ref. No.	Director—torpedo	B-1	Not catalogued
64-950	A.E. Ref. No.	Director—torpedo	B-2	249
64-950	A.E. Ref. No.	Director—torpedo	Mk 28, Mod. 2	248
64-970	" " "	Dynamotor—400 cycle		Not catalogued
64-980	" " "	Equipment—automatic flight control	M-5	Not catalogued
64-1400	A.E. Ref. No.	Handle—bomb release	A-3	250
64-1600	A.E. Ref. No.	Handle—bomb and flare release	A-3A	251
64-1600	A.E. Ref. No.	" " " release	A-3	250
64-1610	" " "	" " " and flare release	A-3A	251
64-1610	A.E. Ref. No.	Handle—bomb and flare release	A-3B	252
64-1610	A.E. Ref. No.	Handle—bomb release	A-3	250
64-1800	A.E. Ref. No.	Handle—bomb release	L-21A	253
64-1800	A.E. Ref. No.	Rack—bomb	N-5	275
64-1800	" " "	" " "	Q-2	276
64-1900	A.E. Ref. No.	Handle—bomb release	Mk 4, Mod. 2	254
64-1900	A.E. Ref. No.	Rack—bomb	AN-MK 51, Mod. 7	272
64-1900	" " "	" " "	Mk 43, Mod. 1	274
64-2000	A.E. Ref. No.	Head—pilot's bombsight	A-1	255
64-2000	A.E. Ref. No.	Ring—pilot's bombsight adapter	43B15328	256
64-2000	" " "	Sight—fixed gun	N-3A	85
64-2000	" " "	" " " "	N-3B	86
64-2000	" " "	" " flexible gun	N-6	87
64-2000	" " "	" " " "	N-6A	89
64-2001	" " "	Head—pilot's bombsight	A-1	255
64-2001	" " "	" " " "	A-2	257
64-2001	A.E. Ref. No.	Ring—pilot's bombsight adapter	43B15328	256
64-2005	A.E. Ref. No.	Head—pilot's bombsight	A-2	257
64-2005	A.E. Ref. No.	Ring—pilot's bombsight adapter	43B15328	256
64-2005	" " "	Sight—fixed gun	N-3A	85
64-2005	" " "	" " " "	N-3B	86
64-2005	" " "	" " flexible gun	N-6	87
64-2005	" " "	" " " "	N-6A	89
64-2200	A.E. Ref. No.	Hoist—bomb	C-3	260
64-2200	A.E. Ref. No.	Sling—bomb hoist	A-1	289
64-2200	" " "	" " " "	A-2	290
64-2250	A.E. Ref. No.	Hoist—portable bomb	AN-MK 7, Mod. 1	259
64-2254	A.E. Ref. No.	Indicator—bombsight pilot director		Not catalogued
64-2255	" " "	Control—pilot director indicator	A-1	243
64-2255	" " "	Indicator—pilot director	Mk 15, Mod. 3	267
64-2255	A.E. Ref. No.	Indicator—pilot director	Mk 15, Mod. 5	264, 265
64-2255	A.E. Ref. No.	Pilot—automatic	C-1	268, 269
64-2256	" " "	Control—pilot director indicator		243
64-2256	" " "	Indicator—pilot director		Not catalogued



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
64-2257	A.E. Ref. No.	Control—pilot director indicator.	A-1	243
64-2257	A.E. Ref. No.	Indicator—pilot director	Mk 15, Mod. 3	266, 267
64-2257	A.E. Ref. No.	Indicator—pilot director	Mk 15, Mod. 5	265
64-2260	" " "	" — steering	Mk 1	Not catalogued
64-2261	" " "	Kit—emergency repair	A	Not catalogued
64-2262	" " "	" — " "	B	Not catalogued
64-2265	A.E. Ref. No.	Mount—grenade	A-1	261
64-2269	A.E. Ref. No.	Mount assembly—bombsight		Not catalogued
64-2270	" " "	Control—bomb arming	AN-A-2	237
64-2270	" " "	" — " "	B-2	238
64-2270	A.E. Ref. No.	Mount—bomb arming control	A-1	262
64-2272	A.E. Ref. No.	Mount—bombsight	B-7	263
64-2275	A.E. Ref. No.	Pilot—automatic	B-1	Not catalogued
64-2300	" " "	Indicator—pilot director	Mk 15, Mod. 3	266
64-2300	" " "	" — " "	Mk 15, Mod. 5	264
64-2300	" " "	Panel—autopilot control	A-6A	232
64-2300	A.E. Ref. No.	Pilot—automatic	C-1	268
64-2340	A.E. Ref. No.	Rack—bomb	Mk 43, Mod. 1	274
64-2349	A.E. Ref. No.	Handle—bomb release	Mk 4, Mod. 2	254
64-2349	A.E. Ref. No.	Rack—bomb	AN-MK 51, Mod. 7	272
64-2350	A.E. Ref. No.	Handle—bomb release	Mk 4, Mod. 2	254
64-2350	A.E. Ref. No.	Rack—bomb	AN-MK 51, Mod. 7	272
64-2351	A.E. Ref. No.	Handle—bomb release	Mk 4, Mod. 2	254
64-2351	A.E. Ref. No.	Rack—bomb	AN-MK 51, Mod. 7	272
64-2400	A.E. Ref. No.	Rack—bomb	N-5	275
64-2600	A.E. Ref. No.	Rack—bomb	N-5	275
64-2600	A.E. Ref. No.	Rack—bomb	Q-2	276
64-2800	A.E. Ref. No.	Rack assembly—flare	A-4	Not catalogued
64-2900	A.E. Ref. No.	Receptacle—bomb release	A-1	277
64-2900	A.E. Ref. No.	Release—bomb rack left hand	A-2	278
64-2900	A.E. Ref. No.	" — " " right hand	A-2	279
64-2900	" " "	" — " " right hand	A-3	280
64-3000	" " "	Receptacle—bomb release	A-1	277
64-3000	A.E. Ref. No.	Release—bomb rack left hand	A-2	278
64-3000	A.E. Ref. No.	Shackle—bomb	AN-B-9	283
64-3000	" " "	" — " "	AN-B-10	284
64-3000	" " "	" — " "	B-7	282
64-3000	" " "	" — " "	D-6	287
64-3000	" " "	" — " "	D-7	288
64-3200	" " "	Receptacle—bomb release	A-1	277
64-3200	A.E. Ref. No.	Release—bomb rack right hand	A-2	279
64-3200	A.E. Ref. No.	Shackle—bomb	AN-B-9	283
64-3200	" " "	" — " "	AN-B-10	284
64-3200	" " "	" — " "	B-7	282
64-3200	" " "	" — " "	D-6	287
64-3200	" " "	" — " "	D-7	288
64-3400	" " "	Release assembly—bomb rack L.H. (12 volt)	A-3	Not catalogued
64-3425	" " "	Receptacle—bomb release	A-1	277
64-3425	A.E. Ref. No.	Release—bomb rack right hand	A-3	280
64-3425	A.E. Ref. No.	Shackle—bomb	AN-B-9	283
64-3425	" " "	" — " "	AN-B-10	284
64-3425	" " "	" — " "	B-7	282
64-3425	" " "	" — " "	D-6	287
64-3425	" " "	" — " "	D-7	288
64-3430	" " "	Receptacle—bomb release	A-1	277
64-3430	" " "	Release—bomb rack L.H.	A-4	Not catalogued
64-3430	" " "	Shackle—bomb	AN-B-9	283
64-3430	" " "	" — " "	AN-B-10	284
64-3430	" " "	" — " "	B-7	282
64-3430	" " "	" — " "	D-6	287
64-3430	" " "	" — " "	D-7	288
64-3431	" " "	Receptacle—bomb release	A-1	277
64-3431	" " "	Release—bomb rack R.H.	A-4	Not catalogued
64-3431	" " "	Shackle—bomb	AN-B-9	283
64-3431	" " "	" — " "	AN-B-10	284
64-3431	" " "	" — " "	B-7	282



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
64-3431	A.E. Ref. No.	Shackle—bomb	D-6	287
64-3431	" " "	" — "	D-7	288
64-3501	" " "	Indicator—resistance unit		Not catalogued
64-3502	" " "	Transmitter—resistance unit		Not catalogued
64-3600	A.E. Ref. No.	Shackle—bomb	B-7	282
64-3700	A.E. Ref. No.	Shackle—bomb	AN-B-9	283
64-3725	A.E. Ref. No.	Shackle—bomb	AN-B-10	284
64-3725	A.E. Ref. No.	Shackle—bomb	B-7	282
64-3750	A.E. Ref. No.	Shackle—bomb	D-3	285
64-3800	A.E. Ref. No.	Shackle—bomb	D-3	285
64-3800	A.E. Ref. No.	Shackle—bomb	D-5	286
64-4000	A.E. Ref. No.	Shackle—bomb	D-5	286
64-4000	A.E. Ref. No.	Shackle—bomb	D-6	287
64-4050	A.E. Ref. No.	Shackle—bomb	D-7	288
64-4075	A.E. Ref. No.	Shackle assembly—bomb	D-8	Not catalogued
64-4100	" " "	Hoist—bomb	C-3	260
64-4100	A.E. Ref. No.	Sling—bomb hoist	A-1	289
64-4150	A.E. Ref. No.	Hoist—bomb	C-3	260
64-4150	" " "	Hoist—portable bomb	AN-Mk 7, Mod. 1	258
64-4150	A.E. Ref. No.	Sling—bomb hoist	A-2	290
64-4195	A.E. Ref. No.	Adapter—box	A	231
64-4195	" " "	Carrier—universal bomb	No. 1 Mk 3	233
64-4195	A.E. Ref. No.	Socket—5 way bomb	A	291
64-4200	A.E. Ref. No.	Socket—7 way	U	Not catalogued
64-4300	" " "	Strap—torpedo hoisting	Mk 13	Not catalogued
64-4350	" " "	Switch—pilot director dash		Not catalogued
64-4400	A.E. Ref. No.	Tachometer—bombsight disc speed	4050 & 4050A	292
64-4450	A.E. Ref. No.	Tachometer—bombsight roto speed		Not catalogued
71-A-0	Mfr's. Model	Station—sighting	2CSD1C1	221
88-3200	A.E. Ref. No.	Sight—fixed gun	N-3A	85
88-3200	" " "	" — " " "	N-3B	86
88-3200	" " "	" — flexible gun	N-6	87
88-3200	" " "	" — " " "	N-6A	89
88-3200	" " "	" — " " "	N-8	91
88-3300	" " "	" — " " "	N-6	87
88-3300	" " "	" — " " "	N-6A	89
88-3300	" " "	" — " " "	N-8	91
88-3300	" " "	" — fixed gun	N-3A	85
88-3300	" " "	" — " " "	N-3B	86
88-3300	" " "	" — flexible gun	N-6	87
88-3300	" " "	" — " " "	N-6A	89
88-3300	" " "	" — " " "	N-8	91
88-3300	" " "	" — " " "	N-6	87
88-3300	" " "	" — " " "	N-6A	89
88-3300	" " "	" — " " "	N-8	91
88-3700	" " "	Station—left blister sighting	2CSR1B2	192
88-3700	" " "	" — nose sighting	2CSR3C1	193
88-3700	" " "	" — right blister sighting	2CSR3B1	194
88-3700	" " "	" — tail sighting	2CSR3B3	195
88-3700	" " "	" — upper ring sighting	2CSR1A1	196
93-200	A.E. Ref. No.	Adapter assembly, 20-mm., AN-M1		301
93-200	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298
93-250	A.E. Ref. No.	Adapter assembly, 20-mm., AN-M6		303
93-300	A.E. Ref. No.	Capsules—fuse		Not catalogued
93-400	" " "	Cartridge—1 1/2" green		Not catalogued
93-400 to				
93-650 Incl.	" " "	Pistol, signal	No. 4 Mk 1	328
93-450	" " "	Cartridge—1 1/2" red		Not catalogued
93-500	" " "	" — " yellow		Not catalogued
93-550	" " "	" — " green and red		Not catalogued
93-600	" " "	" — " yellow and green		Not catalogued
93-650	" " "	" — " " red		Not catalogued
93-725	A.E. Ref. No.	Destructor, AN-M3		295
93-800	A.E. Ref. No.	Discharger, pyrotechnic, AN-M3		326
93-850	A.E. Ref. No.	Discharger—automatic and control signal	Mk 2	Not catalogued
93-900	" " "	Flame floats—aircraft navigation box 285	Mk 2	Not catalogued



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
93-950	A.E. Ref. No.	Flare—reconnaissance 4 1/2"	Mk 2	Not catalogued
93-1100	" " "	Gun, machine, caliber .50 Browning, M2, aircraft, basic		309
93-1109	A.E. Ref. No.	Slide, operating, group assembly	D28200	310
93-1100	A.E. Ref. No.	Stud—bolt	A13424	319
93-1125	" " "	Gun, machine, caliber .50 Browning, M2, aircraft, basic		309
93-1125	A.E. Ref. No.	Slide, retracting, group assembly	D28300A	311
93-1125	A.E. Ref. No.	Stud—bolt	A13424	319
93-1280	A.E. Ref. No.	Gun, automatic, 37-mm., M4		296
93-1280	A.E. Ref. No.	Magazine, endless belt, 37-mm., M6		314
93-1280	" " "	" " " " M7		315
93-1280	" " "	" " " " 15 round, 37-mm., M2		312
93-1280	" " "	Solenoid—gun	G-13	118
93-1280	" " "	" " " " " " " "	G-15	119
93-1300	" " "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		297, 299
93-1350	" " "	" " " " " " " "		297, 299
93-1351	" " "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298, 299
93-1351	A.E. Ref. No.	Trigger—electric AN-M1		120
93-1352	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298, 299
93-1353	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298, 299
93-1354	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298, 299
93-1355	A.E. Ref. No.	Charger—20-mm. hydraulic gun	H-3	39
93-1355	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298, 299
93-1355	A.E. Ref. No.	Trigger—electric AN-M1		120
93-1356	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298, 299
93-1357	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298, 299
93-1420	A.E. Ref. No.	Bolt and bracket—gun trunnion	A-3	20
93-1420	A.E. Ref. No.	Gun, machine, caliber .30 Browning, M2, aircraft, fixed		306
93-1420	A.E. Ref. No.	Handle—gun charging	A-2	46
93-1420	" " "	Post—gun mounting	A-4	73
93-1420	" " "	Roll, tool armorer's w contents, complete	A-28	321
93-1420	" " "	Solenoid—left hand gun	C-4B	106
93-1420	" " "	" " " " " " " "	C-5	110
93-1420	" " "	" " " " " " " "	C-4B	108
93-1420	" " "	" " " " " " " "	C-4B	112
93-1440	" " "	Adapter—gun mount		5
93-1440	" " "	" " " " " " " "	C-16	7
93-1440	" " "	Feed—left hand upper continuous	CF-3L	43
93-1440	" " "	" " " " " " " "	CF-3R	44
93-1440	A.E. Ref. No.	Gun, machine, caliber .30 Browning, M2, aircraft, flexible with fixed back plate		307
93-1440	A.E. Ref. No.	Mount—ammunition box	A-3	53
93-1440	" " "	Roll, tool armorer's w contents, complete	A-28	321
93-1520	" " "	Adapter—gun mount	C-12	6
93-1520	" " "	" " " " " " " "	C-17	8
93-1520	" " "	" " " " " " " "	C-18	9
93-1520	" " "	Container—ejected case	A-4	29
93-1520	" " "	Feed—left hand upper continuous	CF-3L	43
93-1520	" " "	" " " " " " " "	CF-3R	44
93-1520	A.E. Ref. No.	Gun, machine, caliber .30 Browning, M2, aircraft, flexible		308
93-1520	A.E. Ref. No.	Mount—ammunition box	A-3	53
93-1520	" " "	" " " " " " " "	K-2	63
93-1520	" " "	" " " " " " " "	K-2A	64
93-1520	" " "	" " " " " " " "	K-3	65
93-1520	" " "	" " " " " " " "	K-1	62
93-1520	" " "	Roll, tool armorer's w contents, complete	A-28	321
93-1520	" " "	Sight—flexible gun post	A-4	76
93-1520	" " "	" " " " " " " "	B-10	79
93-1560	" " "	Adapter—gun mount	E-5	12
93-1560	" " "	" " " " " " " "	E-5A	11
93-1560	" " "	" " " " " " " "	E-8	14
93-1560	" " "	" " " " " " " "	E-10	15
93-1560	" " "	" " " " " " " "	E-11	16
93-1560	" " "	" " " " " " " "	E-12	18
93-1560	" " "	Bolt and bracket—gun trunnion	A-3	20
93-1560	A.E. Ref. No.	Gun, machine, caliber .50 Browning, M2, aircraft, basic		309
93-1560	A.E. Ref. No.	Handle—gun charging	A-2	46



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
93-1560	A.E. Ref. No.	Mount—ball and socket gun.	K-4	66
93-1560	" " "	" —gun	M-1	69
93-1560	" " "	" —	M-5	72
93-1560	" " "	" —	M-6	71
93-1560	" " "	" —left hand ammunition box.	C-2	54
93-1560	" " "	" —	C-3	56
93-1560	" " "	" —right hand ammunition box.	C-2	55
93-1560	" " "	" —	C-3	57
93-1560	" " "	" —swivel gun.	K-5	67
93-1560	" " "	Post—gun mounting.	A-4	73
93-1560	" " "	Roll, tool, armorer's w contents complete.	A-38	323
93-1560	" " "	Solenoid—gun	G-4A	114
93-1560	" " "	" —	G-9	116
93-1560	" " "	" —	G-11	117
93-1560	" " "	" —left hand gun.	C-4B	106
93-1560	" " "	" —	C-4C	110
93-1560	" " "	" —right hand gun.	C-4B	108
93-1560	" " "	" —	C-4C	112
93-1560	" " "	Stud—bolt	A13424	319
93-1560	" " "	Trigger—manual	A-1	127
93-1590	" " "	Gun—machine, .50 caliber Browning, flexible.	M2	Not catalogued
93-1590	" " "	Mount—left hand ammunition box	C-2	54
93-1590	" " "	" —	C-3	56
93-1590	" " "	" —right hand ammunition box.	C-2	55
93-1590	" " "	" —	C-3	57
93-1590	" " "	Roll, tool, armorer's w contents, complete	A-38	323
93-1590	" " "	Sight—flexible gun post	A-5	77
93-1590	" " "	" —	A-11	78
93-1590	" " "	" —" " " ring	B-11	80
93-1590	" " "	" —	B-13	81
93-2000	" " "	Links—20-mm. for feed mechanism.	M-1	Not catalogued
93-2100	" " "	Gun, automatic, 37-mm., M4		296
93-2100	A.E. Ref. No.	Magazine, 15 round, 37-mm., M2		312
93-3050	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		299
93-3050	A.E. Ref. No.	Magazine, 60 RD, 20-mm., M1		313
93-3100	A.E. Ref. No.	Gun, automatic, 37-mm., M4		296
93-3100	A.E. Ref. No.	Magazine, endless belt, 37-mm., M6		314
93-3110	A.E. Ref. No.	Gun, automatic, 37-mm., M4		296
93-3110	A.E. Ref. No.	Magazine, endless belt, 37-mm., M7		315
93-3125	A.E. Ref. No.	Marker—aluminum—sea	Mk 5	Not catalogued
93-3200	" " "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		299
93-3200	A.E. Ref. No.	Mechanism, feed, left hand, 20-mm., AN-M1		316
93-3205	A.E. Ref. No.	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		299
93-3205	A.E. Ref. No.	Mechanism, feed, right hand, 20-mm., AN-M1		317
93-4000	A.E. Ref. No.	Mount, gun, airplane, 75-mm., M6		318
93-4200	A.E. Ref. No.	Mount—75-mm. gun		Not catalogued
93-5400	" " "	" —pyrotechnic pistol.	M-2	Not catalogued
93-6000	" " "	Holder—pyrotechnic pistol	A-1	48
93-6100	A.E. Ref. No.	Pistol, pyrotechnic, M2		327
93-6100	A.E. Ref. No.	Holder—pyrotechnic pistol	A-2	49
93-6500	A.E. Ref. No.	Pistol, pyrotechnic, AN-M8, w mount		330
93-6500	A.E. Ref. No.	Pistol, signal	No. 4, Mk 1	328
93-6500	A.E. Ref. No.	Sleeve, mounting	No. 2, Mk 1	329
93-6501	A.E. Ref. No.	Disc, aperture	No. 2, Mk 1	329
93-6501	A.E. Ref. No.	Sleeve, mounting	No. 2, Mk 1	329
93-6502	" " "	Disc, aperture	No. 2, Mk 1	329
93-6502	A.E. Ref. No.	Sleeve, mounting	No. 2, Mk 1	329
93-6575	A.E. Ref. No.	Roll, tool armorer's w contents, complete	A-28	321
93-6577	A.E. Ref. No.	Roll, tool armorer's w contents, complete	A-38	323
93-6579	A.E. Ref. No.	Roll—armorer's tool .30 and .50 caliber.		Not catalogued
93-7000	A.E. Ref. No.	Stud—bolt	A13424	319
93-24542	Army Spec.	Handle—bomb and flare release	A-3A	251, 252
93-24542	" " "	" —" release	A-3	250
93-24542-A	" " "	" —" and flare release	A-3A	251
93-24542-B	" " "	" —" and flare release	A-3A	252
93-24555	" " "	Shackle—bomb	D-3	285



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
93-24555-A	Army Spec.	Shackle—bomb	D-3	285
93-24557	"	"	B-7	282
93-24561	"	Mount—gun	G-1A	59
93-24561-A	"	"	G-1A	59
93-24563	"	Handle—bomb release	L-21A	253
93-24563-A	"	"	L-21A	253
93-24583	"	Hoist—bomb	C-3	260
93-24585	"	Sight—flexible gun post	A-4	76
93-24586	"	"	A-5	77
93-24587	"	" " " ring	B-10	79
93-24588	"	"	B-11	80
93-24591	"	Switch—control stick gun	B-1A	124
93-24592	"	Ends—impulse unit	E-3	98
93-24593	"	Motor—trigger	E-3	99
93-24593	"	"	E-3A	100
93-24593-A	"	"	E-3A	100
93-24596	"	Bolt and bracket—gun trunnion	A-3	20
93-24604	"	Container—ejected case	A-4	29
93-24605	"	" link	A-4	32
93-24608	"	Post—gun mounting	A-4	73
93-24609	"	Generator—gun synchronizer impulse	E-8	97
93-24609-A	"	"	E-8	97
93-24622	"	Shackle—bomb	D-5	286
93-24626	"	Rack—bomb	N-5	275
93-24628	"	"	Q-2	276
93-24630	"	Control—bomb release interval	B-2A	241
93-24630-A	"	"	B-2	240
93-24630-A	"	"	B-2A	241
93-24638	"	Adapter—gun mount	E-5	12
93-24639	"	"	C-16	7
93-24640	"	Mount—left hand ammunition box	C-2	54
93-24640	"	" right " " "	C-2	55
93-24640-A	"	" left " " "	C-2	54
93-24640-A	"	" right " " "	C-2	55
93-24643	"	Adapter—gun mount	C-12	6
93-24653	"	Box—ammunition	L-4	21
93-24655	"	Mount assembly—ball and socket gun	K-1	62
93-24659-A	"	Sight—fixed gun	N-3A	85
93-24659-A	"	Support—gun sight image reflector	41D4892	121
93-24659-B	"	Sight—fixed gun	N-3A	85
93-24659-B	"	Support—gun sight image reflector	41D4892	121
93-24660	"	Holder—ammunition box	A-1	47
93-24661	"	Mount— " "	A-3	53
93-24663	"	Handle—gun charging	A-2	46
93-24667	"	Sight—telescopic gun	E-5	82
93-24669	"	Mount—flexible gun sight	C-4	58
93-24673	"	Box—ammunition	O-1	23
93-24674	"	Container—ejected link	A-3	31
93-24682	"	Solenoid—left hand gun	C-4B	106
93-24682	"	" " " "	C-4C	110
93-24682	"	" right " "	C-4B	108
93-24682	"	" " " "	C-4C	112
93-24682-A	"	" left " "	C-4B	106
93-24682-A	"	" " " "	C-4C	110
93-24682-A	"	" right " "	C-4B	108
93-24682-A	"	" " " "	C-4C	112
93-24686	"	Container—ejected case	A-5	30
93-24687	"	Support—gun sight image reflector	41D3024	122
93-24689	"	Adapter—gun mount	E-8	14
93-24690	"	Mount—left hand ammunition box	C-3	56
93-24690	"	" right " " "	C-3	57
93-24690-A	"	" left " " "	C-3	56
93-24690-A	"	" right " " "	C-3	57
93-24694	"	Shackle—bomb	D-6	287
93-24696	"	Adapter—gun mount	C-17	8
93-24697	"	Mount—ball and socket gun	K-2	63



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
93-24697	Army Spec.	Mount--ball and socket gun.	K-2A	64
93-24698	" "	Mount gun	H-1	61
93-24699	" "	Release--bomb rack left hand.	A-2	278
93-24699	" "	" " " right "	A-2	279
93-24699-A	" "	" " " left "	A-2	278
93-24699-A	" "	" " " right "	A-2	279
93-24702	" "	Solenoid--gun	G-8	115
93-24703	" "	Adapter--gun mount.	E-10	15
93-24704	" "	Sight--flexible gun.	N-6A	89
93-24706	" "	Solenoid--gun	G-9	116
93-24706-A	" "	" "	G-9	116
93-24708	" "	Switch--control stick gun.	B-5	125
93-24713	" "	Container--signal flare	A-1	34
93-24717	" "	Control--bomb release interval.	AN-B-3	242
93-24718	" "	Holder--pyrotechnic pistol.	A-1	48
93-24719	" "	Mount--gun	G-5	60
93-24720	" "	Adapter--gun mount.	C-18	9
93-24721	" "	Container--ejected link.	A-5	33
93-24730	" "	Adapter--gun mount.	E-11	16
93-24731	" "	Sling--bomb hoist.	A-1	289
93-24740	" "	Solenoid--gun	G-10	104
93-24742	" "	Release--bomb rack right hand.	A-3	280
93-24743	" "	Solenoid--gun	E-6	102
93-24746	" "	" "	G-11	117
93-24748	" "	Shackle--bomb	D-7	288
93-24749	" "	" "	AN-B-9	283
93-24750	" "	Box--ammunition	L-7	22
93-24752	" "	Adapter--gun mount.	E-12	18
93-24753	" "	Control--bomb arming	AN-A-1	236
93-24758	" "	Sight--flexible gun post.	A-11	58
93-24759	" "	" " " ing.	D-13	81
93-24763	" "	Adapter--gun mount.	E-5A	11
93-24764	" "	Solenoid--gun	G-15	119
93-24768	" "	" "	E-8	103
93-24769	" "	" "	G-16	105
93-24771	" "	Container--signal flare	A-5	35
93-24772	" "	" "	A-6	36
93-24773	" "	" "	A-7	37
93-24778	" "	Charger, manual, M2.		38
93-24780	" "	Mount--ball and socket gun.	K-3	65
93-24814	" "	" " " " "	K-4	66
93-24817	" "	Sight--fixed gun.	N-3B	86
93-24820	" "	Holder--pyrotechnic pistol.	A-2	49
93-24828	" "	Control--bomb arming	AN-A-2	237
93-24829	" "	" " " "	B-2	238
93-24840	" "	Mount--grenade	A-1	261
94-24610	" "	Solenoid--gun	E-4	101
94-24610	" "	" "	E-6	102
94-24620	" "	" "	G-4A	114
94-32008-A	" "	Rheostat--variable resistance.	D-1	123
94-32010-A	" "	" " " "	D-1	123
94-32010-B	" "	" " " "	D-1	123
95-24739	" "	Valve--hydraulic gun charging.	A-1	128
104G/28	British Ref.	Hoist--bomb.	C-3	260
105A12	Mfr's Dwg.	Adapter--gun end.	L-1	26
105A24	" "	" --box "	L-2	27
105A40	" "	Chute--flexible feed.	B	25
105B1	" "	" " " "	A	28
105B1	" "	" " " "	B	25
105C/146	British Ref.	Switch--single pole toggle.	AN3022-2	126
105C/146	" "	" --tail cannon selector.	AN3022-2	197
105C/2353	" "	Unit--double power hydraulic.	AA-16804	171
105C/2494	" "	" " " "	AA-16804	171
105D/13	" "	Solenoid--gun	G-8	115
105D/13	" "	Trigger--electric AN-M1		120
105D/16	" "	Socket--5 way bomb	A	291



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
105D/17	British Ref.	Solenoid—gun	G-4A	114
105D/17	" "	" — "	G-9	116
105D/22	" "	Socket—5 way bomb	A	291
105D/29	" "	Solenoid—gun	G-4A	114
105D/29	" "	" — "	G-9	116
105D/30	" "	Control—bomb release interval	B-2	240
105D/31	" "	" — " " "	AN-B-3	242
105D/36	" "	Solenoid—gun	G-8	115
105D/36	" "	Trigger—electric AN-M1		120
105D/45	" "	Solenoid—left hand gun	C-4B	107
105D/46	" "	" — " " "	C-4C	111
105D/46	" "	" —right " "	C-4B	109
105D/46	" "	" — " " "	C-4C	113
105D/51	" "	Solenoid—gun	G-10	104
105D/57	" "	" —left hand gun	C-4B	107
105D/57	" "	" — " " "	C-4C	111
105D/57	" "	" —right " "	C-4B	109
105D/57	" "	" — " " "	C-4C	113
105D/58	" "	" —left " "	C-4B	107
105D/58	" "	" — " " "	C-4C	111
105D/58	" "	" —right " "	C-4B	109
105D/58	" "	" — " " "	C-4C	113
105D/59	" "	" —gun	G-11	117
105D/72	" "	Switch—control stick gun	B-1A	124
105D/72	" "	" — " " "	B-5	125
105D/75	" "	" — " " "	B-1A	124
105D/76	" "	" — " " "	B-5	125
105D/77	" "	Solenoid—left hand gun	C-4B	107
105D/77	" "	" —right " "	C-4B	109
105D/77	" "	" — " " "	C-4C	113
105D/77	" "	" assembly—gun L.H.	C-4C	111
105D/80	" "	" —gun	G-16	105
105D/84	" "	Control—bomb release interval	B-2	240
105D/84	" "	" — " " "	B-2A	241
105D/87	" "	Solenoid—gun	E-4	101
105D/87	" "	" — " " "	E-6	102
105D/90	" "	" — " " "	E-8	103
105D/91	" "	" — " " "	G-13	118
105D/91	" "	" — " " "	G-15	119
105D/92	" "	" — " " "	E-4	101
105D/92	" "	" — " " "	E-6	102
105D/94	" "	Control—bomb release interval	AN-B-3	242
105D/95	" "	Receptacle—bomb release	A-1	277
105D/99	" "	Control—bomb arming	AN-A-1	236
105D/99	" "	" — " " "	AN-A-2	237
105D/194	" "	" — " " "	AN-A-1	236
105D/194	" "	" — " " "	AN-A-2	237
105D/195	" "	" — " " "	AN-A-1	236
105D/195	" "	" — " " "	AN-A-2	237
105D/196	" "	Solenoid—gun	G-13	118
105D/196	" "	" — " " "	G-15	119
106J/693	" "	Pilot—automatic	C-1	270
106J/694	" "	" — " " "	C-1	269
106J/695	" "	" — " " "	C-1	270
106J/696	" "	" — " " "	C-1	270
106J/697	" "	" — " " "	C-1	271
106J/698	" "	" — " " "	C-1	271
106J/699	" "	Panel—autopilot control	A-6A	232
106J/700	" "	Pilot—automatic	C-1	269
106J/758	" "	" — " " "	C-1	269
106J/759	" "	" — " " "	C-1	270
107G/5	" "	Gun, aircraft, automatic 20-mm, M1 and AN-M2 (all types)		299
107G/80	" "	Mechanism, feed, left hand, 20-mm, AN-M1		316
107G/86	" "	" — " —right hand, 20-mm, AN-M1		317
107G/279	" "	Gun, aircraft, automatic, 20-mm, M1 and AN-M2 (all types)		299
107K/118	" "	Stud—bolt	AFB24	319



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
107K/119	British Ref.	Slide, operating, group assembly	D28200	310
107K/225	" "	" — retracting, group assembly	D28300A	311
107K/482	" "	Gun, machine, caliber .50, Browning, M2, aircraft, basic		309
107L/390	" "	" " " " " " " "		
		with fixed back plate		307
107L/391	" "	Gun, machine, caliber .30 Browning, M2, aircraft fixed		306
107L/392	" "	" " " " .30, Browning, M2, aircraft, flexible		308
107M/1	" "	" " automatic, 37-mm, M4		296
107M/52	" "	Magazine, 15 round, 37-mm, M2		312
108A/1	" "	Motor—trigger	E-3	99
108A/1	" "	" — " "	E-3A	100
108A/20	" "	Valve—hydraulic gun charging	A-1	128
108A/21	" "	Charger—20-mm hydraulic gun	D-3	39
108A/37	" "	Ends—impulse unit	E-3	98
108A/66	" "	Charger—.50 caliber hydraulic gun	D-2	41
108A/158	" "	Motor—trigger	E-3	99
108A/158	" "	" — " "	E-3A	100
108A/159	" "	Charger, manual, M2	B-6	38
108A/160	" "	Handle—gun charging	A-2	46
108A/161	" "	Generator—gun synchronizer impulse	E-8	97
108A/171	" "	Charger—.30 caliber hydraulic gun	D-1	40
108B/3	" "	Sight—flexible gun post	A-5	77
108B/4	" "	" — " " ring	E-11	80
108B/12	" "	" — fixed gun	N-3A	85
108B/12	" "	Sight—fixed gun	N-3B	86
108B/15	" "	" — flexible gun post	A-4	76
108B/18	" "	" — " " ring	B-10	79
108B/19	" "	" — " " "	N-6	87
108B/19	" "	" — " " "	N-6A	89
108B/19	" "	" — " " "	N-8	91
108B/20	" "	" — illuminated	Mk 5	83
108B/21	" "	" — " "	Mk 5	90
108B/63	" "	Support—gun sight image reflector	41D3024	122
108B/63	" "	" — " " " "	41D4892	121
108B/68	" "	Sight—fixed gun	N-3A	85
108B/68	" "	" — " " "	N-3B	86
108B/70	" "	" — flexible gun	N-6	87
108B/70	" "	" — " " "	N-6A	89
108B/70	" "	" — " " "	N-8	91
108B/74	" "	" — " " post	A-11	78
108B/75	" "	" — " " ring	B-13	81
108B/79	" "	Support—gun sight image reflector	41D3024	122
108B/79	" "	" — " " " "	41D4892	121
108B/80	" "	Mount—flexible gun sight	C-4	58
108D/89	" "	Roll tool, armorer's w/contents, complete	A-28	321
108D/90	" "	" " " " " "	A-38	323
109/40	" "	Director—torpedo	Mk 23, Mod. 2	248
109/43	" "	Cover—electrically heated bombsight	A-2	245
109/44	" "	Director—torpedo	B-2	249
109/45	" "	Indicator—pilot director	Mk 15, Mod. 3	267
109/45	" "	" — " " "	Mk 15, Mod. 5	265
111A/1	" "	Shackle—bomb	B-7	282
111A/2	" "	" — " "	D-3	285
111A/2	" "	" — " "	D-5	286
111A/27	" "	" — " "	D-3	285
111A/27	" "	" — " "	D-5	286
111A/29	" "	" — " "	D-6	287
111A/30	" "	Handle—bomb and flare release	A-3A	251
111A/30	" "	" — " " " "	A-3B	252
111A/30	" "	" — " " release	A-3	250
111A/31	" "	Release—bomb rack left hand	A-2	278
111A/32	" "	" — " " right hand	A-2	279
111A/33	" "	Shackle—bomb	D-6	287
111A/34	" "	" — " " "	AN-B-9	283
111A/35	" "	Handle—bomb release	L-21A	263
111A/36	" "	Rack—bomb	Q-2	276

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
111A/40	British Ref.	Release—bomb rack right hand.	A-3	280
111A/41		Carrier—universal bomb.	No. 1, Mk 3.	233
111A/44		Shackle—bomb	AN-B-10	284
111A/45		" — "	D-7	288
111A/46		Hoist—portable bomb	AN-Mk 7 Mod. 1	259
111A/51		Handle—bomb and flare release.	A-3A	251, 252
111A/51		" — " release	A-3	250
111A/52		" — " and flare release.	Mk 4 Mod. 2	254
111A/53		Rack—bomb	AN-Mk 51 Mod 7	273
111A/59		Handle—bomb and flare release.	A-3A	251
111A/59		" — " " " " "	A-3B	252
111A/59		" — " release	A-3	250
112D/8		Destructor, AN-M3		295
150A/1		Turret—upper gun	A-3	137
150A/1		" — " " "	A-3A	139
150A/1		" — " " "	A-3B	141
150A/1		" — " " "	A-3C	143
150A/1		" — " " "	A-11	145
150A/1		" — " " "	A-14	147
150A/2		" — " " "	A-3	137
150A/2		" — " " "	A-3A	139
150A/2		" — " " "	A-3B	141
150A/2		" — " " "	A-3C	143
150A/2		" — " " "	A-11	145
150A/2		" — " " "	A-14	147
150A/3		" — " " "	A-1	133
150A/3		" — " " "	A-1A	135
150A/4		" — lower gun	A-2	157
150A/4		" — retractable lower gun	A-13	159
150A/5		" — upper gun	A-4	149
150A/5		" — " " "	A-9	151
150A/5		" — " " "	A-9A	153
150A/6		" — lower gun	A-5	161
150A/6		" — " " "	A-10	163
150A/7		" — upper gun	A-3	137
150A/7		" — " " "	A-3A	139
150A/7		" — " " "	A-3B	141
150A/7		" — " " "	A-3C	143
150A/7		" — " " "	A-11	145
150A/7		" — " " "	A-14	147
150A/8		" — " " "	A-3	137
150A/8		" — " " "	A-3A	139
150A/8		" — " " "	A-3B	141
150A/8		" — " " "	A-3C	143
150A/8		" — " " "	A-11	145
150A/8		" — " " "	A-14	147
150A/9		" — " " "	A-3	137
150A/9		" — " " "	A-3A	139
150A/9		" — " " "	A-3B	141
150A/9		" — " " "	A-3C	143
150A/9		" — " " "	A-11	145
150A/9		" — " " "	A-14	147
150A/10		" — tail gun.	A-6	165
150A/11		" — upper gun	A-3	137
150A/11		" — " " "	A-3A	139
150A/11		" — " " "	A-3B	141
150A/11		" — " " "	A-3C	143
150A/11		" — " " "	A-11	145
150A/11		" — " " "	A-14	147
150A/20		" — " " "	A-3	137
150A/20		" — " " "	A-9	151
150A/20		" — " " "	A-9A	153
150A/21		" — lower gun	A-5	161
150A/21		" — " " "	A-10	163
150A/22		" — upper gun	A-3	137
150A/22		" — " " "	A-3A	139



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
150A/22	British Ref.	Turret—upper gun	A-3B	141
150A/22	" "	" "	A-3C	143
150A/22	" "	" "	A-11	145
150A/22	" "	" "	A-14	147
150A/23	" "	" "	A-3	137
150A/23	" "	" "	A-3A	139
150A/23	" "	" "	A-3B	141
150A/23	" "	" "	A-3C	143
150A/23	" "	" "	A-11	145
150A/23	" "	" "	A-14	147
150A/24	" "	" "	A-3	137
150A/24	" "	" "	A-3A	139
150A/24	" "	" "	A-3B	141
150A/24	" "	" "	A-3C	143
150A/24	" "	" "	A-11	145
150A/24	" "	" "	A-14	147
150A/26	" "	" —nose gun	A-16	168
150A/30	" "	" —upper gun	A-9	151
150A/30	" "	" "	A-9A	153
150A/31	" "	" —lower gun	A-2	157
150A/31	" "	" —retractable lower gun	A-13	159
150A/32	" "	" —upper gun	A-3A	139
150A/32	" "	" "	A-3B	141
150A/32	" "	" "	A-3C	143
150A/32	" "	" "	A-11	145
150A/32	" "	" "	A-13	137
150A/32	" "	" "	A-14	147
150B/1019	" "	Motor—azimuth turret drive	5BA50LJ1	51
150B/1027	" "	" —elevation turret drive	5BA50GJ1	52
150B/1506	" "	Motor generator—amplidyne local control	5AM31NJ16	50
150C/2353	" "	Unit—double power hydraulic	AA-16801	169
150C/2492	" "	" "	AA-16801	169
150J/6	" "	Adapter—gun mount		5
150J/11	" "	" "	E-5	13
150J/11	" "	" "	E-8	14
150J/11	" "	" "	E-11	17
150J/11	" "	" "	E-12	18
150J/16	" "	" "	C-12	6
150J/17	" "	" "	C-17	8
150J/17	" "	" "	C-18	9
150J/18	" "	Mount—ball and socket gun	K-2	63
150J/18	" "	" "	K-2A	64
150J/18	" "	" "	K-3	65
150J/18	" "	assembly—ball and socket gun	K-1	62
150J/19	" "	" —ball and socket gun	K-2	63
150J/19	" "	" "	K-2A	64
150J/19	" "	" "	K-3	65
150J/19	" "	assembly—ball and socket gun	K-1	62
150J/21	" "	Adapter—gun mount	E-5	13
150J/21	" "	" "	E-8	14
150J/21	" "	" "	E-11	17
150J/21	" "	" "	E-12	18
150J/22	" "	" "	E-10	15
150J/24	" "	" "	E-5	13
150J/24	" "	" "	E-8	14
150J/24	" "	" "	E-11	17
150J/24	" "	" "	E-12	18
150J/26	" "	" "	E-5	13
150J/26	" "	" "	E-8	14
150J/26	" "	" "	E-11	17
150J/26	" "	" "	E-12	18
150J/27	" "	Mount—ball and socket gun	K-2	63
150J/27	" "	" "	K-2A	64
150J/27	" "	" "	K-3	65
150J/27	" "	assembly—ball and socket gun	K-1	62
150J/28	" "	Adapter—gun mount	C-17	8



NUMERICAL INDEX
ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
150J/28	British Ref.	Adapter—gun mount.	C-18	9
150J/30	"	"	C-16	7
150J/33	"	Mount—gun	M-6	71
150J/47	"	Adapter—gun mount	C-19	10
150J/48	"	Mount—gun	G-1A	59
150J/48	"	"	G-5	60
150J/50	"	" —gun	H-1	61
150J/51	"	" —ball and socket gun	K-2	63
150J/51	"	"	K-2A	64
150J/51	"	"	K-3	65
150J/51	"	" assembly—ball and socket gun	K-1	62
150J/52	"	" —ball and socket gun	K-4	66
150J/53	"	" —swivel gun	K-5	67
150J/54	"	" —gun	M-1	69
150J/56	"	Adapter assembly, 20-mm., AN-M1		301
150J/559	"	Adapter—gun mount	F-5A	11
150J/573	"	Post—gun mounting	A-4	73
150J/574	"	Mount—gun	G-1A	59
150J/574	"	"	G-5	60
150J/575	"	Box—ammunition	L-4	21
150J/576	"	"	L-7	22
150J/576	"	Mount—left hand ammunition box	C-2	54
150J/576	"	"	C-3	56
150J/577	"	Holder—ammunition box	A-1	47
150J/578	"	Box—ammunition	O-1	23
150J/579	"	Container—ejected case	A-4	29
150J/579	"	"	A-5	30
150J/580	"	" —link	A-3	31
150J/580	"	"	A-4	32
150J/580	"	"	A-5	33
150J/584	"	Mount—ammunition box	A-3	53
150J/585	"	" —right hand ammunition box	C-2	55
150J/585	"	"	C-3	57
150J/587	"	Feed—lower continuous	CF-5	45
150J/596	"	Bolt and bracket—gun trunnion	A-3	20
150J/597	"	Box—ammunition	L-4	21
150J/597	"	"	L-7	22
150J/702	"	Mount—left hand ammunition box	C-2	54
150J/702	"	"	C-3	56
150J/703	"	" —right hand ammunition box	C-2	55
150J/703	"	"	C-3	57
150J/761	"	Container—ejected case	A-4	29
150J/761	"	"	A-5	30
150J/752	"	" —link	A-3	31
150J/752	"	"	A-4	32
150J/752	"	"	A-5	33
150J/754	"	Feed—left hand upper continuous	CF-3L	43
150J/755	"	" —right hand upper continuous	CF-3R	44
150J/756	"	Chute—flexible feed	A	28
150J/757	"	"	A	28
150J/758	"	"	A	28
150J/759	"	"	A	28
150J/760	"	"	A	28
150J/761	"	"	A	28
150J/763	"	Container—ejected link	A-3	31
150J/763	"	"	A-4	32
150J/763	"	"	A-5	33
150J/776	"	Chute—flexible feed	B	25
150J/782	"	Adapter—gun end	L-1	26
150J/783	"	" —box end	L-2	27
163-A	Mfr's Dwg.	Sight—flexible gun	N-6	87
163-A	"	"	N-6A	89
163-A	"	"	N-8	91
165	Spec.	Turret—upper gun	A-3	137
165	"	"	A-3A	139
165	"	"	A-3B	141



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
165	Mfr's Spec.	Turret—upper gun	A-3C	143
165	" "	" "	A-11	145
165	" "	" "	A-14	147
165A	" "	" "	A-3	137
165A	" "	" "	A-3A	139
165A	" "	" "	A-3B	141
165A	" "	" "	A-3C	143
165A	" "	" "	A-11	145
165A	" "	" "	A-14	147
165B	" "	" "	A-3	137
165B	" "	" "	A-3A	139
165B	" "	" "	A-3B	141
165B	" "	" "	A-3C	143
165B	" "	" "	A-11	145
165B	" "	" "	A-14	147
212	" "	" "	A-3	137
212	" "	" "	A-3A	139
212	" "	" "	A-3B	141
212	" "	" "	A-3C	143
212	" "	" "	A-11	145
212	" "	" "	A-14	147
215	Ord. Pamphlet	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		299
215	" "	Gun, machine, caliber .50 Browning, M2, aircraft, basic		309
215	" "	Stud—bolt	A13424	319
230-A	Navy Type	Solenoid—gun	E-6	102
240	" "	" "	G-10	104
250CE1	Mfr's Mod.	Turret—upper gun	A-3	137
250CE1	" "	" "	A-3A	139
250CE1	" "	" "	A-3B	141
250CE1	" "	" "	A-3C	143
250CE1	" "	" "	A-11	145
250CE1	" "	" "	A-14	147
250CE2	" "	" "	A-3	137
250CE2	" "	" "	A-3A	139
250CE2	" "	" "	A-3B	141
250CE2	" "	" "	A-3C	143
250CE2	" "	" "	A-11	145
250CE2	" "	" "	A-14	147
250CE2A	" "	" "	A-3	137
250CE2A	" "	" "	A-3A	139
250CE2A	" "	" "	A-3B	141
250CE2A	" "	" "	A-3C	143
250CE2A	" "	" "	A-11	145
250CE2A	" "	" "	A-14	147
250CE3	" "	" "	A-3	137
250CE3	" "	" "	A-3A	139
250CE3	" "	" "	A-3B	141
250CE3	" "	" "	A-3C	143
250CE3	" "	" "	A-11	145
250CE3	" "	" "	A-14	147
250CE3A	" "	" "	A-3	137
250CE3A	" "	" "	A-3A	139
250CE3A	" "	" "	A-3B	141
250CE3A	" "	" "	A-3C	143
250CE3A	" "	" "	A-11	145
250CE3A	" "	" "	A-14	147
250CE4	" "	" "	A-3	137
250CE4	" "	" "	A-3A	139
250CE4	" "	" "	A-3B	141
250CE4	" "	" "	A-3C	143
250CE4	" "	" "	A-11	145
250CE4	" "	" "	A-14	147
250CE5	" "	" "	A-3	137
250CE5	" "	" "	A-3A	139
250CE5	" "	" "	A-3B	141
250CE5	" "	" "	A-3C	143



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
250CE5	Mfr's Mod.	Turret—upper gun.	A-11	145
250CE5	" "	" "	A-14	147
250CE6	" "	" "	A-3	137
250CE6	" "	" "	A-3A	139
250CE6	" "	" "	A-3B	141
250CE6	" "	" "	A-3C	143
250CE6	" "	" "	A-11	145
250CE6	" "	" "	A-14	147
250CE7	" "	" "	A-3	137
250CE7	" "	" "	A-3A	139
250CE7	" "	" "	A-3B	141
250CE7	" "	" "	A-3C	143
250CE7	" "	" "	A-11	145
250CE7	" "	" "	A-14	147
250CE8	" "	" "	A-3	137
250CE8	" "	" "	A-3A	139
250CE8	" "	" "	A-3B	141
250CE8	" "	" "	A-3C	143
250CE8	" "	" "	A-11	145
250CE8	" "	" "	A-14	147
250CE8A	" "	" "	A-3	137
250CE8A	" "	" "	A-3A	139
250CE8A	" "	" "	A-3B	141
250CE8A	" "	" "	A-3C	143
250CE8A	" "	" "	A-11	145
250CE8A	" "	" "	A-14	147
250CE10	" "	" "	A-3	137
250CE10	" "	" "	A-3A	139
250CE10	" "	" "	A-3B	141
250CE10	" "	" "	A-3C	143
250CE10	" "	" "	A-11	145
250CE10	" "	" "	A-14	147
250CE11	" "	" "	A-3	137
250CE11	" "	" "	A-3A	139
250CE11	" "	" "	A-3B	141
250CE11	" "	" "	A-3C	143
250CE11	" "	" "	A-11	145
250CE11	" "	" "	A-14	147
250CE40	Mfr's Dwg.	" "	A-3	137
250CE40	" "	" "	A-3A	139
250CE40	" "	" "	A-3B	141
250CE40	" "	" "	A-3C	143
250CE40	" "	" "	A-11	145
250CE40	" "	" "	A-14	147
250CE50	" "	" "	A-3	137
250CE50	" "	" "	A-3A	139
250CE50	" "	" "	A-3B	141
250CE50	" "	" "	A-3C	143
250CE50	" "	" "	A-11	145
250CE50	" "	" "	A-14	147
250CE70	" "	" "	A-3	137
250CE70	" "	" "	A-3A	139
250CE70	" "	" "	A-3B	141
250CE70	" "	" "	A-3C	143
250CE70	" "	" "	A-11	145
250CE70	" "	" "	A-14	147
250CE100	" "	" "	A-3	137
250CE100	" "	" "	A-3A	139
250CE100	" "	" "	A-3B	141
250CE100	" "	" "	A-3C	143
250CE100	" "	" "	A-11	145
250CE100	" "	" "	A-14	147
250CE110	" "	" "	A-3	137
250CE110	" "	" "	A-3A	139
250CE110	" "	" "	A-3B	141
250CE110	" "	" "	A-3C	143



NUMERICAL INDEX
ARMAMENT SECTION

Number	Identification	Used in Connection with	Type, Drawing or Designation	Page
250CR110	Mfr's Dwg.	Turret—upper gun	A-11	145
250CR110	" "	" — " "	A-14	147
258	Mfr's Spec.	" — " "	A-3	137
258	" "	" — " "	A-3A	139
258	" "	" — " "	A-3B	141
258	" "	" — " "	A-3C	143
258	" "	" — " "	A-11	145
258	" "	" — " "	A-14	147
263	Ord. Pamphlet	Sight—flexible gun post	A-4	76
263	" "	" — " "	A-5	77
263	" "	" — " " ring	B-10	79
263	" "	" — " "	B-11	80
263	" "	" —illuminated	Mk 8	83
263	" "	" — "	Mk 9	90
264	Mfr's Spec.	Turret—upper gun	A-3	137
264	" "	" — " "	A-3A	139
264	" "	" — " "	A-3B	141
264	" "	" — " "	A-3C	143
264	" "	" — " "	A-11	145
264	" "	" — " "	A-14	147
281	" "	" — " "	A-3	137
281	" "	" — " "	A-3A	139
281	" "	" — " "	A-3B	141
281	" "	" — " "	A-3C	143
281	" "	" — " "	A-11	145
281	" "	" — " "	A-14	147
290-I	Tech. Bulletin	Pistol, pyrotechnic, M2		327
300	Mfr's Dwg.	Shackle—bomb	D-3	285
300	" "	" — "	D-5	286
398	Ord. Pamphlet	Gun, machine, caliber .30 Browning, M2, aircraft, fixed		306
398	" "	" " " " " " M2, aircraft, flexible		308
398	" "	" " " " " " " " " " " " with fixed back plate		307
548	" "	Gun, machine, caliber .50 Browning, M2, aircraft, basic		309
548	" "	Stud—bolt	A13424	319
552	Navy T.O.	Ends—impulse unit	E-3	98
552	Ord. Pamphlet	Generator—gun synchronizer impulse	E-8	97
552	" "	Motor—trigger	E-3 Mk 1	99
552	" "	" — "	E-3A	100
562	" "	Discharger, pyrotechnic, AN-M5		326
639	" "	Panel—autopilot control	A-6A	232
639	" "	Pilot—automatic	C-1	268
714	" "	Gun, machine, caliber .30 Browning, M2, aircraft, fixed		306
714	" "	" " " " " " M2, aircraft, flexible		308
714	" "	" " " " " " " " " " " " with fixed back plate		307
714	" "	Roll, tool armorer's w./contents, complete	A-28	321
716	" "	Gun, machine, caliber .50 Browning, M2, aircraft, basic		309
716	" "	Roll, tool, armorer's w. contents, complete	A-38	323
716	" "	Slide, operating, group assembly	D28200	310
716	" "	" retracting, group assembly	D28300A	311
716	" "	Stud—bolt	A13424	319
803	" "	Sight—illumined	Mk 8	83
827	" "	Valve—hydraulic gun charging	A-1	128
828	" "	Charger—.50 caliber hydraulic gun	D-2	41
829	" "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		299
842	Lamp Trade No.	Sight—flexible gun	N-6	87
842	" "	" — " "	N-6A	89
842	" "	" — " "	N-8	91
844	" "	" — " "	N-6	87
844	" "	" — " "	N-6A	89
844	" "	" — " "	N-8	91
865	Ord. Pamphlet	Adapter - gun mount		5
865	" "	" — " "	C-12	6
865	" "	" — " "	C-16	7
865	" "	" — " "	F-5	1



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
865	Ord. Pamphlet	Adapter—gun mount.....	E-10.....	15
865	" "	" " " ".....	E-11.....	17
865	" "	" assembly, 20-mm., AN-M1.....		301
865	" "	Bolt and bracket—gun trunnion.....	A-3.....	20
865	" "	Box—ammunition.....	L-4.....	21
865	" "	Charger—20-mm. hydraulic gun.....	D-3.....	39
865	" "	" —.50 caliber hydraulic gun.....	D-2.....	41
865	" "	Director—torpedo.....	Mk 28, Mod 2.....	248
865	" "	Discharger, pyrotechnic, AN-M5.....		326
865	Navy T.O.	Ends—impulse unit.....	E-3.....	98
865	Ord. Pamphlet	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types).....		299
865	" "	" machine, caliber .30 Browning, M2, aircraft fixed.....		93
865	" "	Handle—bomb release.....	A-3.....	250
865	" "	" —gun charging.....	A-2.....	46
865	" "	Hoist—portable bomb.....	AN-Mk 7 Mod 1.....	259
865	" "	Mechanism, feed, left hand, 20-mm., AN-M1.....		316
865	" "	" " right hand, 20-mm., AN-M1.....		317
865	" "	Motor—trigger.....	E-3.....	99
865	" "	" " " ".....	E-3A.....	100
865	" "	Pistol, pyrotechnic, AN-M8, w mount.....		330
865	" "	" " M2.....		327
865	" "	Post—gun mounting.....	A-4.....	13
865	" "	Sight—flexible gun post.....	A-4.....	76
865	" "	" " " ".....	A-5.....	77
865	" "	" " " " ring.....	B-10.....	79
865	" "	" " " " ".....	B-11.....	80
865	" "	" —illuminated.....	Mk 8.....	83
865	" "	" " " ".....	Mk 9.....	90
865	" "	Slide, operating, group assembly.....	D28200.....	310
865	" "	" retracting, group assembly.....	D28300A.....	311
865	" "	Solenoid—gun.....	G-4A.....	114
865	" "	" " " ".....	G-9.....	116
865	" "	" " " ".....	G-11.....	117
865	" "	" —left hand gun.....	C-4B.....	107
865	" "	" " " " ".....	C-4C.....	111
865	" "	" —right hand gun.....	C-4B.....	109
865	" "	" " " " ".....	C-4C.....	113
865	" "	Trigger—electric AN-M1.....		120
865A	" "	Rack—bomb.....	AN-Mk 51 Mod 7.....	273
865A	" "	Roll, tool armorer's w/contents, complete.....	A-28.....	321
865A	" "	" " " " ".....	A-38.....	323
925	" "	Rack—bomb.....	AN-Mk 51 Mod 7.....	273
949	" "	Hoist—portable bomb.....	AN-Mk 7 Mod 1.....	259
981-1	Av. Ord. Pam'let	Pistol, pyrotechnic, M2.....		327
1052 I.F.	Lamp Trade No.	Sight—fixed gun.....	N-3A.....	85
1052 I.F.	" " " "	" " " ".....	N-3B.....	86
1052 I.F.	" " " "	" —flexible gun.....	N-6.....	87
1052 I.F.	" " " "	" " " ".....	N-6A.....	89
1052 I.F.	" " " "	" " " ".....	N-8.....	91
1099-25-50	Mfr's Dwg.	Rheostat—variable resistance.....	D-1.....	123
1120 I.F.	Lamp Trade No.	Sight—fixed gun.....	N-3A.....	85
1120 I.F.	" " " "	" " " ".....	N-3B.....	86
1120 I.F.	" " " "	" —flexible gun.....	N-6.....	87
1120 I.F.	" " " "	" " " ".....	N-6A.....	89
1120 I.F.	" " " "	" " " ".....	N-8.....	91
1173-2	Mfr's Dwg.	Switch—control, stick gun.....	B-1A.....	124
1173-2	NAF Dwg.	" " " ".....	B-5.....	125
1300	Mfr's Dwg.	Turret—lower gun.....	A-2.....	157
1300	" " " "	" —retractable lower gun.....	A-13.....	159
1327	Lamp Trade No.	Sight—automatic compensating gun.....	K-3.....	92
1380	" " " "	Station—left blister sighting.....	2CSR31B2.....	192
1380	" " " "	" —nose sighting.....	2CSR31C1.....	193
1380	" " " "	" —right blister sighting.....	2CSR31B1.....	191
1380	" " " "	" —tail sighting.....	2CSR31B3.....	195
1380	" " " "	" —upper ring sighting.....	2CSR31A1.....	196
1411G2	Mfr's Dwg.	Solenoid—gun.....	E-8.....	103



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
1652 I.F.	Lamp Trade No.	Sight—illuminated	Mk 8.	83
1664 I.F.	" " "	" " "	Mk 9.	90
1666 I.F.	" " "	Director—torpedo	B-2	249
1684 I.F.	" " "	Sight—illuminated shell	Mk 9.	90
1900-12	T.B.	Destructor, AN-M3		295
2349	Ord. Spec.	Sight—illuminated	Mk 8.	83
2366	" " "	" " "	Mk 9.	90
3786	Ord. Data	Director—torpedo	Mk 28 Mod 2.	248
4050	Mfr's Part	Tachometer—bombsight disc speed	4050 & 4050A	292
4050A	" " "	" " " " " "	4050A & 4050	292
4303	Mfr's Spec.	Unit—double power hydraulic	AA-16801	169
4303	" " "	" " " " " "	AA-16804	171
4348	" " "	" " " " " "	AA-16801	169
4348	" " "	" " " " " "	AA-16804	171
4410	Ord. Data	Director—torpedo	Mk 28 Mod 2.	248
4447	" " "	Adapter assembly, 20-mm., AN-M1		301
4447	" " "	" " " " " " AN-M6		303
7542	Mfr's Part	Cover—electrically heated automatic pilot	PK 1A1	246
7542	" " "	" " " " bombsight	A-1	244
7542	" " "	" " " " " "	A-2	245
7545	" " "	" " " " automatic pilot	PK 1A1	246
7545	" " "	" " " " bombsight	A-1	244
7545	" " "	" " " " " "	A-2	245
7588	Bu. Aer. Dwg.	Generator—gun synchronizer impulse	E-8	97
8895	Mfr's Spec.	Switch—control stick gun	B-1A	124
8895	" " "	" " " " " "	B-5	125
20388	Mfr's Dwg.	Adapter—box	A	231
20933	" " "	Handle—bomb release	L-21A	253
24542	A.A.F. Spec.	" " " " " "	A-3	250
24557	" " "	Shackle—bomb	B-7	282
24583	" " "	Hoist—bomb	C-3	260
24591	" " "	Switch—control stick gun	B-1A	124
24592	" " "	Ends—impulse unit	E-3	98
24604	" " "	Container—ejected case	A-4	29
24605	" " "	" " " " link	A-4	32
24608	" " "	Post—gun mounting	A-4	73
24610B	" " "	Solenoid—gun	E-4	101
24620	" " "	" " " " " "	G-4A	114
24622	" " "	Shackle—bomb	D-5	286
24626	" " "	Rack—bomb	N-5	275
24628	" " "	" " " " " "	Q-2	276
24630	" " "	Control—bomb release interval	B-2	240
24638	" " "	Adapter—gun mount	E-5	12
24639	" " "	" " " " " "	C-16	7
24643	" " "	" " " " " "	C-12	6
24653	" " "	Box—ammunition	L-4	21
24655	" " "	Mount assembly—ball and socket gun	K-1	62
24660	" " "	Holder—ammunition box	A-1	47
24661	" " "	Mount—ammunition box	A-3	53
24667	" " "	Sight—telescopic gun	E-5	82
24669	" " "	Mount—flexible gun sight	C-4	58
24670	" " "	Box—ammunition	O-1	23
24674	" " "	Container—ejected link	A-3	31
24686	" " "	" " " " case	A-5	30
24687	" " "	Support—gun sight image reflector	41D3024	122
24689	" " "	Adapter—gun mount	E-8	14
24694	" " "	Shackle—bomb	D-6	287
24696	" " "	Adapter—gun mount	C-17	8
24697	" " "	Mount—ball and socket gun	K-2	63
24697	" " "	" " " " " "	K-2A	64
24698	" " "	" " " " " "	H-1	61
24702	" " "	Solenoid—gun	G-8	115
24703	" " "	Adapter—gun mount	E-10	15
24704	" " "	Sight—flexible gun	N-6	87
24704A	" " "	" " " " " "	N-6	87
24704A	" " "	" " " " " "	N-6A	89



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
24708	A. A. F. Spec.	Switch—control stick gun	B-5	125
24713	" "	Container—signal flare	A-1	34
24717	" "	Control—bomb release interval	AN-B-3	242
24718	" "	Holder—pyrotechnic pistol	A-1	48
24719	" "	Mount—gun	G-5	60
24720	" "	Adapter—gun mount	C-18	9
24721	" "	Container—ejected link	A-5	33
24730	" "	Adapter—gun mount	E-11	16
24731	" "	Sling—bomb hoist	A-1	289
24739	" "	Valve—hydraulic gun charging	A-1	128
24740	" "	Solenoid—gun	G-10	104
24742	" "	Release—bomb rack right hand	A-3	280
24743	" "	Solenoid—gun	E-6	102
24746	" "	" — "	G-11	117
24748	" "	Shackle—bomb	D-7	288
24749	" "	" — "	AN-B-9	283
24750	" "	Box—ammunition	L-7	22
24752	" "	Adapter—gun mount	E-12	18
24753	" "	Control—bomb arming	AN-A-1	236
24754	" "	Solenoid—gun	G-13	118
24758	" "	Sight—flexible gun post	A-11	78
24759	" "	" — " — " ring	B-13	81
24763	" "	Adapter—gun mount	E-5A	11
24764	" "	Solenoid—gun	G-15	119
24768	" "	" — "	E-8	103
24769	" "	" — "	G-16	105
24771	" "	Container—signal flare	A-5	35
24772	" "	" — " — "	A-6	36
24773	" "	" — " — "	A-7	37
24778	" "	Charger, manual, M2		38
24780	" "	Mount—ball and socket gun	K-3	65
24781	" "	Sling—bomb hoist	A-2	290
24808	" "	Trigger—electric AN-M1		120
24809	" "	Mount—bombaught	B-7	263
24814	" "	" — ball and socket gun	K-4	66
24815	" "	Adapter—gun mount	C-19	10
24817	" "	Sight—fixed gun	N-3B	86
24820	" "	Holder—pyrotechnic pistol	A-2	49
24823	" "	Trigger—manual	A-1	127
24828	" "	Control—bomb arming	AN-A-2	237
24829	" "	" — " — "	B-2	238
24830	" "	Mount—bomb arming control	A-1	262
24832	" "	Shackle—bomb	AN-B-10	284
24838	" "	Mount—swivel gun	K-5	67
24840	" "	" — grenade	A-1	261
24841	" "	Control—pilot director indicator	A-1	243
24843	" "	Receptacle—bomb release	A-1	277
24850	" "	Chute—flexible feed	B	25
24875	" "	Adapter—gun end	L-1	26
24876	" "	" — box end	L-2	27
30000	Mfr's Dwg.	Turret—lower gun	A-2	157
30000	" "	" — retractable lower gun	A-13	159
32968	" "	Chute—flexible feed	A	28
32968-150	" Mod.	" — " — "	A	28
32968-360	" "	" — " — "	A	28
32968-650	" "	" — " — "	A	28
40453	A. A. F. Spec.	Cover—electrically heated bombsight	A-1	244
40453-A	" "	" — " — " — "	A-1	244
40630	" "	" — " — " — "	A-2	245
40631	" "	" — " — " — automatic pilot	PK 1A1	246
40633	" "	" — " — " — " — "	PK 1A1	246
60050	Mfr's Dwg.	Socket—5 way bomb	A	291
66412	" "	Unit—double power hydraulic	AA-16801	169
66412	" "	" — " — " — " — "	AA-16804	171
63404	" "	" — " — " — " — "	AA-16801	169
63404	" "	" — " — " — " — "	AA-16804	171



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
76860	Mfr's Dwg.	Turret—lower gun	A-5	161
76860	" "	" — " "	A-10	163
76860-A	Mfr's Spec.	" — " "	A-5	161
76860-A	" "	" — " "	A-10	163
76861	Mfr's Dwg.	Valve—hydraulic gun charging	A-1	128
76862	" "	Charger—.50 caliber hydraulic gun	D-2	41
78001	" "	Turret—upper gun	A-4	149
78001	" "	" — " "	A-9	151
78001	" "	" — " "	A-9A	153
78001A	Mfr's Spec.	" — " "	A-4	149
78001A	" "	" — " "	A-9	151
78001A	" "	" — " "	A-9A	153
78002	Mfr's Dwg.	Charger—.30 caliber hydraulic gun	D-1	40
78003	" "	" —20-mm. hydraulic gun	D-3	39
79800	" "	Turret—lower gun	A-5	161
79800	" "	" — " "	A-10	163
80701	" "	" —upper gun	A-4	149
80701	" "	" — " "	A-9	151
80701	" "	" — " "	A-9A	153
82000	" "	" — " "	A-9	151
82000	" "	" — " "	A-9A	153
82500	" "	" —nose gun	A-16	168
99028	" "	Solenoid—gun	G-8	115
99030**	Bu. Ord. Sketch & Mfr's Dwg.	" — " "	G-11	117
076023*	Army & Mfr's Dwg.	Motor—trigger	E-3	99
076023*	" " " "	" — " "	E-3A	100
076031*	" " " "	Ends—impulse unit	E-3	98
108611	Bu. Ord. Dwg.	Handle—bomb release	Mk 4 Mod. 2	254
114081-N-1	" Aer. Dwg.	Generator—gun synchronizer impulse	E-8	97
15316	" Ord. Dwg.	Box—ammunition	L-4	21
15316	" " "	" — " "	L-7	22
155981	" " "	Handle—bomb release	A-3	250
155982	" " "	" — " "	A-3	250
163658	" " "	Ends—impulse unit	E-3	98
167348	" " "	Bolt and bracket—gun trunnion	A-3	20
169516	" " "	Shackle—bomb	B-7	282
169790	" " "	Slide, operating, group assembly	D28200	310
178456**	" " & Mfr's Dg.	Box—ammunition	L-4	21
178456	" " Dwg.	" — " "	L-7	22
178468**	" " & Mfr's Dg.	Adapter—gun mount	C-12	6
178474**	" " " "	Motor—trigger	E-3 Mk 1	99
178489**	" " " "	Handle—gun charging	A-2	46
179000**	" " " "	" —bomb release	Mk 4 Mod. 2	254
179007**	" " " "	Post—gun mounting	A-4	73
182900**	" " " "	Rack—bomb	Mk 43 Mod. 1	274
189812**	" " " "	Solenoid—left hand gun	C-4B	107
189812**	" " " "	Solenoid—left hand gun	C-4C	111
189812**	" " " "	" —right hand gun	C-4B	109
189812**	" " " "	" —right hand gun	C-4C	113
204674	" " Dwg.	Gun, machine, caliber .30 Browning, M2, aircraft, flexible		306
204676	" " " "	" " " " " aircraft, fixed		306
205955M	Mfr's Dwg.	Turret—lower gun	A-2	157
205955M	" "	" —retractable lower gun	A-13	159
210860J	" "	" —upper gun	A-1	133
210960J	" "	" — " "	A-1A	135
227622	" "	Motor—trigger	E-3	99
227622**	Bu. Ord. & Mfr's Dg.	" — " "	E-3A	100
238544	" " Dwg.	Sight—illuminated	Mk 8	83
247642	" " " "	Pistol, pyrotechnic, AN-M8 w mount		330
265673	" " " " modif.	Indicator—pilot director	Mk 15 Mod. 3	267
265673	" " " "	" — " "	Mk 15 Mod. 5	265
275122	" " " "	Director—torpedo	Mk 28 Mod. 2	248
278292	" " " "	Adapter—gun mount	E-11	17

*Army designation also used as commercial identification.

**Navy designation also used as commercial identification.

[illegible]

*Navy designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
646398-A	Mfr's Dwg. Asa's	Sight—automatic compensating gun	K-4	93
646636-A	" " "	" " " " " "	K-3	92
646636-A	" " "	" " " " " "	K-4	93
0153322	Army Dwg.	Switch—control stick gun	B-1A	124
0159268*	Army & Mfr's Dwg.	Handle—bomb and flare release	A-3A	251
0159268*	" " " " " "	" " " " " " release	A-3B	252
0159268	Mfr's Dwg.	Handle—bomb and flare release	A-3	250
0169221*	Army & Mfr's Dwg.	Switch—control stick gun	B-1A	124
0169221*	" " " " " "	" " " " " "	B-5	125
1590752	Mfr's Dwg.	Director—torpedo	Mk 28, Mod. 2	248
5147380	" " "	" " " " " "	B-2	249
8621274	" Part	Station—left blister sighting	2CSR3B2	192
8621274	" " "	" —nose sighting	2CSR3C1	193
8621274	" " "	" —right blister sighting	2CSR3B1	194
8621274	" " "	" —tail sighting	2CSR3B3	195
8621274	" " "	" —upper ring sighting	2CSR3A1	196
42578201K4	A.S.C. Stock	Switch—single pole toggle	AN3021-2	126
42578201K4	" " "	" —tail cannon selector	B-5A	197
4200613500	" " "	Rheostat—variable resistance	D-1	123
4200894750	" " "	Switch—single pole toggle	AN3021-2	126
4200894750	" " "	" —tail cannon selector	B-5A	197
4500216600	" " "	Container—signal flare	A-1	34
4500230375	" " "	" " " " " "	A-6	35
4500230400	" " "	" " " " " "	A-6	36
4500230450	" " "	" " " " " "	A-7	37
4500494500	" " "	Holder—pyrotechnic pistol	A-1	48
4500494600	" " "	" " " " " "	A-2	49
5200001775	" " "	Adapter—gun end	L-1	26
5200001785	" " "	" —box end	L-2	27
5200002365	" " "	" —gun mount		5
5200004500	" " "	" " " " " "	C-12	6
5200004850	" " "	" " " " " "	C-16	7
5200004870	" " "	" " " " " "	C-17	8
5200004870	" " "	" " " " " "	C-18	9
5200004900	" " "	" " " " " "	C-17	8
5200004900	" " "	" " " " " "	C-18	9
5200004950	" " "	" " " " " "	C-19	10
5200005450	" " "	" " " " " "	E-5	13
5200005450	" " "	" " " " " "	E-8	14
5200005450	" " "	" " " " " "	E-11	17
5200005450	" " "	" " " " " "	E-12	18
5200005460	" " "	" " " " " "	E-5A	11
5200005525	" " "	" " " " " "	E-5	13
5200005525	" " "	" " " " " "	E-8	14
5200005525	" " "	" " " " " "	E-11	17
5200005525	" " "	" " " " " "	E-12	18
5200005545	" " "	" " " " " "	E-10	15
5200005560	" " "	" " " " " "	E-5	13
5200005560	" " "	" " " " " "	E-8	14
5200005560	" " "	" " " " " "	E-11	17
5200005560	" " "	" " " " " "	E-12	18
5200005575	" " "	" " " " " "	E-5	13
5200005575	" " "	" " " " " "	E-8	14
5200005575	" " "	" " " " " "	E-11	17
5200005575	" " "	" " " " " "	E-12	18
5200043000	" " "	Barrel—gun charging turnbuckle		19
5200075000	" " "	Bolt and bracket—gun trunnion	A-3	20
5200090300	" " "	Box—ammunition	L-4	21
5200090300	" " "	" " " " " "	L-7	22
5200090500	" " "	" " " " " "	L-4	21
5200090500	" " "	" " " " " "	L-7	22
5200090900	" " "	" " " " " "	O-1	23
5200174506-5	" " "	Chute—flexible feed	A	28
5200174506-8	" " "	" " " " " "	A	28
5200174506-55	" " "	" " " " " "	A	28

*Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
5200174506-82	A.S.C. Stock	Chute—flexible feed	A	28
5200174506-84	" "	" "	A	28
5200174506-86	" "	" "	A	28
5200174506-555	" "	" "	A	28
5200174506-884	" "	" "	A	28
5200174506-888	" "	" "	A	28
5200177125	" "	" "	B	25
5200211900	" "	Container—ejected case	A-4	29
5200211900	" "	" "	A-5	30
5200211920	" "	" "	A-4	29
5200211920	" "	" "	A-5	30
5200213400	" "	" link	A-3	31
5200213400	" "	" "	A-4	32
5200213400	" "	" "	A-5	33
5200213700	" "	" "	A-3	31
5200213700	" "	" "	A-4	32
5200213700	" "	" "	A-5	33
5200213740	" "	" "	A-3	31
5200213740	" "	" "	A-4	32
5200213740	" "	" "	A-5	33
5200239040	" "	Motor—trigger	E-3	99
5200239040	" "	" "	E-3A	100
5200250600	" "	Ends—impulse unit	E-3	98
5200265250	" "	Feed—lower continuous	CF-5	45
5200265400	" "	" —left hand upper continuous	CF-3L	43
5200265420	" "	" —right hand upper continuous	CF-3R	44
5200291050	" "	Generator—gun synchronizer impulse	E-8	97
5200315800	" "	Handle—gun charging	A-2	46
5200328900	" "	Holder—ammunition box	A-1	47
5200465600	" "	Motor—trigger	E-3	99
5200465600	" "	" "	E-3A	100
5200466980	" "	Mount—ammunition box	A-3	53
5200467000	" "	" —left hand ammunition box	C-2	54
5200467000	" "	" "	C-3	56
5200467050	" "	" —right hand ammunition box	C-2	55
5200467050	" "	" "	C-3	57
5200467350	" "	" —left hand ammunition box	C-2	54
5200467350	" "	" "	C-3	56
5200467360	" "	" —right hand ammunition box	C-2	55
5200467360	" "	" "	C-3	57
5200468540	" "	" —ball and socket gun	K-4	66
5200471000	" "	" —flexible gun sight	C-4	58
5200473200	" "	" —swivel gun	K-5	67
5200473300	" "	" —gun	G-1A	59
5200473300	" "	" "	G-5	60
5200473325	" "	" "	G-1A	59
5200473325	" "	" "	G-5	60
5200473335	" "	" "	H-1	61
5200473350	" "	" —ball and socket gun	K-2	63
5200473350	" "	" "	K-2A	64
5200473350	" "	" "	K-3	65
5200473350	" "	assembly—ball and socket gun	K-1	62
5200473370	" "	" —ball and socket gun	K-2	63
5200473370	" "	" "	K-2A	64
5200473370	" "	" "	K-3	65
5200473370	" "	assembly—ball and socket gun	K-1	62
5200473380	" "	" —ball and socket gun	K-2	63
5200473380	" "	" "	K-2A	64
5200473380	" "	" "	K-3	65
5200473380	" "	assembly—ball and socket gun	K-1	62
5200473385	" "	" —ball and socket gun	K-2	63
5200473385	" "	" "	K-2A	64
5200473385	" "	" "	K-3	65
5200473385	" "	assembly—ball and socket gun	K-1	62
5200473500	" "	" —gun	M-1	69
5200473550	" "	" "	M-5	72



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
5200473555	A.S.C. Stock	Mount—gun	M-6	71
5200567100	" "	Post—gun mounting	A-4	73
5200726630	" "	Sight—fixed gun	N-3A	85
5200726630	" "	" " " "	N-3B	86
5200726635	" "	" " " "	N-3A	85
5200726635	" "	" " " "	N-3B	86
5200726690	" "	" —flexible gun	N-6	87
5200726690	" "	" " " "	N-6A	89
5200726690	" "	" " " "	N-8	91
5200727200	" "	" " " post	A-4	76
5200727500	" "	" " " "	A-6	77
5200727575	" "	" " " " "	A-11	78
5200728700	" "	" " " ring	B-10	79
5200729000	" "	" " " " "	B-11	80
5200729115	" "	" " " " "	B-13	81
5200729700	" "	" —telescopic gun	E-5	82
5200730700	" "	" —flexible gun	N-6	87
5200730700	" "	" " " "	N-6A	89
5200730700	" "	" " " "	N-8	91
5200730750	" "	" —illuminated	Mk 8	83
5200730760	" "	" " " "	Mk 9	90
5200731575	" "	" —flexible gun	N-6	87
5200731575	" "	" " " "	N-6A	89
5200731575	" "	" " " "	N-8	91
5200750000	" "	Solenoid—gun	G-16	106
5200751600	" "	" —left hand gun	C-4B	107
5200751600	" "	" " " "	C-4C	111
5200751600	" "	" —right hand gun	C-4B	109
5200751600	" "	" " " "	C-4C	113
5200751900	" "	" —left hand gun	C-4B	107
5200751900	" "	" " " "	C-4C	111
5200751900	" "	" —right hand gun	C-4B	109
5200751900	" "	" " " "	C-4C	113
5200751950	" "	" —left hand gun	C-4B	107
5200751950	" "	" " " "	C-4C	111
5200751950	" "	" —right hand gun	C-4B	109
5200751950	" "	" " " "	C-4C	113
5200751960	" "	" —left hand gun	C-4B	107
5200751960	" "	" " " "	C-4C	111
5200751960	" "	" —right hand gun	C-4B	109
5200751960	" "	" " " "	C-4C	113
5200752550	" "	" —gun	E-4	101
5200752550	" "	" " " "	E-6	102
5200752600	" "	" " " "	E-4	101
5200752600	" "	" " " "	E-6	102
5200752625	" "	Solenoid—gun	E-8	103
5200752755	" "	" " " "	G-4A	114
5200752825	" "	" " " "	G-4A	114
5200752825	" "	" " " "	G-9	116
5200752845	" "	" " " "	G-8	115
5200752845	" "	Trigger—electric AN-M1	G-17	120
5200752855	" "	Solenoid—gun	G-4A	114
5200752855	" "	" " " "	G-9	116
5200752865	" "	" " " "	G-10	104
5200752867	" "	" " " "	G-11	117
5200752870	" "	" " " "	G-13	118
5200752870	" "	" " " "	G-16	119
5200752890	" "	" " " "	G-13	118
5200752890	" "	" " " "	G-15	119
5200858150	" "	Support—gun sight image reflector	41D3024	122
5200858150	" "	" " " " " "	41D4892	121
5200858170	" "	" " " " " "	41D3024	122
5200858170	" "	" " " " " "	41D4892	121
5200875350	" "	Switch—control stick gun	B-1A	124
5200875350	" "	" " " " " "	B-5	125
5200875500	" "	" " " " " "	B-1A	124



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
5200875500	A.S.C. Stock	Switch—control stick gun.....	B-5.....	125
5200934150	" "	Trigger—manual.....	A-1.....	127
5200965700	" "	Valve—hydraulic gun charging.....	A-1.....	128
5200992900	" "	Yoke—gun mount adapter.....	41D6865.....	129
5400009212	" "	Motor generator—amplidyne local control.....	5AM31NJ18.....	50
5400239000	" "	Charger—20-mm. hydraulic gun.....	D-3.....	39
5400239040	" "	" —.30 caliber hydraulic gun.....	D-1.....	40
5400239050	" "	" —.50 caliber hydraulic gun.....	D-2.....	41
5400465615	" "	Motor—azimuth turret drive.....	5BA60LJ1.....	51
5400465630	" "	" —elevation turret drive.....	5BA60GJ1.....	52
5400963033	" "	Turret—tail gun.....	A-6.....	165
5400963035	" "	" —upper gun.....	A-4.....	149
5400963035	" "	" — " ".....	A-9.....	151
5400963035	" "	" — " ".....	A-9A.....	153
5400963064	" "	" —nose gun.....	A-16.....	168
5400963064	" "	" —upper gun.....	A-9.....	151
5400963066	" "	" —lower gun.....	A-2.....	157
5400963066	" "	" —retractable lower gun.....	A-13.....	159
5400963070	" "	" —lower gun.....	A-5.....	161
5400963070	" "	" — " ".....	A-10.....	163
5400963080	" "	" — " ".....	A-5.....	161
5400963080	" "	" — " ".....	A-10.....	163
5400963090	" "	" — " ".....	A-2.....	157
5400963090	" "	" —retractable lower gun.....	A-13.....	159
5400963103	" "	" —nose gun.....	A-15.....	167
5400963110	" "	" —lower gun.....	A-2.....	157
5400963110	" "	" —retractable lower gun.....	A-13.....	159
5400963140	" "	" —upper gun.....	A-4.....	149
5400963140	" "	" — " ".....	A-9.....	151
5400963140	" "	" — " ".....	A-9A.....	153
5400963141	" "	" — " ".....	A-3.....	137
5400963141	" "	" — " ".....	A-3A.....	139
5400963141	" "	" — " ".....	A-3B.....	141
5400963141	" "	" — " ".....	A-3C.....	143
5400963141	" "	" — " ".....	A-11.....	145
5400963141	" "	" — " ".....	A-14.....	147
5400963141-3	" "	" — " ".....	A-3.....	137
5400963141-3	" "	" — " ".....	A-3A.....	139
5400963141-3	" "	" — " ".....	A-3B.....	141
5400963141-3	" "	" — " ".....	A-3C.....	143
5400963141-3	" "	" — " ".....	A-11.....	145
5400963141-3	" "	" — " ".....	A-14.....	147
5400963142	" "	" — " ".....	A-3.....	137
5400963142	" "	" — " ".....	A-3A.....	139
5400963142	" "	" — " ".....	A-3B.....	141
5400963142	" "	" — " ".....	A-3C.....	143
5400963142	" "	" — " ".....	A-11.....	145
5400963142	" "	" — " ".....	A-14.....	147
5400963143-3	" "	" — " ".....	A-3.....	137
5400963143-3	" "	" — " ".....	A-3A.....	139
5400963143-3	" "	" — " ".....	A-3B.....	141
5400963143-3	" "	" — " ".....	A-3C.....	143
5400963143-3	" "	" — " ".....	A-11.....	145
5400963143-3	" "	" — " ".....	A-14.....	147
5400963144	" "	" — " ".....	A-3.....	137
5400963144	" "	" — " ".....	A-3A.....	139
5400963144	" "	" — " ".....	A-3B.....	141
5400963144	" "	" — " ".....	A-3C.....	143
5400963144	" "	" — " ".....	A-11.....	145
5400963144	" "	" — " ".....	A-14.....	147
5400963145	" "	" — " ".....	A-3.....	137
5400963145	" "	" — " ".....	A-3A.....	139
5400963145	" "	" — " ".....	A-3B.....	141
5400963145	" "	" — " ".....	A-3C.....	143
5400963145	" "	" — " ".....	A-11.....	145
5400963145	" "	" — " ".....	A-14.....	147



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
5400963149-3	A.S.C. Stock	Turret—upper gun	A-3	137
5400963149-3	" "	" "	A-3A	139
5400963149-3	" "	" "	A-3B	141
5400963149-3	" "	" "	A-3C	143
5400963149-3	" "	" "	A-11	145
5400963149-3	" "	" "	A-14	147
5400963149-5	" "	" "	A-3	137
5400963149-5	" "	" "	A-3A	139
5400963149-5	" "	" "	A-3B	141
5400963149-5	" "	" "	A-3C	143
5400963149-5	" "	" "	A-11	145
5400963149-5	" "	" "	A-14	147
5400963149-7	" "	" "	A-3	137
5400963149-7	" "	" "	A-3A	139
5400963149-7	" "	" "	A-3B	141
5400963149-7	" "	" "	A-3C	143
5400963149-7	" "	" "	A-11	145
5400963149-7	" "	" "	A-14	147
5400963149-43	" "	" "	A-3	137
5400963149-43	" "	" "	A-3A	139
5400963149-43	" "	" "	A-3B	141
5400963149-43	" "	" "	A-3C	143
5400963149-43	" "	" "	A-11	145
5400963149-43	" "	" "	A-14	147
5400963150	" "	" "	A-1	133
5400963150	" "	" "	A-1A	135
5400963165	" "	" "	A-1	133
5400963165	" "	" "	A-1A	135
5400963175	" "	" "	A-9A	153
5400963200	" "	" "	A-8	155
5400964512	" "	Unit—double power hydraulic	AA-16801	169
5400964512	" "	" "	AA-16804	171
5900092848	" "	Box—control	T-8007619	208
5900092849	" "	" —junction	T-8007523	209
5900170000	" "	Charger—gun	T-8252878	182, 213, 226
5900264875	" "	Dynamotor	5D21FJ2A	210
5900466500	" "	Motor generator—amplidyne remote control	5AM31NJ9	189, 211, 220
5900642525	" "	Selsyn	2J1G1	212
5900642550	" "	Servo—amplifier	2CV1B1	207, 216
5900719910	" "	Sight—automatic compensating gun	K-3	92
5900719910	" "	" "	K-4	93
5900721500	" "	" —compensating	K-8	95
5900731750	" "	Sight—automatic compensating gun	K-3	92
5900731750	" "	" "	K-4	93
5900883000	" "	Turret—upper gun	2CGQ50URA4	214
6400008420	" "	Adapter—box	A	231
6400009400	" "	Pilot—automatic	C-1	269
6400091560	" "	Pilot—automatic	C-1	271
6400092800	" "	Panel—autopilot control	A-6A	232
6400162010	" "	Carrier—universal bomb	No. 1 Mk 3	233
6400217000	" "	Control—bomb arming	AN-A-1	236
6400217000	" "	" "	AN-A-2	237
6400217050	" "	" "	AN-A-1	236
6400217050	" "	" "	AN-A-2	237
6400217100	" "	" "	B-2	238
6400217520	" "	" —release interval	B-2	240
6400217550	" "	" "	B-2	240
6400217550	" "	" "	B-2A	241
6400217700	" "	" "	AN-B-3	242
6400219325	" "	" —pilot director indicator	A-1	243
6400219650	" "	Pilot—automatic	C-1	270
6400225911	" "	Cover—electrically heated automatic pilot	PK 1A1	246
6400225919	" "	" —" " bomheight	A 2	245
6400225915	" "	" " " " " "	A-1	244
6400242425	" "	Director—torpedo	Mk 28 Mod 2	248
6400242430	" "	" "	B-2	249

(RESTRICTED)



NUMERICAL INDEX
ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
A-1*	Mfr's & Army Mod.	Control—bomb arming.	AN-A-2	237
A-1	Army Type	" " " "	B-2	238
A-1	" " " "	" " —pilot director indicator.	A-1	243
A-1	" " " "	Cover—electrically heated bombsight.	A-1	244
A-1*	Army & Mfr's Mod.	Head—pilot's bombsight.	A-1	255
A-1*	" " " "	" " " "	A-2	257
A-1	Army Type	Hoist—bomb	C-3	260
A-1	" " " "	Holder—ammunition box.	A-1	47
A-1	" " " "	" " —pyrotechnic pistol.	A-1	48
A-1	" " " "	Indicator—pilot director.	Mk 15 Mod. 3	266
A-1	" " " "	" " " "	Mk 15 Mod. 5	264
A-1	" " " "	Mount—ammunition box.	A-3	53
A-1	" " " "	" " —bomb arming control.	A-1	262
A-1	" " " "	" " —grenade	A-1	261
A-1	" " " "	Pistol—pyrotechnic, M2.	"	327
A-1	" " " "	Receptacle—bomb release.	A-1	277
A-1	" " " "	Release—bomb rack left hand.	A-2	278
A-1	" " " "	" " " " right hand.	A-2	279
A-1	" " " "	" " " " " "	A-3	280
A-1	" " " "	Ring—pilot's bombsight adapter.	43B15328	256
A-1	" " " "	Sight—automatic compensating gun.	K-3	92
A-1	" " " "	" " —fixed gun.	N-3A	85
A-1	" " " "	" " " "	N-3B	86
A-1	" " " "	" " —flexible gun.	N-6	87
A-1	" " " "	" " " "	N-6A	89
A-1	" " " "	Sling—bomb hoist.	A-1	249
A-1	" " " "	Solenoid—gun	G-11	117
A-1*	Army & Mfr's Mod.	Trigger—manual	A-1	127
A-1	Army Type	Turret—upper gun	A-1	132, 133
A-1	" " " "	" " " "	A-1A	135
A-1	" " " "	Unit—double power hydraulic.	AA-16901	169
A-1	" " " "	Valve—hydraulic gun charging.	A-1	128
A-1A	" " " "	Sight—automatic compensating gun.	K-3	92
A-1A*	Army & Mfr's Mod.	Turret—upper gun	A-1	133
A-1A	Army Type	" " " "	A-1A	134, 135
A-1A	" " " "	Unit—double power hydraulic.	AA-16801	169
A-2	" " " "	Container—signal flare.	A-5	35
A-2	" " " "	" " " "	A-6	36
A-2	" " " "	" " " "	A-7	37
A-2	" " " "	Control—bomb arming.	AN-A-2	237
A-2	" " " "	Cover—electrically heated bombsight.	A-2	245
A-2	" " " "	Handle—gun charging.	A-2	46
A-2*	Army & Mfr's Mod.	Head—pilot's bombsight.	A-1	255
A-2*	" " " "	" " " "	A-2	257
A-2	Army Type	Hoist—bomb	C-3	260
A-2	" " " "	" " —portable bomb.	AN-Mk 7 Mod. 1	258, 259
A-2	" " " "	Holder—pyrotechnic pistol.	A-2	49
A-2	" " " "	Receptacle—bomb release.	A-1	277
A-2*	Army & Mfr's Mod.	Release—bomb rack left hand.	A-2	278
A-2*	" " " "	" " " " right hand.	A-2	279
A-2	Army Type	Ring—pilot's bombsight adapter.	43B15328	256
A-2	" " " "	Shackle—bomb	AN-B-9	283
A-2	" " " "	" " " "	B-7	282
A-2	" " " "	" " " "	AN-B-10	284
A-2	" " " "	" " " "	D-6	287
A-2	" " " "	" " " "	D-7	288
A-2	" " " "	Sight—automatic compensating gun.	K-4	93
A-2	" " " "	" " —fixed gun.	N-3A	85
A-2	" " " "	" " " "	N-3B	86
A-2	" " " "	" " —flexible gun.	N-6	87
A-2	" " " "	" " " "	N-6A	89
A-2	" " " "	Sling—bomb hoist.	A-2	290
A-2*	Army & Mfr's Mod.	Solenoid—gun	A-2	156, 157
A-2*	" " " "	Turret—retractable lower gun.	A-13	159
A-2	Army Type	Unit—double power hydraulic.	AA-16804	170, 171

*Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
A-3	Army Type	Bolt and bracket—gun trunnion	A-3	20
A-3	" "	Container—ejected link	A-3	31
A-3*	Army & Mfr's Mod.	" " " "	A-4	32
A-3	" " " "	" " " "	A-5	33
A-3	Army Type	Cover—electrically heated automatic pilot	PK 1A1	246
A-3	Army & Mfr's Mod.	Handle—bomb and flare release	A-3A	251
A-3	" " " "	" " " "	A-3B	252
A-3	Army Type	" — " release	A-3	250
A-3	" "	Motor—azimuth turret drive	5BA50LJ1	51
A-3	" "	" —elevation turret drive	5BA50GJ1	52
A-3	" "	" generator—amplidyne local control	5AM31NJ18	50
A-3	" "	Mount—ammunition box	A-3	53
A-3	" "	Receptacle—bomb release	A-1	217
A-3	Army & Navy Type	Release—bomb rack right hand	A-3	280
A-3	Army Type	Shackle—bomb	AN-B-9	283
A-3	" "	" "	AN-B-10	284
A-3	" "	" "	B-7	282
A-3	" "	" "	D-6	287
A-3	" "	" "	D-7	288
A-3	" "	Turret—upper gun	A-3	136, 137
A-3	" "	" "	A-3A	139
A-3	" "	" "	A-3B	141
A-3	" "	" "	A-3C	143
A-3	" "	" "	A-11	145
A-3	" "	" "	A-14	147
A-3A	" "	Handle—bomb and flare release	A-3A	251
A-3A*	Army & Mfr's Mod.	" " " "	A-3B	252
A-3A	Army Type	" — " release	A-3	250
A-3A	" "	Motor—azimuth turret drive	5BA50LJ1	51
A-3A	" "	" —elevation turret drive	5BA50GJ1	52
A-3A	" "	" generator—amplidyne local control	5AM31NJ18	50
A-3A	" "	Turret—upper gun	A-3	137
A-3A	" "	" "	A-3A	138, 139
A-3A	" "	" "	A-3B	141
A-3A	" "	" "	A-3C	143
A-3A	" "	" "	A-11	145
A-3A	" "	" "	A-14	147
A-3B	" "	Handle—bomb and flare release	A-3A	251
A-3B*	Army & Mfr's Mod.	" " " "	A-3B	252
A-3B	Army Type	" — " release	A-3	250
A-3B	" "	Motor—azimuth turret drive	5BA50LJ1	51
A-3B	" "	" —elevation turret drive	5BA50GJ1	52
A-3B	" "	" generator—amplidyne local control	5AM31NJ18	50
A-3B	" "	Turret—upper gun	A-3	137
A-3B	" "	" "	A-3A	139
A-3B	" "	" "	A-3B	140, 141
A-3B	" "	" "	A-3C	143
A-3B	" "	" "	A-11	145
A-3B	" "	" "	A-14	147
A-3C	" "	Motor—azimuth turret drive	5BA50LJ1	51
A-3C	" "	" —elevation turret drive	5BA50GJ1	52
A-3C	" "	" generator—amplidyne local control	5AM31NJ18	50
A-3C	" "	Sight—compensating	K-8	95
A-3C	" "	Turret—upper gun	A-3	137
A-3C	" "	" "	A-3A	139
A-3C	" "	" "	A-3B	141
A-3C	" "	" "	A-3C	142, 143
A-3C	" "	" "	A-11	145
A-3C	" "	" "	A-14	147
A-4	" "	Container—ejected case	A-4	29
A-4*	Army & Mfr's Mod.	" " " "	A-5	30
A-4*	" " " "	" " " "	A-3	31
A-4*	" " " "	" " " "	A-4	32
A-4*	" " " "	" " " "	A-5	33
A-4	Army Type	Cover—electrically heated automatic pilot	PK 1A1	246

*Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
A-4	Army Type	Post—gun mounting	A-4	73
A-4	" "	Receptacle—bomb release	A-1	277
A-4	" "	Shackle—bomb	AN-B-9	283
A-4	" "	" — "	AN-B-10	284
A-4	" "	" — "	B-7	282
A-4	" "	" — "	D-6	287
A-4	" "	" — "	D-7	288
A-4	" "	Sight—flexible gun post	A-4	76
A-4	" "	" — " " ring	B-10	79
A-4	" "	Turret—upper gun	A-4	148, 149
A-4	" "	" — " "	A-9	151
A-4	" "	" — " "	A-9A	153
A-5	" "	Container—ejected case	A-4	29
A-5*	Army & Mfr's Mod.	" — " "	A-5	30
A-5*	" " " "	" — " link	A-3	31
A-5*	" " " "	" — " "	A-4	32
A-5*	" " " "	" — " "	A-5	33
A-5*	" " " "	" — signal flare	A-5	35
A-5	Army Type	Holder—pyrotechnic pistol	A-2	49
A-5	" "	Mount—gun	M-5	72
A-5*	Army & Mfr's Mod.	Sight—flexible gun post	A-5	77
A-5	Army Type	" — " " ring	B-11	80
A-5	" "	Turret—lower gun	A-5	160, 161
A-5	" "	" — " "	A-10	163
A-6	" "	Container—signal flare	A-6	36
A-6	" "	Holder—pyrotechnic pistol	A-2	49
A-6*	Army & Mfr's Mod.	Turret—tail gun	A-6	164, 165
A-6A	Army Type	Panel—autopilot control	A-6A	232
A-7	" "	Container—signal flare	A-1	34
A-7	" "	" — " "	A-7	37
A-7	" "	Holder—pyrotechnic pistol	A-2	49
A-8	" "	Turret—upper training	A-8	154, 155
A-9	" "	Motor—azimuth turret drive	5BA50LJ1	51
A-9	" "	" — elevation turret drive	5BA50GJ1	52
A-9	" "	" generator—amplidyne local control	5AM31NJ18	50
A-9	" "	Turret—upper gun	A-9	150, 151
A-9	" "	" — " "	A-9A	153
A-9A	" "	Motor—azimuth turret drive	5BA50LJ1	51
A-9A	" "	" — elevation turret drive	5BA50GJ1	52
A-9A	" "	" generator—amplidyne local control	5AM31NJ18	50
A-9A	" "	Turret—upper gun	A-4	149
A-9A	" "	" — " "	A-9	151
A-9A	" "	" — " "	A-9A	152, 153
A-10	" "	Motor—azimuth turret drive	5BA50LJ1	51
A-10	" "	" — elevation turret drive	5BA50GJ1	52
A-10	" "	" generator—amplidyne local control	5AM31NJ18	50
A-10	" "	Turret—lower gun	A-5	161
A-10	" "	" — " "	A-10	162, 163
A-10	" "	" — upper gun	A-4	149
A-11	" "	Motor—azimuth turret drive	5BA50LJ1	51
A-11	" "	" — elevation turret drive	5BA50GJ1	52
A-11*	Army & Mfr's Mod.	Sight—flexible gun post	A-11	78
A-11	Army Type	" — " " ring	B-13	81
A-11	" "	Turret—upper gun	A-3	137
A-11	" "	" — " "	A-3A	139
A-11	" "	" — " "	A-3B	141
A-11	" "	" — " "	A-3C	143
A-11	" "	" — " "	A-11	144, 145
A-11	" "	" — " "	A-14	147
A-13	" "	Sight—automatic compensating gun	K-4	93
A-13*	Army & Mfr's Mod.	Turret—lower gun	A-2	157
A-13*	" " " "	" — retractable lower gun	A-13	158, 159
A-13	Army Type	Unit—double power hydraulic	AA-16804	170, 171
A-14	" "	Turret—upper gun	A-3	137
A-14	" "	" — " "	A-3A	139

*Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
A-14	Army Type	Turret—upper gun.	A-3B	141
A-14	" "	" — " "	A-3C	143
A-14	" "	" — " "	A-11	145
A-14	" "	" — " "	A-14	146, 147
A-15	" "	Motor—azimuth turret drive.	5BA50LJ1	51
A-15	" "	" —elevation turret drive.	5BA50GJ1	52
A-15	" "	" generator—amplidyne local control.	5AM31NJ18	50
A-15*	Army & Mfr's Mod.	Turret—nose gun.	A-15	166, 167
A-16	Army Type	Motor generator—amplidyne local control.	5AM31NJ18	50
A-16	" "	Turret—nose gun.	A-16	168
A-26	" "	Box—junction	T-8252853	218
A-28	Std. Nom. List No.	Gun, machine, caliber .30 Browning, aircraft, fixed.	M2	306
A-28	" " " "	" " " " " M2, aircraft, flexible.		308
A-28	" " " "	" " " " " " " "		
A-28	" " " "	with fixed back plate.	M2	307
A-28	Ord. SNL	Roll, tool armorer's w/ contents, complete.	A-28	320, 321
A-38	Std. Nom. List No.	Gun, machine, caliber .50 Browning, M2, aircraft, basic.		309
A-38	" " " "	Roll, tool, armorer's w/ contents, complete.	A-38	322, 323
A-38	" " " "	Slide, operating, group assembly.	D28200	310
A-38	" " " "	" retracting, group assembly.	D28300A	311
A-38	" " " "	Stud—bolt	A13424	319
A-46	" " " "	Gun, automatic, 37-mm., M4.	M4	296
A-46	" " " "	Magazine, endless belt, 37-mm., M6.		314
A-46	" " " "	" 15 round, 37-mm., M2.		312
A-47	" " " "	Adapter assembly, 20-mm., AN-M1.	AN-M1	301
A-47	" " " "	" " " AN-M6.	M6	303
A-47	" " " "	Gun, aircraft, automatic 20-mm., M1 and AN-M2 (all types).	M1 and AN-M2	299
A-47	" " " "	Magazine, 60 RD, 20-mm., M1.		313
A-47	" " " "	Mechanism, feed, left hand, 20-mm., AN-M1.	M1	316
A-47	" " " "	" " right hand, 20-mm., AN-M1.	M1	317
A13424	Ord. Dwg.	Stud—bolt	A13424	319
A-16750	Mfr's Dwg. No.	Hoist—bomb	C-3	260
A25940	Ord. Dwg.	Mechanism, feed, left hand, 20-mm., AN-M1.	M1	316
A25940	Army Dwg.	" " right hand, 20-mm., AN-M1.	M1	317
A196228	Ord. Dwg.	Roll, tool, armorer's w/ contents, complete.	A-38	322
A196229	" " " "	" " " " " " " "	A-28	320
AA-16801	Mfr's Mod.	Unit—double power hydraulic.	AA-16801	169
AA-16801	" " " "	" " " " " " " "	AA-16804	171
AA-16804	" " " "	" " " " " " " "	AA-16801	169
AA-16804	" " " "	" " " " " " " "	AA-16804	170, 171
Aer-Ma-12431				
-EG-F41-14	Navy Tech. Note	Generator—gun synchronizer impulse.	E-8	97
Aer-Ma-12431				
-EG-F41-14	Bu. Aer. Note No.	Solenoid—gun	E-6	102
AG-100	Mfr's Dwg.	Shackle—bomb	D-6	287
AG-150	" " " "	Mount—ball and socket gun.	K-2	63
AG-150	" " " "	" — " " " " " " " "	K-2A	64
AG-150	" " " "	" — " " " " " " " "	K-3	65
AG-150	" " " "	" assembly—ball and socket gun.	K-1	62
AG-200	" " " "	Shackle—bomb	D-3	285
AG-200	" " " "	" — " " " " " " " "	D-5	286
AG-300	" " " "	" — " " " " " " " "	AN-B-9	283
AG-360	" " " "	Mount—ball and socket gun.	K-4	66
AG-400	" " " "	Adapter—gun mount.	C-19	10
AG-500	" " " "	Shackle—bomb	AN-B-10	284
AG-700	" " " "	" — " " " " " " " "	D-7	288
AG-800	" " " "	Mount—swivel gun.	K-5	67
AN3015*	AN & Mfr's Dwg.	Switch—single pole toggle.	AN3022-2	126
AN3015*	" " " " " "	" —tail cannon selector.	B-5A	197
AN3022	AN Dwg.	" —single pole toggle.	AN3022-2	126
AN3022-2	" " " "	Rock—bomb	N-5	275
AN3022-2	" Part	" — " " " " " " " "	Q-2	276
AN3022-2*	AN Part & Mfr's Dg.	Switch—single pole toggle.	AN3022-2	126
AN3022-2	AN Part	" —tail cannon selector.	AN3022-2	197
AN3022-2B	" " " "	" —single pole toggle.	AN3022-2	126

*Army designation also used as commercial identification



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
AN3102-8S-1P	AN Part	Director—torpedo	B-2	249
AN3102-10S-2P	" "	Sight—flexible gun	N-6A	89
AN3102-10S-2P	" "	Solenoid—gun	G-4A	114
AN3102-10S-2P	" "	" — "	G-8	115
AN3102-10S-2P	" "	" — "	G-13	118
AN3102-10S-2P	" "	" — "	G-15	119
AN3102-10S-2P	" "	Trigger—electric, AN-M1	G-17	120
AN3102-12S-3P	" "	Sight—fixed gun	N-3B	86
AN3102-12S-3P	" "			
(2 pin)	" "	Indicator—pilot director	Mk 15 Mod. 3	267
AN3102-14S-5P	" "	Pilot—automatic	C-1	270
AN3102-12S-3P	" "			
(2 pin)	" "	Indicator—pilot director	Mk 15 Mod. 5	265
AN3102-14S-7P	" "	Control—bomb release interval	AN-B-3	242
AN3106-10S-2S	" "	" — " arming	B-2	238
AN3106-10S-2S	AN & Mfr's Part	" — " " "	AN-A-1	236
AN3106-10S-2S	" " " "	" — " " "	AN-A-2	237
AN3106-10S-2S	AN Part	Solenoid—gun	E-8	103
AN3106-12S-3S	" "	Indicator—pilot director	Mk 15 Mod. 5	264, 265
AN3106-14S-5S	" "	Rack—bomb	AN Mk 51 Mod. 7	272
AN3106-16-11P	" "	Cover—electrically heated bombsight	A-1	244
AN3108-14S-5S	" "	Rack—bomb	AN Mk 51 Mod. 7	272
AN3155	AN Dwg.	Rheostat—variable resistance	D-1	123
AN-A-1	AN Type	Control—bomb arming	AN-A-1	236
AN-A-1	" "	" — " " "	AN-A-2	237
AN-A-2	" "	" — " " "	AN-A-1	236
AN-A-2	" "	" — " " "	AN-A-2	237
AN-A-2	" "	Mount—bomb arming control	A-1	262
AN-B-3*	AN & Mfr's Mod.	Control—bomb release interval	AN-B-3	242
AN-B-9	AN Type	Shackle—bomb	AN-B-9	283
AN-B-10	" "	" — "	AN-B-10	284
AN-M1	" "	Adapter assembly, 20-mm., AN-M1	AN-M1	300, 301
AN-M1	" "	" — " " " AN-M6	AN-M6	302, 303
AN-M1	" "	Gun, aircraft, automatic, 20-mm., AN-M2	M1 & AN-M2	298, 299
AN-M1	" "	Mechanism, feed, left hand, 20-mm., AN-M1	M1	316
AN-M1	" "	" — " right hand, 20-mm., AN-M1	M1	317
AN-M1	Ord. Office Mod.	Solenoid—gun	G-8	115
AN-M1*	Ord. & Mfr's Mod.	Trigger—electric, AN-M1	G-17	120
AN-M2	AN Type	Adapter assembly, 20-mm., AN-M1	M1	301
AN-M2	" "	" — " " " AN-M6	AN-M6	303
AN-M2	" "	Charger—20-mm. hydraulic gun	D-3	39
AN-M2	" "	Charger, manual, M2	B-6	38
AN-M2	" "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)	M1 and AN-M2	297, 298, 299
AN-M2	" "	Magazine, 60 RD, 20-mm., M1		313
AN-M2	" "	Mechanism, feed, left hand, 20-mm., AN-M1	M1	316
AN-M2	" "	" — " right hand, 20-mm., AN-M1	M1	317
AN-M2	" "	Solenoid—gun	G-8	115
AN-M2	" "	Trigger—electric, AN-M1	G-17	120
AN-M2	" "	Valve—hydraulic gun charging	A-1	128
AN-M3	" "	Destructor, AN-M3	AN-M3	295
AN-M5	" "	Discharger, pyrotechnic, AN-M5	M5	326
AN-M6	" "	Adapter assembly, 20-mm., AN-M1	AN-M1	300
AN-M6	" "	" — " " " AN-M6	AN-M6	302, 303
AN-M6	" "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)	M1 and AN-M2	298
AN-M8	" "	Discharger—pyrotechnic	AN-M5	326
AN-M8	" "	Holder—pyrotechnic pistol	A-2	49
AN-M8	" "	Pistol—pyrotechnic, AN-M8, w/mount	M8	330
AN-M8	" "	Pistol, pyrotechnic, M2		327
AN-M8	" "	" — " signal	No. 4 Mk 1	328
AN-M14	" "	Mount—grenade	A-1	261
AN-M28 to	" "			
AN-M36, inc.	" "	Signals, aircraft, rimless type		325
AN-M37 to	" "			
AN-M45, inc.	" "	Container—signal flare	A-5	35
AN-M37	" "	" — " " "	A-6	36

*Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
AN-M37 to AN-M45, inc.	AN Type	Container—signal flare	A-7	37
AN-M37 to AN-M45, inc.	" "	Discharger, pyrotechnic, AN-M5		326
AN-M37 to AN-M45, inc.	" "	Pistol, pyrotechnic, AN-M8, w/mount		330
AN-M37 to AN-M45, inc.	" "	" signal	No. 4 Mk 1	329
AN-M37 to AN-M45, inc.	" "	signals, aircraft: cartridge type		325
AN-M45	" "	Container—signal flare	A-6	36
AN-Mk. 7, Mod. 1*	" " Mfr's Mod.	Hoist—portable bomb	AN-Mk 7 Mod. 1	258, 259
AN-Mk. 51, Mod. 5	" "	Rack—bomb	AN-Mk 51, Mod. 7	272
AN-Mk. 51, Mod. 7*	" " " "	Handle—bomb release	Mk 4 Mod. 2	254
AN-Mk. 51, Mod. 7*	" " " "	Rack—bomb	AN-Mk 51 Mod. 7	272, 273
AN-R-14	" Spec.	Rheostat—variable resistance	D-1	123
AN-RR-C-43	" "	Handle—bomb and flare release	3A	251
AN-RR-C-43	" "	" — " " " "	A-3B	252
AN-S-20	" "	Switch—single pole toggle	AN3022-2	126
AND10066- 10S-2P	" Part	Solenoid—gun	E-6	102
AND10066- 10S-2P	" "	" — "	E-8	103
AND10427- 14S-5P	" "	Rack—bomb	AN-Mk 51 Mod. 7	272
AT-40N-127	Mfr's Spec.	Turret—nose gun	A-15	167
B	" Type	Adapter—box end	L-2	27
B	" "	" —gun end	L-1	26
B	" "	Chute—flexible feed	A	28
B	" "	" — " "	B	25
B-1A*	Army & Mfr's Mod.	Switch—control stick gun	B-1A	124
B-1A	" Type	" — " "	B-6	125
B-2	" "	Control—bomb arming	B-2	238
B-2	" "	" — " release interval	B-2	240
B-2	" "	Direction—torpedo	B-2	249
B-2	" "	Director—torpedo	Mk 28 Mod. 2	248
B-2	" "	Mount—bomb arming control	A-1	262
B-2A*	" & Mfr's Mod.	Control—bomb release interval	B-2	240
B-2A	" Type	" — " " " "	B-2A	241
B-3	" "	" — " " " "	AN-B-3	242
B-5	" "	Barrel—gun charging turnbuckle		19
B-5	" "	Rack—bomb	N-5	275
B-5	" "	" — " "	Q-2	276
B-5*	" & Mfr's Mod.	Switch—control stick gun	B-1A	124
B-5	" Type	" — " " " "	B-5	125
B-5A*	" & Mfr's Mod.	" —single pole toggle	AN3022-2	126
B-5A*	" " " "	" —tail cannon selector	B-5A	197
B-6	" Type	Charger—20-mm. hydraulic gun	D-3	39
B-6*	" & Mfr's Mod.	Charger, manual, M2	B-6	38
B-6	" Type	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		298
B-7	" "	Mount—bombsight	B-7	263
B-7*	AN Type			
	& Mfr's Mod.	Shackle—bomb	B-7	282
B-9	Army Type	" — " "	AN-B-9	283
B-10	" "	" — " "	B-7	282
B-10	" "	Sight—flexible gun post	A-4	76
B-10*	" & Mfr's Mod.	" — " " ring	B-10	79
B-11	" Type	Mount—gun	M-5	72
B-11	" "	Sight—flexible gun post	A-5	77
B-11	" "	" — " " ring	B-11	80
B-13	" "	" — " " post	A-11	78

*Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
B-13*	Army & Mfr's Mod.	Sight—flexible gun ring	B-13	81
B-16	" Type	" — " " "	B-11	80
B-18	Ord. SNL	Pistol, pyrotechnic, M2		327
B-29	Army Type	Computer—double parallax	2CH1D1	183
B-29	" "	Switch—tail cannon selector	B-5A	191
B-33	Ord. SNL	Pistol, pyrotechnic, AN-M8, w/mount	M8	330
B-34	" "	Discharger, pyrotechnic, AN-M6	M5	326
B-134163	Mfr's Dwg.-outline	Control—bomb arming	AN-A-1	236
B-134163	" " "	" — " " "	AN-A-2	237
B-134163	" " "	" — " " "	B-2	238
B-134204	" " "	" — " release interval	B-2	240
B-134204	" " "	" — " " "	B-2A	241
B-134375	" " "	Receptacle—bomb release	A-1	277
B-134405	Mfr's Dwg.-outline	Control—pilot director indicator	A-1	243
B8514	Ord. Dwg.	Roll, tool, armorer's w/contents, complete	A-38	322
B108828	" " "	" " " " " " "	A-28	320
B108828	" " "	" " " " " " "	A-38	322
B131314	" " "	" " " " " " "	A-28	323
B147001	" " "	" " " " " " "	A-28	320
B147160	" " "	" " " " " " "	A-28	320
B147160	" " "	" " " " " " "	A-38	322
B163511A	" " "	Mechanism, feed, left hand, 20-mm., AN-M1	M1	316
B163511A	" " "	" " " right hand, 20-mm., AN-M1	M1	317
BA-106000	Mfr's Dwg.	Control—bomb arming	AN-A-1	236
BA-106000	" " "	" — " " "	AN-A-2	237
BR-719-CSP	" " "	Carrier—universal bomb	No. 1 Mk 3	233
BR-105000	Mfr's Dwg.	Control—bomb release interval	B-2	240
BR-105000	" " "	" — " " " "	B-2A	241
BR-105100	" " "	" — " " " "	AN-B-3	242
BR-BT-7R	" Spec.	Turret—lower gun	A-2	157
BR-BT-7R	" " "	" —retractable lower gun	A-13	159
C	" Mod.	Charger—.50 caliber hydraulic gun	D-2	41
C	" " "	Valve—hydraulic gun charging	A-1	128
C-1	Army Type	Adapter—gun mount	E-8	14
C-1	" " "	" — " " "	E-12	18
C-1	" " "	Control—pilot director indicator	A-1	243
C-1	" " "	Cover—electrically heated automatic pilot	PK 1A1	246
C-1	" " "	Indicator—pilot director	Mk 15 Mod. 3	266
C-1	" " "	" — " " " "	Mk 15 Mod. 5	264
C-1	" " "	Panel—autopilot control	A-6A	232
C-1	" " "	Pilot—automatic	C-1	248
C-2	" " "	Adapter—gun end	L-1	26
C-2	" " "	Box—ammunition	O-1	23
C-2	" " "	Chute—flexible feed	A	28
C-2*	" & Mfr's Mod.	Mount—left hand ammunition box	C-2	54
C-2*	" " " "	" — " " " " "	C-3	56
C-2*	" " " "	" —right hand ammunition box	C-2	55
C-2*	" " " "	" — " " " " "	C-3	57
C-3	" Type	Adapter—gun end	L-1	26
C-3	" " "	" — " mount	E-8	14
C-3	" " "	" — " " "	E-12	18
C-3	" " "	Box—ammunition	O-1	23
C-3	" " "	Chute—flexible feed	A	28
C-3	" " "	Hoist—bomb	C-3	260
C-3*	" & Mfr's Mod.	Mount—left hand ammunition box	C-2	54
C-3*	" " " "	" — " " " " "	C-3	56
C-3*	" " " "	" —right hand ammunition box	C-2	55
C-3*	" " " "	" — " " " " "	C-3	57
C-3	" Type	Sling—bomb hoist	A-1	289
C-3	" " "	" — " " "	A-2	290
C-4	" " "	Adapter—gun mount	E-8	14
C-4	" " "	" — " " "	E-12	18
C-4*	" & Mfr's Mod.	Mount—flexible gun sight	C-4	58
C-4	" Type	Sight—telescopic gun	E-5	82
C-4B*	" & Mfr's Mod.	Solenoid—left hand gun	C-4B	106, 107

*Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used In Connection with	Type, Drawing or Designation	Page
C-4B*	Army & Mfr's Mod.	Solenoid—left hand gun.	C-4C	111
C-4B*	" " " "	" —right hand gun	C-4B	108, 109
C-4B*	" " " "	" — " " "	C-4C	113
C-4C*	" " " "	" —left hand gun	C-4C	104, 107, 111
C-4C	Type	" —right hand gun	C-4B	108, 109
C-4C*	& Mfr's Mod.	" " " "	C-4C	112, 113
C-12	Type	Adapter—gun mount	C-12	6
C-12	" "	Container—ejected case	A-4	29
C-12	" "	" — " "	A-5	30
C-16	" "	Adapter—gun mount	C-12	6
C-16	" "	" — " "	C-16	7
C-16	" "	Mount—gun	G-1A	59
C-16	" "	" — " "	G-6	60
C-17	" "	Adapter—gun mount	C-17	8
C-17*	& Mfr's Mod.	" — " "	C-18	9
C-17	Army Type	Mount—ball and socket gun	K-2	63
C-17	" "	" — " " "	K-2A	64
C-17	" "	" — " " "	K-3	65
C-17	" "	" assembly—ball and socket gun	K-1	62
C-18*	& Mfr's Mod.	Adapter—gun mount	C-17	8
C-18	Army Type	" — " "	C-18	9
C-18	" "	Mount—ball and socket gun	K-2A	64
C-18	" "	" — " " "	K-3	65
C-19	" "	Adapter—gun mount	C-19	10
C-19	" "	Mount—ball and socket gun	K-4	66
C-47	SNL	Mount, gun, airplane, 75-mm., M6		318
C-57-58	Mfr's Dwg.	Release—bomb rack right hand	A-2	279
C-57-57	" "	" — " left hand	A-2	278
C-24580-C	AAF Spec.	Indicator—pilot director	Mk 15 Mod. 3	267
C-24580-D	" "	" — " "	Mk 15 Mod. 3	267
C-24825	" "	" — " "	Mk 15 Mod. 3	267
C-24796	" "	Pilot—automatic	C-1	270
C-24825	" "	Indicator—pilot director	Mk 15 Mod. 5	264
C-24825	" "	Panel—autopilot control	A-6A	232
C-24825	" "	Pilot—automatic	C-1	268
C-24827	" "	" — " "	C-1	270
C-24858	" "	" — " "	C-1	269
C-24859	" "	" — " "	C-1	269
C-24860	" "	" — " "	C-1	270
C-24861	" "	Panel—autopilot control	A-6A	232
C-24861	" "	Pilot—automatic	C-1	271
C-24862	" "	" — " "	C-1	270
C-24863	" "	Indicator—pilot director	Mk 15 Mod. 5	264
C-24864	" "	Pilot—automatic	C-1	271
C-134558	Mfr's Dwg.-outline	Control—bomb release interval	AN-B-3	242
C-134558	" " " "	" — " " "	B-2	240
C-134558	" " " "	" — " " "	B-2A	241
C-134584	" " " "	" — " " "	B-2	240
C-134584	" " " "	" — " " "	B-2A	241
C-134588	" "	Release—bomb rack	A-2	279
C-134588	" " -outline	" — " left hand	A-2	278
C-134600	" " -assy.	" — " right hand	A-3	280
C-134624	" "	Control—bomb arming	AN-A-1	236
C-134624	" "	" — " " "	AN-A-2	237
C-134643	" "	" — " release interval	B-2	240
C-134643	" "	" — " " "	B-2A	241
C-134727	" " -outline	Release—bomb rack right hand	A-3	280
C-134729	" " " "	Control—bomb release interval	AN-B-3	242
C-134729	" " " "	" — " " "	B-2	240
C-134729	" " " "	" — " " "	B-2A	241
C-134732	" "	Release—bomb rack left hand	A-2	278
C-134732	" " " "	" — " right hand	A-2	279
C-134815	" " -part	Control—pilot director indicator	A-1	243
C3854	Ord. Dwg.	Roll. tool, armorer's w/contents, complete	A-28	320
C3856	" " " "	" " " "	A-28	320

*Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
C3856	Ord. Dwg.	Roll, tool, armorer's w/contents, complete.	A-38	322
C4035	" "	" " " " " "	A-28	320
C4037	" "	" " " " " "	A-38	322
C6573	" "	" " " " " "	A-28	320
C59737	" "	" " " " " "	A-28	320
C59737	" "	" " " " " "	A-38	322
C64255	" "	" " " " " "	A-38	322
C64274	" "	" " " " " "	A-38	322
C64302	" "	" " " " " "	A-28	320
C70512	" "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types).	M1 and AN-M2	298
C70590	" "	" " " " " " " " " " " "	M1 and AN-M2	298
C70766*	Army & Mfr's Dwg.	Solenoid—gun	G-8	115
C70766	" " " "	Trigger—electric AN-M1	G-17	120
C70814	Ord. Dwg.	Solenoid—gun	G-8	115
CF-3L	Army & Mfr's Mod.	Feed—left hand upper continuous.	CF-3L	43
CF-3R	" " " "	" —right hand upper continuous.	CF-3R	44
CF-5	" " " "	" —left hand upper continuous.	CF-3L	43
CF-5	" " " "	" —right hand upper continuous.	CF-3R	44
CF-5	" " " "	" —lower continuous	CF-5	45
D	" " " "	Turret—nose gun	A-16	168
D-1	" Type	Charger—.30 caliber hydraulic gun.	D-1	40
D-1	" " "	Rheostat—variable resistance	D-1	123
D-2	" " "	Charger—.50 caliber hydraulic gun.	D-2	41
D-3	" " "	" —20-mm. hydraulic gun.	D-3	39
D-3	" " "	Gun, aircraft, automatic, 20-mm., AN-M2	M1 and AN-M2	298
D-3*	" & Mfr's Mod.	Shackle—bomb	D-3	285
D-3*	" " " "	" — " "	D-5	286
D-4*	" " " "	" — " "	D-6	287
D-5*	" " " "	" — " "	D-3	285
D-5*	" " " "	" — " "	D-5	286
D-6	" Type	" — " "	D-5	286
D-6*	A & N & Mfr's Mod.	" — " "	D-6	287
D-7*	Army & Mfr's Mod.	" — " "	D-7	288
D-210530	Mfr's Dwg.	Release—bomb rack left hand.	A-2	278
D-210607	" " "	" — " " right hand	A-2	279
D1888	Ord. Dwg.	Roll, tool, armorer's w/contents, complete.	A-28	320
D1888	" " "	" " " " " " " "	A-38	323
D8237	" " "	" " " " " " " "	A-28	320
D10305	" " "	Pistol, pyrotechnic, M2		327
D28200	" " "	Slide, operating, group assembly	D28200	310
D28242	" " "	Roll, tool, armorer's w/contents, complete.	A-38	322
D28300A	" " "	Slide, retracting, group assembly	D28300A	311
D35441	" " "	Roll, tool, armorer's w/contents, complete.	A-38	322
D36321	" " "	Magazine, 15 round, 37-mm., M2		312
D36339	" " "	" 60 RD, 20-mm., M1		313
D36370	" " "	Mechanism, feed, right hand, 20-mm., AN-M1	M1	317
D36371	" " "	" " left hand, 20-mm., AN-M1	M1	315
D36488	" " "	Magazine, endless belt 37-mm., M6		314
D36592	" " "	Adapter assembly, 20-mm., AN-M1	AN-M1	300
D36593	" " "	" " " " AN-M6	M6	303
D69343	" " "	Charger, manual, M2	B-6	38
D69446	" " "	Gun, automatic, 37-mm., M4		296
D210438	Mfr's Dwg.	Shackle—bomb	B-7	282
DR2000	" " -outline	Pilot—automatic	C-1	269
DR2001	" " " "	" — " "	C-1	270
DR2002	" " " "	" — " "	C-1	269
DR2003	" " " "	" — " "	C-1	270
DR2004	" " " "	" — " "	C-1	270
DR2031	" Part & Dwg.	" — " "	C-1	271
DR2033	" Dwg.-outline	" — " "	C-1	270
DR2155	" " " "	Panel—autopilot control	A-6A	232
DS-6300	" " "	Adapter—gun mount	E-5	13
DS-6300	" " "	" — " "	E-8	14
DS-6300	" " "	" — " "	E-11	17
DS-6300	" " "	" — " "	E-12	18

*Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
DS-6382	Mfr's Dwg.	Adapter—gun mount	E-10	15
DS-6670	" "	" — " "	E-5	13
DS-6670	" "	" — " "	E-8	14
DS-6670	" "	" — " "	E-11	17
DS-6670	" "	" — " "	E-12	18
E	Army Type	Charger—20-mm. hydraulic gun	D-3	39
E	" "	Charger, manual, M2	B-6	38
E-2A	" "	Solenoid—gun	E-8	103
E-3	" "	Ends—impulse unit	E-3	98
E-3	" "	Generator—gun synchronizer impulse	E-8	97
E-3*	" & Mfr's Mod.	Motor—trigger	E-3	99
E-3	" Type	" — " "	E-3A	100
E-3A	" "	Ends—impulse unit	E-3	98
E-3A	" "	Generator—gun synchronizer impulse	E-8	97
E-3A*	" & Mfr's Mod.	Motor—trigger	E-3	99
E-3A	" Type	" — " "	E-3A	100
E-4	" "	Mount—flexible gun sight	C-4	58
E-4*	" & Mfr's Mod.	Solenoid—gun	E-4	101
E-4*	" " " "	" — " "	E-6	102
E-4	" Type	" — " "	E-8	103
E-4	" "	" — " "	G-16	105
E-5	" "	Adapter—gun mount	E-5	12
E-5	" "	" — " "	E-8	14
E-5	" "	" — " "	E-11	17
E-5	" "	" — " "	E-12	18
E-5	" "	Mount—flexible gun sight	C-1	58
E-5	" "	Sight—telescopic gun	E-5	82
E-5A	" "	Adapter—gun mount	E-5A	11
E-6	" "	Solenoid—gun	E-4	101
E-6	" "	" — " "	E-6	102
E-8*	" & Mfr's Mod.	Adapter—gun mount	E-5	13
E-8*	" " " "	" — " "	E-8	14
E-8	" Type	" — " "	E-10	15
E-8	" "	" — " "	E-11	17
E-8*	" & Mfr's Mod.	" — " "	E-12	18
E-8	" Type	Box—ammunition	O-1	23
E-8	" "	Ends—impulse unit	E-3	98
E-8	" "	Sight—flexible gun ring	B-13	81
E-8*	" & Mfr's Mod.	Generator—gun synchronizer impulse	E-8	97
E-8	" Type	Motor—trigger	E-3	99
E-8	" "	" — " "	E-3A	100
E-8	" "	Mount—flexible gun sight	C-4	58
E-8	" "	" —left hand ammunition box	C-3	56
E-8	" "	" —right hand ammunition box	C-3	57
E-8	" "	Sight—flexible gun post	A-11	78
E-8	" "	Solenoid—gun	E-8	103
E-8	" "	" — " "	G-10	104
E-8	" "	Yoke—gun mount adapter	41D6865	129
E-10	" "	Adapter—gun mount	E-8	14
E-10*	" & Mfr's Mod.	" — " "	E-10	15
E-10	" Type	" — " "	E-12	18
E-11	" "	" — " "	C-19	10
E-11	" "	" — " "	E-5	13
E-11*	" & Mfr's Mod.	" — " "	E-8	14
E-11	" Type	" — " "	E-11	17
E-11	" & Mfr's Mod.	" — " "	E-12	18
E-11	" Type	Box—ammunition	O-1	23
E-11	" "	Mount—ball and socket gun	K-4	66
E-11	" "	" —gun	H-1	61
E-11	" "	" —swivel gun	K-5	67
E-12*	" & Mfr's Mod.	Adapter—gun mount	E-5	13
E-12*	" " " "	" — " "	E-8	14
E-12	" Type	" — " "	E-10	15
E-12	" "	" — " "	E-11	17
E-12*	" & Mfr's Mod.	" — " "	E-12	18

*Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used In Connection with	Type, Drawing or Designation	Page
E-12	Army Type	Mount—gun	H-1	61
E-12	" "	" —left hand ammunition box	C-3	56
E-12	" "	" —right hand ammunition box	C-3	57
E11779	Mfr's Dwg.	" —bombsight	B-7	263
E.S.A.-1738	" "	Magazine, endless belt, 37-mm., M7		315
ES0385	" Spec.	Turret—lower gun	A-5	161
ES0385	" "	" — " "	A-10	163
ES0386	" "	" —upper gun	A-4	149
ES0386	" "	" — " "	A-9	151
ES0386	" "	Turret—upper gun	A-9A	153
EST1002	" "	" — " training	A-8	155
F	Army & Mfr's Mod.	Charger—20-mm. hydraulic gun	D-3	39
F	" " "	Valve—hydraulic gun charging	A-1	128
F-180	" " & Spec.	Sight—compensating	K-8	93
FI-106	Mfr's Spec.	Turret—nose gun	A-16	168
G-1	" "	Adapter—gun end	L-1	26
G-1	Mfr's Type	Chute—flexible feed	B	25
G-1A*	Army & Mfr's Mod.	Mount—gun	G-1A	59
G-1A*	" " "	" — " "	G-5	60
G-2	" Type	Solenoid—gun	G-10	104
G-4A*	" & Mfr's Mod.	" — " "	G-4A	114
G-4A*	" " " "	" — " "	G-9	116
G-5*	" " " "	Mount—gun	G-1A	59
G-5*	" " " "	" — " "	G-5	60
G-8*	" " " "	Solenoid—gun	G-8	115
G-8*	" " " "	Trigger—electric AN-M1	G-17	120
G-9*	" " " "	Solenoid—gun	G-4A	114
G-9	" Type	" — " "	G-9	116
G-10	" "	Generator—gun synchronizer impulse	E-8	97
G-10*	" & Mfr's Mod.	Solenoid—gun	G-10	104
G-11*	" " " "	" — " "	G-11	117
G-11	" Type	Trigger—manual	A-1	127
G-13*	" & Mfr's Mod.	Solenoid—gun	G-13	118
G-13*	" " " "	" — " "	G-15	119
G-15*	" " " "	" — " "	G-13	118
G-15*	" " " "	" — " "	G-15	119
G-16	" Type	" — " "	G-16	105
G-17	" "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)	M1 and AN-M2	299
G-17*	" & Mfr's Mod.	Solenoid—gun	G-8	115
G-17*	" " " "	Trigger—electric AN-M1	G-17	120
G-29990	Mfr's Spec.	Switch—control stick gun	B-1A	124
G-29990	" "	" — " " "	B-5	125
G1005A	" Part & Dwg.	Pilot—automatic	C-1	270
G1020	" " " "	" — " "	C-1	270
G1021A	" " " "	" — " "	C-1	269
G1023A	" " " "	" — " "	C-1	271
G1024A	" " " "	" — " "	C-1	269
G1025A	" " " "	" — " "	C-1	270
G1027A	" " " "	" — " "	C-1	271
G1029A2	" " " "	" — " "	C-1	270
G1047	" " " "	Panel—autopilot control	A-6A	232
G1048	" " " "	Pilot—automatic	C-1	269
G32693	" Spec.	Adapter—box	A	231
GK-M5-32S	" Part	Control—bomb release interval	B-2	240
GK-M5-32S	" "	" — " " "	B-2A	241
GM-11G	" Mod.	Adapter—gun mount	C-16	7
GM-32	" " "	" — " "	E-5	13
GM-32	" " "	" — " "	E-8	14
GM-32	" " "	" — " "	E-11	17
GM-32	" " "	" — " "	E-12	18
GM-32A	" " "	" — " "	E-5	13
GM-32A	" " "	" — " "	E-8	14
GM-32A	" " "	" — " "	E-11	17
GM-32A	" " "	" — " "	E-12	18
GM-41	" " "	" — " "	E-5A	11

*Army designation also used as commercial identification.

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
GM-43	Mfr's Mod.	Adapter—gun mount.....	E-5	13
GM-43	" "	" — " "	E-8	14
GM-43	" "	" — " "	E-11	17
GM-43	" "	" — " "	E-12	18
GM-59	" "	" — " "		5
GM749-601	" Dwg. No.	" — " "	E-5	13
GM749-601	" "	" — " "	E-8	14
GM749-601	" "	" — " "	E-11	17
GM749-601	" "	" — " "	E-12	18
GM749-602	" "	" — " "	E-5	13
GM749-602	" "	" — " "	E-8	14
GM749-602	" "	" — " "	E-11	17
GM749-602	" "	" — " "	E-12	18
GM749-615	" "	" — " "		5
GM749-658	" "	" — " "	C-16	7
GM749-663	" "	Feed—lower continuous	CF-5	45
GM749-692	" part "	Adapter—gun mount	C-16	7
GO-17397-B	" Dwg. Spec.	" — " "	E-5A	11
GO-17397-B	" "	Box—control	T-8252925	217
GO-17397-B	" "	" —junction	T-8252853	218
GO-17397-B	" "	Charger gun	T-8262878	182, 213, 226
GO-17397-B	" "	Dynamotor	5D21NJ3A	187, 219
GO-17397-B	" "	Station—sighting	2CSDIC1	221
GO-17397-B	" "	Turret—lower aft gun	2CGD50LRC5	199
GO-17397-B	" "	Servo—amplifier	2CV1B1	207, 216
GO-17397-B	" "	Turret—lower forward gun	2CGD50LRC4	201
GO-17397-B	" "	" — " gun	2CGD50LRC1	223
GO-17397-B	" "	" —upper aft gun	2CGD50URC4	203
GO-17397-B	" "	" — " forward gun	2CGD50URC3	205
GO-17397-B	" "	" — " gun	2CGD50URC1	225
GO-17400-B	" "	Box—control	T-8007519	208
GO-17400-B	" "	" —junction	T-8007523	209
GO-17400-B	" "	Charger—gun	T-825878	182, 213, 226
GO-17400-B	" "	Dynamotor	5D21FJ2A	210
GO-17400-B	" "	Selayn	2JIG1	212
GO-17400-B	" "	Servo—amplifier	2CGQ50URA4	214
GO-17400-B	" "	Turret—upper gun	2CV1B1	207, 216
GO-18393-B-1	" "	Box—left blister auxiliary control	P-8242380	175
GO-18393-B-1	" "	" —nose system control	W-8258868	176
GO-18393-B-1	" "	" —right blister auxiliary control	P-8242380	177
GO-18393-B-1	" "	" —side blister selector switch	T-8252890	179
GO-18393-B-1	" "	" — " " system control	W-8258874	178
GO-18393-B-1	" "	" —tail system control	W-8258881	180
GO-18393-B-1	" "	" —upper blister system control	W-8258865	181
GO-18393-B-1	" "	Charger—gun	T-8252878	182, 213, 226
GO-18393-B-1	" "	Computer—double parallax	2CH1D1	183
GO-18393-B-1	" "	" —single parallax	2CH1C1	184
GO-18393-B-1	" "	Drive—tail gun mount azimuth	W-8258810	185
GO-18393-B-1	" "	" — " " elevation	W-8258807	186
GO-18393-B-1	" "	Dynamotor	5D21NJ3	187, 219
GO-18393-B-1	" "	Hand set—altitude and air speed	T-8252908	188
GO-18393-B-1	" "	Motor generator—amplidyne remote control	5AM61NJ1C	190
GO-18393-B-1	" "	Ring assembly—upper sight collector	T-8252843	191
GO-18393-B-1	" "	Servo—amplifier	2CV1C1	174
GO-18393-B-1	" "	Station—left blister sighting	2CSR3B2	192
GO-18393-B-1	" "	" —nose sighting	2CSR3C1	193
GO-18393-B-1	" "	" —right blister sighting	2CSR3B1	194
GO-18393-B-1	" "	" —tail sighting	2CSR3B3	195
GO-18393-B-1	" "	" —upper ring sighting	2CSR3A1	196
GO-18393-B-1	" "	Turret—lower aft gun	2CGD50LRC5	199
GO-18393-B-1	" "	" — " forward gun	2CGD50LRC4	201
GO-18393-B-1	" "	" — " gun	2CGD50LRC1	223
GO-18393-B-1	" "	" —upper aft gun	2CGD50URC4	203
GO-18393-B-1	" "	" — " forward gun	2CGD50URC3	205
GO-18393-B-1	" "	" — " gun	2CGD50URC1	225
H	Army & Mfr's Mod.	Charger—.40 caliber hydraulic gun	D-1	40



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
H	Army & Mfr's Mod.	Valve—hydraulic gun charging.	A-1	128
H-1	" Type	Adapter—gun mount	C-12	6
H-1	" "	Mount—gun	H-1	61
H32D3819	" Dwg.	Bolt and bracket—gun trunnion	A-3	20
H36G5394	" "	Ends—impulse unit	E-3	98
H38D5278	" "	Post—gun mounting	A-4	73
H38D6421	" "	Container—ejected case	A-4	29
H39B5344	" "	Slide, retracting, group assembly	D28300A	311
H39D5353	" "	Container—ejected link	A-4	32
H39G5331	" "	Gun, machine, caliber .30 Browning, aircraft, fixed	M2	306
H39G5331	" "	" " " " " " M2, aircraft, flexible	M2	308
H39G5331	" "	Gun, machine, caliber .30 Browning, M2 aircraft, flexible with fixed back plate		307
H39G5332	" "	Gun, machine, caliber .50 Browning, M2, aircraft, basic		309
H39G5346	" "	Mount—gun	G-1A	59
H39G5561	" "	Gun, automatic, 37-mm., M4		296
H39G5584	" "	Magazine, 15 round, 37-mm., M2		312
H41B5344	" "	Valve—hydraulic gun charging	A-1	128
H41D10198	" "	Adapter assembly, 20-mm., AN-M1		301
H41D10198	" "	" " " " " " AN-M6		303
H41D10358	" & Mfr's Dwg.	Solenoid—gun	G-4A	114
H41D10358	" Dwg.	" — "	G-9	116
H41D10378	" "	Holder—pyrotechnic pistol	A-1	48
H41D10594	" "	Flare, aircraft, parachute: rimless type		325
H41D10594	" "	Pistol, pyrotechnic, M2		327
H41D10594	" "	Signals, aircraft: rimless type		324
H41G5287	" "	Charger—.30 caliber hydraulic gun	D-1	40
H41G5288	" "	" —.50 caliber hydraulic gun	D-2	41
H41G5289	" "	" —20-mm. hydraulic gun	D-3	39
H41G9104	" "	Solenoid—gun	G-9	115
H41H5144	" "	Mechanism, feed, left hand, 20-mm., AN-M1		316
H41H5144	" "	" " " " right hand, 20-mm., AN-M1		317
H41J5074	" "	Gun, aircraft, automatic, 20-mm., M1 and AN-M2 (all types)		299
H41J9229	" "	" " " " " " " " " " " "		299
H42B6598	" "	Control—bomb arming	AN-A-1	236
H42B10457	" "	Signals, aircraft: cartridge type		325
H42B10666	" "	Pistol, pyrotechnic, AN-M8, w/mount		330
H42B10947	" "	Discharger, pyrotechnic, AN-M5	M6	326
H42B16116	" "	Hoist—portable bomb	AN-Mk 7 Mod. 1	259
H42G2391	" "	Magazine, 60 RD, 20-mm., M1		313
H42G2521	" "	" " " " " " " " " " " "		314
H42G4769	" "	Gun, automatic, 37-mm., M4		296
H42G4872	" "	Release—bomb rack right hand	A-3	280
H43D6383	" "	Charger, manual, M2	B-6	38
H43G10990	" "	Trigger—electric, AN-M1	G-17	120
I	" & Mfr's Mod.	Valve—hydraulic gun charging	A-1	128
J	" " " " "	Turret—lower gun	A-5	161
J	" " " " "	" — " " " " " " " " " " " "	A-10	163
K	" " " " "	" — " " " " " " " " " " " "	A-5	161
K	" " " " "	" — " " " " " " " " " " " "	A-10	163
K-1*	" " " " "	Mount—ball and socket gun	K-2	63
K-1*	" " " " "	" — " " " " " " " " " " " "	K-2A	64
K-1*	" " " " "	" — " " " " " " " " " " " "	K-3	65
K-1*	" " " " "	" assembly—ball and socket gun	K-1	62
K-2	" Type	Adapter—gun mount	C-17	8
K-2	" " " " "	" — " " " " " " " " " " " "	C-18	9
K-2**	Navy & Mfr's Mod.	Control—bomb release interval	AN-B-3	242
K-2*	Army & Mfr's Mod.	Mount—ball and socket gun	K-2	63
K-2*	" " " " "	" — " " " " " " " " " " " "	K-2A	64
K-2*	" " " " "	" — " " " " " " " " " " " "	K-3	65
K-2*	" " " " "	" assembly—ball and socket gun	K-1	62
K-2A	" Type	Adapter—gun mount	C-17	8
K-2A	" " " " "	" — " " " " " " " " " " " "	C-18	9
K-2A*	" & Mfr's Mod.	Mount—ball and socket gun	K-2	63

*Army designation also used as commercial identification.

**Navy designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
K-2A	Army Type	Mount—ball and socket gun.	K-2A	64
K-2A*	" & Mfr's Mod.	" — " " " "	K-3	65
K-2A*	" " " "	" assembly—ball and socket gun.	K-1	62
K-3	" Type	Adapter—gun mount	C-17	8
K-3	" " " "	" — " " " "	C-18	9
K-3*	" & Mfr's Mod.	Mount—ball and socket gun.	K-2	63
K-3*	" " " "	" — " " " " "	K-2A	64
K-3*	" " " "	" — " " " " "	K-3	65
K-3*	" " " "	" assembly—ball and socket gun.	K-1	62
K-3*	" " " "	Sight—automatic compensating gun.	K-3	92
K-3	" Type	" — " " " "	K-4	93
K-4	" " " "	Adapter—gun mount	C-19	10
K-4	" " " "	Mount—ball and socket gun.	K-4	66
K-4*	" & Mfr's Mod.	Sight—automatic compensating gun.	K-3	92
K-4*	" " " "	Sight—automatic compensating gun.	K-4	93
K-5	" Type	Mount—swivel gun.	K-5	67
K-8	" " " "	Sight—compensating	K-8	94, 95
L	" & Mfr's Mod.	Turret—upper gun.	A-4	149
L	" " " "	" — " " " "	A-9	151
L	" " " "	" — " " " "	A-9A	153
L-1	" Type	Adapter—box end.	L-2	27
L-1	" " " "	" —gun end	L-1	23
L-1	" " " "	Chute—flexible feed.	B	25
L-2	" " " "	Adapter—box end.	L-2	27
L-2	" " " "	" —gun end.	L-1	23
L-2	" " " "	Chute—flexible feed.	B	25
L-4	A & N Type	Box—ammunition	L-4	21
L-4	Army Type	" — " " " "	L-7	22
L-4	" " " "	Holder—ammunition box.	A-1	47
L-7	" " " "	Box—ammunition	L-4	21
L-7	" " " "	" — " " " "	L-7	22
L-7	" " " "	Holder—ammunition box.	A-1	47
L-21A	" " " "	Handle—bomb release	L-21A	253
L-21A	" " " "	Rack—bomb	N-6	275
L-21A	" " " "	" — " " " "	Q-2	276
LLA50-M1-	" " " "	" — " " " "	"	"
G1-15	" & Mfr's Mod.	Chute—flexible feed	A	28
LLA50-M1-	" " " "	" — " " " "	A	28
G1-29	" " " "	" — " " " "	A	28
LLA50-M1-	" " " "	" — " " " "	A	28
G1-36	" " " "	" — " " " "	A	28
LLA50-M1-	" " " "	" — " " " "	A	28
G1-48	" " " "	" — " " " "	A	28
LLA50-M1-	" " " "	" — " " " "	A	28
G1-66	" " " "	" — " " " "	A	28
LLA50-M1-	" " " "	" — " " " "	A	28
G1-85	" " " "	" — " " " "	A	28
LLA50-M1-	" " " "	" — " " " "	A	28
G1-107	" " " "	" — " " " "	A	28
LLB50	" " " "	" — " " " "	B	25
M	" Type	Tachometer—bombsight disc speed.	4050 & 4050A	292
M-1	A & N Type	Adapter assembly, 20-mm., AN-M1		300, 301
M-1	Army Type	" " " " AN-M6		302
M-1	" " " "	Mount—gun	M-1	68, 69
M-3	" & Mfr's Mod.	Adapter—box end.	L-2	27
M-3	" " " "	Chute—flexible feed	B	25
M-4	" Type	Magazine, 15 round, 37-mm., M2		312
M-5	" " " "	Mount—gun	M-5	72
M-6	" " " "	" — " " " "	M-6	70, 71
M-10	" " " "	Container—signal flare	A-1	34
M-11	" " " "	" — " " " "	A-1	34
M-11	" " " "	" — " " " "	A-1	34
M-16	" " " "	" — " " " "	A-1	34
M-16	" " " "	" — " " " "	A-1	34
M-460	Navy Spec.	Generator—gun synchronizer impulse	E-8	97

*Army designation also used as commercial identification.



NUMERICAL INDEX
ARMAMENT SECTION

[illegible]

**Navy designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
Mk 1	Navy Type	Cover—electrically heated bombsight	A-1	244
Mk 1	" "	Ends—impulse unit	E-3	98
Mk 1	" "	Motor—trigger	E-3	99
Mk 1**	" & Mfr's Mod.	" — " —	E-3A	100
Mk 1	" Type	Post—gun mounting	A-4	73
Mk 1	" "	Receptacle—bomb release	A-1	277
Mk 1 Mod. 1	" "	Handle—gun charging	A-2	46
Mk 1 Mod. 1	" "	Motor—trigger	E-3	99
Mk 1 Mod. 1	" "	" — " —	E-3A	100
Mk 2 Mod. 1	" "	Hoist—portable bomb	AN-Mk 7 Mod. 1	259
Mk 2 Mod. 1	" "	Panel—autopilot control	A-6A	232
Mk 2 Mod. 1	" "	Pilot—automatic	C-1	268
Mk 3 Mod. 2	" "	Solenoid—left hand gun	C-4B	107
Mk 3 Mod. 2	" "	" — " —	C-4C	110, 111
Mk 3 Mod. 2	" "	" —right hand gun	C-4B	108, 109
Mk 3 Mod. 2	" "	" — " —	C-4C	112, 113
Mk 4 Mod. 2	" "	Handle—bomb release	Mk 4 Mod. 2	254
Mk 4 Mod. 2	" "	Rack—bomb	Mk 43 Mod. 1	274
Mk 4 Mod. 1	" "	Solenoid—gun	G-4A	114
Mk 4 Mod. 2	" "	Rack—bomb	AN-Mk 41 Mod. 7	272
Mk 5 Mod. 1	" "	Shackle—bomb	B-7	282
Mk 5 Mod. 1	" "	Solenoid—gun	G-9	116
Mk 6 Mod. 1**	Navy & Mfr's Mod.	" — " —	G-8	115
Mk 6 Mod. 1**	" " " "	Trigger—electric AN-M1	G-17	120
Mk 6 Mod. 2	" Type	Adapter—gun mount	E-8	14
Mk 6 Mod. 3	" "	" — " —	E-5	12, 13
Mk 6 Mod. 3	" "	" — " —	E-11	16, 17
Mk 6 Mod. 3	" "	" — " —	E-12	18
Mk 7	" "	Box—ammunition	L-4	21
Mk 7	" "	Hoist—portable bomb	AN-Mk 7 Mod. 1	259
Mk 7 Mod. 1	" "	Solenoid—gun	G-11	117
Mk 8**	" & Mfr's Mod.	Sight—illuminated	Mk 8	83
Mk 9	" Type	Mount—gun	M-6	71
Mk 9**	" & Mfr's Mod.	Sight—illuminated	Mk 9	90
Mk 9 Mod. 1	" Type	" — " —	Mk 9	90
Mk 11 Mod. 2	" "	Adapter—gun mount	"	5
Mk 12	" "	" — " —	C-16	7
Mk 15	" "	" — " —	E-10	15
Mk 15	" "	Tachometer—bombsight disc speed	4050 & 4050A	292
Mk 15 Mod. 3	" "	Indicator—pilot director	Mk 15 Mod. 3	266, 267
Mk 15 Mod. 3	" "	" — " —	Mk 15 Mod. 5	265
Mk 16 Mod. 5	" "	Cover—electrically heated bombsight	A-1	244
Mk 15 Mod. 5	" "	Indicator—pilot director	Mk 15 Mod. 3	267
Mk 15 Mod. 5	" "	" — " —	Mk 15 Mod. 5	264, 265
Mk 15 Mod. 7	" "	Cover—electrically heated bombsight	A-1	244
Mk 28 Mod. 2	" "	Director—torpedo	Mk 28 Mod. 2	248
Mk 43 Mod. 1	" "	Rack—bomb	Mk 43 Mod. 1	274
MD3071	Army & Mfr's Mod.	Indicator—pilot director	Mk 15 Mod. 3	267
MD3071-2 Pole	" " " "	" — " —	Mk 15 Mod. 5	265
MD3071-4 Pole	" " " "	" — " —	Mk 15 Mod. 5	265
N	" " " "	Turret—upper gun	A-4	149
N	" " " "	" — " —	A-9	151
N	" " " "	" — " —	A-9A	153
N-3A	" Type	Head—pilot's bombsight	A-1	255
N-3A	" "	" — " —	A-2	257
N-3A*	" & Mfr's Mod.	Sight—fixed gun	N-3A	84, 85
N-3A*	" " " "	" — " —	N-3B	86
N-3A*	" " " "	Support—gun sight image reflector	41D3024	122
N-3A*	" " " "	" — " —	41D4892	121
N-3B	" Type	Head—pilot's bombsight	A-1	255
N-3B	" "	" — " —	A-2	257
N-3B*	" & Mfr's Mod.	Sight—fixed gun	N-3A	85
N-3B*	" " " "	" — " —	N-3B	86
N-3B	" Type	Support—gun sight image reflector	41D3024	122

*Army designation also used as commercial identification.

**Navy designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
N-3B	Army Type	Support—gun sight image reflector.	41D4892	121
N-5	" "	Rack—bomb	N-5	275
N-5*	" & Mfr's Mod.	Support—gun sight image reflector.	41D3024	122
N-5*	" " "	" " " "	41D4892	121
N-6	" Type	Head—pilot's bombsight	A-1	255
N-6	" " "	" " " "	A-2	257
N-6	" " "	Mount—gun	M-1	68, 69
N-6	" " "	Rheostat—variable resistance	D-1	123
N-6	" " "	Ring—pilot's bombsight adapter	43B15328	256
N-6	" " "	Sight—flexible gun	N-6	87
N-6*	" & Mfr's Mod.	" " " "	N-6A	88
N-6*	" " " "	" " " "	N-8	91
N-6A	" Type	Head—pilot's bombsight	A-1	255
N-6A	" " "	" " " "	A-2	257
N-6A	" " "	Rheostat—variable resistance	D-1	123
N-6A	" " "	Ring—pilot's bombsight adapter	43B15328	256
N-6A	" " "	Sight—flexible gun	N-8	87
N-6A*	" & Mfr's Mod.	" " " "	N-6A	88, 89
N-6A*	" " " "	" " " "	N-8	91
N-8	" Type	Mount—gun	M-6	71
N-8*	Army & Mfr's Mod.	Sight—flexible gun	N-6	87
N-8*	" " " "	Sight—flexible gun	N-6A	89
N-8*	" " " "	" " " "	N-8	91
N-8	" Type	" —illuminated	Mk 9	90
N-238544	Mfr's Dwg.	" " " "	Mk 8	83
NMT5500N	" " "	Turret—upper training	A-8	155
O-1*	Army & Mfr's Mod.	Box—ammunition	O-1	23
O-1	" Type	Mount—left hand ammunition box	C-2	54
O-1	" " "	" " " "	C-3	56
O-1	" " "	" —right hand ammunition box	C-2	55
O-1	" " "	" " " "	C-3	55, 57
OCLV-54	Navy Pub.	Ends—impulse unit	E-3	98
OHIV-43	" " "	Adapter—gun mount	E-5	13
OHIV5-43	" " "	" " " "	E-11	17
ORD28177	Mfr's Dwg.	Sight—illuminated	Mk 9	90
OS2359	Navy Pub.	Solenoid—gun	G-4A	114
OST-1B	Mfr's Spec.	Motor—azimuth turret drive	5BA50LJ1	51
OST-1B	" " "	" —elevation turret drive	5BA50GJ1	52
OST-1B	" " "	" —turret drive	5BA50IJ2A	227
OST-1B	" " "	" generator—amplidyne local control	5AM31NJ18	50
OST-1B	" " "	" " —remote	5AM31NJ9	189, 211, 220
OTIV18-43	Navy Pub.	Adapter—gun mount	E-10	15
P-6A	" Mod.	Shackle—bomb	AN-B-10	284
P-56	" " "	" " " "	D-7	288
P-6907744	" Dwg.	Selsyn	2J1G1	212
P-8111135	" " —outline	Motor generator—amplidyne remote control	5AM31NJ9	189, 211, 220
P-8111282	" " " "	" " —local control	5AM31NJ18	50
P-8242380	" " "	Box—left blister auxiliary control	P-8242380	175
P-8242380	" " "	" —right blister auxiliary control	P-8242380	177
PC 15A6	" Cat. No.	Cover—electrically heated bombsight	A-1	244
PC 16A1	" " " "	" " " "	A-2	245
PDI 100	Mfr's Dwg.	Indicator—pilot director	Mk 15 Mod. 3	267
2 Pole 26 V	" " "	" " " "	" " " "	"
PDI 100	" " "	" " " "	Mk 15 Mod. 3	267
4 Pole 26 V	" " "	" " " "	" " " "	"
PDI 100-26 V	" " "	" " " "	Mk 15 Mod. 5	263
PK 1A1	" Cat. No.	Cover—electrically heated	PK 1A1	246
Q-2	Army Type	Rack—bomb	N-5	275
Q-2	" " "	" " " "	Q-2	276
R-7	Ord. SNL	Destructor, AN-M3	"	295
R-12	Army Type	Station—left blister sighting	2CSR3B2	192
R-12	" " "	" —right blister sighting	2CSR3B1	194
R-24789	" Spec.	Director—torpedo	B-2	249
R-266800	Mfr's Dwg.	Turret—upper gun	A-3	137
R-266800	" " "	" " " "	A-3A	139

Army designation also used as commercial identification.



NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
R-266800	Mfr's Dwg.	Turret—upper gun	A-3B	141
R-266800	" "	" — " "	A-11	145
R-266800	" "	" — " "	A-14	147
R-266800	" "	" — " "	A-3C	143
R-271400	" "	" — " "	A-14	147
R-312285	" "	" — " "	A-3	137
R-312285	" "	" — " "	A-11	145
R-312285	" "	" — " "	A-14	147
R-312300	" "	" — " "	A-3	137
R-312300	" "	" — " "	A-3A	139
R-312300	" "	" — " "	A-3B	141
R-312300	" "	" — " "	A-3C	143
R-312300	" "	" — " "	A-11	145
R-312300	" "	" — " "	A-14	147
R-312310	" "	" — " "	A-3	137
R-312310	" "	" — " "	A-3A	139
R-312310	" "	" — " "	A-3B	141
R-312310	" "	" — " "	A-3C	143
R-312310	" "	" — " "	A-11	145
R-312310	" "	" — " "	A-14	147
R-314560	" "	" — " "	A-3	137
R-314560	" "	" — " "	A-3A	139
R-314560	" "	" — " "	A-3B	141
R-314560	" "	" — " "	A-3C	143
R-314560	" "	" — " "	A-11	145
R-314560	" "	" — " "	A-14	147
R-371300	" "	" — " "	A-3	137
R-371300	" "	" — " "	A-3A	139
R-371300	" "	" — " "	A-3B	141
R-371300	" "	" — " "	A-11	145
R-371300	" "	" — " "	A-14	147
R-371400	" "	" — " "	A-3	137
R-371400	" "	" — " "	A-3A	139
R-371400	" "	" — " "	A-3B	141
R-371400	" "	" — " "	A-3C	143
R-371400	" "	" — " "	A-11	145
R1A-AM-3	R.I. Arsenal Notes	Mount, gun, airplane, 75-mm., M6		318
R17-R-7110	F.S.S.C.	Rheostat—variable resistance	D-1	123
R17-S-28260	A.S.O. Stock	Switch—single pole toggle	AN3022-2	126
R17-S-28260	" "	" —tail cannon selector	B-5A	197
R17-S-28266-22	" "	" —single pole toggle	AN3022-2	126
R17-S-28266-22	" "	" —tail cannon selector	B-5A	197
R17-S-35510	F.S.S.C.	" —control stick gun	B-5	125
R86-G-37010	" "	Generator—gun synchronizer impulse	E-8	97
R86-S-60000	A.S.O. Stock	Solenoid—gun	E-6	102
R86-S-60010	" "	" — " "	G-10	104
R86-S-60040	" "	" — " "	E-6	102
RCL-2	Army & Mfr's Mod.	Director—torpedo	B-2	249
S-1	" Type	Cover—electrically heated bombsight	A-2	245
S-81F	Mfr's Trade No.	Sight—illuminated	Mk 8	83
S-69808	" Spec.	Turret—lower gun	A-2	157
S-69808	" "	" —retractable lower gun	A-13	159
S-69809B	" "	" —upper gun	A-1	133
S-69809B	" "	" — " "	A-1A	135
S-69834	" "	Sight—automatic compensating gun	K-3	92
S-69834	" "	" — " "	K-4	93
S41D6785	Army Dwg.	Mount—gun	11-1	61
S42D5223	" "	Adapter—gun mount	E-11	16
SF-4**	Mfr Mod & N. Type	Control—bomb arming	AN-A-1	236
SF-4**	" " " " "	" — " "	AN-A-2	237
SF-6**	" " " " "	" — " "	AN-A-1	236
SF-6**	" " " " "	" — " "	AN-A-2	237
SF-10**	" " " " "	" — " "	B-2	238
SG1	" Dwg.	Turret—upper gun	A-1	133
SG1	" "	" — " "	A-1A	135

**Navy designation also used as commercial identification.




NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used in Connection with	Type, Drawing or Designation	Page
SK 99028	Ord. Dwg.	Trigger—electric, AN-M1	G-17	120
SP-2475	Mfr's Dwg.	Turret—upper gun	A-1	133
SP-2475	" "	" — " "	A-1A	135
SP-S-2475	" Spec.	" — " "	A-1	133
SP-S-2475	" "	" — " "	A-1A	135
SR105800	" Dwg.	Release—bomb rack right hand	A-2	279
SR105801	" "	" — " " left hand	A-2	278
T-5500-N	" "	Turret—upper training	A-8	155
T-5818166	" "	Dynamotor	5D21FJ2A	210
T-8007519	" "	Box—control	T-8007519	208
T-8007523	" "	" — junction	T-8007523	209
T-8007523	" "	Servo—amplifier	2CV1B1	207, 216
T-8252833	" "	Ring assembly—upper sight collector		191
T-8252853	" "	Box—junction	T-8252853	218
T-8252878	" "	Charger—gun	T-8252878	182, 213, 226
T-8252890	" "	Box—side blister selector switch	T-8252890	179
T-8252908	" "	Hand set—altitude and air speed	T-8252908	188
T-8252925	" "	Box—control	T-8252925	217
T-8254157	" "	Servo—amplifier	2CV1C1	174
T14	Army Type	Magazine, endless belt, 37mm., M7		313
TAFX2A	Ord. Dwg.	Roll, tool armorer's w contents, complete	A-28	320
TAFX2A	" "	" " " " " "	A-38	322
TCDX1A	" "	" " " " " "	A-28	320
TCDX1A	" "	" " " " " "	A-38	322
TCFX2A	" "	" " " " " "	A-28	320
TCFX2A	" "	" " " " " "	A-38	322
TCFX2C	" "	" " " " " "	A-28	320
TCFX2C	" "	" " " " " "	A-38	322
TCFX2D	" "	" " " " " "	A-28	320
TCFX2D	" "	" " " " " "	A-38	322
TCFX2F	" "	" " " " " "	A-28	320
TCFX2F	" "	Roll, tool armorer's w contents, complete	A-28	320
TCFX2F	" "	" " " " " "	A-38	322
TGAX1A	" "	" " " " " "	A-28	320
TGAX1A	" "	" " " " " "	A-38	322
THBX1A	" "	" " " " " "	A-28	320
THBX1A	Mfr's Dwg.	" " " " " "	A-38	322
TT-5818150	" "	Motor—elevation turret drive	5BA50GJ1	52
TT-5818151	" "	" — azimuth turret drive	5BA50LJ1	51
TT-5818156	" " -assy.	" generator—amplidyne remote control	5AM31NJ9	189, 211, 220
TT-5818186	" "	" " — " " " "	5AM61NJ1C	190
TT-5818190	" " -assy.	" " — " " " local control	5AM31NJ18	50
TT-8117000	" "	" — turret drive	5BA50LJ2A	227
TT-8117016	" "	Dynamotor	5D21NJ3A	187, 219
US-220	" "	Switch—control stick gun	B-1A	124
V-4-43	Ord. Tech. Inst.	Cover—electrically heated bombsight	A-1	244
V-7-43	" Cir. Letter	Motor—trigger	E-3A	100
V-34	" " "	Gun, machine, caliber .50 Browning, M2 aircraft, basic		309
V-34	Army & Mfr's Mod.	Socket—5 way bomb	A	291
V-361	Mfr's Dwg.	Sight—compensating	K-8	95
V10-43	Ord. Cir. Letter	Rack—bomb	AN-Mk 51 Mod. 7	273
V11-42	" " "	Pistol, pyrotechnic, M2		327
V12-42	" " "	Discharger, pyrotechnic, AN-M5		326
V14-42	" " "	Hoist—portable bomb	AN-Mk 7 Mod. 1	259
V35-42	" " "	Pistol, pyrotechnic, AN-M8, w mount		330
V1-17	Mfr's Dwg.	Mount—gun	M-1	69
V1-152	" "	" — " "	M-1	69
V1-153	" "	" — " "	M-2	69
V2-26	" "	" — " "	M-5	72
V19-42	Ord. Cir. Letter	Sight—illuminated	Mk 8	83
V19-42	" " "	" — " "	Mk 9	90
W-8009100	Mfr's Dwg.	Station—sighting	2CSD1C1	221
W-8248849	" "	" — tail sighting	2CSR3B3	195
W-8257749	" "	" — left blister sighting	2CSR3B2	192
W-8258807	" "	Drive—tail gun mount elevation	W-8258807	186
W-8258810	" "	" — " " " azimuth	W-8258810	185




NUMERICAL INDEX ARMAMENT SECTION

Number	Number Identification	Used In Connection with	Type, Drawing or Designation	Page
W-8258820	Mfr's Dwg.	Station—upper ring sighting.	2CSR3A1	196
W-8258849	" "	" —right blister sighting.	2CSR3B1	194
W-8258865	" "	Box—upper blister system control.	W-8258865	181
W-8258868	" "	" —nose system control.	W-8258868	176
W-8258870	" "	Station—nose sighting.	2CSR3C1	193
W-8258874	" "	Box—side blister system control.	W-8258874	178
W-8258881	" "	" —tail system control.	W-8258881	180
W.A.C. 114081	Bu. Aer. Dwg.	Generator—gun synchronizer impulse.	E-8	97
WK-4-32S-4Pin	Mfr's Part	Indicator—pilot director	Mk 15 Mod. 3	267
WK-4-32S-4Pin	" Dwg.	" — " " right hand.	Mk 15 Mod. 5	263
WP-70L	Army & Mfr's Mod.	Release—bomb rack left hand.	A-2	278
WP-70R	" " " "	" — " " right hand.	A-2	279
WP-80	" " " "	Shackle—bomb	B-7	282
WW-8009111	Mfr's Dwg.	Turret—upper aft gun	2CGD50URC4	203
WW-8009111	" "	" — " forward gun	2CGD50URC3	205
WW-8009111	" "	" — " gun	2CGD50URC1	225
WW-8009112	" "	" — " aft gun	2CGD50URC4	203
WW-8009112	" "	" — " forward gun	2CGD50URC3	205
WW-8009112	" "	" — " gun	2CGD50URC1	225
WW-8009113	" "	" —lower aft gun	2CGD50LRC5	199
WW-8009113	" "	" — " forward gun	2CGD50LRC4	201
WW-8009113	" "	" — " gun	2CGD50LRC1	223
WW-8009114	" "	" — " aft gun	2CGD50LRC5	199
WW-8009114	" "	" — " forward gun	2CGD50LRC4	201
WW-8009114	" "	" — " gun	2CGD50LRC1	223
WW-8009119	" "	Computer—single parallax	2CH1C1	184
WW-8009120	" "	" —double parallax	2CH1D1	183
WW-8019517	" "	Turret—upper gun	2CHD50URA4	214
WW-8019523	" "	" —lower aft gun	2CGD50LRC5	199
WW-8019523	" "	" — " forward gun	2CGD50LRC4	201
WW-8019523	" "	" — " gun	2CGD50LRC1	223
WW-8019524	" "	" —upper aft gun	2CGD50URC4	203
WW-8019524	" "	" — " forward gun	2CGD50URC3	205
WW-8019524	" "	" — " gun	2CGD50URC1	225




ARMAMENT



GUNNERY EQUIPMENT





GUN MOUNTS AND GUN MOUNT ADAPTERS


A machine gun is attached to an airplane by means of a gun mount and a gun mount adapter. The type of mounting device employed depends on the type of gun and the purpose for which it is intended. Mounts and adapters are classified primarily for use with .30 caliber or .50 caliber machine guns. For each size of gun, the mounts are further classified according to their function, i.e., fixed, flexible, or turret installation.

Fixed gun mounts are used on fighter aircraft. Since these airplanes are highly maneuverable, the guns may be aimed by pointing the airplane at the target. Fixed guns are installed in the wings or in the fuselage nose. If installed in the fuselage of a single engine airplane the gun fire must be synchronized with the engine to prevent the bullets from striking the propeller.

Flexible gun installations are employed on attack or bombardment airplanes as a defense against enemy attack from any direction. The flexible gun mount and adapter allows movement of the gun in any position, independent of the line of flight of the airplane.


Gun turrets, installed on bombardment airplanes, perform a function similar to flexible gun mounts and adapters. The turrets, however, have a much larger fire coverage, range of vision, and better stability, thereby increasing the efficiency of the gunner.

The forces involved in the rapid firing of .30 and .50 caliber guns must be reduced to a minimum for efficient use on airplanes, this is the primary purpose of gun mount adapters. Most gun mount adapters are provided with mechanical, pneumatic, or hydraulic means for absorbing the recoil force of the gun. However, many .30 caliber adapters and a few .50 caliber types are not equipped in this manner and recoil force must be dissipated through the mount to the airplane structure.



ADAPTER—GUN MOUNT
BELL AIRCRAFT MODEL 19G

NAMES: Gun mount adapter
Adapter—gun mount BAM—.30 M2, flexible, twin (Navy)
Adapter—machine gun (British)
Twin gun mount adapter
.30 caliber twin adapter



(Continued on page 5)



ADAPTER—GUN MOUNT

(Continued from page 4)

DESCRIPTION: This gun mount adapter absorbs the recoil shock of twin, right and left hand, .30 caliber, M2 machine guns. It consists of a frame made of four parallel bars attached to front and rear supports, and a centrally-located ejection chute, which serves both guns. Pneumatic shock absorbers are fastened to the front support and suspended from the bars. The rear support carries the hand grips and mounts the removable backplate which contains the trigger and trigger safety mechanism. The guns are fired, and the safety control operated, by the thumb of either hand.

This adapter is furnished with ring and bead sight. Ammunition box holders were also supplied with adapters of early manufacture.

CHARACTERISTICS:

Dimensions approximately 11 by 5½ by 2¾ inches
 Weight approximately 17 pounds

RELATIONSHIP OF PARTS: Used with:

Twin .30 caliber M2 machine guns A. E. Reference Number 93-1440

ARMY

A. E. REFERENCE NUMBER: 52-400

TYPE DESIGNATION: None. Procured as manufacturer's model 19-G.

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

Information listed below pertains only to Navy adapter Mark 11, Modification 2, which is the Navy equivalent and is interchangeable with Bell Aircraft Corporation model 19-G, with modifications as noted on interchangeability chart.

BU. ORD. DRAWING NUMBER: Installation 329516, Assembly 329925

AVIATION ORDNANCE STOCK LIST NUMBER: 1-A-67-75



ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4
 A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Bell Aircraft Corporation	19-G	GM-749-615	A-B	5200002365	11-10-10	150J/6	
	GM-59	03-059-001	N				Navy Mark 11 modification 2. May be made interchangeable by modifying armor plate brackets, sight mount, and yoke.

**ADAPTER—GUN MOUNT****ARMY TYPE C-12 NAVY—SEE BELOW****NAMES:** Gun mount adapter

Adapter—gun mount, BAM—.30 M2, flexible, single (Navy)

Adapter—machine gun (British)

Single gun mount adapter

DESCRIPTION: The Army type C-12 gun mount adapter accommodates a single .30 caliber M2 machine gun. It consists of two side plates, bolted to the gun at the front trunnion and rear mounting attachments. These plates bolt to a curved yoke, the lower end of which is grooved to engage the locking balls of standard gun mount sockets.

This adapter, which is not recoil absorbing, has an Army type H-1 ammunition box holder attached to studs on the left side plate.

CHARACTERISTICS:

Dimensions

approximately 12 $\frac{3}{4}$ by 10 $\frac{1}{8}$ by 4 $\frac{3}{8}$ inches

Weight

approximately 5 $\frac{1}{2}$ pounds**RELATIONSHIP OF PARTS:** Used with:

A single .30 caliber M2 machine gun.

A. E. Reference Number 93-1520

ARMY

A. E. REFERENCE NUMBER: 52-500

SPECIFICATIONS:

Detail

93-24643

Superseded

24643

A. A. F. DRAWING NUMBER: 37G4926

TYPE DESIGNATION: C-12

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation.

Superseded by Army type C-16 gun mount adapter, A. E. Reference Number 52-600.

SHIPPING DATA: Shipped as a complete unit.

NAVY

Information listed below pertains only to Navy Mark 1 adapter, which is the Navy equivalent. It is interchangeable with the Army type C-12, with the modifications noted on the chart.

BU. ORD. DRAWING NUMBER: 178468

AVIATION ORDNANCE STOCK LIST NUMBER: 1-A-65

ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Not under procurement for initial installation.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Ohmer Fare Register Company	*C-12	**37G4926	A-B	5200004500	11-10-9	150J/16	
Groetchen Tool and Manufacturing Company	*C-12 †Mark 1	**37G4926 ††178468	A-B N	5200004500	11-10-9	150J/16	The Navy Mark 1 may be made interchangeable by substitution of yoke, Army part number 37D4929.

Note: *AAF type, **AAF drawing, †Navy type, ††Navy drawing.

**ADAPTER—GUN MOUNT****ARMY TYPE C-16 NAVY—SEE BELOW**

NAMES: Gun mount adapter .30 caliber adapter
 Adapter—gun mount, BAM—.30 M2, flexible, single (Navy)
 Adapter—machine gun (British) Single gun mount adapter


DESCRIPTION: The Army type C-16 gun mount adapter absorbs recoil shock for a single .30 caliber M2 machine gun. It consists of a frame, which includes a single pneumatic shock absorber, slide blocks for the rear mount of the gun, and a removable backplate containing the trigger and trigger safety mechanism. The single trigger is operated by the forefinger, and the safety control by the thumb. This safety control is located near the top of the right hand-grip support. When in a forward position, the yoke of the mount allows an upward swing of 90 degrees and a downward swing of 35 degrees. By reversing the yoke, upward swing is 35 degrees and downward swing is 90 degrees.

CHARACTERISTICS:

Dimensions approximately 22 1/4 by 11 by 7 1/4 inches
 Weight approximately 8 pounds 10 ounces

RELATIONSHIP OF PARTS: Used with:

A single .30 caliber M2 machine gun A. E. Reference Number 93-1440

**ARMY**

A. E. REFERENCE NUMBER: 52-600

SPECIFICATIONS:

Detail 93-24639
 Superseded 24639

A. A. F. DRAWING NUMBER: 40K3852 (Superseded by manufacturer's drawing number GM-749-658)

TYPE DESIGNATION: C-16

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION DATA: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

Information listed below pertains only to Navy Mark 12 adapter, which is the Navy equivalent. It is interchangeable with the Army type C-16, with the modifications noted on the chart.

BU. ORD. DRAWING NUMBER: Assembly 320160, Installation 328551

AVIATION ORDNANCE STOCK LIST NUMBER: 1-A-67-15

ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Under procurement.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Type	Remarks
Bell Aircraft Corporation	GM-11G	GM-749-658	A-B	5200004850	11-10-14	150J/30	Army C-16	
	GM-11G	GM-749-658	N				Navy Mark 12	*

*The Navy Mark 12 includes a telescopic sight bracket and ammunition box holder. It may be made interchangeable with Army type C-16 by substitution of yoke, Bell part number GM-749-692, and removal of the telescopic sight bracket and ammunition box holder.



ADAPTER—GUN MOUNT ARMY TYPE C-17

NAMES: Gun mount adapter

Adapter—machine gun (British)

DESCRIPTION: The Army type C-17 gun mount adapter attaches a single .30 caliber, M2 machine gun to a ball and socket type mount, and has provisions for a gun camera. The adapter consists of a frame with a pair of lugs and a circular spring latch. The lugs are attached to the gun by a bolt, and the latch locks the gun to the mount.

The adapter, which is not recoil absorbing, is quickly detachable from the ball and socket mount.

CHARACTERISTICS:

Dimensions..... approximately 4 1/4 by 4 1/4 by 3 1/2 inches
Weight..... approximately 2 pounds

RELATIONSHIP OF PARTS: Used with:

A single .30 caliber M2 machine gun, A. E. Reference Number 93-1520, and Army types K-2, K-2A, or K-3 ball and socket gun mounts, A. E. Reference Number 52-3850, 52-3900, and 52-3950.

ARMY

A. E. REFERENCE NUMBER: 52-700

SPECIFICATIONS:

Detail..... 93-24696
Superseded..... 24696

A. A. F. DRAWING NUMBER: 41D5642 (Supersedes Army drawing number 40G6567)

TYPE DESIGNATION: C-17

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Iron Fireman Manufacturing Company	*C-17	**41D5642	A-B	5200004870	11-10-9	150J 17	
Warner Industries	*C-18	**41D11020	A-B	5200004900	11-10-9	150J 28	The Army type C-18 does not contain a mounting bolt for gun camera installation.
Crosley Corporation	*C-18	**41D11020	A-B	5200004900	11-10-9	150J 28	

Note: *AAF type; **AAF drawing.



ADAPTER—GUN MOUNT

ARMY TYPE C-18

NAMES: Gun mount adapter
Adapter—machine gun (British)

DESCRIPTION: The Army type C-18 gun mount adapter attaches a single .30 caliber, M2 machine gun to a ball and socket type mount. The adapter consists of a frame with a pair of lugs, and a circular spring latch. The lugs are attached to the gun by a bolt, and the latch locks the gun to the mount. The adapter, which is not recoil absorbing, is quickly detachable from the ball and socket mount.

CHARACTERISTICS:

Dimensions approximately 4 by 3 $\frac{3}{4}$ by 3 inches
Weight approximately 1 pound 13 ounces

RELATIONSHIP OF PARTS: Used with:

A single .30 caliber M2 machine gun, A. E. Reference Number 93-1520, and Army types K-2, K-2A, or K-3 ball and socket gun mounts, A. E. Reference Number 52-3850, 52-3900, and 52-3950.

ARMY

A. E. REFERENCE NUMBER: 52-800

SPECIFICATIONS:

Detail 93-24720
Superseded 24720

A. A. F. DRAWING NUMBER: 41D11020

TYPE DESIGNATION: C-18

A. S. C. STOCK NUMBER: Refer to chart

TECHNICAL ORDER NUMBER: Refer to chart

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Warner Industries	*C-18	**41D11020	A-B	5200004900	11-10-9	150J 28	
Croley Corporation	*C-18	**41D11020	A-B	5200004900	11-10-9	150J 28	
Iron Fireman Manufacturing Company	*C-17	**41D5642	A-B	5200004870	11-10-9	150J 17	The Army type C-17 contains an extra mounting bolt for a gun camera.

Note: *AAF type, **AAF drawing.

**ADAPTER—GUN MOUNT****ARMY TYPE C-19**

NAMES: Gun mount adapter
Adapter—machine gun (British)

DESCRIPTION: The Army type C-19 gun mount adapter is used to attach a single .50 caliber, M2, machine gun to a ball and socket mount. This mount is supported by a metal spider since plexiglass alone is not strong enough to absorb recoil shock. A recoil-absorbing Army type E-11 adapter must be used in addition.
The type C-19 adapter locks the machine gun to an Army type K-4 ball and socket mount by means of a ring latch.

CHARACTERISTICS:

Dimensions	approximately 9 $\frac{3}{4}$ by 4 $\frac{3}{8}$ by 4 $\frac{1}{4}$ inches
Weight	approximately 2 pounds

RELATIONSHIP OF PARTS: Used with:

A single .50 caliber M2 machine gun, A. E. Reference Number 93-1560, and an Army type E-11 gun mount adapter, A. E. Reference Number 52-1300, mounted in an Army type K-4 ball and socket gun mount, A. E. Reference Number 52-3960.

ARMY

A. E. REFERENCE NUMBER: 52-850

SPECIFICATIONS:

Detail 24815

MANUFACTURER: Ainsworth Manufacturing Corporation.
MANUFACTURER'S DRAWING NUMBER: AG-400

A. A. F. DRAWING NUMBER: 42D19090

TYPE DESIGNATION: C-19

A. S. C. STOCK NUMBER: 5200004950

PRODUCTION STATUS: Under procurement.


SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 150J/47

**ADAPTER—GUN MOUNT**

ARMY TYPE E-5A NAVY—SEE BELOW

NAMES: Gun mount adapter

Adapter—gun mount BAM—.50, M2, turret type (Navy)

Adapter—machine gun (British)

.50 caliber M2 machine gun adapter

DESCRIPTION: The Army type E-5A gun mount adapter absorbs the recoil shock of twin .50 caliber M2 machine guns. It consists of two separate units, each containing two hydraulic shock absorbers, trunnion bolts, and spacers. The absorbers dampen recoil shock by the action of a piston and a recoil spring.

This adapter is designed for gun turret installation, or for mounting fixed guns. The guns are fired electrically by remote control.

CHARACTERISTICS:

Dimensions..... approximately 3¾ by 8¾ by 1⅞ inches
Weight..... approximately 3 pounds 3 ounces

RELATIONSHIP OF PARTS: Used with:

Twin .50 caliber M2 machine guns..... A. E. Reference Number 93-1560

ARMY

A. E. REFERENCE NUMBER: 52-1000

SPECIFICATIONS:

Detail..... 93-24763
Superseded..... 24763

MANUFACTURER: Bell Aircraft Corporation

MANUFACTURER'S DRAWING NUMBER: GM-749-732

MANUFACTURER'S MODEL: GM-41

TYPE DESIGNATION: E-5A

A. S. C. STOCK NUMBER: 5200005460

TECHNICAL ORDER NUMBER: 11-10-6

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as two completely identical units, packed in a single container.

NAVY

TYPE DESIGNATION: Army type E-5A



BU. ORD. DRAWING NUMBER: Assembly 372704; Installation 375033

AVIATION ORDNANCE STOCK LIST NUMBER: 1-A-68-95

PROCUREMENT STATUS: Under procurement.

BRITISH

REFERENCE NUMBER: 150J/559



ADAPTER—GUN MOUNT

ARMY TYPE E-5 NAVY MARK 6 MODIFICATION 3

NAMES: Gun mount adapter .50 caliber M2 machine gun adapter
 Adapter—.50 caliber machine gun—spade grip
 Adapter—gun mount, BAM—.50, M2, flexible, single (Navy)
 Adapter—machine gun (British)

DESCRIPTION: The Army type E-5 gun mount adapter absorbs the recoil shock of a single .50 caliber, M2 machine gun. It consists of a frame, which includes two hydraulic shock absorbers, slide blocks for the rear mount of the gun, a hand-grip assembly, and a removable backplate, which contains the trigger and trigger safety mechanism. The single trigger is operated by the forefinger, and the safety control by the thumb. This safety control is located between the hand-grip supports.

Provisions are made for the use of telescopic sights.

CHARACTERISTICS:

Dimensions approximately 28 $\frac{7}{8}$ by 5 $\frac{3}{4}$ by 7 $\frac{1}{8}$ inches
 Weight approximately 11 pounds 10 ounces

RELATIONSHIP OF PARTS: Used with:

A single .50 caliber M2 machine gun A. E. Reference Number 93-1560

ARMY

A. E. REFERENCE NUMBER: 52-875

SPECIFICATIONS:

Detail 93-24638
 Superseded 24638

A. A. F. DRAWING NUMBER: 39G5016

TYPE DESIGNATION: E-5

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type E-11 adapter, A. E. Reference Number 52-1300.

SHIPPING DATA: Shipped as a complete unit.

(Continued on page 13)



ADAPTER—GUN MOUNT

(Continued from page 12)

NAVY


TYPE DESIGNATION: Mark 6 Modification 3
 BU. ORD. DRAWING NUMBER: 278926
 AVIATION ORDNANCE STOCK LIST NUMBER: 1-A-68-13
 PUBLICATIONS: O. P. 865; O. H. I. V5-43
 PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE
 Models are used in services as noted in column 4
 A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	A. S. Service Command Stock Number	Army Technical Order Number	British Reference Number	Type	Remarks
Bell Aircraft Corporation	GM-32	GM-749-601	A-B	5200005450	11-10-7	150J/11	Army E-5	
	GM-43	GM-749-602	N		11-10-8		Navy Mark 6 Modification 3	The Navy Mark 6 Modification 3 includes a telescopic sight bracket and ammunition box holder.
The John C. Turner Corporation	GM-32A	03-043-012	A-B	5200005560	11-10-7	150J/26	Army E-11	Has two firing triggers.
	*E-11	03-043-012	A-B	5200005560	11-10-7	150J/26	Army E-11	Has two firing triggers.
Edgewater Steel Company	*E-8	DS-6300	A-B	5200005525	11-10-9	150J/21	Army E-8	Interchangeable with Army type E-5 in all applications except ball and socket gun mounts.
	*E-12	DS-6670	A-B	5200005575	11-10-9	150J/24	Army E-12	Has two triggers. Interchangeable with Army type E-5 in all applications except ball and socket gun mounts.
Brunhoff Manufacturing Company	*E-8	DS-6300	A-B	5200005525	11-10-9	150J/21	Army E-8	Interchangeable with Army type E-5 in all applications except ball and socket gun mounts.
	*E-12	DS-6670	A-B	5200005575	11-10-9	150J/24	Army E-12	Has two triggers. Interchangeable with Army type E-5 in all applications except ball and socket gun mounts.

Note: *AAF type.

GUN MOUNT ADAPTERS ARMAMENT—GUNNERY



ADAPTER—GUN MOUNT

ARMY TYPE E-8

NAMES: Gun mount adapter

Adapter—machine gun (British)

.50 caliber M2 machine gun adapter

DESCRIPTION: The Army type E-8 gun mount adapter absorbs the recoil shock of a single .50 caliber, M2 machine gun. It consists of two rectangular tubes bolted to the sides of a type E-10 recoil absorbing gun mount adapter. This adapter eliminates the need for a front trunnion block. The rear support of the gun fastens to a member attached near the rear of the side tubes. The gun and adapter are supported from the airplane structure by a yoke, which is not furnished with the adapter. Above the gun, and fixed to the rear of the tubes, is a gun sight platform, upon which a type C-4 gun sight mount may be installed. The base of the platform carries dual hand grips, a single trigger, and the safety mechanism. A type C-3 ammunition box mount supports a type C-1 ammunition box at the side of the adapter.

CHARACTERISTICS:

Dimensions

approximately 33 by 7 by 6 1/4 inches

Weight

approximately 16 pounds

RELATIONSHIP OF PARTS: Used with:

A single .50 caliber M2 machine gun

A. E. Reference Number 93-1560

ARMY

A. E. REFERENCE NUMBER: 52-1100

SPECIFICATIONS:

Detail

93-24689

Superseded

24689

A. A. F. DRAWING NUMBER: 41K3650

TYPE DESIGNATION: E-8

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type E-12.

A. E. Reference Number 52-1325.

SHIPPING DATA: Shipped as a complete unit, including the Army type E-10 gun mount adapter.

NAVY

There is no Navy equivalent for the Army item.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	As Service Command Stock Number	Army Technical Order Number	British Reference Number	Type	Remarks
Brunhoff Manufacturing Company	*E-8	DS-6300	A-B	5200005525	11-10-9	150J 21		
	*E-12	DS-6670	A-B	5200005575	11-10-9	150J 24	Army type E-12	Has two firing triggers.
Edgewater Steel Company	*E-8	DS-6300	A-B	5200005525	11-10-9	150J 21		
	*E-12	DS 6670	A-B	5200005575	11-10-9	150J 24	Army type E-12	Has two firing triggers.
Bell Aircraft Corporation	GM-32	GM749-601	A-B	5200005450	11-10-7	150J 11	Army type E-5	
	GM-43	GM749-602	N		11-10-8		Navy Mark 6	Has telescopic sight bracket and ammunition box holder.
	GM-32A	03-043-012	A-B	5200005560	11-10-7	150J 26	Army type E-11	Has two firing triggers.
The John C. Turner Corporation	*E-11	03-043-012	A-B	5200005560	11-10-7	150J 26	Army type E-11	Has two firing triggers.

Note: *AAF type.

**ADAPTER—GUN MOUNT****ARMY TYPE E-10 NAVY MARK 15****NAMES:** Gun mount adapter

Adapter—gun mount, BAM—.50 M2, turret type (Navy)

Adapter—machine gun (British)

DESCRIPTION: This gun mount adapter absorbs the recoil shock of a single .50 caliber M2 machine gun. It consists of a housing inclosing a series of ring springs that fit concentrically around an inner sliding shell. This shell is fastened to, and moves with, the gun barrel. After each shot the gun recoil causes the rings to telescope into each other, thus absorbing the energy of recoil and preventing transmission of shocks to the airplane structure.

Two threaded holes on opposite sides of the housing permit attachment of the adapter to a mount or turret gun carriage

CHARACTERISTICS:Dimensions.....approximately 5 $\frac{3}{8}$ by 3 $\frac{1}{2}$ by 3 $\frac{1}{2}$ inchesWeight.....approximately 5 $\frac{1}{2}$ pounds**RELATIONSHIP OF PARTS:** Used with:

A single .50 caliber M2 machine gun, A. E. Reference Number 93-1560. It is also used as a part of the Army types E-8 and E-12 gun mount adapters, A. E. Reference Numbers 52-1100 and 52-1325.

ARMY

A. E. REFERENCE NUMBER: 52-1200

SPECIFICATIONS:

Detail.....93-24703

Superseded.....24703

A. A. F. DRAWING NUMBER: 41B2679

TYPE DESIGNATION: E-10

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: E-10 (Also known as Mark 15)

BU. ORD. DRAWING NUMBER: Assembly 300200, Installation 328862.

AVIATION ORDNANCE STOCK LIST NUMBER: 1-A-69-35



PUBLICATIONS: O. P. 865; O. T. I. V18-43.

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Crosley Corporation	*E-10	**41B2679	A-N-B	5200005545	11-10-5	150J/22
Edgewater Steel Company	*E-10	DS-6382	A-N-B	5200005545	11-10-5	150J/22
Metal Specialties Manufacturing Company	*E-10	DS-6382	A-N-B	5200005545	11-10-5	150J/22

Note: *AAF type; **AAF drawing.



ADAPTER—GUN MOUNT

ARMY TYPE E-11 NAVY MARK 6 MODIFICATION 3

NAMES: Gun mount adapter .50 caliber M2 machine gun adapter
 Adapter—gun mount, BAM—.50, M2, flexible, single (Navy)
 Adapter—gun mount trigger backplate
 Adapter—machine gun (British)

DESCRIPTION: This gun mount adapter absorbs the recoil shock of a single .50 caliber, M2 machine gun. It consists of a frame, which includes two hydraulic shock absorbers, slide blocks for the rear mount of the gun, a hand-grip assembly, and a removable backplate. The backplate contains two triggers and the trigger safety mechanism. The triggers are operated by the forefingers of both hands, or of either hand. The safety control is located between the hand-grip supports, and can be actuated by either thumb.

CHARACTERISTICS:

Dimensions approximately 28 $\frac{7}{8}$ by 6 $\frac{7}{8}$ by 6 $\frac{3}{8}$ inches
 Weight approximately 11 pounds 10 ounces

RELATIONSHIP OF PARTS: Used with:

A single .50 caliber M2 machine gun A. E. Reference Number 93-1560

ARMY

A. E. REFERENCE NUMBER: 52-1300

SPECIFICATIONS:

Detail 93-24730
 Superseded 24730

A. A. F. DRAWING NUMBER: S42D5223

TYPE DESIGNATION: E-11

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

(Continued on page 17)



ADAPTER—GUN MOUNT

(Continued from page 16)

NAVY

TYPE DESIGNATION: Mark 6 Modification 3
 BU. ORD. DRAWING NUMBER: 278292
 AVIATION ORDNANCE STOCK LIST NUMBER: 1-A-68-13
 PUBLICATIONS: O. P. 865; O. H. I. V5-43.
 PROCUREMENT STATUS: Under procurement.


MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Type	Remarks
Bell Aircraft Corporation	GM-32A	03-043-012	A-B	5200005560	11-10-7	150J 26	Army E-11	
	GM-43	GM749-602	N		11-10-8		Navy Mark 6 Modification 3	Has a telescopic sight bracket and ammunition box holder.
	GM-32	GM749-601	A-B	5200005450	11-10-7	150J 11	Army E-5	Has one firing trigger.
The John C. Turner Corporation	*E-11	03-043-012	A-B	5200005560	11-10-7	150J 26	Army E-11	
Brunhoff Manufacturing Company	*E-8	DS-6300	A-B	5200005525	11-10-9	150J 21	Army E-8	Has one firing trigger.
	*E-12	DS-6670	A-B	5200005575	11-10-9	150J 24	Army E-12	
Edgewater Steel Company	*E-8	DS-6300	A-B	5200005525	11-10-9	150J 21	Army E-8	Has one firing trigger.
	*E-12	DS-6670	A-B	5200005575	11-10-9	150J 24	Army E-12	

Note: *AAF type.



GUN MOUNT ADAPTERS ARMAMENT—GUNNERY



ADAPTER—GUN MOUNT ARMY TYPE E-12

NAMES: Gun mount adapter

Adapter—machine gun (British)

DESCRIPTION: The Army type E-12 gun mount adapter absorbs the recoil shock of a single .50 caliber, M2 machine gun. It consists of two rectangular tubes bolted to the sides of a type E-10 recoil absorbing gun mount adapter. This adapter eliminates the need for a front trunnion block. The rear support of the gun fastens to a member attached near the rear of the side tubes. The gun and adapter are supported from the airplane structure by a yoke, which is not furnished with the adapter. Above the gun, and fixed to the rear of the tubes, is a gun sight platform, upon which a type C-4 gun sight mount may be installed. The base of the platform carries dual hand grips, dual triggers, and the safety mechanism. A type C-3 ammunition box mount supports a type C-1 ammunition box at the side of the adapter.

CHARACTERISTICS:

Dimensions approximately 33 by 7 by 6 $\frac{3}{4}$ inches
Weight approximately 16 pounds

RELATIONSHIP OF PARTS: Used with:

A single .50 caliber M2 machine gun A. E. Reference Number 93-1560

ARMY

A. E. REFERENCE NUMBER: 52-1325

SPECIFICATIONS:

Detail 93-24752

Superseded 24752

A. A. F. DRAWING NUMBER: 42K6978.

TYPE DESIGNATION: E-12

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, including the Army type E-10 gun mount adapter.

NAVY

There is no Navy equivalent for the Army item.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Type	Remarks
Edgewater Steel Company	*E-12	DS-6670	A-B	5200005575	11-10-9	150J 24		
	*E-8	DS-6300	A-B	5200005525	11-10-9	150J 21	Army type E-8	Has one firing trigger.
Brunhoff Manufacturing Company	*E-12	DS-6670	A-B	5200005575	11-10-9	150J 24		
	*E-8	DS-6300	A-B	5200005525	11-10-9	150J 21	Army type E-8	Has one firing trigger.
Bell Aircraft Corporation	GM-32	GM749-601	A-B	5200005450	11-10-7	150J 11	Army type E-5	Has one firing trigger.
	GM-32A	03-043-012	A-B	5200005560	11-10-7	150J 26	Army type E-11	
	GM-43	GM749-602	N-B		11-10-8	150J 11	Navy Mark 6, Modification 3	Has a telescopic sight bracket and ammunition box holder.
The John C. Turner Corporation	E-11	03-043-012	A-B	5200005560	11-10-7	150J 26		

Note: *AAF type.



BARREL—GUN CHARGING TURNBUCKLE

NAMES: Gun charging turnbuckle barrel
Barrel—gun charging control turnbuckle
Turnbuckle barrel

DESCRIPTION: This steel turnbuckle barrel is used to adjust the tension of the charging cable for a remotely placed .30 caliber M2 machine gun. It has a right and a left hand thread in opposite ends of the barrel. The rod that fits into the charging slide of a type B-5 charging handle is screwed into the right hand thread, and a clevis, carrying the charging cable, screws into the other end.

CHARACTERISTICS:

Dimensions	approximately $1\frac{1}{8}$ by $\frac{3}{8}$ by $\frac{1}{8}$ inches
Weight	approximately 3 ounces
Right hand thread	$\frac{3}{8}$ —24 NF—3
Left hand thread	$\frac{1}{4}$ —28 NF—3


RELATIONSHIP OF PARTS: Used with:
Army type B-5 gun charging handle.

ARMY

A. E. REFERENCE NUMBER: 52-1400
MANUFACTURER: Gray Laboratory Manufacturing Company.
A. A. F. DRAWING NUMBER: 31-808
A. S. C. STOCK NUMBER: 5200043000
PRODUCTION STATUS: Not under procurement for initial installation.
SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



BOLT AND BRACKET—GUN TRUNNION

ARMY TYPE A-3 NAVY—SEE BELOW

NAMES: Gun trunnion bolt and bracket

Bolt and bracket assembly—gun trunnion

Bolt, trunnion, BAM—.30 and .50 caliber M2 (Navy)

DESCRIPTION: The Army type A-3 gun trunnion bolt and bracket is used with either a .30 or .50 caliber M2 machine gun. It consists of a U-shaped bracket and bolt for connecting the forward mounting trunnion of the gun to the mounting post in the airplane. The entire unit can be removed from the mounting post by turning a knurled collar on the bracket.

CHARACTERISTICS:

Dimensions

approximately 4 by 2½ by 2½ inches

Weight

approximately 1 pound 3 ounces

RELATIONSHIP OF PARTS: Used with:

Single .30 or .50 caliber M2 machine gun

A. E. Reference Numbers 93-1420 or 93-1560

ARMY

A. E. REFERENCE NUMBER: 52-1450

SPECIFICATIONS:

Detail

93-24596

A. A. F. DRAWING NUMBER: 32B1644 (Supersedes Army drawing number H32D3819)

TYPE DESIGNATION: A-3

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: A-3

BU. ORD. DRAWING NUMBER: 167348

AVIATION ORDNANCE STOCK LIST NUMBER: 1-B-4536

ORDNANCE PAMPHLET: 865

PROCUREMENT STATUS: Under procurement.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Crosley Corporation	*A-3	**32B1644	A-N-B	5200075000	150J 596
Aerial Machine and Tool Company	*A-3	**32B1644	A-N-B	5200075000	150J 596
Taco Heater Corporation	Mark 1		N		
Appliance Manufacturing Company	Mark 1		N		

Note: *AAF type; **AAF drawing.



BOX—AMMUNITION

ARMY TYPE L-4 NAVY TYPE L-4

NAMES: Ammunition box
Magazine (Navy)
.30 caliber ammunition box

DESCRIPTION: The type L-4 ammunition box is a rectangular metal box, with a capacity of 100 rounds of .30 caliber ammunition in a metallic link belt. It is secured to the gun mount adapter by a type A-1 ammunition box holder. The edge of the box has a curved lip, which prevents the ammunition belt from catching during firing.


Initial feeding of the ammunition belt into the gun is accomplished by sliding the box cover toward the gun.

CHARACTERISTICS:

Dimensions, approximately 8½ by 4½ by 5 inches
Weight approximately 1½ pounds

RELATIONSHIP OF PARTS: Used with:

Army type A-1 ammunition box holder A. E. Reference Number 52-2800



ARMY

A. E. REFERENCE NUMBER: 52-1500

SPECIFICATIONS:

Detail 93-24653
Superseded 24653

A. A. F. DRAWING NUMBER: 30-616

TYPE DESIGNATION: L-4

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type L-7, ammunition box, A. E. Reference Number 52-1550.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION:

	Mark 1	Mark 7	L-4
Assembly Installation	178456	300526	294272
Assembly	1-M-176	1-M-176-20	1-M-176-30
Assembly	865	None	None
Procurement	Not Under Procurement	Under Procurement	Not Under Procurement

BU. ORD. DRAWING NUMBERS:

AVIATION ORDNANCE STOCK LIST NUMBER:

ORDNANCE PAMPHLET NUMBER:

PROCUREMENT STATUS:

NOTE: Navy Mark 1 and L-4 are identical.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Geuder, Paeschke and Frey, Company	*L-4	**36-6108	A-N-B	5200090300	150J, 575	Has ¾ inch feed lip.
Pittsburgh-Dubois Company	*L-4	**30-616	A-N-B	5200090300	150J, 575	Has ¾ inch feed lip.
	‡Mark 1	‡‡178456	N			Has ¾ inch feed lip.
	‡Mark 7	‡‡294272	N			"
Brunhoff Manufacturing Company	*L-7	**42D6839	A-B	5200090300	150J, 597	

Note: *AAF type; **AAF drawing; ‡Bu. Ord. type; ‡‡Bu. Ord. drawing.



BOX—AMMUNITION ARMY TYPE L-7

NAMES: Ammunition box
.30 caliber ammunition box
Magazine

DESCRIPTION: The Army type L-7 ammunition box is a rectangular metal box, with a capacity of 100 rounds of .30 caliber ammunition in a metallic link belt. It is identical with the type L-4 ammunition box, except that the type L-7 has a rolled edge instead of a bent lip. The top of the box is removable for loading the ammunition.

This box fits into an ammunition box holder secured to the gun mount adapter.

CHARACTERISTICS:

Dimensions approximately 8 $\frac{3}{4}$ by 4 $\frac{1}{2}$ by 4 $\frac{3}{8}$ inches
Weight approximately 1 $\frac{1}{2}$ pounds

RELATIONSHIP OF PARTS: Used with:
Army type A-1 ammunition box holder

A. E. Reference Number 52-2800

ARMY

A. E. REFERENCE NUMBER: 52-1550

SPECIFICATIONS:

Detail 93-24750
Superseded 24750

A. A. F. DRAWING NUMBER: 42D6859

TYPE DESIGNATION: L-7

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Brunhoff Manufacturing Company	*L-7	**42D6859	A-B	5200090500	150J/597	
Geuder, Paeschke, and Frey, Inc.	*L-4	**36-6108	A-B	5200090300	150J/575	Has $\frac{1}{8}$ inch feed lip
Pittsburgh-Dubois Company	*L-4	**30-616	A-B	5200090300	150J/575	Has $\frac{1}{8}$ inch feed lip
	*L-4	††155316	N			Has $\frac{1}{8}$ inch feed lip
	‡Mark 1	‡†178456	N			Has $\frac{1}{8}$ inch feed lip
	‡Mark 7	‡†294272	N			

Note: *AAF type; **AAF drawing; †Bu. Ord. type; ‡†Bu. Ord. drawing.




BOX—AMMUNITION

ARMY TYPE O-1

NAMES: Ammunition box
Box—ammunition .50 caliber

DESCRIPTION: The Army type O-1 ammunition box is a rectangular metal box, with a capacity of 30 rounds of .50 caliber ammunition in a metallic link belt. It is secured to the gun mount adapter by an ammunition box mount. The edge of the box has a curved lip, to insure smooth feed and to prevent the ammunition belt from catching during firing. The top is removable for loading. While the gun is firing, a flat spring on one side of the box engages the rear of each shell before it enters the gun. This prevents the ammunition from getting out of line, due to vibration, and from slipping back into the box. A tubular grip attached to the cover assists in handling the box during initial feeding of the belt into the gun.



CHARACTERISTICS:

Dimensions approximately 10 by 6 by 4 $\frac{5}{8}$ inches
Weight approximately 2 $\frac{1}{2}$ pounds

RELATIONSHIP OF PARTS: Used with:

Army type C-3 ammunition box mount, A. E. Reference Numbers 52-3350 or 52-3360. When installed on Army type E-8 gun mount adapter, A. E. Reference Number 52-1100.

Army type C-2 ammunition box mount, A. E. Reference Numbers 52-3200 or 52-3300. When installed on Army type E-11 gun mount adapter, A. E. Reference Number 52-1300.

ARMY

A. E. REFERENCE NUMBER: 52-1600

SPECIFICATIONS:

Detail 93-24673

Superseded 24673

MANUFACTURER: Brunhoff Manufacturing Company.

A. A. F. DRAWING NUMBER: 35D3891

TYPE DESIGNATION: O-1

A. S. C. STOCK NUMBER: 5200090900

PRODUCTION STATUS: Under procurement.


SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 150J/578



FLEXIBLE FEED CHUTES

Flexible feed chutes are used to keep the cartridge belt from catching as it travels from the ammunition box to the gun, and to prevent cartridges from twisting and causing a jam. Chutes enable ammunition boxes of large carrying capacity to be located at some distance from the machine guns. This allows placement of guns in positions on the airplane where limited space prevents normal installation.


Interlocked metal stampings, shaped to support and direct the cartridge belt, comprise the chute. At both ends of the chute are adapters, one for the gun, the other for the ammunition box.

The length of flexible chuting, when compressed, is about forty per cent less than when extended; length of chuting is measured when extended.

Flexible feed chutes have been supplied in two general types, separable and permanent. The permanent type chute is composed of a series of links which are spot-welded together to form a permanent flexible chute. The separable type chute is composed of links which are held together by spring action and may be separated by a special tool which releases the spring tension. The separable type chute has superseded the permanent type chute for all initial installations.



FLEXIBLE FEED CHUTES ARMAMENT—GUNNERY



CHUTE—FLEXIBLE FEED LEWIS-LARSON TYPE B

NAMES: Flexible feed chute
Lewis-Larson flexible chuting
Chuting assembly—flexible ammunition .50 cal.
Flexible ammunition chute
Flexible feed chuting

DESCRIPTION: The Lewis-Larson type B flexible feed chute is a separable feed chute, for use with M2 .50 caliber machine guns. This type is supplied in various lengths as ordered, but must be equipped with a box end and gun end adapter before it is ready for use.

CHARACTERISTICS: Dimensions (less adapters):

Width	approximately 5 ⁷ / ₈ inches
Height	approximately 1 ¹ / ₄ inches
Length	must be specified when ordering
Weight	approximately 3 ¹ / ₄ pound per foot of length

RELATIONSHIP OF PARTS: Used with:

Army type L-1 (Lewis-Larson type G-1) gun end adapter, A. E. Reference Number 52-1723, and
Army type L-2 (Lewis-Larson type M-3) Box end adapter, A. E. Reference Number 52-1724.

ARMY

A. E. REFERENCE NUMBER: 52-1722

SPECIFICATIONS:

Detail 24850

A. A. F. DRAWING NUMBER: 43A20364

TYPE DESIGNATION: None (Procured as manufacturer's type B).


A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit in 15, 25, or 50 foot lengths as ordered.

NAVY


The Navy is presently procuring this item from the Army.



MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Brunhoff Manufacturing Company	LLB50	105A40	A-N-B	5200177125	150J 776
Smoot-Holman Company	LLB50	105A40	A-N-B	5200177125	150J 776

NOTE: The Lewis-Larson model LLB50 supersedes, and is interchangeable with, flexible ammunition chuting assemblies A. E. Reference Numbers 52-1730, 52-1750, 52-1760, 52-1770, 52-1790, 52-1800, and 52-1810. When replacing any of these assemblies, one gun end adapter, A. E. Reference Number 52-1723, and one box end adapter, A. E. Reference Number 52-1724, must be supplied for each installation.

**ADAPTER—GUN END****ARMY TYPE L-1**

NAMES: Gun End Adapter
Gun Feedway Adapter
Flexible Feed Chute Adapter

DESCRIPTION: The Army type L-1 gun end adapter is used to connect the flexible feed chute to the gun in such a manner that the function of the chute is not impaired. It is attached to the M2, .50 caliber machine gun by means of the Army type C-2 or C-3 ammunition box mount, and may be quickly attached or removed from this mount by releasing a spring-held latch which forms a part of the adapter.

CHARACTERISTICS:

Weight approximately 1 $\frac{1}{2}$ pound.
Dimension approximately 2 $\frac{1}{16}$ by 5 $\frac{7}{8}$ by 1 $\frac{1}{2}$ inches.

RELATIONSHIP OF PARTS: Used with:

Army type L-2 box end adapter, A. E. Reference Number 52-1724, and Lewis-Larson type B flexible feed chute, A. E. Reference Number 52-1722.

ARMY

A. E. REFERENCE NUMBER: 52-1723

SPECIFICATIONS:

Detail 24875

AN OR A. A. F. DRAWING NUMBER: 43A20362

TYPE DESIGNATION: L-1

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY


There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Am Service Command Stock Number	British Reference Number
Smoot-Holman Company	G-1	105A12	A-B	5200001775	150J 782
Brunhoff Mfg. Company	G-1	105A12	A-B	5200001775	150J 782

**ADAPTER—BOX END****ARMY TYPE L-2**

NAMES: Box end adapter
Box feedway adapter
Flexible feed chute adapter

DESCRIPTION: The Army type L-2 box end adapter is used to provide a quickly detachable means of connecting the flexible feed chute to a .50 caliber ammunition box. This adapter is supplied in three parts: one reinforced chute link with a bayonet connector at each end, and two channel connectors. The chute link is attached to, and becomes a part of, the flexible feed chute, and the two channel connectors are welded to the ammunition box.

CHARACTERISTICS:

Dimensions approximately 1 $\frac{1}{4}$ by 6 by 3 inches.
Weight approximately $\frac{1}{4}$ pound.

RELATIONSHIP OF PARTS: Used with:

Army type L-1 gun end adapter, A. E. Reference Number 52-1723, and Lewis-Larson type B flexible feed chute, A. E. Reference Number 52-1722.

ARMY

A. E. REFERENCE NUMBER: 52-1724

SPECIFICATIONS:

Detail 24876

A. A. F. DRAWING NUMBER: 43A20361

TYPE DESIGNATION: L-2

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY


There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Smoot-Holman Company	M-3	105A24	A-B	5200001785	150J 783
Brunhoff Mfg. Company	M-3	105A24	A-B	5200001785	150J 783

**CHUTE—FLEXIBLE FEED****LEWIS-LARSON TYPE A HUGHES AIRCRAFT PART NO. 32968****NAMES:** Flexible feed chute

Chuting assembly—flexible ammunition .50 cal.

Flexible ammunition chute

Flexible feed chuting

DESCRIPTION: This flexible feed chute is a permanent type feed chute for use with .50 caliber M2 machine guns. This type was supplied in definite lengths, and was equipped with a gun end and box end adapter. Chutes of different manufacture are interchangeable for a definite length, provided the adapters are identical.

CHARACTERISTICS:

Height

approximately 5 $\frac{7}{8}$ inches.

Width

approximately 1 $\frac{1}{2}$ inches.

Weight (less adapters)

approximately $\frac{3}{4}$ pound per foot of length.

Weight of adapters

approximately $\frac{1}{4}$ pound each.**RELATIONSHIP OF PARTS:** Used with:

Army type C-2 ammunition box mount, A. E. Reference Numbers 52-3200 and 52-3300; or Army type C-3 ammunition box mount, A. E. Reference Numbers 52-3350 and 52-3360.

ARMY**A. E. REFERENCE NUMBER:** Refer to chart.**A. S. C. STOCK NUMBER:** Refer to chart.**PRODUCTION STATUS:** Not under procurement for initial installation. Superseded by Lewis-Larson type B, A. E. Reference Number 52-1722.**SHIPPING DATA:** Shipped as a complete unit, including gun end and box end adapters.**NAVY**

The Navy uses this item on airplanes procured from the Army.

The following chart is a list of permanent type flexible feed chutes, formerly procured by the Army. All models listed below have been superseded by separable chute type B, A. E. Reference Number 52-1722, for initial installation.

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Length In Inches	A. E. Reference Number	British Reference Number
Smoor-Holman Company and Brunhoff Manufacturing Company	LLA50-M1-G1-15	10581	A-B	5200174506-8	15	52-1730	150J 756
	LLA50-M1-G1-29	10581	A-B	5200174506-82	29	52-1750	150J 757
	LLA50-M1-G1-36	10581	A-B	5200174506-84	36	52-1760	150J 758
	LLA50-M1-G1-48	10581	A-B	5200174506-86	48	52-1770	150J 759
	LLA50-M1-G1-66	10581	A-B	5200174506-884	66	52-1790	150J 760
	LLA50-M1-G1-85	10581	A		85	52-1800	None
Hughes Aircraft Company	LLA50-M1-G1-103	10581	A-B	5200174506-888	103	52-1810	150J 761
	32968-150	32968	A-B	5200174506-5	15	52-1730	150J 756
	32968-360	32968	A-B	5200174506-55	36	52-1760	150J 758
	32968-650	32968	A-B	5200174506-555	65 or 66	52-1790	150J 760

NOTE: Smoor-Holman Company and Brunhoff Manufacturing Company manufacture their chutes in accordance with Lewis-Larson Company drawings and model designation. The model identification serves as a code to the chute required.

EXAMPLE: LLA50-M1-G1-15 specifies Lewis-Larson—type A (permanent)—.50 caliber—M1—box end adapter—G1—gun end adapter—15 inch length.

Hughes Aircraft Company manufacture their chutes in accordance with Hughes drawing number 32968, and their model designation was represented by the drawing number, a dash and the length in inches, with the last digit signifying the fraction of inches in eighths, if any. The adapters for this chute were specified on Army Air Forces Contracts when ordered.

EXAMPLE: 32968-150 signifies drawing number—15 inches, and 0 eighths of an inch in length.



CONTAINER—EJECTED CASE

ARMY TYPE A-4

NAMES: Ejected case container
Container, ejected case, BAM—.30, M2
Container—case ejection
Case ejection container

DESCRIPTION: The Army type A-4 ejected case container is used with a single .30 caliber, M2 machine gun installed on an Army type C-12 gun mount adapter. After being fired, the empty cartridge cases are ejected from the gun into the container. The container is of sheet metal, semi-circular in shape, and has a capacity of about 100 ejected cartridge cases. It is removable for emptying.

CHARACTERISTICS:

Dimensions	approximately 11 $\frac{5}{8}$ by 5 $\frac{1}{2}$ by 2 $\frac{3}{8}$ inches.
Weight	approximately 1 pound 6 ounces.
Capacity	approximately one hundred .30 caliber cartridge cases.

RELATIONSHIP OF PARTS: Used with:

A single .30 caliber M2 machine gun A. E. Reference Number 93-1520 mounted on an Army type C-12 adapter, A. E. Reference Number 52-500.

ARMY

A. E. REFERENCE NUMBER: 52-1950

SPECIFICATIONS:

Detail	93-24604
Superseded	24604

A. A. F. DRAWING NUMBER: 37D5641 (Supersedes H38D6421)

TYPE DESIGNATION: A-4

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-5 ejected case container, A. E. Reference Number 52-2000.

NAVY

There is no Navy equivalent for the Army item.


MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Dayton Manufacturing Company	*A-4	**37D5641	A-B	5200211900	150J 579	
	*A-5	**40G7385	A-B	5200211920	150J 751	Has canvas holder for 400 .30 caliber ejected cartridge cases.

Note: *AAF type; **AAF drawing.



CONTAINERS ARMAMENT—GUNNERY



CONTAINER—EJECTED CASE

ARMY TYPE A-5

NAMES: Ejected case container
Case ejection container
Container—ejection case

DESCRIPTION: The Army type A-5 ejected case container is used with any single .30 caliber, M2 machine gun. It has a metal top, equipped with ends which are designed for quick attachment to the underside of the gun by means of two studs. After being fired, the empty cartridge cases are ejected from the gun into the container. The actual container is a canvas sack suspended from the metal top, and is emptied by means of a slide fastener at the bottom.

CHARACTERISTICS:

Dimensions approximately $26\frac{1}{2}$ by $11\frac{3}{4}$ by $3\frac{5}{8}$ inches.
Weight approximately $1\frac{1}{8}$ pounds.
Capacity approximately four hundred .30 caliber cartridge cases.

RELATIONSHIP OF PARTS: Used with:
Any single .30 caliber M2 machine gun.

ARMY

A. E. REFERENCE NUMBER: 52-2000

SPECIFICATIONS:

Detail 93-24686
Superseded 24686

A. A. F. DRAWING NUMBER: 40G7385

TYPE DESIGNATION: A-5

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY


There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Dayton Manufacturing Company	*A-5	**40G7385	A-B	5200211920	150J 751	
	*A-4	**37D5641	A-B	5200211900	150J 579	Capacity limited to 100 cases. Interchangeable when gun is used with type C-12 adapter only.

Note: *AAF type; **AAF drawing.

**CONTAINER-EJECTED LINK****ARMY TYPE A-3**

NAMES: Ejected link container
Link ejection container
Container—link ejection

DESCRIPTION: The Army type A-3 ejected link container is used with a single .30 caliber M2 machine gun. After being stripped from the cartridges by the gun, the links are ejected from the gun into the container. The container consists of a metal tube, the upper end of which is attached to either the right or left hand side of the gun by means of the belt retaining pawl pin. A canvas container is suspended from the lower end of the tube, where it is held by means of a snap fastener. This container may be emptied quickly by unsnapping the fastener.

CHARACTERISTICS:

Dimensions approximately 28 $\frac{3}{4}$ by 3 $\frac{3}{4}$ by 8 $\frac{5}{8}$ inches.
Weight approximately $\frac{3}{4}$ pound.
Capacity approximately two hundred .30 caliber ammunition belt links.

RELATIONSHIP OF PARTS: Used with:
Any .30 caliber M2 machine gun.

ARMY

A. E. REFERENCE NUMBER: 52-2100

SPECIFICATIONS:

Detail 93-24674
Superseded 24674

A. A. F. DRAWING NUMBER: 37D2077

TYPE DESIGNATION: A-3

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-5 ejected link container, A. E. Reference Number 52-2200.

SHIPPING DATA: Shipped as a complete unit.

NAVY


There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Dayton Manufacturing Company	*A-3	**37D2077	A-B	5200213400	150J 752	
	*A-4	**37D5642	A-B	5200213700	150J 763	Metallic box.
	*A-5	**41D11038	A-B	5200213740	150J 580	Metallic box.

Note: *AAF type; **AAF drawing.



CONTAINER—EJECTED LINK

ARMY TYPE A-4

NAMES: Ejected link container
Link ejection container
Container—link ejection

DESCRIPTION: The Army type A-4 ejected link container is used with a .30 caliber, M2 machine gun. After being stripped from the cartridges by the gun, the links are ejected from the gun into the container. The container consists of a rectangular metal box with a tapering elbow neck which can be attached to the right or left side of the gun. At the bottom of the box is a metal flap which is kept closed with a snap latch. Links are emptied from the container by opening the flap.

CHARACTERISTICS:

Dimensions: approximately 9 $\frac{1}{4}$ " by 5 $\frac{3}{4}$ " by 3 $\frac{3}{8}$ " inches.
Weight: approximately 1 $\frac{1}{4}$ pounds.
Capacity: approximately two hundred .30 caliber links.

RELATIONSHIP OF PARTS: Used with:
Any .30 caliber M2 machine gun.

ARMY

A. E. REFERENCE NUMBER: 52-2150

SPECIFICATIONS:

Detail: 93-24605
Superseded: 24605

A. A. F. DRAWING NUMBER: 37D5642 (supersedes Army drawing number H39D5353)

TYPE DESIGNATION: A-4

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-5, ejected link container, A. E. Reference Number 52-2200.

SHIPPING DATA: Shipped as a complete unit.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Alt Service Command Stock Number	British Reference Number	Remarks
Dayton Manufacturing Company	*A-4	**37D5642	A-B	5200213700	150J 763	
	*A-3	**37D2077	A-B	5200213400	150J 752	Has canvas holder.
	*A-5	**41D11038	A-B	5200213740	150J 580	

Note: *AAF type; **AAF drawing.



CONTAINER—EJECTED LINK ARMY TYPE A-5

NAMES: Ejected link container
Link ejection container

DESCRIPTION: The Army type A-5 link ejection container is used with a single .30 caliber, M2 machine gun. After being stripped from the cartridges by the gun, the links are ejected from the gun into the container. The container consists of a rectangular metal box with a tapering elbow neck, which can be attached to either the right or left side of the gun by means of the belt holding pawl pin. At the bottom of the box is a metal flap, which is kept closed with a snap latch. Links are emptied from the container by opening the flap.

CHARACTERISTICS:

Dimensions	approximately 8 1/4 by 5 1/2 by 3 1/2 inches.
Weight	approximately 1 1/4 pounds.
Capacity	approximately two hundred .30 caliber ejected links.

RELATIONSHIP OF PARTS: Used with:
Any .30 caliber M2 machine gun.

ARMY

A. E. REFERENCE NUMBER: 52-2200

SPECIFICATIONS:

Detail	93-24721
Superseded	24721

A. A. F. DRAWING NUMBER: 41D11038

TYPE DESIGNATION: A-5

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Dayton Manufacturing Company	*A-5	**41D11038	A-B	5200213740	150J, 580	
	*A-3	**37D2077	A-B	5200213400	150J, 752	Has canvas holder.
	*A-4	**37D5642	A-B	5200213700	150J, 763	

Note: *AAF type, **AAF drawing.



CONTAINER—SIGNAL FLARE ARMY TYPE A-1

NAME: Signal flare container

DESCRIPTION: The Army type A-1 signal flare container is a portable carrier for aircraft signal flares. It is made of canvas, has a plywood bottom support, and cotton webbing strap handles for carrying. A full length zipper enables the entire top to be opened.

The container is divided into two parallel compartments, one able to hold four and the other five M-10, M-11, M-14, M-15, or M-16 signal flares. Snap fasteners attach the container to the pistol holder inside the airplane.

CHARACTERISTICS:

Dimensions.....	approximately 8½ by 9¼ by 3¼ inches.
Weight.....	approximately ¾ pound.
Capacity.....	9 flares.

ARMY

A. E. REFERENCE NUMBER: 52-2250

SPECIFICATIONS:

Detail.....	93-24713
Superseded.....	24713

MANUFACTURER: Troy Sunshade Company.

A. A. F. DRAWING NUMBER: 41G9233

TYPE DESIGNATION: A-1

A. S. C. STOCK NUMBER: 4500216600

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-7 signal flare container A. E. Reference Number 52-2256.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



CONTAINER—SIGNAL FLARE

ARMY TYPE A-5

NAME: Signal flare container

DESCRIPTION: The Army type A-5 signal flare container is a carrier for aircraft signal flares. It is made of canvas, with a plywood bottom and cotton webbing strap handles for carrying.

The container has two parallel compartments, each able to hold three flares of types AN-M37 to AN-M45 inclusive. A full length zipper enables the entire top to be opened. Snap fasteners attach the container to the pistol holder inside the airplane.

CHARACTERISTICS:

Dimensions	approximately 4¾ by 5¾ by 4½ inches.
Weight	approximately 1½ pound.
Capacity	6 flares.

RELATIONSHIP OF PARTS: Used with:

Army type A-2 pyrotechnic pistol holder, A. E. Reference Number 52-2826.

ARMY

A. E. REFERENCE NUMBER: 52-2254

SPECIFICATIONS:

Detail	93-24771
Superseded	24771

MANUFACTURER: Troy Sunshade Company.

A. A. F. DRAWING NUMBER: 42G11966

TYPE DESIGNATION: A-5

A. S. C. STOCK NUMBER: 4500230375

TECHNICAL ORDER NUMBER: 11-15-8

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



CONTAINER—SIGNAL FLARE

ARMY TYPE A-6

NAME: Signal flare container

DESCRIPTION: The Army type A-6 signal flare container is a carrier for aircraft signal flares. It is made of canvas with a plywood bottom, and cotton webbing strap handles for carrying. The container has two parallel compartments, each able to hold six flares of types AN-M37 to AN-M45 inclusive. A full length zipper enables the entire top to be opened. Snap fasteners attach the container to the pistol holder inside the airplane.

CHARACTERISTICS:

Dimensions.....	approximately 4 3/4 by 11 1/4 by 4 1/2 inches.
Weight.....	approximately 1 1/2 pound.
Capacity.....	12 flares.

RELATIONSHIP OF PARTS: Used with:

Army type A-2 pyrotechnic pistol holder, A. E. Reference Number 52-2826.

ARMY

A. E. REFERENCE NUMBER: 52-2255

SPECIFICATIONS:

Detail.....	93-24772
Superseded.....	24772

MANUFACTURER: Troy Sunshade Company.

A. A. F. DRAWING NUMBER: 42G11967

TYPE DESIGNATION: A-6

A. S. C. STOCK NUMBER: 4500230400


TECHNICAL ORDER NUMBER: 11-15-8

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



CHARGER, MANUAL, M2

FORMER ARMY TYPE B-6

NAMES: Manual charger
Gun charger control
Manual charger 20-mm cannon
Control—gun charger

DESCRIPTION: The M2 manual gun charger is the internal mechanism for manually charging a 20-mm automatic gun. It consists of a cable which passes through a spring and fastens to a piston backed against the spring.

The entire unit is inserted into a cylinder which is mounted on the side, and is a part of the gun. The cable passes around a pulley on the outside of the cylinder, and is attached to a handle accessible to the pilot. When the cable is pulled, the piston, which is secured to the gun bolt, moves backward, compressing the spring against the rear of the cylinder and charging the gun. When the cable is released, the spring restores the piston to its original position and allows the gun bolt to operate independently of the charger.

This unit was formerly known as the AAF type B-6 gun charger control assembly. It is now supplied by Ordnance Office, War Department.

CHARACTERISTICS:

Dimensions.....	approximately 25 $\frac{5}{8}$ by 2 $\frac{1}{8}$ by 1 $\frac{3}{4}$ inches.
Weight.....	approximately 1 $\frac{3}{4}$ pounds.

RELATIONSHIP OF PARTS: Used with:
M1 or AN-M2, 20-mm automatic guns.

ARMY

A. E. REFERENCE NUMBER: 52-2275

SPECIFICATIONS:

Detail.....	93-24778
Superseded.....	24778

ORDNANCE DRAWING NUMBER: D69343

FORMER A. A. F. DRAWING NUMBER: 42C10439 and H43D6383

TYPE DESIGNATION: M2

FORMER TYPE DESIGNATION: B-6

PRODUCTION STATUS: Under procurement. Now supplied by Ordnance Office, War Department.


SHIPPING DATA: This item is usually supplied as a component part of the 20-mm gun.

NAVY

The Navy does not use this item, generally, since their equivalent would be the hydraulic 20-mm gun charger, which is procured as a component part of the AN-M2, 20-mm gun, type E, Aviation Ordnance Stock List Number 1-G-5599.

BRITISH

REFERENCE NUMBER: 108A/159



CHARGER—20 mm HYDRAULIC GUN

ARMY TYPE D-3 NAVY—SEE BELOW

NAMES: 20-mm Hydraulic Gun charger
Hydraulic gun charger cylinder

Cylinder—hydraulic gun charger—20-mm cannon
Charger—gun, hydraulic BAM .50, M2 (Navy)

DESCRIPTION: This hydraulic gun charger, Army type D-3, provides a means for charging a 20-mm aircraft cannon located in a position remote from the gunner. The charger consists of a piston in a hydraulic cylinder, and is operated by a remote control valve. The charging cylinder is mounted in a tubular housing on the right hand side of the gun. The piston is forced against the gun bolt stud under hydraulic pressure and carries the bolt back to the recoil position. The gun control valve can be set either to hold the bolt in the safety position or to complete the charging cycle and prepare the gun for firing.

Hydraulic pressure to operate the charger is supplied by the airplane's hydraulic system.

CHARACTERISTICS:

Dimensions	approximately 11 by 1¼ by 1¼ inches.
Weight	approximately 2 pounds 4 ounces.
Piston diameter	¾ inch.
Charging stroke	10 inches.
Minimum hydraulic pressure	800 pounds per square inch.
Maximum hydraulic pressure	1500 pounds per square inch.

RELATIONSHIP OF PARTS: Used with:

Army type A-1 hydraulic gun charging valve, A. E. Reference Number 52-8450.

ARMY

A. E. REFERENCE NUMBER: 52-2300

MANUFACTURER: Bendix Products Division of Bendix Aviation Corporation.

MANUFACTURER'S DRAWING NUMBER: 78003

MANUFACTURER'S MODEL: F

A. A. F. DRAWING NUMBER: H41G5289

TYPE DESIGNATION: D-3

A. S. C. STOCK NUMBER: 5400239000

TECHNICAL ORDER NUMBER: 11-1-21

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type B-6 gun charger, A. E. Reference Number 52-2275.

SHIPPING DATA: This item shipped as a component part of AN-M2, 20-mm gun, Type E, A. E. Reference Number 93-1355.

NAVY

BUORD. DRAWING NUMBER: 332358


AVIATION ORDNANCE STOCK LIST NUMBER: 1-C-3412-50 (supersedes 1-C-7680).

ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Under procurement. Supplied with AN-M2, 20-mm gun, Type E, Aviation Ordnance Stock List Number 1-G-5599.

BRITISH

REFERENCE NUMBER: 108A/21



CHARGER—.30 CALIBER HYDRAULIC GUN ARMY TYPE D-1

NAMES: .30 caliber hydraulic gun charger
Hydraulic gun charger cylinder
.30 caliber hydraulic charger
Cylinder—hydraulic gun charger .30 caliber

DESCRIPTION: This Army type D-1 hydraulic gun charger provides a means of charging a .30 caliber M2 machine gun located in a position remote from the gunner. The charger, which consists of a piston in a hydraulic cylinder, can be mounted on either side of the gun and operated by a remote control valve.

Hydraulic pressure, from the airplane's hydraulic system, is applied through the control valve to the cylinder, forcing the piston against the gun bolt stud. This action carries the bolt back to the recoil position. A latch mechanism holds the bolt in this position until the pressure is released from the cylinder, permitting the bolt to return. The control valve can be set either to hold the bolt in the safety position or to complete the charging cycle and prepare the gun for firing.

CHARACTERISTICS:

Dimensions	approximately 17 $\frac{7}{8}$ by $\frac{7}{8}$ by $\frac{7}{8}$ inches.
Weight	approximately 2 $\frac{1}{4}$ pounds.
Piston diameter	$\frac{1}{2}$ inch.
Charging stroke	4 $\frac{1}{2}$ inches.
Minimum hydraulic pressure	800 pounds per square inch.
Maximum hydraulic pressure	1500 pounds per square inch.

RELATIONSHIP OF PARTS: Used with:

Any single .30 caliber M2 machine gun, and an Army type A-1 hydraulic gun charger. A. E. Reference Number 52-8450.

ARMY


A. E. REFERENCE NUMBER: 52-2400
MANUFACTURER: Bendix Products Division of Bendix Aviation Corporation.
MANUFACTURER'S DRAWING NUMBER: 78002
MANUFACTURER'S MODEL: H
A. A. F. DRAWING NUMBER: H41G5287
TYPE DESIGNATION: D-1
A. S. C. STOCK NUMBER: 5400239040
TECHNICAL ORDER NUMBER: None.
PRODUCTION STATUS: Not under procurement for initial installation.
SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 108A/171.

**CHARGER—.50 CALIBER HYDRAULIC GUN****ARMY TYPE D-2 NAVY—SEE BELOW**

NAMES: .50 caliber hydraulic gun charger
Hydraulic gun charger cylinder

Cylinder—hydraulic gun charger .50 caliber
Charger—gun, hydraulic BAM .50, M2 (Navy)

DESCRIPTION: This Army type D-2 hydraulic gun charger provides a means of charging a .50 caliber M2 machine gun located in a position remote from the gunner. The charger, which consists of a piston in a hydraulic cylinder, can be mounted on either side of the gun and is operated by a remote control valve.

Hydraulic pressure, from the airplane's hydraulic system, is applied through the control valve to the charging cylinder, and forces the piston against the gun bolt stud. This action carries the bolt back to the recoil position. A latch mechanism holds the bolt in this position until the pressure is released from the cylinder, permitting the bolt to return. The control valve can be set either to hold the bolt in safety position or to complete the charging cycle and prepare the gun for firing.

CHARACTERISTICS:

Dimensions	approximately 18½ by 1½ by 3 inches.
Weight	approximately 2¼ pounds.
Piston diameter	1½ inch.
Charging stroke	7½ inches.
Minimum hydraulic pressure	800 pounds per square inch.
Maximum hydraulic pressure	1500 pounds per square inch.

RELATIONSHIP OF PARTS: Used with:

A single .50 caliber M2 machine gun, and Army type A-1 hydraulic gun charging valve, A. E. Reference Number 52-8450.

ARMY

A. E. REFERENCE NUMBER: 52-2500

MANUFACTURER: Bendix Products Division of Bendix Aviation Corporation.

MANUFACTURER'S DRAWING NUMBER: 76862

MANUFACTURER'S MODEL: C

A. A. F. DRAWING NUMBER: H41G5288

TYPE DESIGNATION: D-2

A. S. C. STOCK NUMBER: 5400239050

TECHNICAL ORDER NUMBER: None.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by manual type, contractor furnished equipment.

SHIPPING DATA: Shipped as a complete unit.

NAVY

BUORD. DRAWING NUMBER: 332358


AVIATION ORDNANCE STOCK LIST NUMBER: 1-C-3512-95 (supersedes 1-C-7685).

ORDNANCE PAMPHLET NUMBER: 865,828

PROCUREMENT STATUS: Not under procurement for initial installation.

BRITISH

REFERENCE NUMBER: 108A/66




CONTINUOUS FEED UNITS

Continuous feed units enable a .30 caliber ammunition belt to be guided into a machine gun while the gun is swiveled, elevated, or depressed. These units are used with remote gun installations where ammunition must be guided for a distance. The upper unit is mounted directly on the adapter of the gun and the lower unit is placed on the ammunition box.

The units decrease belt bending but permit an increase in turning radius as the belt enters the gun.

Both units, each consisting of a guide, roller and chute, are able to turn through a complete circle. The guides and chute lead the ammunition belt, and the roller provides an even flow of cartridges.



FEED—LEFT HAND UPPER CONTINUOUS

BELL AIRCRAFT CORP. MODEL CF-3L NAVY—SEE BELOW

NAMES: Left hand upper continuous feed
.30 caliber upper continuous feed—left hand

DESCRIPTION: The upper continuous feed unit, designed for attachment to the left hand side of the gun adapter, is used to guide and feed .30 caliber ammunition to a machine gun from a remote source. It consists of a chute, guide and rollers, through which the ammunition belt passes. This unit can be rotated through 360 degrees, and provides for adjustment of alignment between the chute and guide so that the ammunition belt can feed properly.

CHARACTERISTICS:

Dimensions approximately 6 by 5¼ by 3¼ inches.
Weight approximately 1¾ pounds.

RELATIONSHIP OF PARTS: Used with:

Lower continuous feed, Bell model CF-5, A. E. Reference Number 52-2682, and on a single .30 caliber M2 machine gun, A. E. Reference Number 93-1440 or 93-1520.

ARMY

A. E. REFERENCE NUMBER: 52-2680

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation.

SHIPPING DATA: Shipped as a complete unit.

NAVY


This item is identified by the Navy under the manufacturer's designation.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A—Army, N—Navy, B—British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Bell Aircraft Corp.	CF-3L	03-042-1971	A-B	5200265400	11-1-41	150J 754	
	03-059-051	03-059-051	N				Identical with the Bell model CF-3L, except includes a ratchet which can be removed if necessary.



FEED—RIGHT HAND UPPER CONTINUOUS

BELL AIRCRAFT CORP. MODEL CF-3R NAVY—SEE BELOW

NAME: Right hand upper continuous feed

DESCRIPTION: The upper continuous feed unit, designed for attachment to the right hand side of the gun adapter, is used to guide and feed .30 caliber ammunition to a machine gun from a remote source. It consists of a chute, guide and rollers, between which the ammunition belt passes. This unit can be rotated through 360 degrees, and provides for adjustment of alignment between the chute and guide so that the ammunition belt can feed properly.

CHARACTERISTICS:

Dimensions.....approximately 6 by 5¼ by 3¼ inches.
Weight.....approximately 1½ pounds.

RELATIONSHIP OF PARTS: Used with:

Lower continuous feed, Bell model CF-5, A. E. Reference Number 52-2682, and a single .30 caliber M2 machine gun, A. E. Reference Numbers 93-1440 or 93-1520.

ARMY

A. E. REFERENCE NUMBER: 52-2681

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation.

SHIPPING DATA: Shipped as a complete unit.

NAVY


This item is identified by the Navy under the manufacturer's designation.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Bell Aircraft Corporation	CF-3R	03-042-197R	A-B	5200265420	11-1-41	150J/755	
	03-059-052	03-059-052	N				Identical with Bell model CF-3R except includes a ratchet which can be removed if necessary.



FEED—LOWER CONTINUOUS
BELL AIRCRAFT CORP. MODEL CF-5 **NAVY—SEE BELOW**

NAMES: Lower continuous feed
 Feed—.30 caliber lower continuous

DESCRIPTION: The lower continuous feed unit, mounted above the ammunition box, is used to guide and feed .30 caliber ammunition to a machine gun.

It consists of a guide housing, guide, guide deflectors, and rollers between which the ammunition belt passes.

One of the rollers is held in place by an eccentric bolt. This bolt is used for adjustment and alignment to insure proper ammunition feed.

The unit can be rotated 360 degrees, either horizontally or vertically, following the movement of the gun.

CHARACTERISTICS:

Dimensions.....approximately 6 by 5 $\frac{1}{4}$ by 3 $\frac{1}{4}$ inches.
 Weight.....approximately 1 pound 7 ounces.

RELATIONSHIP OF PARTS: Used with:

Upper continuous feed, A. E. Reference Numbers 52-2680 or 52-2681.

ARMY


A. E. REFERENCE NUMBER: 52-2682
 MANUFACTURER: Bell Aircraft Corporation.
 MANUFACTURER'S MODEL NUMBER: CF-5
 MANUFACTURER'S DRAWING NUMBER: GM-749-663
 A. S. C. STOCK NUMBER: 5200265250
 TECHNICAL ORDER NUMBER: 11-1-41
 PRODUCTION STATUS: Not under procurement for initial installation.
 SHIPPING DATA: Shipped as a complete unit.

NAVY

This item is identified by the Navy under the manufacturer's designation.

BRITISH

REFERENCE NUMBER: 150J/587



HANDLE—GUN CHARGING

ARMY TYPE A-2 NAVY MARK 1 MOD. 1

NAME: Gun charging handle

DESCRIPTION: This gun charging handle is used for manually charging fixed M2 remotely located machine guns. A cable connects the handle to the charging slide on the gun.

The unit consists of a tubular member, threaded at one end for mounting to the airplane structure. A grooved rod with a handle on the end passes through the tube; the cable from the gun charging device is fastened to the other end. The rod is notched so that the handle may be turned, locking the charging device in a safety position, or it may be pulled out and locked in a full recoil position. If the handle is pulled out all the way and released without turning, the full charging cycle will be completed.

CHARACTERISTICS:

Dimensions.....approximately 12 $\frac{3}{4}$ by 3 $\frac{5}{8}$ by $\frac{3}{4}$ inches.
Weight.....approximately $\frac{5}{8}$ pound.

RELATIONSHIP OF PARTS: Used with:

Fixed .30 and .50 caliber M2 machine guns, A. E. Reference Numbers, 93-1420 and 93-1560, or with Army M2 manual charger, A. E. Reference Number 52-2275 mounted on M1 or AN-M2 20-mm automatic guns.

ARMY

A. E. REFERENCE NUMBER: 52-2750

SPECIFICATIONS:

Detail.....93-24663

MANUFACTURER: General Aviation Equipment Company.

A. A. F. DRAWING NUMBER: 31B1:84 (Supersedes Army drawing 02-A-28)

TYPE DESIGNATION: A-2

A. S. C. STOCK NUMBER: 5200315800

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: Mark 1, Modification 1

BU. ORD. DRAWING NUMBER: 178489


AVIATION ORDNANCE STOCK LIST NUMBER: 1-H-475

ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Under procurement.

BRITISH

REFERENCE NUMBER: 108A 160



HOLDER—AMMUNITION BOX

ARMY TYPE A-1

NAMES: Ammunition box holder
.30 caliber ammunition box holder

DESCRIPTION: The Army type A-1 ammunition box holder is fastened to the gun mount adapter, and is used to hold an ammunition box for a .30 caliber gun. This holder consists of a perforated metal retainer with a horizontal metal strip which secures the ammunition box when it is inserted. The holder is constructed so that empty ammunition boxes may be removed and replaced with full boxes.

CHARACTERISTICS:

Dimensions. approximately $7\frac{1}{4}$ by $5\frac{1}{2}$ by 5 inches.
Weight. approximately 1-1/10 pounds.

RELATIONSHIP OF PARTS: Used with:

Army type L-4 ammunition box, A. E. Reference Number 52-1500 and Army type L-7 ammunition box, A. E. Reference Number 52-1550.

ARMY

A. E. REFERENCE NUMBER: 52-2800

SPECIFICATIONS:

Detail. 93-24660
Superseded. 24660

MANUFACTURER: Warner Industries.

A. A. F. DRAWING NUMBER: 40G7402

TYPE DESIGNATION: A-1

A. S. C. STOCK NUMBER: 5200328900

PRODUCTION STATUS: Not under procurement for initial installation.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 150J/577



HOLDER—PYROTECHNIC PISTOL
ARMY TYPE A-1

NAMES: Pyrotechnic pistol holder
Pistol holder

DESCRIPTION: The Army type A-1 pyrotechnic pistol holder, constructed of canvas duck, is used for carrying the Army type M2 pyrotechnic pistol. It has a zipper opening for the pistol, and four snap fasteners for attachment to a signal flare container.

CHARACTERISTICS:

Dimensions approximately 8 $\frac{1}{4}$ by 7 by 2 $\frac{1}{4}$ inches.
Weight approximately $\frac{1}{4}$ pound.

RELATIONSHIP OF PARTS: Used with:

Army type A-1 signal flare container, A. E. Reference Number 52-2250 and M2 pyrotechnic pistol,
A. E. Reference Number 93-6000.

ARMY

A. E. REFERENCE NUMBER: 52-2825

SPECIFICATIONS:

Detail 93-24718
Superseded 24718

MANUFACTURER: Lite Manufacturing Company.

A. A. F. DRAWING NUMBER: 41G8920 (Supersedes drawing H41D10378).

TYPE DESIGNATION: A-1


A. S. C. STOCK NUMBER: 4500494500

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

**HOLDER—PYROTECHNIC PISTOL****ARMY TYPE A-2**

NAMES: Pyrotechnic pistol holder
Pistol holder

DESCRIPTION: The Army type A-2 pyrotechnic pistol holder, constructed of canvas duck, is used for carrying the Army type M8 pyrotechnic pistol. It is attached to a signal flare container by means of canvas straps and snap fasteners.

CHARACTERISTICS:

Dimensions.....approximately 11 ¹/₈ by 3 by 2 inches.
Weight.....approximately ¹/₈ pound.

RELATIONSHIP OF PARTS: Used with:

Army type A-5, signal flare container, A. E. Reference Number 52-2254, Army type A-6 signal flare container, A. E. Reference Number 52-2255 or Army type A-7 signal flare container, A. E. Reference Number 52-2256, and AN-M8 pyrotechnic pistol, A. E. Reference Number 93-6100.

**ARMY**

A. E. REFERENCE NUMBER: 52-2826

SPECIFICATIONS:

Detail.....93-24820
Superseded.....24820

A. A. F. DRAWING NUMBER: 43G7044

TYPE DESIGNATION: A-2

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4
A-Army, N-Navy, B-British


Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number
Lite Manufacturing Company	*A-2	**43G7044	A	4500494600	11-15-8
Crawford Manufacturing Company	*A-2	**43G7044	A	4500494600	11-15-8
Troy Sunshade Company	*A-2	**43G7044	A	4500494600	11-15-8

Note: *AAF type; **AAF drawing.



MOTOR — GENERATOR AMPLIDYNE LOCAL CONTROL GENERAL ELECTRIC MODEL 5AM31NJ18

NAMES: Amplidyne local control motor generator
Amplidyne Motor generator



DESCRIPTION: This type of amplidyne motor-generator, used to supply current for the operation of locally-controlled machine gun turrets, consists essentially of a direct current electric motor and a direct current output generator mounted on the same shaft. In spite of the fact that the motor operates constantly to turn the shaft, there is no output from the generator unless the generator field is excited. This field requires but a small current to produce full generator output voltage. Minute variation in the field current instantaneously produces large variations in the generator's output. This field current is controlled by two variable resistors in the turret control handles. The further the handles are moved from the center position by the gunner, the greater is the output from the amplidyne generator and the faster the turret motors move the turret and gun carriage.

Two amplidyne motor generators and two turret drive motors are required for each turret; one of each for movement of the guns in elevation and depression, the others for rotation of the turret.

CHARACTERISTICS:

Dimensions.....approximately 12 by 8½ by 6½ inches
Weight.....approximately 29 pounds
Revolutions per minute.....8300

Motor input:
Volts.....27
Amperes.....44
Generator output:
Volts.....60
Amperes.....8.8
Watts.....530

RELATIONSHIP OF PARTS: Used in:

Turrets	A. E. Reference Number
Army type A-8	52-7400
Army type A-3A	52-7425
Army type A-3B	52-7460
Army type A-3C	52-7472
Army type A-15	52-7790
Army type A-16	52-7350
Army type A-9	52-7900
Army type A-9A	52-7910
Army type A-10	52-7950

Turret Drive Motor	A. E. Reference Number
G. E. model 5BA50LJ1	52-3060
G. E. model 5BA50GJ1	52-3070

ARMY


A. E. REFERENCE NUMBER: 52-3030
A. S. C. STOCK NUMBER: Refer to chart.
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Manufacturer's Specification	British Reference Number
General Electric Company	5AM31NJ18	P-8111282 outline TT-5818190 assembly	A	5400009212	OST-1B	150B/1506
Thomas A. Edison, Incorporated	5AM31NJ18	P-8111282 outline TT-5818190 assembly	A	5400009212	OST-1B	150B/1506
Emerson Electric Manufacturing Company	5AM31NJ18	P-8111282 outline TT-5818190 assembly	A	5400009212	OST-1B	150B/1506



MOTOR—AZIMUTH TURRET DRIVE

GENERAL ELECTRIC COMPANY MODEL 5BA50LJ1

NAMES: Azimuth turret drive motor
Drive motor
Turret drive motor

DESCRIPTION: This $\frac{1}{4}$ horsepower azimuth turret drive motor is used to horizontally rotate a gun turret. It is of the four-pole two-brush type, with a separately excited field. The motor is bolted to the turret in a vertical position, so that the armature shaft is down. This shaft carries the drive pinion of a 500 to 1 reduction gear train. The motor is equipped with sealed type ball bearings containing enough low temperature lubricant to last throughout its normal operational life. One amplidyne motor-generator is required to furnish power for operation of each drive motor.

CHARACTERISTICS:

Dimensions	approximately $9\frac{5}{16}$ by $5\frac{3}{8}$ by $4\frac{1}{4}$ inches
Weight	approximately 8 pounds
Type	$\frac{1}{4}$ horsepower direct current
Full load revolutions per minute	3000
Field current	2.3 amperes
Field voltage	24 volts
Field resistance	9.4 ohms

RELATIONSHIP OF PARTS: Used with:

Amplidyne motor-generator G. E. model 5AM31NJ18, A. E. Reference Number 52-3030 in the following turrets: Army type A-3, A. E. Reference Number 52-7400; Army type A-3A, A. E. Reference Number 52-7425; Army type A-3B, A. E. Reference Number 52-7450; Army type A-3C, A. E. Reference Number, 52-7475; Army type A-15, A. E. Reference Number 52-7790; Army type A-9, A. E. Reference Number 52-7900; Army type A-9A, A. E. Reference Number 52-7910; Army type A-10, A. E. Reference Number 52-7950 and Army type A-11, A. E. Reference Number 52-8000.

ARMY

A. E. REFERENCE NUMBER: 52-3060

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.


SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Manufacturer's Specification Number	British Reference Number
General Electric Company	5BA50LJ1	TT-5818151	A	5400465615	OST-18	150B/1019
Emerson Electric Manufacturing Company	5BA50LJ1	TT-5818151	A	5400465615	OST-18	150B/1019
American Generator and Armature Company	5BA50LJ1	TT-5818151	A	5400465615	OST-18	150B/1019



MOTOR—ELEVATION TURRET DRIVE

GENERAL ELECTRIC COMPANY MODEL 5BA50GJ1

NAMES: Elevation turret drive motor
Drive motor

Turret drive motor

DESCRIPTION: This $\frac{1}{2}$ horsepower elevation turret drive motor is used to elevate and depress a two-gun turret gun carriage. It is of the four-pole, two-brush type, with a separately excited field. The motor is bolted to the turret in a vertical position, so that the armature shaft is up. This shaft carries the drive pinion of an 800 to 1 reduction gear train. The motor is equipped with sealed type ball bearings containing enough low temperature lubricant to last throughout normal operational life. One amplidyne motor-generator is required to furnish power for the operation of each drive motor.

CHARACTERISTICS:

Dimensions	approximately $8\frac{3}{4}$ by $5 \times 4\frac{1}{4}$ inches
Weight	approximately 7 pounds
Type	$\frac{1}{2}$ horsepower direct current
Full load revolutions per minute	3000
Field current	1.8 amperes
Field voltage	24 volts
Field resistance	11.6 ohms

RELATIONSHIP OF PARTS: Used with:

Amplidyne motor-generator, G. E. model 5AM31NJ18, A. E. Reference Number 52-3030 in the following turrets: Army type A-3, A. E. Reference Number 52-7400; Army type A-3A, A. E. Reference Number 52-7425; Army type A-3B, A. E. Reference Number 52-7450; Army type A-3C, A. E. Reference Number 52-7475; Army type A-15, A. E. Reference Number 52-7790; Army type A-9, A. E. Reference Number 52-7900; Army type A-9A, A. E. Reference Number 52-7910; Army type A-10, A. E. Reference Number 52-7950 and Army type A-11, A. E. Reference Number 52-8000.

ARMY

A. E. REFERENCE NUMBER: 52-3070

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY


There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Manufacturer's Specification Number	British Reference Number
General Electric Company	5BA50GJ1	TT-5818150	A	5400465630	OST-18	150B, 1027
Emerson Electric Manufacturing Company	5BA50GJ1	TT-5818150	A	5400465630	OST-18	150B, 1027



MOUNT-AMMUNITION BOX

ARMY TYPE A-3

NAMES: Ammunition box mount

DESCRIPTION: The Army type A-3 ammunition box mount is used for attaching a type A-1 ammunition box holder to a .30 caliber M2 machine gun. The mount is a welded metal bracket that is held to the gun by the belt retaining pawl pin and the gun trunnion bolt.

CHARACTERISTICS:

Dimensions approximately 7 $\frac{1}{8}$ by 3 by $\frac{7}{8}$ inches.
Weight approximately 1 $\frac{1}{2}$ pounds.

RELATIONSHIP OF PARTS: Used with:

Army type A-1 ammunition box holder, A. E. Reference Number 52-2800 and .30 caliber M2 machine guns, A. E. Reference Numbers 93-1440 or 93-1520.

ARMY

A. E. REFERENCE NUMBER. 52-3100

SPECIFICATIONS:

Detail 93-24661
Superseded 24661

A. A. F. DRAWING NUMBER: 40D5858

TYPE DESIGNATION: A-3

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
St. Louis Aircraft Corporation	*A-3	**40D5858	A-B	5200466980	150J 584	
Dahlstrom Metallic Door Company	*A-3	**40D5858	A-B	5200466980	150J 584	

Note: *AAF type; **AAF drawing.



MOUNT—LEFT HAND AMMUNITION BOX ARMY TYPE C-2

NAMES: Left hand ammunition box mount
.50 caliber flexible gun ammunition box mount
Ammunition box mount

DESCRIPTION: The Army type C-2 left hand ammunition box mount is used to secure a type O-1 ammunition box, or boxes of similar design, to the left side of a .50 caliber M2 machine gun. The mount is a machined metal plate with a pair of lugs which are attached to the gun by the belt retaining pawl pin. The ammunition box is slid on the plate and spring-loaded plungers, located on the mounting bracket, prevent the box from becoming dislodged by vibration.

CHARACTERISTICS:

Dimensions approximately 5 $\frac{11}{32}$ by 1 by 1 inches.
Weight approximately 6 $\frac{1}{2}$ ounces.

RELATIONSHIP OF PARTS: Used with:

Army type O-1 ammunition box, A. E. Reference Number 52-1600 and .50 caliber M2 machine guns, A. E. Reference Numbers 93-1560 and 93-1590.

ARMY

A. E. REFERENCE NUMBER: 52-3200

SPECIFICATIONS:

Detail 93-24640A
Superseded 93-24640

A. A. F. DRAWING NUMBER: 37B2675

TYPE DESIGNATION: C-2

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type C-3 mount, A. E. Reference Number 52-3350.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Ar Service Command Stock Number	British Reference Number
Dayton Tool & Engineering Company	"C-2	**37B2675	A-B	5200467000	150J 576
	"C-3	**39B3905-1	A-B	5200467350	150J 702

Note: "AAF type; **AAF drawing.



MOUNT—RIGHT HAND AMMUNITION BOX ARMY TYPE C-2

NAMES: Right hand ammunition box mount
.50 caliber flexible gun ammunition box mount
Ammunition box mount

DESCRIPTION: The Army type C-2 right hand ammunition box mount is used to secure a type O-1 ammunition box, or boxes of similar design, to the right side of a .50 caliber M2 machine gun. The mount is a machined metal plate with a pair of lugs which are attached to the gun by the belt retaining pawl pin. The ammunition box is slid on the plate and spring-loaded plungers, located on the mounting bracket, preventing the box from becoming dislodged due to vibration.

CHARACTERISTICS:

Dimensions.....approximately 5 $\frac{11}{32}$ by 1 by 1 inches.
Weight.....approximately 6 $\frac{1}{2}$ ounces.

RELATIONSHIP OF PARTS: Used with:

Army type O-1 ammunition box, A. E. Reference Number 52-1600 and .50 caliber M2 machine guns,
A. E. Reference Numbers 93-1560 and 93-1590.

ARMY

A. E. REFERENCE NUMBER: 52-3300

SPECIFICATIONS:

Detail.....93-24640A
Superseded.....93-24640

A. A. F. DRAWING NUMBER: 37B2675

A. A. F. PART NUMBER: 37B2675-1

TYPE DESIGNATION: C-2

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type C-3 mount, A. E. Reference Number 52-3350.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Dayton Tool & Engineering Company	*C-2	**37B2675-1	A-B	5200467050	1501/585
	*C-3	**39B3905-R	A-B	5200467360	1501/703

Note: *AAF type; **AAF drawing.



MOUNT—LEFT HAND AMMUNITION BOX ARMY TYPE C-3

NAMES: Left hand ammunition box mount
.50 caliber flexible gun ammunition box mount
Ammunition box mount

DESCRIPTION: The Army type C-3 left hand ammunition box mount is used to secure a type O-1 ammunition box, or boxes of similar design, to the left side of a .50 caliber M2 machine gun. The mount is a machined metal plate with a pair of lugs which are attached to the gun by the belt retaining pawl pin. The ammunition box is slid on the plate and spring-loaded plungers, located on the mounting bracket, prevent the box from becoming dislodged due to vibration. This mount is similar to the Army type C-2, except that the bracket position is located $\frac{5}{16}$ inch further out from the side of the gun. This increased dimension permits the use of the type O-1 ammunition box with Army types E-8 and E-12 gun mount adapters.

CHARACTERISTICS:

Dimensions..... approximately $5\frac{11}{32}$ by $1\frac{3}{8}$ by 1 inches.
Weight..... approximately $6\frac{1}{2}$ ounces.

RELATIONSHIP OF PARTS: Used with:

Army type O-1 ammunition box, A. E. Reference Number 52-1600 on .50 caliber M2 machine guns,
A. E. Reference Numbers 93-1560 and 93-1590.

ARMY

A. E. REFERENCE NUMBER: 52-3350

SPECIFICATIONS:

Detail..... 93-24690A
Superseded..... 93-24690

A. A. F. DRAWING NUMBER: 39B3905

TYPE DESIGNATION: C-3

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Dayton Tool and Engineering Company	*C-3	**39B3905-L	A-B	5200467350	150J 702	
	*C-2	**37B2675	A-B	5200467000	150J 576	Cannot be used with Army types E-8 and E-12 gun mount adapters.

Note: *AAF type; **AAF drawing.



MOUNT—RIGHT HAND AMMUNITION BOX ARMY TYPE C-3

NAMES: Right hand ammunition box mount
.50 caliber flexible gun ammunition box mount
Ammunition box mount

DESCRIPTION: The Army type C-3 ammunition box mount is used to secure a type O-1 ammunition box, or boxes of similar design, to the right side of a .50 caliber M2 machine gun. The mount is a machined metal plate with a pair of lugs which attach to the gun by the belt retaining pawl pin. The ammunition box is slid on the plate and spring-loaded plungers, located on the mounting bracket, prevent the box from becoming dislodged due to vibration. This mount is similar to the Army type C-2, except that the bracket position is located $\frac{3}{8}$ inch further out from the side of the gun. This increased dimension permits the use of the type O-1 ammunition box with Army types E-8 and E-12 gun mount adapters.

CHARACTERISTICS:

Dimensions approximately $5\frac{11}{32}$ by $1\frac{1}{8}$ by 1 inches.
Weight approximately $6\frac{1}{2}$ ounces.

RELATIONSHIP OF PARTS: Used with:

Army type O-1 ammunition box, A. E. Reference Number 52-1600 on .50 caliber M2 machine guns,
A. E. Reference Numbers 93-1560 and 93-1590.

ARMY

A. E. REFERENCE NUMBER: 52-3360

SPECIFICATIONS:

Detail 93-24690A
Superseded 93-24690

A. A. F. DRAWING NUMBER: 39B3905

TYPE DESIGNATION: C-3

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Dayton Tool and Engineering Company	*C-3	**39B3905-R	A-B	5200467360	150J 703	
	*C-2	**37B2675-1	A-B	5200467050	150J 585	Cannot be used with Army type E-8 and E-12 gun mount adapters.

Note: *AAF type; **AAF drawing.



MOUNT—FLEXIBLE GUN SIGHT

ARMY TYPE C-4

NAMES: Flexible gun sight mount
Telescopic sight mount

DESCRIPTION: The Army type C-4 flexible gun sight mount is used to attach types E-4 and E-5 telescopic sights to Army types E-5 and E-8 gun mount adapters. It consists of two ring clamps which hold the sight, a vernier for aligning the sight to the gun, and a baseplate bracket for bolting the entire mount to the adapter.

CHARACTERISTICS:

Dimensions.....	approximately 6 $\frac{7}{16}$ by 3 $\frac{1}{2}$ by 2 $\frac{1}{2}$ inches.
Weight.....	approximately 1 pound 2 ounces.

RELATIONSHIP OF PARTS: Used with:

Army type E-4 or E-5 telescopic sights, A. E. Reference Numbers 52-5300 and 52-5350, on Army type E-5 or E-8 adapters, A. E. Reference Numbers 52-875 and 52-1100.

ARMY

A. E. REFERENCE NUMBER: 52-3400

SPECIFICATIONS:

Detail.....	93-24669
Superseded.....	24669

MANUFACTURER: American Thermometer Company.

A. A. F. DRAWING NUMBER: 40D6090

TYPE DESIGNATION: C-4

A. S. C. STOCK NUMBER: 5200471000

PRODUCTION STATUS: Not under procurement for initial installation.


SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 108B/80



MOUNT—GUN

ARMY TYPE G-1A

NAMES: Gun mount
Flexible gun mount

DESCRIPTION: The Army type G-1A gun mount provides means for moving a .30 caliber M2 machine gun along a stationary track or rail conforming to the shape of a fuselage opening. The mount consists of a steel housing surrounding a movable truck which engages the rail, a brake mechanism, and a socket with a locking device to hold and lock the gun in the desired position. It also aids in stowing the gun horizontally, when not in use.

CHARACTERISTICS:

Dimensions approximately 7 by 11 by 4½ inches
Weight approximately 8 pounds 6 ounces

RELATIONSHIP OF PARTS: Used with:

A single .30 caliber M2 machine gun mounted on an
Army type C-16 gun mount adapter A. E. Reference Number 52-600

ARMY

A. E. REFERENCE NUMBER: 52-3500

SPECIFICATIONS:

Detail 93-24561A
Superseded 93-24561

A. A. F. DRAWING NUMBER: 37G6581 (Supersedes Army Drawing Number H39G5346)

TYPE DESIGNATION: G-1A

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type G-5 mount, A. E. Reference Number 52-3600.

SHIPPING DATA: Shipped as a complete unit without rail which is not furnished by the government.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
The Duro Company	*G-1A	**37G6581	A-B	5200473300		150J 48	
	*G-5	**41G10752	A-B	5200473325	11-10-13	150J 574	Aluminum housing.

Note: *AAF type; **AAF drawing.



MOUNT—GUN

ARMY TYPE G-5

NAMES: Gun mount
Flexible gun mount

DESCRIPTION: The Army type G-5 gun mount provides means for moving a .30 caliber M2 machine gun along a stationary track or rail, conforming to the shape of a fuselage opening. The mount consists of an aluminum housing surrounding a movable truck which engages the rail, a brake mechanism, and a socket with a locking device to hold and lock the gun in the desired position. It also aids in stowing the gun horizontally, when not in use.

CHARACTERISTICS:

Dimensions approximately 7½ by 11½ by 4½ inches
Weight approximately 8 pounds 6 ounces

RELATIONSHIP OF PARTS: Used with:

A single .30 caliber M2 machine gun mounted on an
Army type C-16 gun mount adapter A. E. Reference Number 52-600

ARMY

A. E. REFERENCE NUMBER: 52-3600

SPECIFICATIONS:

Detail 93-24719
Superseded 24719

A. A. F. DRAWING NUMBER: 41G10752

TYPE DESIGNATION: G-5

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, without rail which is not furnished by the government.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
The Duro Company	*G-5	**41G10752	A-B	5200473325	11-10-13	150J 574	
	*G-1A	**37G6581	A-B	5200473300		150J 48	Steel housing

Note: *AAF type; **AAF drawing.



MOUNT—GUN

ARMY TYPE H-1

NAMES: Gun mount
Flexible gun mount

DESCRIPTION: The Army type H-1 gun mount provides means for moving one .50 caliber M2 machine gun or twin, .30 caliber M2 machine guns along a stationary track or rail conforming to the shape of a fuselage opening. The mount consists of a steel housing surrounding a movable truck which engages the rail, a brake mechanism, and a socket with a locking device to hold and lock the gun, or guns, in the desired position.

CHARACTERISTICS:

Dimensions.....approximately 11 by 7 by 4½ inches
Weight.....approximately 16 pounds 8 ounces

RELATIONSHIP OF PARTS: Used with:

A single .50 caliber M2 machine gun mounted on an Army type E-11 or E-12 adapter, A. E. Reference Number 52-1300 or 52-1325; or two .30 caliber M2 machine guns mounted on a Bell model 19-G gun mount adapter, A. E. Reference Number 52-400.

ARMY

A. E. REFERENCE NUMBER: 52-3700

SPECIFICATIONS:

Detail.....93-24698
Superseded.....24698

A. A. F. DRAWING NUMBER: 41G6410 (Supersedes Army Drawing S41D6785).

TYPE DESIGNATION: H-1

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, without rail which is not furnished by the government.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
The Dura Company	*H-1	**41G6410	A-B	5200473335	150J 50
Aerial Machine and Tool Company	*H-1	**41G6410	A-B	5200473335	150J 50

Note: *AAF type; **AAF drawing.



MOUNTS ARMAMENT—GUNNERY

MOUNT ASSEMBLY— BALL AND SOCKET GUN ARMY TYPE K-1

NAMES: Ball and socket gun mount assembly
Ball and socket mount
Gun mount

DESCRIPTION: The Army type K-1 ball and socket gun mount consisting of a type K-2 ball and a type C-17 adapter, accommodates a single .30 caliber M2 machine gun. The adapter is fastened to the front trunnion of the gun and clips to the rear of the ball. The socket halves, which surround the ball, attach to both sides of a plexiglass enclosure or window, where they are held by two retaining flanges. A removable sleeve in the ball may be withdrawn to permit use of a gun camera in this mount.

CHARACTERISTICS:

Dimensions approximately 5 $\frac{3}{4}$ by 5 $\frac{3}{4}$ by 7 $\frac{1}{2}$ inches.

Weight approximately 4 $\frac{1}{4}$ pounds.

RELATIONSHIP OF PARTS: Used with:

A .30 caliber M2 flexible machine gun, A. E. Reference Number 93-1520.

ARMY

A. E. REFERENCE NUMBER 52-3800

SPECIFICATIONS:

Detail 93-24655

Superseded 24655

A. A. F. DRAWING NUMBER: 40G6567

TYPE DESIGNATION K-1

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type K-8 ball and socket gun mount, A. E. Reference Number 52-3950.

SHIPPING DATA: Shipped as a complete unit.


NAVY

There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Moore-Eastwood and Company	*K-1	**40G6567	A-B	5200473350	150J 18	
	*K-2	**41B5641	A-B	5200473370	150J 27	Ball mount only. Requires adapter.
Iron Fireman Manufacturing Company	*K-1	**40G6567	A-B	5200473350	150J 18	
	*K-2	**41B5641	A-B	5200473370	150J 27	Ball mount only. Requires adapter.
	*K-2A	**41B10360	A-B	5200473380	150J 19	Ball mount only. Requires adapter. Non-removable sleeve.
Anetsberger Brothers Incorporated	*K-2A	**41B10360	A-B	5200473380	150J 19	Ball mount only. Requires adapter. Non-removable sleeve.
Ainsworth Manufacturing Company	*K-3	AG-150	A-B	5200473385	150J 51	Ball mount only. Requires adapter. Non-removable sleeve.

Note: *AAF type; **AAF drawing.

**MOUNT — BALL AND SOCKET GUN****ARMY TYPE K-2**

NAMES: Ball and socket gun mount
Ball and socket mount
Gun mount

DESCRIPTION: The Army type K-2 ball and socket gun mount, used with a single .30 caliber M2 machine gun, is a subassembly of the K-1 mount and is procured as such.

A sleeve inside the ball fits over the air jacket of the gun and is locked in place by set screws.

The sleeve is removable, to permit use of a gun camera in this mount. Six bolts mount this unit through a plexiglass panel, either in the nose or waist of the airplane.

CHARACTERISTICS:

Dimensions of socket approximately 5 3/4 inches in diameter.

Dimensions of ball approximately 4 by 4 by 5 inches.

Weight approximately 4 1/4 pounds.

RELATIONSHIP OF PARTS: Used with:

Army type C-17 gun mount adapter, A. E. Reference Number 52-700 to form the type K-1 gun mount which is used on .30 caliber M2 machine guns, A. E. Reference Number 93-1520.

ARMY

A. E. REFERENCE NUMBER: 52-3850

SPECIFICATIONS:

Detail 93-24697

Superseded 24697

A. A. F. DRAWING NUMBER: 41B5641 (Supersedes Army Drawing Number 40G6567).

TYPE DESIGNATION: K-2

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type K-3 gun mount adapter, A. E. Reference Number 52-3950.

SHIPPING DATA: Shipped as a sub-assembly of Army type K-1, A. E. Reference Number 52-3800.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Moore-Eastwood and Company	*K-2	**41B5641	A-B	5200473370	150J 27	
	*K-1	**40G6567	A-B	5200473350	150J 18	Includes Army type C-17 gun mount adapter.
Iron Fireman Manufacturing Company	*K-2	**41B5641	A-B	5200473370	150J 27	
	*K-1	**40G6567	A-B	5200473350	150J 18	Includes Army type C-17 gun mount adapter.
	*K-2A	**41B10360	A-B	5200473380	150J 19	Non-removable sleeve.
Ainsworth Manufacturing Company	*K-3	AG-150	A-B	5200473385	150J 51	Non-removable sleeve.
Anetsberger Brothers, Incorporated	*K-2A	**41B10360	A-B	5200473380	150J 19	Non-removable sleeve.

Note: *AAF type, **AAF drawing.



MOUNT—BALL AND SOCKET GUN

ARMY TYPE K-2A

NAMES: Ball and socket gun mount
Ball and socket mount

DESCRIPTION: The Army type K-2A ball and socket gun mount is used with a single .30 caliber M2 machine gun. This mount is a complete assembly, cast in one hollow piece with an integral sleeve. Nine bolts mount this unit through a plexiglass panel, either in the nose or waist of an airplane. A spring cap fits over the end of the ball exposed to the slipstream.

CHARACTERISTICS:

Dimensions of socket	approximately 5 ³ / ₄ inches in diameter.
Dimensions of ball	approximately 4 by 4 by 5 inches.
Weight	approximately 4 ¹ / ₂ pounds.

RELATIONSHIP OF PARTS: Used with:

Army type C-17 gun mount adapter, A. E. Reference Number 52-700, or Army type C-18 gun mount adapter and .30 caliber M2 machine gun, A. E. Reference Number 93-1520.

ARMY

A. E. REFERENCE NUMBER: 52-3900

SPECIFICATIONS:

Detail	93-24697
Superseded	24697

A. A. F. DRAWING NUMBER: 41B10360

TYPE DESIGNATION: K-2A

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by the Army type K-3 mount, A. E. Reference Number 52-3950.

SHIPPING DATA: Shipped as a complete unit.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Anetsberger Brothers, Incorporated	*K-2A	**41B10360	A-B	5200473380	150J 19	
Iron Fireman Manufacturing Company	*K-2A	**41B10360	A-B	5200473380	150J 19	
	*K-2	**41B5641	A-B	5200473370	150J 27	
	*K-1	**40G6567	A-B	5200473350	150J 18	Includes Army type C-17 gun mount adapter.
Moore-Eastwood and Company	*K-2	**41B5641	A-B	5200473370	150J 27	
	*K-1	**40G6567	A-B	5200473350	150J 18	Includes Army type C-17 gun mount adapter.
Ainsworth Manufacturing Company	*K-3	AG-150	A-B	5200473385	150J 51	

Note: *AAF type; **AAF drawing.



MOUNT—BALL AND SOCKET GUN ARMY TYPE K-3

NAMES: Ball and socket gun mount
Ball and socket mount

DESCRIPTION: The Army type K-3 ball and socket gun mount is used with a single .30 caliber M2 machine gun. It is composed of ball halves, stamped out and tightly butt-jointed, with a non-removable sleeve extending the entire length of the ball. Six bolts mount this unit through the plexiglass in either the nose or waist of an airplane. A spring cap fits over the end of the ball exposed to the slipstream.

CHARACTERISTICS:

Dimensions of socket.....	approximately 5 ⁷ / ₈ inches in diameter.
Dimensions of ball.....	approximately 4 ¹ / ₈ by 4 ¹ / ₈ by 5 ³ / ₈ inches.
Weight.....	approximately 4 ¹ / ₂ pounds.

RELATIONSHIP OF PARTS: Used with:

Army type C-17 or C-18 gun mount adapters, A. E. Reference Numbers 52-700 and 52-800, and .30 caliber M2 machine gun, A. E. Reference Number 93-1520.

ARMY

A. E. REFERENCE NUMBER: 52-3950

SPECIFICATIONS:

Detail.....	93-24780
Superseded.....	24780

A. A. F. DRAWING NUMBER: 42B12323

TYPE DESIGNATION: K-3

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Ainsworth Manufacturing Company	*K-3	AG-150	A-B	5200473385	150J 51	
Anshberger Brothers, Incorporated	*K-2A	**41B10360	A-B	5200473380	150J 19	
Iron Fireman Manufacturing Company	*K-2A	**41B10360	A-B	5200473380	150J 19	
	*K-2	**41B5641	A-B	5200473370	150J 27	
	*K-1	**40G6567	A-B	5200473350	150J 18	Includes Army type C-17 gun mount adapter.
Moore-Eastwood and Company	*K-2	**41B5641	A-B	5200473370	150J 27	
	*K-1	**40G6567	A-B	5200473350	150J 18	Includes Army type C-17 gun mount adapter.

Note: *AAF type; **AAF drawing.



MOUNT—BALL AND SOCKET GUN

ARMY TYPE K-4

NAMES: Ball and socket gun mount
Ball and socket mount

DESCRIPTION: The Army type K-4 ball and socket gun mount is used with a single .50 caliber M2 machine gun. The ball halves are stamped out and tightly butt-jointed, with a non-removable sleeve extending the entire length of the ball. Six bolts mount this unit to a spider through a plexiglas panel in either the nose or waist of an airplane.

CHARACTERISTICS:

Dimensions of socket	approximately 5 ¹ / ₈ inches in diameter
Dimensions of ball	approximately 4 ¹ / ₈ by 4 ¹ / ₈ by 5 ¹ / ₈ inches
Weight	approximately 3 ¹ / ₂ pounds

RELATIONSHIP OF PARTS: Used with:

A .50 caliber M2 machine gun, A. E. Reference Number 93-1560 with Army type C-19 gun mount adapter, A. E. Reference Number 52-850; and Army type E-11 gun mount adapter, A. E. Reference Number 52-1300.

ARMY

A. E. REFERENCE NUMBER: 52-3960

SPECIFICATIONS:

Detail	93-24814
Superseded	24814

MANUFACTURER: Ainsworth Manufacturing Company

MANUFACTURER'S DRAWING NUMBER: AG-360

A. A. F. DRAWING NUMBER: 42B19084

TYPE DESIGNATION: K-4

A. S. C. STOCK NUMBER: 5200468540

PRODUCTION STATUS: Under procurement.


SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 150J/52



MOUNT—SWIVEL GUN

ARMY TYPE K-5

NAMES: Swivel gun mount
Ball and socket mount
Ball and socket gun mount

DESCRIPTION: The Army type K-5 swivel gun mount is used with a single .50 caliber M2 machine gun. The mount comprises a universal joint in the form of a welded stamping, consisting of two cylinders, one rotating within the other. Their axis of rotation are at right angles to each other. A tube, which fits around the gun barrel, extends through the inner cylinder, and carries the necessary parts for attaching the mount to the gun.

CHARACTERISTICS:

Dimensions	approximately 15½ by 6 by 4¾ inches.
Weight	approximately 5 pounds.

RELATIONSHIP OF PARTS: Used with:

A .50 caliber M2 machine gun, A. E. Reference Number 93-1560, and Army type E-11 gun mount adapter, A. E. Reference Number 52-1300.

ARMY

A. E. REFERENCE NUMBER: 52-3965

SPECIFICATIONS:

Detail	24838
------------------	-------

MANUFACTURER: Ainsworth Manufacturing Co.

MANUFACTURER'S DRAWING NUMBER: AG-800

A. A. F. DRAWING NUMBER: 43G10872

TYPE DESIGNATION: K-5

A. S. C. STOCK NUMBER: 5200473200

PRODUCTION STATUS: Under procurement.


SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 150J 53

**MOUNT—GUN****ARMY TYPE M-1**

NAMES: Gun mount
 Hydraulic gun mount
 Hydraulic swivel gun mount
 United Shoe gun mount

DESCRIPTION: The Army type M-1 gun mount accommodates remotely-controlled twin .50 caliber M2 machine guns in the tail of an airplane. It consists of a separate hydraulic unit, an N-6 flexible gun sight and camera bracket, a mount to support the guns, and a tracking device to establish rate control. The quantity of oil supplied from the hydraulic unit to the pistons and cylinders is controlled by metering valves. The gunner, situated behind armor plate, operates control handles that regulate these valves and cause the guns to move. The system can be manually operated in case of power failure by opening a dump valve and releasing trapped oil. The sight, located approximately 17 inches above the mount, is coordinated with the guns by means of mechanical linkage.

Continued on page 1004



MOUNT—GUN

(Continued from page 68)

CHARACTERISTICS:

Dimensions	approximately 45 by 24 by 19 inches
Weight	approximately 145 pounds
Cone of fire	60 degrees
Speed in any direction	30 degrees per second
Electric motor:	
Horsepower	3 5
Voltage	24 volts direct current
Revolutions per minute	1000

RELATIONSHIP OF PARTS: Used with:

Army type N-6 flexible gun sight, A. E. Reference Number 52-4500, and twin .50 caliber M2 machine guns, A. E. Reference Number 93-1560.

ARMY

A. E. REFERENCE NUMBER: 52-3975
 MANUFACTURER: United Shoe Machinery Corp.
 MANUFACTURER'S DRAWING NUMBERS: V1-17; V1-152, and V1-153
 TYPE DESIGNATION: M-1
 A. S. C. STOCK NUMBER: 5200473500
 PRODUCTION STATUS: Under procurement.
 SHIPPING DATA: Shipped unassembled in three units.

NAVY



There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 150J 54



MOUNTS ARMAMENT—GUNNERY



MOUNT—GUN ARMY TYPE M-6

NAMES: Gun mount

Bell turret

Hydraulic gun mount

Hydraulic swivel gun mount

(Continued on page 71)



MOUNT—GUN

Continued from page 700

DESCRIPTION: The Army type M-6 gun mount accommodates remotely-controlled twin .50 caliber M2 machine guns in the tail of an airplane. It consists of an hydraulic unit, a bracket for an Army type N-8 gun sight, a mount to support the guns, and an ammunition feed adapter. The mount is hydraulically-operated and is controlled by two variable displacement pumps. These pumps provide pressure for operation of the quadrant or vane type hydraulic motors; one controls movement in elevation, the other, in rotation. By varying the displacement of the proper pump, the position of the mount is changed. The sight is coordinated with the guns by means of linkage and is located approximately 17 $\frac{1}{2}$ inches above the mount. The gunner operates the control handles, which are mounted above the hydraulic unit, from behind armor plate.

CHARACTERISTICS:

Dimensions	approximately 27 $\frac{1}{2}$ by 28 $\frac{1}{2}$ by 27 inches.
Weight	approximately 125 pounds.
Cone of fire	90 degrees.
Speed in any direction	35 degrees per second.
Electric Motor:	
Horsepower	
Voltage	24 volts direct current
Revolutions per minute	6000

RELATIONSHIP OF PARTS: Used with:

Army type N-8 flexible gun sight, A. E. Reference Number 52-4550 and twin .50 caliber M2 machine guns, A. E. Reference Number 93-1560. Early models of this mount were equipped with Navy Mark 9 illuminated sight, A. E. Reference Number 52-5375.

ARMY


A. E. REFERENCE NUMBER: 52-3980
 MANUFACTURER: Bell Aircraft Corp.
 MANUFACTURER'S SPECIFICATION NUMBER: 03-038-701
 MANUFACTURER'S DRAWING NUMBER: 03-038-700
 TYPE DESIGNATION: M-6
 A. S. C. STOCK NUMBER: 5200473555
 TECHNICAL ORDER NUMBER: 11-10-1
 PRODUCTION STATUS: Under procurement.
 SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 150J 33



MOUNT—GUN

ARMY TYPE M-5

NAMES: Gun mount
Hydraulic gun mount
Hydraulic swivel gun mount

DESCRIPTION: The Army type M-5 gun mount is used for local control of twin .50 caliber M2 machine guns for side window waist installations. It is hydraulically operated from a separate power unit located near the installation. This unit is capable of supplying sufficient hydraulic power for two mounts. Each mount, however, has a dumping valve whereby the gunner may release trapped oil and free the gun for manual operation in case of power failure. Two control grips are located at the rear of the mount. The left hand grip operates a metering valve which regulates the flow of oil to pistons and cylinders thus controlling the direction and rate of gun movement. A trigger which fires both guns is located in front of the right hand grip. A ring and bead sight is used with this mount.

CHARACTERISTICS:

Dimensions	approximately 33 by 24 by 15 inches.
Weight	approximately 90 pounds.
Cone of fire	106 degrees.
Speed in any direction	30 degrees per second.
Electric Motor:	
Horsepower	2 1/2.
Voltage	24 volts direct current.
Revolutions per minute	2150.

RELATIONSHIP OF PARTS: Used with:

Army type A-5 gun post sight, A. E. Reference Number 52-4700 and an Army type B-11 gun ring sight, A. E. Reference Number 52-5000 on twin .50 caliber M2 flexible machine guns, A. E. Reference Number 93-1560.

ARMY

A. E. REFERENCE NUMBER: 52-3978
MANUFACTURER: United Shoe Machinery Corporation.
MANUFACTURER'S DRAWING NUMBER: V2-26
TYPE DESIGNATION: M-5
A. S. C. STOCK NUMBER: 5200473550
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped unassembled.

NAVY

There is no Navy equivalent for the Army item.

**POST—GUN MOUNTING****ARMY TYPE A-4 NAVY—SEE BELOW****NAMES:** Gun mounting post Gun mount post Rear mounting post (Navy)

DESCRIPTION: This gun mounting post is used with fixed .30 and .50 caliber M2 machine guns. It consists of a quickly detachable post connecting the rear mounting lugs of the gun to a mounting plate installed in the airplane. Adjustment from side to side is accomplished by means of a threaded bushing at the top of the post; a set screw holds the bushing in place after adjustment. Vertical adjustment is effected by changing the position of two locking nuts on the lower threaded portion of the post. The upper part of the mount, which is attached to the gun, may be removed from the vertical mounting post by turning the knurled collar.

CHARACTERISTICS:

Dimensions.....approximately 5½ by 3¼ by 1¾ inches
 Weight.....approximately 1½ pounds
 Threaded length of post.....3¼ inches

RELATIONSHIP OF PARTS: Used with:

Gun trunnion bolt and bracket, A. E. Reference Number 52-1450 to mount one .30 caliber M2 fixed machine gun, A. E. Reference Number 93-1420, or one .50 caliber M2 fixed machine gun, A. E. Reference Number 93-1560.

ARMY**A. E. REFERENCE NUMBER:** 52-4100**SPECIFICATIONS:**

Detail.....93-24608
 Superseded.....24608

A. A. F. DRAWING NUMBER: 38B1942 (Supersedes Army Drawing H38D5278)**TYPE DESIGNATION:** A-4**A. S. C. STOCK NUMBER:** Refer to chart.**PRODUCTION STATUS:** Under procurement.**SHIPPING DATA:** Shipped as a complete unit.**NAVY**

TYPE DESIGNATION	A-4	Mark 1
BU. ORD. DRAWING NUMBER	None	179007
AVIATION ORDNANCE STOCK LIST NUMBER	1-P-10840	1-P-10828
ORDNANCE PAMPHLET NUMBER	None	865
PROCUREMENT STATUS	Under procurement.	Under procurement.

MODELS BELOW ARE INTERCHANGEABLE**Models are used in services as noted in column 4****A-Army, N-Navy, B-British**

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Remarks
Crosley Corporation	*A-4	**38B1942	A-N-B	5200567100	150J 573	
Aerial Machine and Tool Company	*A-4	**38B1942	A-N-B	5200567100	150J 573	
Moore-Eastwood and Company	*A-4	**38B1942	A-N-B	5200567100	150J 573	
H. M. Thermal Control Company	*A-4	**38B1942	A-N-B	5200567100	150J 573	
Taco Heaters, Incorporated	‡Mark 1	‡‡179007	N			Has height graduations on post.
	‡Mark 3	‡‡329518	N			Issued to Douglas Aircraft only.
Appliance Manufacturing Company	‡Mark 1	‡‡179007	N			Has height graduations on post.
	‡Mark 3	‡‡329518	N			Issued to Douglas Aircraft only.


Note: *AAF type; **AAF drawing; ‡Navy type; ‡‡Navy drawing.



GUN SIGHTS

Machine gun sights enable a gunner to aim more accurately at a target and thus score a greater number of hits.

The simplest types in use are the telescopic and the ring and bead sights. Telescopic sights, now relatively obsolete, consist of a simple telescope which magnifies the target, and a set of cross hairs incorporated in the eyepiece. The bead part of the ring and bead combination is mounted on top of a post which is attached to the gun adapter or the gun barrel. The ring sight is made up of concentric rings, usually two or three in number, and is mounted to the gun in alignment with the bead. The radius of the outer ring is such that, with the operator's eye located a definite distance (usually eight inches) from the ring, the angle at the gunner's eye, between the edge and center of the ring, is equal to a definite lead angle. This angle is expressed in terms of miles per hour of relative speed perpendicular to the line of sight, i.e., a 150 mile per hour ring establishes the proper lead angle at the gunner's eye when a target is traveling at a relative speed of 150 miles per hour perpendicular to the line of sight. This is true for one range only, usually 400 yards. However, with the relative speed perpendicular to the line of sight, the lead angle changes only slightly with a change in range. The inner ring is used to estimate the range. It is so designed that it will circumscribe a definite wing span at a given distance, making it possible for the gunner, after he identifies the target, to approximate the yardage to it.



(Continued on page 75)




GUN SIGHTS

(Continued from page 74)

When firing, the gunner estimates the distance of the target and its flight path, aligns the bead, ring, and target, and allows a correction for the factors involved, based on his experience.

While using the ring and bead sight, errors may be incurred by a change in the relative position of the gunner's head. To correct for this, the optical, or illuminated reflector type sight, was designed. In the reflector type sight, light rays are passed through a small screen on which a circle and dot are etched. These rays then reflect the image of the circle and dot from a mirror, pass it through lenses, and cast it on a transparent reflector screen in front of the gunner. When peering through this screen at the target, the effect is the same as seeing the target and reflected image of the circle and dot in the same visual plane.



OPTICAL GUN SIGHT

To obtain still greater accuracy, gun sight development has been toward an automatic compensating or computing sight. Sights of this nature take into consideration additional variable factors, such as change in speed and direction of the target, drift of the fired bullet, speed of the airplane in which the gun is mounted, and wind effects on the bullet itself.



SIGHT—FLEXIBLE GUN POST

ARMY TYPE A-4

NAMES: Flexible gun post sight Bead sight
 Gun post sight Sight, open, fore post (Navy)
 Post sight

DESCRIPTION: The type A-4 flexible gun post sight is used on flexibly mounted .30 caliber M2 machine guns. It is usually employed with the Army type B-10 flexible gun ring sight.


The gun post sight is made of rust-proof steel which is given a dull finish to prevent reflection. The post is tapered, and has a red enameled bead at the small end. The other end is inserted into a split collar which is used to secure the assembly to the gun. Inside the collar is a two-piece aluminum bushing. The split collar and bushing are secured near the front of the gun barrel jacket by two bolts.

CHARACTERISTICS:

Dimensions..... approximately $5\frac{1}{4}$ by $1\frac{3}{4}$ by $1\frac{1}{8}$ inches.
 Weight..... approximately $\frac{1}{4}$ pound.
 Height of post (from center of gun bore to center of bead)..... $3\frac{1}{4}$ inches.

RELATIONSHIP OF PARTS: Used with:

Army type B-10 flexible gun ring sight, A. E. Reference Number 52-4900 on .30 caliber M2 machine guns, A. E. Reference Number 93-1520.



ARMY

A. E. REFERENCE NUMBER: 52-4600

SPECIFICATIONS:

Detail..... 93-24585

A. A. F. DRAWING NUMBER: 37B3578

TYPE DESIGNATION: A-4

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: A-4

BU. ORD. DRAWING NUMBER: 297102

AVIATION ORDNANCE STOCK LIST NUMBER: 2-S-3090

ORDNANCE PAMPHLET NUMBER: 263 and 865

PROCUREMENT STATUS: Under procurement.

ALL MODELS BELOW ARE INTERCHANGEABLE
 Models are used in services as noted in column 4
 A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Pausin Manufacturing Company	*A-4	**37B3578	A-N-B	5200727200	108B 15
Moore-Eastwood and Company	*A-4	**37B3578	A-N-B	5200727200	108B 15
International Register Company	*A-4	**37B3578	A-N-B	5200727200	108B 15

Note: *AAF type; **AAF drawing.



SIGHT—FLEXIBLE GUN POST

ARMY TYPE A-5 NAVY—SEE BELOW

NAMES: Flexible gun post sight Bead sight
 Gun post sight Sight, open, fore post (Navy)
 Post sight .50 caliber gun post sight

DESCRIPTION: The type A-5 flexible gun post sight is used on a single .50 caliber M2 machine gun. It is usually employed with a type B-11 flexible gun ring sight.


The gun post sight is made of rust-proof steel which is given a dull finish to prevent reflection. The post is tapered and has a red enameled bead at the small end. The other end is inserted into a split collar which is used to secure the assembly to the gun barrel jacket.

CHARACTERISTICS:

Dimensions approximately $5\frac{3}{4}$ by 1 by 2 inches
 Weight approximately $\frac{1}{4}$ pound
 Height of post (center of gun bore to center of bead) $4\frac{1}{2}$ inches

RELATIONSHIP OF PARTS: Used with:

Army type B-11 flexible gun ring sight, A. E. Reference Number 52-5000 on .50 caliber M2 machine guns, A. E. Reference Number 93-1590.



ARMY

A. E. REFERENCE NUMBER: 52-4700

SPECIFICATIONS:

Detail 93-24586

A. A. F. DRAWING NUMBER: 37A5810

TYPE DESIGNATION: A-5

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: A-5

BU. ORD. DRAWING NUMBER: 297059

AVIATION ORDNANCE STOCK LIST NUMBER: 2-S-3091

ORDNANCE PAMPHLET NUMBER: 263 and 865

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
International Register Company	*A-5	**37A5810	A-N-B	5200727500	108B/3
American Signal Corporation	*A-5	**37A5810	A-N-B	5200727500	108B/3

Note: *AAF type; **AAF drawing.



SIGHT—FLEXIBLE GUN POST ARMY TYPE A-11

NAMES: Flexible gun post sight Bead sight
Gun post sight
Post sight
.50 caliber gun post sight

DESCRIPTION: The Army type A-11 flexible gun post sight is used on a single .50 caliber M2 machine gun. It is usually employed with a type B-13 flexible gun ring sight.



This gun post sight is made of rust-proof steel which is given a dull finish to prevent reflection. The post is tapered and has a red enameled bead at the small end. The other end is inserted into a split collar which is used to secure the assembly to the gun barrel.

CHARACTERISTICS:

Dimensions approximately 6", by 2 by 1 inches
Weight approximately 2 ounces
Height of post (center of gun bore to center of bead) 5 $\frac{1}{8}$ inches

RELATIONSHIP OF PARTS: Used with:

Army type B-13 flexible gun ring sight, A. E. Reference Number 52-5050, on a .50 caliber M2 machine gun, A. E. Reference Number 93-1590, mounted in an Army type E-8 adapter, A. E. Reference Number 52-1100.



ARMY

A. E. REFERENCE NUMBER: 52-4850

SPECIFICATIONS:

Detail 93-24758
Superseded 24758

MANUFACTURER: Ohio Art Company.

A. A. F. DRAWING NUMBER: 42A8317

TYPE DESIGNATION: A-11

A. S. C. STOCK NUMBER: 5200727575

TECHNICAL ORDER NUMBER: 11-35-13

PRODUCTION STATUS: Under procurement.


SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 108B 74

**SIGHT—FLEXIBLE GUN RING****ARMY TYPE B-10 NAVY—SEE BELOW**

NAMES: Flexible gun ring sight
Gun ring sight
Ring sight
.30 caliber gun ring sight

DESCRIPTION: The type B-10 flexible gun ring sight is used on flexibly mounted .30 caliber M2 machine guns. It is usually employed with an A-4 flexible gun post sight.

The gun ring sight is made of rust-proof steel which is given a dull finish to prevent reflection. It consists of two concentric rings and an adjustable clamp. The larger ring is connected to a metal post mounted on the clamp. The smaller ring, or center peep, is supported from the larger ring, and contains two cross hairs which are used to align the bead on the post sight with the target. The clamp, consisting of a horizontal bar with two hooked lugs, secures the sight to the cover plate of the machine gun. When in position, the ring sight will be approximately eight inches from the gunner's eye.

CHARACTERISTICS:

Dimensions approximately $3\frac{1}{2}$ by $2\frac{3}{8}$ by $\frac{7}{8}$ inches
Weight approximately $\frac{1}{4}$ pound
Large ring (inside diameter) approximately $2\frac{1}{4}$ inches
Small ring (inside diameter) approximately $\frac{1}{2}$ inch

RELATIONSHIP OF PARTS: Used with:

Army type A-4 flexible gun post sight, A. E. Reference Number 52-4600 on a .30 caliber M2 machine gun, A. E. Reference Number 93-1520.

ARMY

A. E. REFERENCE NUMBER: 52-4900

SPECIFICATIONS:

Detail 93-24587

A. A. F. DRAWING NUMBER: 37B3574

TYPE DESIGNATION: B-10

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: B-10

BU. ORD. DRAWING NUMBER: 297061

AVIATION ORDNANCE STOCK LIST NUMBER: 2-S-3106

ORDNANCE PAMPHLET NUMBER: 263 and 865

PROCUREMENT STATUS: Under procurement.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Pausin Manufacturing Company	*B-10	**37B3574	A-N-B	5200728700	108B 18
International Register Company	*B-10	**37B3574	A-N-B	5200728700	108B 18

Note: *AAF type; **AAF drawing.

**SIGHT—FLEXIBLE GUN RING****ARMY TYPE B-10 NAVY—SEE BELOW**

NAMES: Flexible gun ring sight
Gun ring sight
Ring sight
.30 caliber gun ring sight

DESCRIPTION: The type B-10 flexible gun ring sight is used on flexibly mounted .30 caliber M2 machine guns. It is usually employed with an A-4 flexible gun post sight.

The gun ring sight is made of rust-proof steel which is given a dull finish to prevent reflection. It consists of two concentric rings and an adjustable clamp. The larger ring is connected to a metal post mounted on the clamp. The smaller ring, or center peep, is supported from the larger ring, and contains two cross hairs which are used to align the bead on the post sight with the target. The clamp, consisting of a horizontal bar with two hooked lugs, secures the sight to the cover plate of the machine gun. When in position, the ring sight will be approximately eight inches from the gunner's eye.

CHARACTERISTICS:

Dimensions approximately $3\frac{1}{2}$ by $2\frac{3}{8}$ by $\frac{7}{8}$ inches
Weight approximately $\frac{1}{4}$ pound
Large ring (inside diameter) approximately $2\frac{1}{4}$ inches
Small ring (inside diameter) approximately $\frac{1}{2}$ inch

RELATIONSHIP OF PARTS: Used with:

Army type A-4 flexible gun post sight, A. E. Reference Number 52-4600 on a .30 caliber M2 machine gun, A. E. Reference Number 93-1520.

ARMY

A. E. REFERENCE NUMBER: 52-4900

SPECIFICATIONS:

Detail 93-24587

A. A. F. DRAWING NUMBER: 37B3574

TYPE DESIGNATION: B-10

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: B-10

BU. ORD. DRAWING NUMBER: 297061

AVIATION ORDNANCE STOCK LIST NUMBER: 2-S-3106

ORDNANCE PAMPHLET NUMBER: 263 and 865

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Pausin Manufacturing Company	*B-10	**37B3574	A-N-B	5200728700	108B 18
International Register Company	*B-10	**37B3574	A-N-B	5200728700	108B 18

Note: *AAF type; **AAF drawing.



SIGHT—FLEXIBLE GUN RING

ARMY TYPE B-11 NAVY—SEE BELOW

NAMES: Flexible gun ring sight
Gun ring sight
Ring sight
.50 caliber gun ring sight
Sight, open, rear ring (Navy)

DESCRIPTION: The type B-11 flexible gun ring sight is used on flexibly mounted .50 caliber M2 machine guns. It is usually employed with an A-5 flexible gun post sight.


The gun ring sight is made of rust-proof steel which is given a dull finish to prevent reflection. It consists of two concentric rings and an adjustable clamp. The larger ring is welded to a metal post mounted on the clamp. The smaller ring, or center piece, is supported from the larger ring, and contains two cross hairs which are used to align the head of the post sight with the target. The clamp, consisting of a horizontal bar with two hooked lugs, secures the sight to the cover plate of the machine gun. When in position, the sight will be approximately eight inches from the gunner's eye.

CHARACTERISTICS:

Dimensions	approximately 3 $\frac{1}{2}$ by 2 $\frac{1}{8}$ by 3 $\frac{3}{4}$ inches
Weight	approximately $\frac{1}{2}$ pound
Large ring (inside diameter)	approximately 2 $\frac{3}{8}$ inches
Small ring (inside diameter)	approximately $\frac{3}{4}$ inch

RELATIONSHIP OF PARTS: Used with:

Army type A-5 flexible gun post sight, A. E. Reference Number 52-4700 on a .50 caliber M2 machine gun, A. E. Reference Number 93-1590.



ARMY

A. E. REFERENCE NUMBER: 52-5000

SPECIFICATIONS:

Detail 93-24588

A. A. F. DRAWING NUMBER: 37A5811

TYPE DESIGNATION: B-11

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type B-15 ring sight, A. E. Reference Number 52-5110

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: B-11

BU. ORD. DRAWING NUMBER: 297057

AVIATION ORDNANCE STOCK LIST NUMBER: 2-S-3107


ORDNANCE PAMPHLET NUMBERS: 263 and 865

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
International Register Company	*B-11	**37A5811	A-N-B	5200729000	1088 4
American Signal Corporation	*B-11	**37A5811	A-N-B	5200729000	1088 4

Note: *AAF type; **AAF drawing.



SIGHT—FLEXIBLE GUN RING

ARMY TYPE B-13

NAMES: Flexible gun ring sight
Gun ring sight
Ring sight
.50 caliber gun ring sight

DESCRIPTION: The Army type B-13 flexible gun ring sight is used on flexibly mounted .50 caliber M2 machine guns. It is usually employed with an A-11 flexible gun post sight.

The gun ring sight is made of rust-proof steel, which is given a dull finish to prevent reflection. It consists of two concentric rings mounted on a bracket which is bolted directly to the rear of the gun mount assembly, approximately eight inches from the gunner's eye.

CHARACTERISTICS:

Dimensions	approximately 3 by 2 $\frac{3}{4}$ by $\frac{5}{4}$ inches
Weight	approximately 1 ounce
Large ring (inside diameter)	approximately 1 $\frac{3}{4}$ inches
Small ring (inside diameter)	approximately $\frac{1}{4}$ inch

RELATIONSHIP OF PARTS: Used with:

Army type A-11 flexible gun post, A. E. Reference Number 52-4850 on a .50 caliber M2 machine gun,
A. E. Reference Number 93-1590, mounted on an Army type E-8 gun mount adapter, A. E. Reference
Number 52-1100.

ARMY

A. E. REFERENCE NUMBER: 52-5050

SPECIFICATIONS:

Detail	93-24759
Superseded	24759

MANUFACTURER: Ohio Art Company.

A. A. DRAWING NUMBER: 42B8318

TYPE DESIGNATION: B-13

A. S. C. STOCK NUMBER: 5200729115

TECHNICAL ORDER NUMBER: 11-35-13

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 108B 75



SIGHT—TELESCOPIC GUN

ARMY TYPE E-5

NAMES: Telescopic gun sight

DESCRIPTION: The Army type E-5 telescopic gun sight is used with .30 and .50 caliber M2 machine guns. The sight is a telescope of approximately one power, incorporating a set of removable cross hairs. It is non-compensating, but when used with a type C-4 adjustable mount, it has limited adjusting facilities for aligning the line of sight to the bore axis of the gun.

Dust caps, connected by a leather strap, are provided to keep the lenses from being scratched.

CHARACTERISTICS

Dimensions	approximately 9 $\frac{1}{2}$ by 1 $\frac{1}{4}$ by 1 $\frac{1}{4}$ inches
Weight	approximately $\frac{3}{8}$ pound

RELATIONSHIP OF PARTS: Used with:

Army type C-4 flexible gun sight mount, A. E. Reference Number 52-3400, on .30 or .50 caliber M2 machine guns.

ARMY

A. E. REFERENCE NUMBER: 52-5350

SPECIFICATIONS:

Detail	93-24667
Superseded:	24667

MANUFACTURER: International Register Company.

A. A. F. DRAWING NUMBER: 40B7830

TYPE DESIGNATION: E-5


A. S. C. STOCK NUMBER: 5200729700

PRODUCTION STATUS: Not under procurement for initial installation.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.





SIGHT—ILLUMINATED

ARMY—SEE BELOW NAVY MARK 8

NAMES: Illuminated sight
Illuminated gun sight
Fixed gun sight
Optical sight

DESCRIPTION: The Navy Mark 8 illuminated optical sight is a device used to bring fixed guns to bear on a target. The sight is secured to the cowl of an airplane so that a reflecting plate is in line with the pilot's line of vision. A lamp in the base of the sight transmits a reticle image onto the reflecting plate, at the base of which is a spirit-level bank indicator. A sponge rubber cushion on the outer rim of the lens housing protects the pilot from injury in case of accident.

This sight uses a double filament lamp. The connector is a three-pin contact type.

CHARACTERISTICS:

Dimensions approximately 10½ by 6½ by 4½ inches
Weight approximately 3½ pounds
Voltage 12 volts direct current

RELATIONSHIP OF PARTS: Used with:

Lamp Trade Number 1652 IF, S-8 IF, 21/21 candlepower, 13 volts.

ARMY

A. E. REFERENCE NUMBER: 52-5370

TYPE DESIGNATION: Navy Mark 8

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Used only on aircraft procured for or from the Navy Department by the Army.

SHIPPING DATA: Shipped as a complete unit including lamp.

NAVY

TYPE DESIGNATION: Mark 8

ORDNANCE SPECIFICATION: 2349


BU. ORD. DRAWING NUMBER: 238544

AVIATION ORDNANCE STOCK LIST NUMBER: 2-S-3114

ORDNANCE PAMPHLET NUMBER: 263, 803 and 865

ORDNANCE CIRCULAR LETTER: V19-42

PROCUREMENT STATUS: Not under procurement for initial installation.




MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British


Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Bausch and Lomb Optical Company	*Mark 8	**N-238544	A-N-B	5200730750	108B 20
Bell and Howell Company	*Mark 8	**N-238544	A-N-B	5200730750	108B 20

Note: *Navy type; **Bu. Ord. drawing



SIGHT— FIXED GUN

ARMY TYPE N-3A
NAVY—SEE BELOW



NAMES: Fixed gun sight
Illuminated sight
Illuminated gun sight
Optical sight

DESCRIPTION: The type N-3A fixed gun sight, usually mounted in the pilot's cockpit, is of the single wire grounded type. The sight consists of a main housing containing a lamp and lamp socket, a circle and center dot reticle, a mirror, a lens, and a toggle switch. This sight projects an image of the reticle on to a reflector screen held in a reflector support. This support is a separate item used in conjunction with the sight.

The lamp used contains two filaments; if one filament does not light, the gunner reverses the toggle switch and brings the other filament into use.

(Continued on page 85)



SIGHT— FIXED GUN

(Continued from page 84)

CHARACTERISTICS:

Dimensions	approximately 7 $\frac{1}{8}$ by 3 $\frac{1}{2}$ by 5 $\frac{1}{2}$ inches
Weight	approximately 3 $\frac{1}{2}$ pounds
Voltage	12 to 28 volts direct current
Electrical receptacle	Army part number 39A2389
Contact pin	Army part number 38A1782

RELATIONSHIP OF PARTS: Used with:

Lamp Trade Number 1052 I. F., A. E. Reference Number 88-8300 and gun sight image reflector support, A. E. Reference Number 52-6400, or Army type A-1 or A-2 pilot's bombsight head, A. E. Reference Number 64-2000 or 64-2005.

ARMY

A. E. REFERENCE NUMBER: 52-4400

SPECIFICATIONS:

Detail	93-24659B
Superseded	93-24659A

A. A. F. DRAWING NUMBER: 41G6436

TYPE DESIGNATION: N-3A

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type N-3B, A. E. Reference Number 52-4425.

SHIPPING DATA: Shipped as a complete unit less lamp.

Note: Gun sight image reflector and pilot's bombsight head must be ordered separately.

NAVY

TYPE DESIGNATION: N-3A

AVIATION ORDNANCE STOCK LIST NUMBER: 2-S-3117

PROCUREMENT STATUS: Not under procurement for initial installation.

MODELS BELOW ARE INTERCHANGEABLE


Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Service Tool and Engineering Company	*N-3A	**41G6436	A-N-B	5200726630	11-35-5	108B 12	Single pin push-on type electrical connector.
	*N-3B	**42G20092	A-B	5200726635	11-35-5	108B 68	Two pin screw-on type electrical connector.

NOTE: These sights may be used in a 12-volt circuit by replacing the lamp with lamp, Trade Number 1120 I.F., A.E. Reference Number 88-3200.

Note: *AAF type, **AAF drawing



SIGHT—FIXED GUN

ARMY TYPE N-3B

NAMES: Fixed gun sight Illuminated sight Illuminated gun sight Optical sight

DESCRIPTION: The Army type N-3B fixed gun sight, usually mounted in the pilot's cockpit, is of the two wire type, to prevent compass deviation. The sight consists of a main housing containing a lamp and lamp socket, a circle and center dot reticle, a mirror, a lens, and a toggle switch. This sight projects an image of the reticle onto a reflector screen held in a reflector support. This support is a separate item used in conjunction with the sight.

The lamp used in this sight contains two filaments; if one filament does not light, the gunner reverses the toggle switch and brings the other filament into use.

CHARACTERISTICS:

Dimensions	approximately 7 $\frac{9}{16}$ by 3 $\frac{1}{2}$ by 5 $\frac{1}{2}$ inches
Weight	approximately 3 $\frac{1}{2}$ pounds
Voltage	12-28 volts direct current
Electrical connector	AN3102-12S-3P

RELATIONSHIP OF PARTS: Used with:

Lamp Trade Number 1052 I. F., A. E. Reference Number 88-8300 and gun sight image reflector, A. E. Reference Number 52-6400, or Army types A-1 and A-2 pilot's bombsight head, A. E. Reference Number 64-2000 or 64-2005.

ARMY

A. E. REFERENCE NUMBER: 52-4425

SPECIFICATIONS:

Detail	93-24817
Superseded	24817

A. A. F. DRAWING NUMBER: 42G20092

TYPE DESIGNATION: N-3B

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit including lamp. Gun sights of early manufacture were shipped less lamp. Gun sight image reflector or pilot's bombsight head must be ordered separately.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	A. E. Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Service Tool and Engineering Company	*N-3B	**42G20092	A-B	52C0726635	11-35-5	108B 68	Two pin screw-on type electrical connector.
	*N-3A	**41G6436	A-N-B	52C0726630	11-35-5	108B 12	Single pin push-on type electrical connector.

NOTE: These sights may be used in a 12-volt circuit by replacing the lamp with lamp, Trade Number 1120 I. F., A. E. Reference Number 88-3200.
*AAF type; **AAF drawing.



SIGHT—FLEXIBLE GUN

ARMY TYPE N-6



NAMES: Flexible gun sight
Illuminated sight
Illuminated gun sight
Optical sight

Reticle reflecting sight

DESCRIPTION: The Army type N-6 flexible gun sight, usually mounted in a machine gun turret, is of the single wire grounded type. The sight consists of a main housing and a removable reflector support. The housing contains a lamp and lamp socket, a circle and center dot reticle, a filter, a mirror, a lens, and a toggle switch. The image reflector support attached to the main housing includes a reticle reflector and a daylight filter, or sun screen. This screen may be placed in one of three positions to control the degree of sunlight protection. The reflector support uses cork strips around the glass to prevent breakage due to severe temperature changes.

This sight projects an image of the reticle onto the reflector screen held in the reflector support.

The lamp used in the sight contains two filaments; if one filament does not light, the gunner reverses the toggle switch and brings the other filament into use.

CHARACTERISTICS:

Dimensions . . . approximately
7 $\frac{1}{8}$ by 4 $\frac{1}{2}$
by 3 $\frac{1}{8}$ inches.


Weight approximately
2 $\frac{1}{8}$ pounds.

Voltage 12-28 volts direct
current.

Electrical
connector . . . AN3102-10S-2P.

RELATIONSHIP OF PARTS: Used with:

Lamp Trade Number 1052 I. F., A. E. Reference Number 88-8300, in 24 volt circuits, and Lamp Trade Number 1120 I.F., A.E. Reference Number 88-3200, in 12 volt circuits. Army type A-1 or A-2 pilot's bombsight head, A. E. Reference Number 64-2000 or 64-2005 may be used with this sight by removing the reflector support and installing an adapter.



7 $\frac{13}{32}$ "
APPROX.

ARMY

A. E. REFERENCE NUMBER: 52-4500

SPECIFICATIONS:

Detail 24704A

Superseded 24704

A. A. F. DRAWING NUMBER: 41D9625

TYPE DESIGNATION: N-6

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type N-6A, A. E. Reference Number 52-4525.

SHIPPING DATA: Shipped as a complete unit, less lamp.

NAVY


There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
S. E. Bowser Company	*N-6	**41D9625	A-B	5200726690	11-35-12	1088 19	
	*N-6A	**42G14292	A-B	5200730700		1088 70	
E. A. Laboratories	*N-6	**41D9625	A-B	5200726690	11-35-12	1088 19	
Bell and Howell Company	*N-8	**163-A	A	5200731575	11-358-1		†

†For 24 volt circuit use lamp, Trade Number 844, A. E. Reference Number 88-8400. Replace with lamp, Trade Number 842, A. E. Reference Number 88-3300 for 12 volt use.

Notes: *AAF type; **AAF drawing.



**SIGHT—
FLEXIBLE GUN**
ARMY TYPE N-6A



NAMES: Flexible gun sight
Illuminated sight
Illuminated gun sight
Optical sight

DESCRIPTION: The Army type N-6A flexible gun sight, usually mounted in a machine gun turret, is of the single wire grounded type. The sight consists of a main housing and removable reflector support. The housing contains a lamp and lamp socket, a circle and center dot reticle, a filter, a mirror, a lens, and a toggle switch. The image reflector support attached to the main housing includes a reticle reflector and a daylight filter, or sun screen. This screen may be placed in any position and has two adjusting knobs to control the degree of sunlight protection.

This sight projects an image of the reticle on to the reflector screen held in the reflector support.

The lamp used in the sight contains two filaments; if one filament does not light, the gunner reverses the toggle switch and brings the other filament into use.

(Continued on page 89)



SIGHT— FLEXIBLE GUN

(Continued from page 88)

CHARACTERISTICS:

Dimensions approximately 7¼ by 5¾ by 4 inches
 Weight approximately 2½ pounds
 Voltage 12-28 volts direct current
 Electrical connector AN3102-10S-2P

RELATIONSHIP OF PARTS: Used with:

Lamp Trade Number 1052 I. F., A. E. Reference Number 88-8300, in 24 volt circuits, and Lamp Trade Number 1120 I. F., A. E. Reference Number 88-3200, in 12 volt circuits.

Army type A-1 or A-2 pilot's bombsight head, A. E. Reference Number 64-2000 or 64-2005 may be used with this sight by removing the reflector support and installing an adapter.

ARMY

A. E. REFERENCE NUMBER: 52-4525

SPECIFICATIONS:

Detail: 93-24704

Superseded: 24704A

A. A. F. DRAWING NUMBER: 42G14292

TYPE DESIGNATION: N-6A

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, including lamp. Gun sights of early manufacture were shipped less lamp.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
S. E. Bowser Company	*N-6A	**42G14292	A-B	5200730700		108B 70	
	*N-6	**41D9625	A-B	5200726690	11-35-12	108B 19	
E. A. Laboratories	*N-6	**41D9625	A-B	5200726690	11-35-12	108B 19	
Bell and Howell Company	*N-8	163-A	A	5200731575	11-35B-1		†

†For 24 volt circuit use lamp, Trade Number 844, A. E. Reference Number 88-8400. Replace with lamp, Trade Number 842, A. E. Reference Number 88-3300, for 12 volt use.

Note: *AAF type; **AAF drawing.

SIGHT—ILLUMINATED


NAVY MARK 9

NAMES: Illuminated sight
Illuminated gun sight

Flexible gun sight
Optical sight



6 ³/₈"
APPROX.



DESCRIPTION: The Navy Mark 9 illuminated optical sight is mounted on turret gun carriages or flexible gun mounts. The sight consists of a main housing and a reflector support. The housing contains a lamp and lamp socket, a reticle, a lens, and a snap type switch. The image reflector support attaches to the main housing and incorporates the reticle reflector and a daylight filter, or sunscreen. This sight projects an image of the reticle onto the reflector screen held in the reflector support. The snap switch incorporates a rheostat, which can be turned to vary the intensity of illumination of the sight.

Connected to the sight is a two-foot rubber insulated wire with a threaded electrical connection containing two pin-type contacts.

CHARACTERISTICS:

Dimensions	approximately 6 ³ / ₈ by 3 ¹ / ₂ by 3 ¹ / ₂ inches
Weight	approximately 1 ¹ / ₂ pounds
Voltage	12 to 28 volts direct current

RELATIONSHIP OF PARTS: Used with:

Lamp, Trade Number 1664 IF, S-8 IF, 21 6 candlepower, 28 volts.

ARMY

A. E. REF. NO.: 52-5375
TYPE DESIGNATION: Navy Mark 9
A. S. C. STOCK NO.: Refer to chart.
PROD. STATUS: Not under procurement for initial installation. Used on aircraft procured for or from the Navy Department. Superseded by Army type N-8 sight, A. E. Reference Number 52-4550.
SHIPPING DATA: Shipped as a complete unit, including lamp.

NAVY


TYPE DESIGNATION: Mark 9
ORD. SPEC.: 2366
BU. ORD. DRAW. NO.: 300481
AVIATION ORDNANCE STOCK LIST NUMBER: 2-S-3115
ORD. PAMPHLET NO.: 263 and 865
ORDNANCE CIRCULAR LETTER NUMBER: V19-42
PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
American Cystoscope Makers, Incorporated	*Mark 9	ORD28177	A-N-B	5200730760	1088 21
Wallensak Optical Company	*Mark 9	ORD28177	A-N-B	5200730760	1088 21

NOTE Navy Mark 9, Mod. 1 sight is identical to the Mark 9 except that Lamp, Trade Number 1664 IF, S-8, IF, 21/6 candlepower, 12-16 volts is used for 12 volt service.

Note. *Navy type.



SIGHT—FLEXIBLE GUN
ARMY TYPE N-8

NAMES: Flexible gun sight
Illuminated sight
Illuminated gun sight
Optical sight

Retiflector sight

DESCRIPTION: The Army type N-8 flexible gun sight, usually mounted in a machine gun turret, is of the single wire grounded type. The sight's main housing consists of a lamp and lamp socket in a removable base, a circle and center dot recticle, a filter or sun screen, and a mirror set up horizontally above a reflector glass.

The recticle consists of a glass with one opaque surface containing the recticle design. This sight projects an image of the recticle onto the reflector screen held in a reflector support.

The lamp used in this sight contains two filaments; if one filament does not light, the gunner reverses the toggle switch and brings the other filament into use. A ring and bead sight is provided in case of power failure.

CHARACTERISTICS:

Dimensions..... approximately 6 $\frac{1}{8}$ by 4 by 5 $\frac{3}{4}$ inches.
Weight..... approximately 1 $\frac{1}{4}$ pounds.
Voltage..... 12-28 volts direct current.
Electrical connector..... AN3102-10S-2P.

RELATIONSHIP OF PARTS: Used with:

Lamp, Trade Number 844, A. E. Reference Number 88-8400 in 24-volt circuits, and Lamp, Trade Number 842, A. E. Reference Number 88-8300, in 12-volt circuits.

ARMY

A. E. REFERENCE NUMBER: 52-4550

TYPE DESIGNATION: N-8

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, including lamp.

NAVY


There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Bell and Howell Company	*N-8	163-A	A	5200731575	11-35B-1		
S. E. Bowser Company	*N-6	**41D9625	A-B	5200726690	11-35-12	108B 19	See note
	*N-6A	**42G14292	A-B	5200730700		108B 70	See note
E. A. Laboratories	*N-6	**41D9625	A-B	5200726690	11-35-12	108B 19	See note

NOTE In 24-volt circuit use Lamp, Trade Number 1052 I.F., A.E. Reference Number 88-8300, and in 12-volt circuit use Lamp, Trade Number 1120 I.F., A. E. Reference Number 88-3200.

Note: *AAF type, **AAF drawing.



SIGHT—AUTOMATIC COMPENSATING GUN

ARMY TYPE K-3

NAMES: Automatic compensating gun sight
Computing sight

Sperry computing sight
Sperry computer

DESCRIPTION: The Army type K-3 automatic compensating gun sight is used in the types A-1 and A-1A upper turrets. The sight is mounted on a cradle that attaches to, and moves with, the guns. This sight consists of an optical system, an automatic computing mechanism and a range finder, combined into a single unit. The optical system is used to locate the target in space. The computing mechanism and range finder solves prediction and ballistic deflections for the projectile and automatically transmits these solutions to the optical system. This causes the line of sight to be offset from the gun bore in proportion to the predicted deflections, thereby insuring a greater proportion of hits. The gunner moves the sight (and the guns) so that the line of sight follows the movement of the target. A ring and bead sight, which is folded when not in use, is provided in case of power supply failure.

CHARACTERISTICS:

Dimensions	approximately 13 $\frac{1}{16}$ by 13 $\frac{1}{2}$ by 10 $\frac{1}{2}$ inches.
Weight	approximately 25 pounds.
Operating voltage	24 volts direct current

RELATIONSHIP OF PARTS: Used with:

Army type A-1 and A-1A upper turrets, A. E. Reference Numbers 52-7600 and 52-7625, and lamp. Trade Number 1327, 12-16 volts, 32 candlepower, RP-11 bulb, single contact prefocused base.

ARMY

A. E. REFERENCE NUMBER: 52-4250

TYPE DESIGNATION: K-3

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit including lamp.

NAVY

There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE


Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	Manufacturer's Specification	
Sperry Gyroscope Company	*K-3	646398-A assembly 644853-H outline	A	5900731750	11-35A-1	S-69834	
	*K-4	646636-A assembly 645418-H outline	A	5900719910	11-35A-1	S-69834	See note
National Cash Register Company	*K-3	646398-A assembly 644853-H outline	A	5900731750	11-35A-1		
	*K-4	646636-A assembly 645418-H outline	A	5900719910	11-35A-1		See note

NOTE: The Army type K-3 is identical to Army type K-4, with the exception that the flexible shaft input connection boxes on the K-3 are tilted at an angle and both outlets face the same direction. Some of the lettering on the K-4 is inverted, for use in lower turrets.

Note: *AAF type



SIGHT-AUTOMATIC COMPENSATING GUN

ARMY TYPE K-4

NAMES: Automatic compensating gun sight Sperry computing sight
Computing sight Sperry computer

DESCRIPTION: The Army type K-4 automatic compensating sight, used in the types A-2 and A-13 lower ball turrets, is mounted securely inside the ball of the turret. This sight consists of an optical system, an automatic computing mechanism, and a range finder, combined into a single unit. The optical system is used to locate the target in space. The computing mechanism and range finder solve prediction and ballistic deflections for the projectile and automatically transmit these solutions to the optical system. This causes the line of sight to be offset from the gun bore in proportion to the predicted deflections, insuring a greater proportion of hits. The gunner moves the sight (and the turret) so that the line of sight follows the movement of the target.

A ring and head sight, which is folded when not in use, is provided, in case of power supply failure.

CHARACTERISTICS:

Dimensions.....approximately 13 $\frac{1}{6}$ by 13 $\frac{1}{4}$ by 10 $\frac{1}{2}$ inches.

Weight approximately 25 pounds.

Operating voltage	24 volts direct current.
-------------------	--------------------------

Lamp Trade Number 1327, 12-16 volts, 32 candle-power, RP-11 bulb, single contact pre-focused base.

RELATIONSHIP OF PARTS: Used with:

Army type A-2 and A-13 lower turrets, A. E. Reference Numbers 52-7200 and 52-8050.

ARMY

A. E. REFERENCE NUMBER: 52-4260

TYPE DESIGNATION: K-4

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit including lamp.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4




A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	Manufacturer's Specification	Remarks
Sperry Gyroscope Company	*K-4	646636-A assembly 645418-H outline	A	5900719910	11-35A-1	S-69834	
	*K-3	646398-A assembly 644853-H outline	A	5900731750	11-35A-1	S-69834	See note
National Cash Register Company	*K-4	616636-A assembly 645418-H outline	A	5900719910	11-35A-1		
	*K-3	646398-A assembly 644853-H outline	A	5900731750	11-35A-1		See note

NOTE: The Army type K-3 is identical to Army type K-4, with the exception that the flexible shaft input connection boxes on the K-3 are tilted at an angle and both outlets face the same direction. Some of the lettering on the K-4 is inverted for use in tower turrets.

Note: *AAF type.

**GUN SIGHTS
ARMAMENT—GUNNERY**



**SIGHT-COMPENSATING
ARMY TYPE K-8**

NAMES: Compensating sight
Computing sight

Fairchild compensating sight
Automatic compensating sight

(Continued on page 95)



SIGHT-COMPENSATING

(Continued from page 94)

DESCRIPTION: The Army type K-8 compensating gun sight is used with .50 caliber M2 machine guns mounted in an upper turret. The sight assembly consists of a control unit, power unit, a sight mount, and a foot control. The sight is driven by flexible shafts from the turret's azimuth and elevation drives and provides compensation for the range, indicated airspeed, altitude of the airplane in which it is mounted, and relative speed of the target with respect to the turret. All corrections are automatically made by the sight after the gunner has set the dials for the altitude, indicated airspeed of his own airplane, and the span of the target.

A ring and bead sight, which can be folded out of the way when not in use, is provided in case the power supply should fail.

CHARACTERISTICS:

Dimensions

Control unit.....	approximately 18½ by 10 by 6¼ inches.
Sight unit.....	approximately 14½ by 14½ by 10 inches.
Foot control unit.....	approximately 12 by 10½ by 7½ inches.
Power unit.....	approximately 16 by 9½ by 4¼ inches.

Weight

Control unit.....	approximately 23 pounds.
Foot control unit.....	approximately 5 pounds.
Sight unit.....	approximately 10 pounds.
Power unit.....	approximately 30 pounds.

RELATIONSHIP OF PARTS: Used with:

Martin turrets type A-3C, A. E. Reference Number 52-7475.

ARMY

A. E. REFERENCE NUMBER: 52-4270

TYPE DESIGNATION: K-8

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped unassembled in separate units.

NAVY


There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Manufacturer's Specification Number
Fairchild Aviation Corporation	F-180	V-361	A	5900721500	F-180
Addressograph Multigraph Corporation	F-180	V-361	A	5900721500	
Thomas B. Gibbs and Company	F-180	V-361	A	5900721500	



MACHINE GUN SYNCHRONIZING SYSTEM MACHINE GUN SYNCHRONIZERS

A machine gun synchronizer is a device to control a fixed machine gun so that its projectiles may be fired through the arc of rotation of a propeller. It is arranged so that the projectile is fired after a propeller blade passes the muzzle of the gun.

This synchronizer includes an impulse generator, an impulse tube and wire, a trigger motor and an electrical control.

The impulse generator creates the timed impulses that actuate the trigger motor. It is mounted on the engine's synchronizer mounting pad, and contains a camshaft which is driven by a splined drive from the airplane engine. The cam is rotated at propeller speed, and has a number of lobes, depending on the number of propeller blades. A cam follower generates an impulse when actuated by each lobe.

Impulses are transmitted to the trigger by the impulse tube and wire unit. This unit consists of a wire inside a steel tube with suitable couplings at each end to allow the wire to move freely. One end of the wire is attached to the plunger on the impulse generator, and the other end to the trigger motor.

The trigger motor, mounted on the side of the fixed machine gun, is actuated by the timed impulses which are transmitted along the impulse wire. Each impulse pulls the trigger motor plunger forward against the trigger motor slide, forcing the end of the slide through a slot in the side of the gun and tripping the firing mechanism.

The entire synchronizer system is operated by an electrical control, which consists of a solenoid attached to the head of the impulse generator, a control handle gun switch, and a safety switch. The type of solenoid used depends on the circuit voltage. When the control handle gun switch is depressed, the solenoid is energized and frees the cam follower in the generator. This allows the spring in the trigger motor to pull the cam follower against the cam. Rotation of the cam produces the timed impulses to actuate the trigger motor. When the control switch is released, the solenoid plunger is returned to its original position by a spring and locks the cam follower in a position where no impulses may be generated.

**GENERATOR—GUN SYNCHRONIZER IMPULSE****ARMY TYPE E-8 NAVY—SEE BELOW**

NAMES: Gun synchronizer impulse generator
Synchronizer—gun impulse generator

DESCRIPTION: The Army type E-8 gun synchronizer impulse generator is part of the synchronizing system which is used to control the firing of .30 and .50 caliber M2 machine guns. This unit generates the timed mechanical impulses which enable the trigger motor to fire the gun.

The major parts of the impulse generator unit are a housing, a cam, an eccentric sleeve and a reciprocating cam follower. The cam is rotated at propeller speed and contains one, two, or three lobes for use with either a two, three, or four bladed propeller. A solenoid, actuated by the control handle gun switch, retracts a plunger from the shoulder of the cam follower and allows the follower to be pulled against the cam. Rotation of the cam then produces a series of mechanical impulses.

CHARACTERISTICS:

Dimensions.....approximately 6 $\frac{1}{8}$ by 3 $\frac{1}{2}$ by 3 inches.
Weight.....approximately 2 $\frac{1}{4}$ pounds.

RELATIONSHIP OF PARTS: Used with:

Army type E-3 impulse unit, A. E. Reference Number 52-2600, Army type E-3A trigger motor, A. E. Reference Number 52-3000, and Army type G-10 gun firing solenoid, A. E. Reference Number 52-6300.

ARMY

A. E. REFERENCE NUMBER: 52-2700

SPECIFICATIONS:

Detail.....93-24609A
Superseded.....93-24609

A. A. F. DRAWING NUMBER: 38D4828

TYPE DESIGNATION: E-8

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: E-8

SPECIFICATIONS:

General.....M-460

BU. AER. DRAWING NUMBER: W. A. C. 114081; 114081-N-1, or Ranger 7588

BU. AER. F. S. S. C. STOCK NUMBER: R-86-G-37010

ORDNANCE PAMPHLET NUMBER: 552

BU. AER. CIRCULAR LETTER NUMBER: Aer-Ma-12431-EG-F41-14


PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Metal Specialty Company	*E-8	**38D4828	A-N-B	5200291050	11-20-13	108A 161
Moore-Eastwood and Company	*E-8	**38D4828	A-N-B	5200291050	11-20-13	108A 161

Note: *AAF type, **AAF drawing.



ENDS—IMPULSE UNIT

ARMY TYPE E-3 NAVY MARK 1

NAMES: Impulse unit ends

Cable ends—impulse, BAM, —.30 and .50 caliber (Navy)

Impulse tube and wire ends

DESCRIPTION: These are the end fittings and couplings of the gun synchronizer's impulse tube and wire unit which connects the impulse generator to the trigger motor. The impulse tube and wire unit consists of a steel tube, a single strand of steel wire and the necessary couplings and fittings. The airplane contractor furnishes the wire and tubing. The end fittings and couplings are provided by the Government.

CHARACTERISTICS:

Dimensions:

End for type E-8 impulse generator approximately 4½ by 1¼ by 1¼ inches.

End for type E-3A trigger motor approximately 1½ by 1¼ by 1¼ inches.

Weight approximately 1 pound (together).

RELATIONSHIP OF PARTS: Used with:

Army type E-8 impulse generator, A. E. Reference Number 52-2700, and Army type E-3A trigger motor, A. E. Reference Number 52-3000.

ARMY

A. E. REFERENCE NUMBER: 52-2600

SPECIFICATIONS:

Detail 93-24592

Superseded 24592

A. A. F. DRAWING NUMBER: 076031 and H35G5394

TYPE DESIGNATION: E-3

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, consisting of one impulse generator end and one trigger motor end packed together.

NAVY

TYPE DESIGNATION: Mark 1

BU. ORD. DRAWING NUMBER: Assembly, 163658; Installation, 300936

AVIATION ORDNANCE STOCK LIST NUMBER: 1-C-60


PUBLICATIONS: O. P. 865, O. P. 552, OCL V-54

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Tietzman Engineering Company	*E-3	**076031	A-N-B	5200250600	11-20-13	108A 37
Johnson Fare Box Company	*E-3	**076031	A-N-B	5200250600	11-20-13	108A 37

NOTE: Ends listed above are identical to Navy Mark 1, except that Navy furnishes ends complete with wire.
Note: *AAF type, **AAF drawing




MOTOR—TRIGGER

ARMY TYPE E-3 NAVY MARK 1

NAMES: Trigger motor

Motor—trigger, BAM—.30 and .50 caliber M2 (Navy)

Synchronizer trigger motor



DESCRIPTION: This trigger motor, mounted on the side of synchronized .30 and .50 caliber M2 fixed machine guns, is actuated by the timed impulses transmitted along the impulse wire from the impulse generator. It consists of a steel housing containing a slide, slide spring, plunger, plunger spring and an adjusting screw. The slide is beveled, and rides on a cam in the plunger. As the plunger is pulled forward, the slide is forced upward and into the gun. This trips the firing mechanism. An adjusting screw is used to vary the distance the slide may project into the gun.

CHARACTERISTICS:

Dimensions.....approximately 4½ by 1½ by 1¾ inches.

Weight.....approximately ¾ pound.

RELATIONSHIP OF PARTS: Used with:

Type E-8 gun synchronizer impulse generator, A. E. Reference Number 52-2700, and Army type E-3 impulse unit er.ds, A. E. Reference Number 52-2600.

ARMY

A. E. REFERENCE NUMBER: 52-2900

SPECIFICATIONS:

Detail.....93-24593

A. A. F. DRAWING NUMBER: 076023

TYPE DESIGNATION: E-3

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type E-3A trigger motor, A. E. Reference Number 52-3000.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: Mark 1

BU. ORD. DRAWING NUMBER: 178474

AVIATION ORDNANCE STOCK LIST NUMBER: 1-M-619

ORDNANCE PAMPHLET NUMBER: 865; 552

PROCUREMENT STATUS: Not under procurement for initial installation.

MODELS BELOW ARE INTERCHANGEABLE


Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
L. A. B. Corporation	*E-3	**076023	A-B	5200465600	11-20-11	108A/1
	*E-3A	**4283980	A-B	5200239040	11-20-15	108A/158
John Oster Manufacturing Company	*E-3	*076023	A-B	5200465600	11-20-11	108A/1
	*E-3A	**4283980	A-B	5200239040	11-20-15	108A/158
Argus Manufacturing Company	!Mark 1	††178474	N			
Crown Cork & Seal Company	†Mark 1, Mod. 1	††227622	N			§


Note: §Same as E-3A, except for 0.0017 inch difference in housing; *AAF type; **AAF drawing; †Navy type; ††Navy drawing.

SYNCHRONIZERS ARMAMENT—GUNNERY



MOTOR—TRIGGER

ARMY TYPE E-3A NAVY MARK 1 MOD. 1



NAMES: Trigger motor
Motor—trigger, BAM—.30 or .50 caliber M2 (Navy)
Synchronizer trigger motor

DESCRIPTION: This trigger motor, mounted on the side of synchronized .30 and .50 caliber M2 fixed machine guns, is actuated by the timed impulses transmitted along the impulse wire from the impulse generator. It consists of a steel housing containing a slide, slide spring, plunger, plunger spring and an adjusting screw. The slide is beveled, and rides on a cam in the plunger. As the plunger is pulled forward, the slide is forced upward and into the gun. This trips the firing mechanism. An adjusting screw is used to vary the distance the slide may project into the gun.

This trigger motor is the same type as the type E-3, except for modification of the plunger and slide. The length of the slide has been shortened 0.010 inch to prevent the gun from firing too close to the propeller blades. A relief has also been added to the top side of the plunger, to limit extent of over-travel.

CHARACTERISTICS:

Dimensions..... approximately 4½ by 1½ by 1¾ inches.
Weight..... approximately ¾ pound.

RELATIONSHIP OF PARTS: Used with:

Type E-8 gun synchronizer impulse generator, A. E. Reference Number 52-2700, and Army type E-3 impulse unit ends, A. E. Reference Number 52-2600.

ARMY

A. E. REFERENCE NUMBER: 52-3000

SPECIFICATIONS:

Detail..... 93-24593A
Superseded..... 93-24593

A. A. F. DRAWING NUMBER: 42B3980

TYPE DESIGNATION: E-3A

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: Mark 1 Mod. 1

BU. ORD. DRAWING NUMBER: 227622

AVIATION ORDNANCE STOCK LIST NUMBER: 1-M-621-200

ORDNANCE PAMPHLET NUMBER: 865; 552

ORDNANCE CIRCULAR LETTER: V-7-43

PROCUREMENT STATUS: Under procurement.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
L. A. B. Corporation	*E-3A	*42B3980	A-B	5200239040	11-20-15	108A/158	
	*E-3	*076023	A-B	5200465600	11-20-11	108A/1	
John Oster Manufacturing Company	*E-3A	*42B3980	A-B	5200239040	11-20-15	108A/158	
	*E-3	*076023	A-B	5200465600	11-20-11	108A/1	
Crown Cork & Seal Company	Mark 1, Mod. 1	227622	N				§
Argus Manufacturing Company	Mark 1	227622	N				

Note: §Same as E-3A except for 0.0017 inch difference in housing; *AAF type; **AAF drawing; §Navy type; ¶Bu. Ord. drawing.

**SOLENOID—GUN****ARMY TYPE E-4**

NAMES: Gun solenoid
Gun firing solenoid

Firing solenoid
Solenoid

DESCRIPTION: The Army type E-4 solenoid, used for electrical trigger control of remotely-placed synchronized machine guns, is attached to an impulse generator which is synchronized with the engine's propeller. A movable plunger in the solenoid is inserted in the locking pin of the impulse generator. When the solenoid is energized by pressing the firing switch in the cockpit, magnetic forces in the core of the solenoid coil attract the plunger, permitting timed mechanical impulses to be transmitted by the generator to a trigger motor. Impulses are generated as long as the solenoid is energized.

This solenoid is provided with a single pin push-on type electrical connector.

CHARACTERISTICS:

Dimensions	approximately 6 $\frac{3}{32}$ by 2 $\frac{3}{16}$ by 2 $\frac{3}{16}$ inches
Weight	approximately 2 $\frac{3}{4}$ pounds
Operating voltage	12 volts direct current
Current drain	16 amperes
Plunger stroke	$\frac{3}{16}$ inch
Electrical receptacle	Army part number 39A2389
Contact pin	Army part number 35A5243

RELATIONSHIP OF PARTS: Used with:

Army type E-4 impulse generator, which is furnished by the airplane contractor.

ARMY

A. E. REFERENCE NUMBER: 52-5600

SPECIFICATIONS:

Detail	94-24610
Superseded	24610B

TYPE DESIGNATION: E-4

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type E-6 solenoid. A. E. Reference Number 52-5650.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Star Machine Manufacturers, Incorporated	*E-4	**Detailed specification 94-24610	A-B	5200752550	11-1-30	105D, 87	
Pallak Manufacturing Company	*E-4	**Detailed specification 94-24610	A-B	5200752550	11-1-30	105D, 87	
Magnavox Company, Incorporated	*E-6	14D3G4	A-N-B	5200752600		105D, 92	†

†Has single pin, screw-on type electrical connector. Airplane connector must be replaced.

Note: *AAF type; **AAF drawing



GUN SOLENOIDS ARMAMENT—GUNNERY



SOLENOID—GUN

ARMY TYPE E-6 NAVY TYPES 12 AND 230-A

NAMES: Gun solenoid
Gun firing solenoid
Firing solenoid

Electric trigger control (Navy)
Solenoid

DESCRIPTION: This solenoid, used for electrical trigger control of remotely-placed synchronized machine guns, is attached to an impulse generator which is synchronized with the engine's propeller. A movable plunger in the solenoid is inserted in the locking pin of the impulse generator. When the solenoid is energized by pressing the firing switch, magnetic forces in the core of the solenoid coil surrounding it attract the plunger, permitting timed mechanical impulses to be transmitted by the generator to a trigger motor. Impulses are generated as long as the solenoid is energized.

This solenoid is provided with a single pin screw-on type electrical connector.

CHARACTERISTICS:

Dimensions	approximately 4 1/2 by 2 1/4 by 2 1/4 inches
Weight	approximately 2 3/4 pounds
Operating voltage	12 volts direct current
Current drain	16 amperes
Plunger stroke	0.122 inches
Electrical connector	AND10066-10S-2P

RELATIONSHIP OF PARTS: Used with:

Army type E-4 impulse generator, which is furnished by the airplane contractor.

ARMY

A. E. REFERENCE NUMBER: 52-5650

SPECIFICATIONS:

Detail	93-24743
Superseded	24743

TYPE DESIGNATION: E-6

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: 12

A. S. O. STOCK NUMBER: R86-S-60000

BU. AER. CIRCULAR LETTER: Aer-MA-12431-EG-F41-14

PROCUREMENT STATUS: Under procurement.

230-A

R86-S-60040

Aer-MA-12431-EG-F41-14

Under procurement.


MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Magnavox Company, Incorporated	*E-6	14D3G4	A-N-B	5200752600		105D 92	
Star Machine Manufacturers, Incorporated	*E-4	**Detailed specification 94-24610	A-B	5200752550	11-1-30	105D 87	†
Pallak Manufacturing Company	*E-4	**Detail specification 94-24610	A-B	5200752550	11-1-30	105D 87	†

†Has single pin push on type electrical connector. Airplane connector must be changed.
Note: *AAF type, **AAF drawing.



GUN SOLENOIDS ARMAMENT—GUNNERY



SOLENOID—GUN ARMY TYPE E-8

NAMES: Gun solenoid
Gun firing solenoid
Firing solenoid
Solenoid

DESCRIPTION: The Army type E-8 solenoid, used for electrical trigger control of remotely-placed synchronized machine guns, is attached to an impulse generator which is synchronized with the engine's propeller. A movable plunger in the solenoid is inserted in the locking pin of the impulse generator. When the solenoid is energized by pressing the firing switch, magnetic forces in the core of the solenoid coil attract the plunger, permitting timed mechanical impulses to be transmitted by the generator to a trigger motor. Impulses are generated as long as the solenoid is energized.

The electrical connector is a single pin screw-on type installed at a 30 degree angle.

CHARACTERISTICS:

Dimensions	approximately 5 ³ / ₄ by 2 ¹ / ₄ by 2 ¹ / ₄ inches
Weight	approximately 2 ³ / ₄ pounds
Operating voltage	12 volts direct current
Current drain	20 amperes
Plunger stroke	0.112 inches
Electrical connector	AND10066-10S-2P

RELATIONSHIP OF PARTS: Used with:

Army type E-4 impulse generator which is furnished by the airplane engine contractor.

ARMY

A. E. REFERENCE NUMBER: 52-5670

SPECIFICATIONS:

Detail:	93-24768
Superseded	24768

MFR.: Magnavox Company, Incorporated

MFR. DRAWING NUMBER: 1411G2

TYPE DESIGNATION: E-8

A. S. C. STOCK NUMBER: 5200752625

TECHNICAL ORDER NUMBER: 11-1-30

PRODUCTION STATUS: Under procurement. Supersedes Army type E-2A gun solenoid, A. E. Reference Number 52-5500.

SHIPPING DATA: Shipped as a complete unit including mating electrical connector plug AN3106-10S-2S.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 105D, 90



GUN SOLENOIDS ARMAMENT—GUNNERY



SOLENOID—GUN

ARMY TYPE G-10 NAVY TYPES 24 AND 240

NAMES: Gun solenoid
Gun firing solenoid
Firing solenoid
Solenoid

Electric trigger control (Navy)

DESCRIPTION: This solenoid, used for electrical trigger control of remotely placed synchronized machine guns, is attached to an impulse generator synchronized with the engine's propeller. A movable plunger in the solenoid is inserted in the locking pin of the impulse generator. When the solenoid is energized by pressing the firing switch, magnetic forces in the core of the solenoid coil attract the plunger, permitting timed mechanical impulses to be transmitted by the generator to a trigger motor. Impulses are generated as long as the solenoid is energized.

The electrical connector is the single pin screw-on type

CHARACTERISTICS:

Dimensions.....	approximately 5½ by 2¼ by 2¼ inches
Weight.....	approximately 2¾ pounds
Operating voltage.....	24 volts, direct current
Current drain.....	10 amperes
Plunger stroke.....	0.112 inches

RELATIONSHIP OF PARTS: Used with:

Army type E-8 impulse generator, A. E. Reference Number 52-2700.

ARMY

A. E. REFERENCE NUMBER: 52-6300

SPECIFICATIONS:

Detail.....	93-24740
Superseded.....	24740

TYPE DESIGNATION: G-10

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement. Supersedes Army Type G-2, A. E. Reference Number 52-5800.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: 24; 240

A. S. O. STOCK NUMBER: R-86-S-60010

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE


Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Magnavox Company	*G-10	14D3G1	A-N-B	5200752865	11-1-30	105D 51
	124; 240	14DG1	N-B			105D 51

Note: *AAF type; †Navy type



GUN SOLENOIDS ARMAMENT—GUNNERY



SOLENOID—GUN ARMY TYPE G-16

NAMES: Gun solenoid
Gun firing solenoid
Firing solenoid
Solenoid

DESCRIPTION: The Army type G-16 solenoid, used for electrical trigger control of remotely placed synchronized machine guns, is attached to an impulse generator which is synchronized with the engine's propeller. A movable plunger in the solenoid is inserted in the locking pin of the impulse generator. When the solenoid is energized by pressing the firing switch, magnetic forces in the core of the solenoid coil attract the plunger, permitting timed mechanical impulses to be transmitted by the generator to the trigger motor. Impulses are generated as long as the solenoid is energized. The electrical connector is a single pin screw-on type, installed at a 30 degree angle.

CHARACTERISTICS:

Dimensions.....	approximately 5¾ by 2¼ by 2¼ inches
Weight.....	approximately 3 pounds
Operating voltage.....	24 volts direct current
Current drain.....	10 amperes
Plunger stroke.....	0.174 inches

RELATIONSHIP OF PARTS: Used with:

Army type E-4 impulse generator, which is furnished by the aircraft engine contractor.

ARMY

A. E. REFERENCE NUMBER: 52-6375

SPECIFICATIONS:

Detail.....	93-24769
Superseded.....	24769

MFR.: Magnavox Company, Incorporated

MFR. DRAWING NUMBER: 14D11G1

TYPE DESIGNATION: G-16

A. S. C. STOCK NUMBER: 5200750000

TECHNICAL ORDER NUMBER: 11-1-30

PRODUCTION STATUS: Under procurement.


SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 105D/80

**SOLENOID—LEFT HAND GUN****ARMY TYPE C-4B NAVY MARK 3 MODIFICATION 2**

NAMES: Left hand gun solenoid
Gun firing solenoid
Firing solenoid
Solenoid

Electric trigger control (Navy)

DESCRIPTION: This solenoid, used for electrical trigger control of free-firing remotely-placed .30 and .50 caliber M2 machine guns, is mounted on the left hand side of the gun. A movable plunger is connected to the sear of the gun by a lever arm. When the solenoid is energized by pressing the firing switch in the cockpit, magnetic forces in the core of the solenoid coil attract the plunger, release the sear the fire the gun. Release of the firing switch opens the circuit and a spring returns the plunger to its original position, causing the gun to cease firing.

This solenoid is provided with a two pin push-on type connector.

CHARACTERISTICS:

Dimensions	approximately 6 $\frac{1}{4}$ by 2 $\frac{1}{4}$ by 2 $\frac{1}{4}$ inches.
Weight	approximately 27 $\frac{1}{8}$ pounds.
Operating voltage	12 volts direct current.
Current drain	18 amperes.
Plunger stroke	0.344 inches.

RELATIONSHIP OF PARTS: Used on:

.30 and .50 caliber M2 free firing machine guns, A. E. Reference Numbers 93-1420 and 93-1560.

ARMY

A. E. REFERENCE NUMBER: 52-5390

SPECIFICATIONS:

Detail	93-24682A
Superseded	93-24682

A. A. F. DRAWING NUMBER: 37B2301 (Supersedes Army Drawing Number 34B6051)

TYPE DESIGNATION: C-4B

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type C-4C Solenoid, A. E. Reference Number 52-5400.

SHIPPING DATA: Shipped as a complete unit.

(Continued on page 107)



SOLENOID—LEFT HAND GUN

(Continued from page 106)

NAVY


TYPE DESIGNATION: Mark 3 Mod. 2
 BU. ORD. DRAWING NUMBER: 189812
 AVIATION ORDNANCE STOCK LIST NUMBER: 1-C-5461
 ORDNANCE PAMPHLET NUMBER: 865
 PROCUREMENT STATUS: Not under procurement for initial installation.

ALL MODELS BELOW ARE INTERCHANGEABLE
 Models are used in services as noted in column 4
 A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Electric Auto Lite Company	*C-4B	**37B2301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector
	*C-4B	**37B2301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector
	*C-4C	**41B5099R	A-N-B	5200751960	11-1-30	105D 58	Has two pin screw-on type electrical connector Airplane connector must be changed.
	*C-4C	**41B5099L	A-N-B	5200751950	11-1-30	105D 57	Has two pin screw-on type electrical connector Airplane connector must be changed.
Pollak Manufacturing Company	*C-4B	**37B2301	A-N-B	5200751600	11-1-03	105D 45	Has two pin push-on type electrical connector
	*C-4B	**37B2301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector
Delco-Remy Division of General Motors Corporation	*C-4B	**37B2301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector.
	*C-4B	**37B2301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector.
	*C-4C	**41B5099R	A-N-B	5200751960	11-1-30	105D 58	Has two pin screw-on type electrical connector. Airplane connector must be changed.
	*C-4C	**41B5099L	A-N-B	5200751950	11-1-30	105D 57	Has two pin screw-on type electrical connector. Airplane connector must be changed.
Star Machine Manufacturers, Incorporated	*C-4B	**37B2301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector.
	*C-4B	**37B2301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector.

NOTE: Type C-4B and C-4C solenoids may be converted from right to left hand, and vice versa, by reversing the terminal positions.

Note: *AAF type; **AAF drawing.



SOLENOID—RIGHT HAND GUN

ARMY TYPE C-4B NAVY MARK 3 MOD. 2

NAMES: Right hand gun solenoid
Gun firing solenoid
Firing solenoid
Solenoid

Electric trigger control (Navy)

DESCRIPTION: This solenoid, used for electrical trigger control of free-firing remotely placed .30 and .50 caliber M2 machine guns, is mounted on the right hand side of the gun. A movable plunger is connected to the sear of the gun by a lever arm. When the solenoid is energized by pressing the firing switch in the cockpit, magnetic forces in the core of the solenoid coil attract the plunger, release the sear, and fire the gun. Release of the firing switch opens the circuit and a spring returns the plunger to its original position, causing the gun to cease firing.

This solenoid is provided with a two-pin push-on type connector.

CHARACTERISTICS:

Dimensions.....	approximately 6 $\frac{5}{8}$ " by 2 $\frac{1}{4}$ " by 2 $\frac{1}{4}$ " inches.
Weight.....	approximately 2 pounds 14 ounces.
Operating voltage.....	12 volts direct current.
Current drain.....	18 amperes.
Plunger stroke.....	0.344 inches.

RELATIONSHIP OF PARTS: Used on:

.30 and .50 caliber M2 free-firing machine guns, A. E. Reference Numbers 93-1420 and 93-1560.

ARMY

A. E. REFERENCE NUMBER: 52-5395

SPECIFICATIONS:

Detail.....	93-24682A
Superseded.....	93-24682

A. A. F. DRAWING NUMBER: 37E2301 (Supersedes Army Drawing Number 34B6051)

A. A. F. PART NUMBER: 37B2301-1

TYPE DESIGNATION: C-4B

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type C-4C solenoid, A. E. Reference Number 52-5450.

SHIPPING DATA: Shipped as a complete unit.

(Continued on page 109)

SOLENOID—RIGHT HAND GUN

(Continued from page 108)

NAVY

TYPE DESIGNATION: Mark 3 Mod. 2

BU. ORD. DRAWING NUMBER: 189812

AVIATION ORDNANCE STOCK LIST NUMBER: 1-C-5461

ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Not under procurement for initial installation.


ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Electric Auto Lite Company	*C-4B	**37B2301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector.
	*C-4B	**37B2301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector.
	*C-4C	**41B5099R	A-N-B	5200751960	11-1-30	105D 58	Has two pin screw-on type electrical connector. Airplane connector must be changed.
	*C-4C	**41B5099L	A-N-B	5200751950	11-1-30	105D 57	Has two pin screw-on type electrical connector. Airplane connector must be changed.
Pollak Manufacturing Company	*C-4B	**37B2301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector.
	*C-4B	**37B2301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector.
Delco-Remy Division of General Motors Corporation	*C-4B	**37B2301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector.
	*C-4B	**37B2301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector.
	*C-4C	**41B5099R	A-N-B	5200751960	11-1-30	105D 58	Has two pin screw-on type electrical connector. Airplane connector must be changed.
	*C-4C	**41B5099L	A-N-B	5200751950	11-1-30	105D 57	Has two pin screw-on type electrical connector. Airplane connector must be changed.
Star Machine Manufacturers, Incorporated	*C-4B	**37B2301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector.
	*C-4B	**37B2301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector.

NOTE: Type C-4B and C-4C solenoids may be converted from right to left hand or vice versa by reversing the terminal positions.

Note: *AAF type; **AAF drawing.





SOLENOID—LEFT HAND GUN

ARMY TYPE C-4C NAVY MARK 3 MODIFICATION 2

NAMES: Left hand gun solenoid
Gun firing solenoid
Firing solenoid
Solenoid

Electric trigger control (Navy)

DESCRIPTION: This solenoid, used for electrical trigger control of free-firing remotely placed .30 and .50 caliber M2 machine guns, is mounted on the left hand side of the gun. A movable plunger is connected to the sear of the gun by a lever arm. When the solenoid is energized by pressing the firing switch, magnetic forces in the core of the solenoid coil attract the plunger, release the sear and fire the gun. Release of the firing switch opens the circuit and a spring returns the plunger to its original position, causing the gun to cease firing.

This solenoid is provided with a two-pin screw-on type electrical connector.

CHARACTERISTICS:

Dimensions	approximately 6 $\frac{1}{2}$ by 2 $\frac{1}{4}$ by 2 $\frac{1}{4}$ inches.
Weight	approximately 27 $\frac{3}{8}$ pounds.
Operating voltage	12 volts direct current.
Current drain	18 amperes.
Plunger stroke	0.344 inches.

RELATIONSHIP OF PARTS: Used with:

.30 and .50 caliber M2 free firing machine guns, A. E. Reference Numbers 93-1420 and 93-1560.

ARMY

A. E. REFERENCE NUMBER: 52-5400

SPECIFICATIONS:

Detail	93-24682A
Superseded	93-24682

A. A. F. DRAWING NUMBER: 41E5099L

TYPE DESIGNATION: C-4C

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation.

SHIPPING DATA: Shipped as a complete unit.

(Continued on page 111)

SOLENOID—LEFT HAND GUN

(Continued from page 110)

NAVY

TYPE DESIGNATION: Mark 3 Mod. 2

BU. ORD. DRAWING NUMBER: 189812

AVIATION ORDNANCE STOCK LIST NUMBER: 1-C-5461


ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Not under procurement for initial installation.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Electric Auto Lite Company	*C-4C	**4185099L	A-N-B	5200751950	11-1-30	105D 57	Has two pin screw-on type electrical connector.
	*C-4C	**4185099R	A-N-B	5200751960	11-1-30	105D 58	Has two pin screw-on type electrical connector.
	*C-4B	**3782301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector. Airplane connector must be changed.
	*C-4B	**3782301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector. Airplane connector must be changed.
Delco-Remy Division of General Motors Corporation	*C-4C	**4185099L	A-N-B	5200751950	11-1-30	105D 57	Has two pin screw-on type electrical connector.
	*C-4C	**4185099R	A-N-B	5200751960	11-1-30	105D 58	Has two pin screw-on type electrical connector.
	*C-4B	**3782301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector. Airplane connector must be changed.
	*C-4B	**3782301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector. Airplane connector must be changed.
Pollak Manufacturing Company	*C-4B	**3782301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector. Airplane connector must be changed.
	*C-4B	**3782301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector. Airplane connector must be changed.
Star Machine Manufacturers, Incorporated	*C-4B	**3782301	A-N-B	5200751600	11-1-30	105D 45	Has two pin push-on type electrical connector. Airplane connector must be changed.
	*C-4B	**3782301-1	A-N-B	5200751900	11-1-30	105D 77	Has two pin push-on type electrical connector. Airplane connector must be changed.

NOTE: Type C-4C and C-4B solenoids may be converted from right to left hand or vice versa by reversing the terminal positions.
Note: *AAF type. **AAF drawing.

**SOLENOID—RIGHT HAND GUN****ARMY TYPE C-4C NAVY MARK 3 MODIFICATION 2**

NAMES: Right hand gun solenoid
Gun firing solenoid
Firing solenoid
Solenoid

Electric trigger control (Navy)

DESCRIPTION: This solenoid, used for electrical trigger control of free-firing remotely-placed .30 and .50 caliber M2 machine guns, is mounted on the right hand side of the gun. A movable plunger is connected to the sear of the gun, by a lever arm. When the solenoid is energized by pressing the firing switch, magnetic forces in the core of the solenoid coil attract the plunger, release the sear, and fire the gun. Release of the firing switch opens the circuit and a spring returns the plunger to its original position, causing the gun to cease firing.

This solenoid is provided with a two pin screw-on type connector.

CHARACTERISTICS:

Dimensions	approximately 6 $\frac{5}{8}$ " by 2 $\frac{1}{4}$ " by 2 $\frac{1}{4}$ " inches.
Weight	approximately 2 $\frac{3}{8}$ pounds.
Operating voltage	12 volts direct current.
Current drain	18 amperes.
Plunger stroke	0.344 inches.

RELATIONSHIP OF PARTS: Used with:

.30 and .50 caliber M2 free firing machine guns, A. E. Reference Numbers 93-1420 and 93-1560.

ARMY

A. E. REFERENCE NUMBER: 52-5450

SPECIFICATIONS:

Detail	93-24682A
Superseded	93-24682

A. A. F. DRAWING NUMBER 41B5099R

TYPE DESIGNATION: C-4C

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation.

SHIPPING DATA: Shipped as a complete unit.

(Continued on page 113)



SOLENOID—RIGHT HAND GUN

(Continued from page 112)

NAVY

TYPE DESIGNATION: Mark 3 Mod. 2

BU. ORD. DRAWING NUMBER: 189812

AVIATION ORDNANCE STOCK LIST NUMBER: 1-C-5461


ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Not under procurement for initial installation.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Electric Auto-Lite Company	*C-4C	**41B5099R	A-N-B	520075196C	11-1-30	105D 58	Two pin screw-on type electrical connector.
	*C-4C	**41B5099L	A-N-B	520075195C	11-1-30	105D 57	Two pin screw-on type electrical connector.
	*C-4B	**37B2301	A-N-B	520075160C	11-1-30	105D 45	Two pin push-on type electrical connector. Airplane connector must be changed.
	*C-4B	**37B2301-1	A-N-B	520075190C	11-1-30	105D 77	Two pin push-on type electrical connector. Airplane connector must be changed.
Delco-Remy Division of General Motors Corporation	*C-4C	**41B5099R	A-N-B	520075196C	11-1-30	105D 58	Two pin screw-on type electrical connector.
	*C-4C	**41B5099L	A-N-B	520075195C	11-1-30	105D 57	Two pin screw-on type electrical connector.
	*C-4B	**37B2301	A-N-B	520075160C	11-1-30	105D 45	Two pin push-on type electrical connector. Airplane connector must be changed.
	*C-4B	**37B2301-1	A-N-B	520075190C	11-1-30	105D 77	Two pin push-on type electrical connector. Airplane connector must be changed.
Pollak Manufacturing Company	*C-4B	**37B2301	A-N-B	520075160C	11-1-30	105D 45	Two pin push-on type electrical connector. Airplane connector must be changed.
	*C-4B	**37B2301-1	A-N-B	520075190C	11-1-30	105D 77	Two pin push-on type electrical connector. Airplane connector must be changed.
Star Machine Manufacturers, Incorporated	*C-4B	**37B2301	A-N-B	520076160C	11-1-30	105D 45	Two pin push-on type electrical connector. Airplane connector must be changed.
	*C-4B	**37B2301-1	A-N-B	520075190C	11-1-30	105D 77	Two pin push-on type electrical connector. Airplane connector must be changed.

NOTE: Type C-4C and C-4B solenoids may be converted from right to left hand or vice versa by reversing the terminal positions.
Note: *AAF type, **AAF drawing.

**SOLENOID—GUN****ARMY TYPE G-4A NAVY MARK 4 MODIFICATION 1**

NAMES: Gun solenoid Solenoid Firing solenoid
 Gun firing solenoid Electric trigger control (Navy)

DESCRIPTION: The G-4A solenoid, used for electrical trigger control of free-firing remotely-placed .50 caliber, M2 machine guns, is mounted on the side of the gun. A movable plunger is connected to the sear of the gun by a lever arm. When the solenoid is energized by pressing the firing switch in the cockpit, magnetic forces in the core of the solenoid coil attract the plunger, release the sear and fire the gun. Release of the firing switch opens the circuit and a spring returns the plunger to its original position, causing the gun to cease firing.

The connector is the single pin screw-on type.

CHARACTERISTICS:

Dimensions	approximately 6 by 2 $\frac{3}{4}$ by 2 $\frac{1}{4}$ inches.
Weight	approximately 2 $\frac{3}{4}$ pounds.
Operating voltage	24 volts direct current.
Current drain	8 amperes.
Plunger stroke	$\frac{3}{8}$ inch.
Electrical connector	Army part number 41A9227 (identical to AN3102-10S-2P)

RELATIONSHIP OF PARTS: Used with:
 .50 caliber M2 machine guns, A. E. Reference Number 93-1560.

ARMY

A. E. REFERENCE NUMBER: 52-6000

SPECIFICATIONS:

Detail	94-24620
Superseded	24620

A. A. F. DRAWING NUMBER: 41B3718

TYPE DESIGNATION: G-4A

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: Mark 4 Mod. 1

BU. ORD. DRAWING NUMBER: 300186

AVIATION ORDNANCE STOCK LIST NUMBER: 1-C-5461-15


PUBLICATIONS: OP. 865, OS. 2359

PROCUREMENT STATUS: Under procurement.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Webster Electric Company	*G-4A	**41B3718	A-N-B	5200752825	11-1-30	105D 17
	*G-9	**H41D10358	A-N-B	5200752755	11-1-30 11-20-12	105D 29
Delco-Remy Division of General Motors Corporation	*G-4A	**41B3718	A-N-B	5200752825	11-1-30	105D 17
Electric Auto Lite Company	*G-9	**H41D10358	A-N-B	5200752855	11-20-16 11-1-30 11-20-12	105D 29
Magnavox Company, Incorporated	*G-9	14D1G1	A-N-B	5200752855	11-20-16 11-1-30 11-20-12	105D 29

Note. *AAF type; **AAF drawing.



SOLENOID—GUN

ARMY TYPE G-8

NAMES: Gun solenoid Gun firing solenoid Firing solenoid Solenoid

DESCRIPTION: The Army type G-8 solenoid is used for electrically controlling the fire of a 20 mm cannon. The axis of the solenoid coil is perpendicular to the mounting flange and a movable plunger is connected to the sear of the gun's trigger mechanism by means of a shaft which protrudes through the solenoid mounting bracket. When the solenoid is energized by pressing the firing switch, magnetic forces in the core of the solenoid coil attract the plunger, release the sear, and fire the gun. Release of the firing switch opens the circuit and a spring returns the plunger to its original position, causing the gun to cease firing.

The electrical connector is the single pin screw-on type.

CHARACTERISTICS:

Dimensions	approximately 5 1/8 by 2 3/8 by 3 1/2 inches
Weight	approximately 4 1/8 pounds.
Operating voltage	24 volts direct current.
Current drain	10 amperes.
Plunger stroke	3/8 inch.
Electrical connector	AN3102-10S-2P.

RELATIONSHIP OF PARTS: Used with:
M1 or AN-M2 20-mm automatic guns.

ARMY

A. E. REFERENCE NUMBER: 52-6100

SPECIFICATIONS:

Detail	93-24702
Superseded	24702

A. A. F. DRAWING NUMBER: H41G9104

TYPE DESIGNATION: G-8

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type G-17 solenoid, A. E. Reference Number 52-6380 (now known as Ordnance type AN-M1).

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British


Manufacturer	Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	Reference Number	Remarks
Magnavox Company, Inc.	G-8	14D2G1	A-B	5200752845	11-1-30 11-1-37	105D 36	
	G-17 (AN-M1)	14D22G3	A-N-B			105D 93	\$
	Mark 6, Mod. 1 (AN-M1)	99028	N-B			105D 93	\$
Ordnance Office, War Department	AN-M1	C70766	A-N-B			105D 93	\$

[Complete with sear cover plate, Ordnance drawing number C70814.

Note: *AAF type. †Navy type.



GUN SOLENOIDS ARMAMENT—GUNNERY



SOLENOID—GUN

ARMY TYPE G-9 NAVY MARK 5 MODIFICATION 1

NAMES: Gun solenoid

Firing solenoid

Solenoid

Gun firing solenoid

Electric trigger control (Navy)

DESCRIPTION: This solenoid, used for electrical trigger control of free-firing .50 caliber M2 machine guns, is attached to a mounting flange which fits into slots in the side of the gun. A movable plunger, in a coil is connected to the sear of the trigger mechanism. When the solenoid is energized by pressing the firing switch, magnetic forces in the core of the solenoid coil attract the plunger, release the sear, and fire the gun. Release of the firing switch opens the circuit and a spring returns the plunger to its original position, causing the gun to cease firing.

The electrical connector is the single pin screw-on type.

CHARACTERISTICS:

Dimensions	approximately 4 1/8 by 2 by 2 1/2 inches.
Weight	approximately 2 1/2 pounds.
Operating voltage	24 volts direct current.
Current drain	4 1/4 amperes.
Plunger stroke	0.322 inches.
Electrical connector	AN3102-10S-2P.

RELATIONSHIP OF PARTS: Used with:

.50 caliber M2 machine guns, A. E. Reference Number 93-1560.

ARMY

A. E. REFERENCE NUMBER: 52-6200

SPECIFICATIONS:

Detail 93-24706-A

Superseded 93-24706

A. A. F. DRAWING NUMBER: H41D10358

TYPE DESIGNATIONS: G-9

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: Mark 5 Mod. 1

BU. ORD. DRAWING NUMBER: 300186

AVIATION ORDNANCE STOCK

LIST NUMBER: 1-C-5462-5

ORDNANCE PAMPHLET NUMBER 865

PROCUREMENT STATUS: Under procurement.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Model Identification	Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Electric Auto Lite Company	*G-9	**H41D10358	A-N-B	5200752855	11-20-16 11-1-30 11-20-12	105D 29	
Magnavox Company, Incorporated	*G-9	14D1G1	A-N-B	5200752855	11-20-16 11-20-12 11-1-30	105D 29	
Webster Electric Company	*G-9	**H41D10358	A-N-B	5200752855	11-20-16 11-20-12 11-1-30	105D 29	
	*G-4A	**41B3718	A-N-B	5200752825	11-1-30	105D 17	†
Delco-Remy Division of General Motors Corporation	*G-4A	**41B3718	A-N-B	5200752825	11-1-30	105D 17	†

† May be used where space permits. Approximately 2 inches longer than type G-9.
Note: *AAF type, **AAF drawing.



SOLENOID—GUN

ARMY TYPE G-11 NAVY MARK 7 MODIFICATION 1

NAMES: Gun solenoid
Gun firing solenoid

Firing solenoid Solenoid
Electric trigger control (Navy)

DESCRIPTION: The G-11 solenoid, used for the electrical trigger control of free firing .50 caliber, model M2 machine guns, is mounted on a bracket attached to the buffer tube of the gun. A movable plunger is connected to the trigger arm. When the solenoid is energized by pressing the firing switch, magnetic forces in the core of the solenoid coil attract the plunger, release the sear and fire the gun. Release of the firing switch opens the circuit and a spring returns the plunger to its original position, causing the gun to cease firing. The coil is connected to the battery system by a long conduit extension with a female connector on the free end. This connector is the single-prong screw-on type.

CHARACTERISTICS:

Dimensions	approximately 3 1/4 by 3 3/4 by 1 3/8 inches.
Weight	approximately 1 1/4 pounds.
Operating voltage	24 volts, direct current.
Current drain	5 1/2 amperes.
Plunger stroke	0.062 inches.

RELATIONSHIP OF PARTS: Used with:

Army type A-1 manual trigger, A. E. Reference Number 52-7075, on a .50 caliber M2 machine gun,
A. E. Reference Number 93-1560.

ARMY

A. E. REFERENCE NUMBER: 52-6350

SPECIFICATIONS:

Detail	93-24746
Superseded	24746

TYPE DESIGNATION: G-11

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: Mark 7 Mod. 1

BU. ORD. SKETCH NUMBER: 59030

AVIATION ORDNANCE STOCK LIST

NUMBER: 1-C-5463

ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Under procurement.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Webster Electric Company	*G-11	**93-24746 Detail Specification	A-B	5200752867	11-1-30	105D/59
Magnavox Company, Incorporated	*G-11 †Mark 7, Mod. 1	**14D5G3 ††99030	A-B N	5200752867	11-1-30	105D/59

Note: *AAF type, **AAF drawing; †Navy type; ††Navy drawing.



GUN SOLENOIDS ARMAMENT—GUNNERY



SOLENOID—GUN

ARMY TYPE G-13

NAMES: Gun solenoid
Gun firing solenoid
Firing solenoid
Solenoid

DESCRIPTION: The Army type G-13 solenoid, used for electrical trigger control of a remotely placed 37 mm automatic cannon, is mounted on a bracket at the rear of the gun. A movable plunger in the solenoid is linked to the firing mechanism. When the solenoid is energized by pressing a firing switch, magnetic forces in the core of the solenoid coil attract the plunger, release the sear, and fire the gun. Release of the firing switch opens the circuit and a spring returns the plunger to its original position, causing the gun to cease firing.

The electrical connector is the single pin screw-on type.

CHARACTERISTICS:

Dimensions	approximately 5 $\frac{5}{16}$ by 2 $\frac{1}{4}$ by 2 $\frac{1}{4}$ inches.
Weight	approximately 2 $\frac{1}{2}$ pounds.
Operating voltage	24 volts direct current.
Current drain	10 amperes.
Plunger stroke	0.250 inches.
Electrical connector	Army part number 41A9227 (identical to AN3102-10S-2P).

RELATIONSHIP OF PARTS: Used with:
37 mm M4 automatic gun, A. E. Reference Number 93-1280.

ARMY

A. E. REFERENCE NUMBER: 52-6360

SPECIFICATIONS:

Detail 24754

A. A. F. DRAWING NUMBER: 42B7343

TYPE DESIGNATION: G-13

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type G-15, A. E. Reference Number 52-6370.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4


A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Webster Electric Company	*G-13	**42B7343	A-B	5200752870	11-1-30	105D 196
Magnavox Company, Incorporated	*G-15	14D14G1	A-B	5200752890	11-1-30	105D 91

Note: *AAF type; **AAF drawing.



GUN SOLENOIDS ARMAMENT—GUNNERY



SOLENOID—GUN ARMY TYPE G-15

NAMES: Gun solenoid
Gun firing solenoid
Firing solenoid
Solenoid

DESCRIPTION: The Army type G-15 solenoid is used for electrical trigger control of a remote 37 mm automatic gun. The solenoid is mounted on a bracket at the rear of the cannon. When the solenoid is energized by depressing a firing switch, magnetic forces in the core of the coil attract a movable plunger, release the sear, and fire the gun. Release of the firing switch opens the solenoid circuit and a spring returns the plunger to its original position, causing the gun to cease firing.

The electrical connector is a single pin screw-on type.

CHARACTERISTICS:

Dimensions	approximately 5 by 2¼ by 2¼ inches.
Weight	approximately 2½ pounds.
Operating voltage	24 volts, direct current.
Current drain	10 amperes.
Plunger stroke	¾ inch.
Electrical connector	AN3102-10S-2P.

RELATIONSHIP OF PARTS: Used with:
37 mm M4 automatic gun, A. E. Reference Number 93-1280.

ARMY

A. E. REFERENCE NUMBER: 52-6370

SPECIFICATIONS:

Detail	93-24764
Superseded	24764

A. A. F. DRAWING NUMBER: Detail specification 93-24764

TYPE DESIGNATION: G-15

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Magnavox Company, Incorporated	*G-15	14D14G1	A-B	5200752890	11-1-30	105D/91
Webster Electric Company	*G-13	**42B7343	A-B	5200752870	11-1-30	105D/196

Note: *AAF type; **AAF drawing.



TRIGGER—ELECTRIC AN-M1

FORMER ARMY TYPE G-17 FORMER NAVY MARK 6, MOD. 1

NAMES: Electric trigger Gun solenoid Electric trigger control (Navy)
Solenoid—cannon Gun firing solenoid

DESCRIPTION: The Ordnance AN-M1 electric trigger, used for electrically controlling the fire of a 20-mm cannon, is mounted on a bracket on the bottom of the gun. The solenoid body is mounted perpendicular to a sear cover plate by means of a snap latch. A movable plunger protruding through the cover plate operates the sear of the gun trigger mechanism. When the solenoid is energized by pressing a firing switch, magnetic forces, in the core of the solenoid coil, attract the plunger, release the sear, and fire the gun. Release of the firing switch opens the circuit and a spring returns the plunger to its original position, causing the gun to cease firing.

The sear cover plate assembly and the solenoid body comprise the complete AN-M1 electric trigger, which was formerly known as the Army type G-17 gun firing solenoid, and the Navy Mark 6, Mod. 1 electric trigger control. The electrical connector is the single pin screw-on type.

CHARACTERISTICS:

Dimensions.....	approximately 8 $\frac{3}{8}$ by 2 $\frac{3}{4}$ by 2 $\frac{3}{8}$ inches.
Weight.....	approximately 5 $\frac{1}{4}$ pounds.
Operating voltage.....	24 volts direct current.
Current drain.....	10 amperes.
Plunger stroke.....	$\frac{5}{16}$ inch.
Electrical connector.....	AN3102-10S-2P.

RELATIONSHIP OF PARTS: Used with: M1 or AN-M2 20-mm automatic gun.

ARMY

A. E. REFERENCE NUMBER: 52-6380

SPECIFICATIONS:

Detail..... 24808 (type G-17)

A. A. F. DRAWING NUMBER: H43G10990

TYPE DESIGNATION: AN-M1

FORMER ARMY TYPE: G-17

PRODUCTION STATUS: Under procurement by Ordnance Office, War Department.

SHIPPING DATA: Normally shipped as an integral part of 20-mm gun (see A. E. Reference Number 93-1351 to 93-1355). Formerly shipped as a separate unit.

NAVY

TYPE DESIGNATION: AN-M1 (Formerly Mark 6 Mod. 1)

BU. ORD. DRAWING NUMBER: SK 99028

AVIATION ORDNANCE STOCK LIST NUMBER: Refer to chart.


ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Under procurement.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Av. Service Command Stock Number	Army Technical Order Number	British Reference Number	Aviation Ordnance Stock List Number	Remarks
Ordnance Office War Department	1AN-M1	C70766	A-N-B			105D 13	1-T-2890	
Magnavox Company, Incorporated	*G-17	14D22G3	A-N-B			105D 13	1-C-5460-75	
	*G-8	14D2G1	A-B	5200752845	11-1-30 11-1-37	105D 36		
	{Mark 6, Mod. 1 {AN-M1}	14D22G3	N				1-C-5460-5	

Note: {Only when height of this solenoid does not interfere with airplane structure; *Army-Navy standard type, *AAF type, {Navy type.



SUPPORT—GUN SIGHT IMAGE REFLECTOR

ARMY DRAWING NUMBER 41D4892

NAMES: Gun sight image reflector support
Gun sight reflector support
Reflector support

DESCRIPTION: The gun sight image reflector support, used with the N-3A fixed gun sight, fits directly around the main housing of the sight and is locked to it by two ears which are clamped together by a bolt and nut. This support provides a rigid mount for the gun sight image reflector, and allows replacement of the glass without disassembly of the entire sight. Cork gaskets prevent cracking of the reflector due to extremes of temperature and vibration.

CHARACTERISTICS:

Dimensions.....approximately $7\frac{3}{16}$ by $3\frac{1}{2}$ by $3\frac{5}{8}$ inches.
Weight.....approximately 1 pound.

RELATIONSHIP OF PARTS: Used with:

Army type N-3A fixed gun sight, A. E. Reference Number 52-4400, or Army type N-3B, fixed gun sight, A. E. Reference Number 52-4425.

ARMY

A. E. REFERENCE NUMBER: 52-6400

SPECIFICATIONS:

Detail.....93-24659B

Superseded.....93-24659A

A. A. F. DRAWING NUMBER: 41D4892

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, less reflector glass.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Ohio Pattern Works	*N-3A	**41D4892	A-B	5200858170	11-35-5	108B/63
	*N-5	**41D3024	A-B	5200858150		108B/79

Note: *For Sight AAF type, **AAF drawing.



SUPPORT—GUN SIGHT IMAGE REFLECTOR

ARMY DRAWING NUMBER 41D3024

NAMES: Gun sight image reflector support

DESCRIPTION: This gun sight image reflector support used with the N-3A fixed gun sight, fits directly around the main housing of the sight and is locked to it by two ears which are clamped together by a bolt and nut.

This support provides a rigid mount for the gun sight image reflector and allows replacement of the glass without disassembly of the entire sight. Cork gaskets prevent cracking of the reflector due to extreme temperature or vibration.

This support is the same as Army Drawing Number 41D4892 support used with the N-3A gunsight, except that it is $1\frac{3}{4}$ inches shorter.

CHARACTERISTICS:

Dimensions..... approximately $5\frac{1}{2}$ by $3\frac{3}{8}$ by $3\frac{3}{8}$ inches.
Weight..... approximately $\frac{1}{8}$ pound.

RELATIONSHIP OF PARTS: Used with:

Army type N-3A fixed gun sight, A. E. Reference Number 52-4400, or Army type N-3B fixed gun sight, A. E. Reference Number 52-4425.

ARMY

A. E. REFERENCE NUMBER: 52-6450

SPECIFICATIONS:

Detail..... 93-24687
Superseded..... 24687

A. A. F. DRAWING NUMBER: 41D3024

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Ohio Pattern Works	*N-5	**41D3024	A-B	5200858150		1088 79	
	*N-3A	**41D4892	A-B	5200858170	11-35-5	1088 63	$1\frac{3}{4}$ inches higher than type N-5 support

Note: *For sight AAF type, **AAF drawing



RHEOSTAT—VARIABLE RESISTANCE

ARMY TYPE D-1 NAVY—SEE BELOW

NAMES: Variable resistance rheostat
Control rheostat
Rheostat
Aircraft power rheostat

DESCRIPTION: This rheostat is a coil of resistance wire, so arranged that, when a knob handle is turned, an internal slider moves over the coil and varies the resistance, depending upon the portion still remaining in the circuit. This rheostat offers maximum resistance in the first ON position and gradually decreases the resistance with further movement of the knob.

CHARACTERISTICS:

Dimensions	approximately 2 $\frac{3}{8}$ by 2 $\frac{3}{8}$ by 1 $\frac{7}{8}$ inches.
Weight	approximately 5 ounces.
Rating	25 watts.
Resistance (maximum)	50 ohms.

RELATIONSHIP OF PARTS: Used with:

Army type N-6 and N-6A flexible gun sights, A. E. Reference Numbers 52-4500 and 52-4525.

ARMY

A. E. REFERENCE NUMBER: 52-4150

SPECIFICATIONS:

General	94-32008A
Detail	94-32010B
Superseded	94-32010A

TYPE DESIGNATION: D-1

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement. Future procurement will be in accord with specification AN-R-14. This covers superseding rheostat AN3155.

SHIPPING DATA: Shipped as a complete unit.

NAVY

N. A. F. DRAWING NUMBER: Refer to chart.

F. S. S. C. NUMBER: R-17-R-7110

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4


A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Ab Service Command Stock Number	British Reference Number
Clarostat Manufacturing Company	*D-1	56-41A	A-8	4200613500	10C 40
Naval Aircraft Factory		†11099-25-50	N		

Note: *AAF type; †Navy drawing



SWITCHES ARMAMENT—GUNNERY



SWITCH—CONTROL STICK GUN

ARMY TYPE B-1A

NAMES: Control stick gun switch
Gun control switch
Gun control stick switch
Control stick switch

DESCRIPTION: The Army type B-1A gun control switch, mounted on the control stick of an airplane, is used to electrically control the gun-firing solenoids of one or more synchronized or free firing machine guns. The switch consists of a rubber coated pistol grip handle and a trigger operated internal spring switch. When the switch is closed by pressing the trigger, the guns commence firing. When the trigger is released, the spring switch opens the electrical circuit and the guns stop firing.

CHARACTERISTICS:

Dimensions approximately $4\frac{1}{2}$ by $2\frac{1}{4}$ by $3\frac{3}{4}$ inches.
Weight approximately 1 pound.

RELATIONSHIP OF PARTS:

Installed on the pilot's control stick, which is contractor furnished equipment.

ARMY

A. E. REFERENCE NUMBER: 52-6475

SPECIFICATIONS:

Detail 93-24591
Superseded 24591

A. A. F. DRAWING NUMBER: 0169221 (Supersedes Army Drawing Number 0153322)

TYPE DESIGNATION: B-1A

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type B-5 control stick gun switch, A. E. Reference Number 52-6600.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Manufacturer's Specification	Remarks
Guardian Electric Manufacturing Company	*B-1A	**0169221	A-B	5200875500	105D 72		
	*B-5	US-220	A-N-B	5200875350	105D 75	G-29990	§
Aerial Machine and Tool Company	*B-1A	**0169221	A-B	5200875500	105D 72		
Air Associates, Incorporated	*B-1A	**0169221	A-B	5200875500	105D 72		
Cutler-Hammer Incorporated		NAF 1173-2	N			8985	§

Note: §Has additional button for bomb release switch; *AAF type; **AAF drawing; ;Navy drawing



SWITCH—CONTROL STICK GUN

ARMY TYPE B-5 NAVY—SEE BELOW

NAMES: Control stick gun switch Switch, trigger gun firing and
Gun control switch bomb release (Navy)
Control stick switch

DESCRIPTION: This gun control switch, mounted on the control stick of an airplane, is used to electrically control the gun firing solenoids of one or more synchronized or free-firing machine guns, and to release bombs. The control handle is of moulded plastic and has two spring switches inside it,—a trigger switch operated by the forefinger for firing guns, and a push button switch, operated by the thumb, for release of bombs.

CHARACTERISTICS:

Dimensions.....approximately 4¾ by 2¼ by 3¼ inches.

Weight.....approximately ¾ pound.

RELATIONSHIP OF PARTS:

Installed on pilot's control stick, which is contractor furnished equipment.

ARMY

A. E. REFERENCE NUMBER: 52-6600

SPECIFICATIONS:

Detail.....93-24708

Superseded.....24708

A. A. F. DRAWING NUMBER: 41B8946

TYPE DESIGNATION: B-5

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

N. A. F. DRAWING NUMBER: 1173-2

F. S. S. C. STOCK NUMBER: R-17-S-35510

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	Manufacturer's Specification	Remarks
Guardian Electric Manufacturing Company	*B-5	**41B8946	A-N-B	5200875350	105D 75	G-29990	
	*B-1A	**0169221	A-B	5200875500	105D 72		§
Cutler-Hammer, Incorporated		§:NAF1173-2	N			8895	
Aerial Machine and Tool Company	*B-1A	**0169221	A-B	5200875500	105D 72		§
Air Associates, Incorporated	*B-1A	**0169221	A-B	5200875500	105D 72		§

Note: §Has no bomb release control switch, *AAF type, **AAF drawing, §:Navy drawing.

**SWITCH—SINGLE POLE TOGGLE****AN PART NUMBER AN3022-2**

NAMES: Single pole toggle switch
 Toggle switch
 Switch
 Switch—three hole mounting single pole toggle

DESCRIPTION: The AN3022-2 single-pole, single-throw toggle switch is used in 12 and 24 volt airplane electrical systems. Positive snap action of a compression spring provides contact pressure when the switch is closed. When pushed to the open or off position, the same spring insures positive opening of the contacts.

This switch is supplied with a luminous tip lever upon special order; this is known as part number AN3022-2B.

CHARACTERISTICS:

Dimensions approximately 2 by 2 by $\frac{3}{4}$ inches.
 Weight approximately 2 ounces.

ARMY

A. E. REFERENCE NUMBER: 52-6650

SPECIFICATIONS:

General AN-S-20

AN DRAWING NUMBER: AN3022

AN PART NUMBER: AN3022-2

A. S. C STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY**SPECIFICATIONS:**

General AN-S-20

AN DRAWING NUMBER: AN3022

AN PART NUMBER: AN3022-2

A. S. O. STOCK NUMBER: Refer to chart.


PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number	A. S. O. Stock Number	Remarks
Cutler-Hammer, Incorporated		**AN3022-2	A-N-B	4200894750	105C 146	R17-S-28266-22	Non-luminous tip. Threaded mounting holes.
	*B-5A	*AN3015	A-N	42578201K4		R17-S-28260	Luminous tip.
Air Associates, Incorporated		**AN3022-2	A-N-B	4200894750	105C 146	R17-S-28266-22	Non-luminous tip. Threaded mounting holes.

Note: *AAF type; **Army-Navy standard drawing.



TRIGGER—MANUAL

ARMY TYPE A-1

NAMES: Manual trigger
Trigger assembly—gun firing

DESCRIPTION: This Army type A-1 trigger fits over the buffer tube of a .50 caliber M2 machine gun mounted in a turret, and is for emergency operation of the gun. In the event of power failure it operates the plunger of a type G-11 solenoid, enabling the gunner to fire the gun manually.

CHARACTERISTICS:

Dimensions approximately 2 $\frac{1}{4}$ by 3 $\frac{1}{4}$ by 1 $\frac{7}{8}$ inches.
Weight approximately $\frac{3}{4}$ pound.

RELATIONSHIP OF PARTS: Used with:
Army type G-11 solenoid, A. E. Reference Number 52-6350, when used on a .50 caliber M2 machine gun, A. E. Reference Number 93-1560.

ARMY

A. E. REFERENCE NUMBER: 52-7075

SPECIFICATIONS:

Detail 24823

MANUFACTURER: Magnavox Company, Incorporated

MANUFACTURER'S DRAWING NUMBER: 14D8

A. A. F. DRAWING NUMBER: 43A15180

TYPE DESIGNATION: A-1


A. S. C. STOCK NUMBER: 520C934150

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



VALVE—HYDRAULIC GUN CHARGING

ARMY TYPE A-1 NAVY—SEE BELOW

NAMES: Hydraulic gun charging valve
Gun charger valve
Charging valve
Valve

DESCRIPTION: The Army type A-1 hydraulic gun charging valve controls that pressure from the airplane hydraulic system which is used to charge machine guns located in a part of the airplane remote from the gunner. The valve can be used with .30 or .50 caliber M2 machine guns, or with the 20-mm M1 or AN-M2 guns. A safety device, incorporated in the valve, makes it impossible to fire the gun should the firing switch be accidentally closed after the gun is charged.

CHARACTERISTICS:

Dimensions approximately 6 1/4 by 4 1/4 by 3 inches.
Weight approximately 1 1/8 pounds.

RELATIONSHIP OF PARTS: Used with:

Bendix model F, 20-mm hydraulic gun charging cylinder, A. E. Reference Number 52-2300; Bendix model H, .30 caliber hydraulic gun charging cylinder, A. E. Reference Number 52-2400 or Bendix model C, .50 caliber hydraulic gun charging cylinder, A. E. Reference Number 52-2500.

ARMY

A. E. REFERENCE NUMBER: 52-8450

SPECIFICATIONS:

Detail 95-24739
Superseded 24739

MANUFACTURER: Bendix Products Division of Bendix Aviation Corporation.

MANUFACTURER'S DRAWING AND PART NUMBER: 76861

MANUFACTURER'S MODEL IDENTIFICATION: I

A. A. F. DRAWING NUMBER: H41B5344

TYPE DESIGNATION: A-1

A. S. C. STOCK NUMBER: 5200965700

TECHNICAL ORDER NUMBER 11-1-14

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

BU. ORD. DRAWING NUMBER: Assembly 332357, Installation 300202

AVIATION ORDNANCE STOCK LIST NUMBER: 1-V-430

ORDNANCE PAMPHLET NUMBER: 827

PROCUREMENT STATUS: Under procurement.

BRITISH

REFERENCE NUMBER: 108A/20



YOKE—GUN MOUNT ADAPTER

ARMY DRAWING NUMBER 41D6865

NAMES: Gun mount adapter yoke

Yoke

Adapter yoke

DESCRIPTION: This yoke provides an universal mounting for an Army type E-8 adapter carrying a .50 caliber, M2 machine gun. It consists of a steel "U" shaped frame welded to a hollow cylindrical stem having a peripheral groove. Two bushings are brazed on either leg of the "U" for receiving the bolt which connects the yoke to the adapter. Locking balls in a socket mounted in the airplane structure engage the groove and prevent the gun from being lifted out of the mount until properly released.

CHARACTERISTICS:

Dimensions.....approximately 10 $\frac{1}{4}$ by 3 $\frac{1}{8}$ by 2 $\frac{1}{4}$ inches.

Weight.....approximately 2 $\frac{3}{4}$ pounds.

RELATIONSHIP OF PARTS: Used with:

Army type E-8 gun mount adapter, A. E. Reference Number 52-1100.

ARMY

A. E. REFERENCE NUMBER: 52-9000

MANUFACTURER: Miller, Debrul, and Peters, Incorporated.

A. A. F. DRAWING NUMBER: 41D6865

A. S. C. STOCK NUMBER: 520092900

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



MACHINE GUN TURRETS

(LOCAL CONTROL TYPES)

The primary function of a machine gun turret is to provide an automatic means for a gunner to track a target and operate the guns. All turrets consist of an enclosure, a turret control system, and means of mounting, sighting, feeding, and firing the guns.

The locally-controlled turret is a rotatable structure in the form of a ball, dome, or rounded cylinder, in which one or more machine guns are mounted. The guns are sighted, controlled, and fired by a gunner within, above, or below the turret, depending upon its type and location in the airplane.

Turrets are designated according to their installation in the airplane, i.e.: upper turrets (on the upper deck), lower or belly turrets (under the fuselage), tail turrets, and nose turrets.


Upper turrets are non-retractable and have dome-like, transparent enclosures of plexiglas and metal under which the gunner sits or stands. The guns may be rotated through 360 degrees horizontally, through 90 degrees in elevation, or any simultaneous combination of the two movements.

Lower, or belly turrets can be either retractable or non-retractable. They may be spherical, with the gunner seated inside; or hemispherical, with the gunner kneeling inside the airplane above the turret. The enclosures are usually of metal and plexiglas. The guns may be rotated through 360 degrees horizontally, through 90 degrees in depression, or any simultaneous combination of the two movements.


Tail turrets are not retractable. The cylindrically-shaped enclosure includes steel armor plate protection, a cover of transparent plexiglas, and, in some installations, flat panes of bullet-proof glass. The gunner is seated completely inside the structure and controls the turret to move the guns through approximately 180 degrees horizontally, 90 degrees upward, and 90 degrees downward.



UPPER
TURRET



LOWER
TURRET




LOWER
BALL TURRET

(Continued on page 131)




MACHINE GUN TURRETS

(Continued from page 130)



Nose turrets are not retractable; two models have exactly the same design as tail turrets, and a third model resembles the dome-type lower turret. This turret consists of a metal enclosure and is located below the fuselage nose. The gunner, seated above the turret and inside the plexiglas nose of the airplane, can control the guns through 360 degrees horizontally and 90 degrees downward.

Control of turrets may be either electric or hydraulic. Electrical installations operate on either a 12 or 24 volt system. Hydraulically-controlled turrets are operated by hydraulic motors.



Electrically-operated turrets are rotated horizontally by means of a reversible electric motor and a system of gears. The guns are elevated or depressed by a second reversible electric motor and gear system which move a gun carriage attached to the turret. Both of these actions may take place at the same time. The gun sight moves with the gun. Hand grips control the electric motors and regulate the speed and direction of turret movement. These controls also have an electric button or trigger mechanism to fire the guns.

Hydraulically-operated turrets use a system of control valves or levers which may be opened, closed, or moved by handgrips. In some turrets, the flow of oil from an electrically-driven pump operates two hydraulic motors, each of which moves a gear train. One system of gears rotates the turret in a horizontal plane and the other elevates or depresses the guns, both actions taking place simultaneously.

Ammunition, in link belts, is stored in containers inside the turrets, and is automatically conveyed to the individual guns. After being fired, ejected cartridge cases and links fall to the floor or into a canvas bag attached to an ejector chute.

Automatic fire cut-off mechanisms, used with all turrets to prevent the gunner from shooting away part of his own airplane, interrupt the firing of the guns when they come in range of airplane parts such as tail surfaces, etc.




TURRET—UPPER GUN

ARMY TYPE A-1 NAVY—SEE BELOW

NAMES: Upper gun turret
Sperry upper turret
Deck turret—Sperry

Turret—upper local control
Upper gun turret—Sperry



(Continued on page 133)



TURRET—UPPER GUN

(Continued from page 132)

DESCRIPTION: The Army type A-1 turret, which mounts two .50 caliber M2 machine guns, is supported on a pivoted pedestal fastened to the floor of the airplane fuselage. It is operated by a Vickers electro-hydraulic unit which rotates the turret and moves the guns in elevation and depression. In the event of power failure, the turret can be moved manually by the gunner.

The gunner, seated in a canvas sling-type seat, is provided with foot rests which are attached to the turret support. He sights through an automatic compensating sight which is fixed to, and moves with the guns. The range adjustment for the sight is made with the thumbs, by twirling a notched wheel located between the control handles. The guns, charged individually by manual chargers, are fired by pressing a trigger switch on the control handles. One handle also has a safety switch which makes the turret operable.

Slip rings on the pedestal bring electric power into the turret for operation of the Vickers unit, gun-sight, interphone, trouble light, and other equipment. An outlet and controlling rheostat are provided inside the turret for the gunner's electrically heated suit.

CHARACTERISTICS:

Turret diameter.....approximately 40 $\frac{1}{4}$ inches.
Turret height.....approximately 90 inches.
Weight.....approximately 650 pounds.
Rotation in azimuth.....360 degrees.
Elevation of guns.....85 degrees above horizontal.
Operating voltage.....27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7600

TYPE DESIGNATION: A-1

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-1A upper turret, A. E. Reference Number 52-7625.

SHIPPING DATA: Shipped as a complete unit less guns, ammunition, and compensating sight.

NAVY

The Navy uses this turret on airplanes procured from the Army.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Ar Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification
Sperry Gyroscope Company	*A-1	644961	A-B	5400963150	11-45C-1	150A 3	S-698098
Steel Products Engineering Corporation	*A-1	SG1	A-B	5400963165	11-45C-1	150A 3	S-698098
	*A-1A	SP-2475	A-B	5400963165	11-45C-1	150A 3	SP-S-2475
Emerson Electric Manufacturing Company	*A-1	210860J	A-B	5400963165	11-45C-1	150A 3	S-698098
	*A-1A	SP-2475	A-B	5400963165	11-45C-1	150A 3	SP-S-2475

Note: *AAF type




TURRET—UPPER GUN

ARMY TYPE A-1A NAVY—SEE BELOW

NAMES: Upper gun turret
Sperry upper turret
Deck turret—Sperry

Turret—upper local control
Upper gun turret—Sperry



(Continued on page 135)



TURRET—UPPER GUN

(Continued from page 134)

DESCRIPTION: The Army type A-1A turret, which mounts two .50 caliber, M2 machine guns, is supported on a pivoted pedestal fastened to the floor of the airplane fuselage. It is operated by a Vickers electro-hydraulic unit which rotates the turret and moves the guns in elevation and depression. In the event of power failure, the turret can be moved manually by the gunner.

The gunner, seated in a canvas sling type seat with an attached cushion, is provided with adjustable foot rests fixed to the turret support. He sights through an automatic compensating sight which is fixed to, and moves with, the guns. A clear-vision glass sighting panel in the dome reduces visual distortion. The range adjustment for the sight is operated by a motorcycle-type grip located on the right hand control handle. The guns, charged individually by manual chargers, are fired by pressing a trigger switch on the turret control handles. The handles also have a safety switch which makes the turret operable.

Slip rings on the pedestal bring electric power into the turret for operation of the Vickers unit, gun-sight, interphone, trouble light, and other equipment. An outlet and controlling rheostat are provided inside the turret for the gunner's electrically heated flying suit.

CHARACTERISTICS:

Turret diameter	approximately 40 $\frac{3}{8}$ inches.
Turret height	approximately 90 inches.
Weight	approximately 650 pounds.
Rotation in azimuth	360 degrees.
Elevation of guns	from 5 degrees below to 85 degrees above horizontal.
Operating voltage	27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7625

TYPE DESIGNATION: A-1A

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, less gun, ammunition, and compensating sight.

NAVY

The Navy uses these turrets on airplanes procured from the Army.


ALL MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification
Steel Products Engineering Corporation	*A-1A	SP-2475	A-B	5400963165	11-45C-1	150A 3	SP-S-2475
	*A-1	SG1	A-B	5400963165	11-45C-1	.50A 3	S-69809B
Emerson Electric Manufacturing Company	*A-1A	SP-2475	A-B	5400963165	11-45C-1	150A 3	SP-S-2475
	*A-1	210960J	A-B	5400963165	11-45C-1	150A 3	S-69809B
Sperry Gyroscope Company	*A-1	644961	A-B	5400963150	11-45C-1	150A 3	S-69809B


Note: *AAF type

**TURRET—UPPER GUN**

ARMY TYPE A-3 NAVY—SEE BELOW

NAMES: Upper gun turret
Martin upper gun turret
Deck turret

Turret—upper gun—Martin
Upper gun turret—local control (British)



DESCRIPTION: The Army type A-3 turret, which mounts two .50 caliber M2 machine guns, is supported on a mounting ring rigidly fastened to the airplane. It is electrically operated by two amplidyne drives, one for rotation of the turret, the other for movement of the guns in elevation and depression. In the event of power failure, the turret can be moved manually by the gunner.

The gunner, seated in a bucket-type seat with a hinged bottom, is provided with an adjustable foot rest. Armor plate provides for his protection.

The target is sighted through a reflector type sight which moves with the guns. This sight is equipped with a sunshield, or glare eliminator, for sighting against the sun.

The guns, charged individually by manual chargers, are fired by pressing a trigger switch on the turret control handle. A safety switch on the same handle makes the turret electrically operable.

(Continued on page 137)

TURRET—UPPER GUN

(Continued from page 186)

CHARACTERISTICS:

Turret diameter.....	approximately 41 inches.
Turret height.....	approximately 60 inches.
Weight.....	approximately 463 pounds.
Rotation in azimuth.....	360 degrees.
Elevation of guns.....	85 degrees above horizontal.
Operating voltage.....	27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7400

TYPE DESIGNATION: A-3

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-3C upper turret, A. E. Reference Number 52-7475.

SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.


NAVY

The Navy uses these turrets on airplanes procured from the Army.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Used on Airplanes	Army Type	Remarks
The Glenn L. Martin Company	250CE2	R-312285	A-B	5400963142	11-45B-1	150A/1	165	B-26A	A-3	Uses block type fire interrupter.
	250CE3	R-312300	A-B	5400963142	11-45B-1	150A/2	165	B-24	A-3	Uses block type fire interrupter.
	250CE4	250CE40	A-B	5400963141	11-45BB-1	150A/22	212	B-26 series	A-3C	Uses profile type fire interrupter.
	250CE5	250CE50	A-B	5400963141-3	11-45BB-1	150A/11	212	B-24 series	A-3C	Uses profile type fire interrupter.
	250CE2A	R-314560	A-B	5400963144	11-45B-1	150A/7	165	B-26B	A-3A	*
	250CE6	R-371300	A-B	5400963144	11-45BA-1	150A/23	165B	B-26B-1	A-3A	Uses profile type fire interrupter.
	250CE3A	R-312310	A-B	5400963143-3	11-45B-1	150A/9	165B	B-24 series	A-3B	Uses block type fire interrupter.
	250CE7	250CE70	A	5400963149-3	11-45BB-1		212	B-34, B-37	A-3C	Uses profile type fire interrupter.
	250CE11	250CE110	A	5400963149-43	11-45BB-1		212	B-40	A-3C	Uses profile type fire interrupter.
	250CE8	R-371400	A-B	5400963149-5	11-45BC-1	150A/8	258	A-30	A-11	Uses profile type fire interrupter.
	250CE8A	R-371400	A-B	5400963149-5	11-45BD-1	150A/24	264	A-30	A-11	Uses block type fire interrupter.
	250CE10	250CE100	A	5400963149-7			281	A-20	A-11	Uses profile type fire interrupter.
	250CE1	R-266800	A-B	5400963145	11-45B-2	150A/32	165A	B-26	A-14	Uses block type fire interrupter.


*Some turrets use block type fire interrupters, others use profile type fire interrupters.

**TURRET—UPPER GUN**

ARMY TYPE A-3B NAVY—SEE BELOW

NAMES: Upper gun turret
 Martin upper gun turret
 Deck turret—Martin

Turret—upper gun—Martin
 Upper gun turret—local control (British)



DESCRIPTION: The Army type A-3B upper gun turret, which mounts two .50 caliber M2 machine guns, is supported on a mounting ring rigidly fastened to the airplane. It is electrically operated by two amplidyne drives, one for rotation of the turret, the other for movement of the guns in elevation and depression. In the event of power failure, the turret can be moved manually by the gunner.

The gunner, seated in a bucket-type seat with a hinged bottom, is provided with an adjustable foot rest. Armor plate provides for his protection.

The target is sighted through a reflector type sight, which moves with the guns. This sight is equipped with a sunshield, or glare eliminator, for sighting against the sun.

The guns, charged individually by manual chargers, are fired by pressing a trigger switch on the turret control handle. A safety switch on the same handle makes the turret electrically operable.

A swivel plug below the turret, on the floor of the airplane, is used for oxygen and interphone connections. An outlet and controlling rheostat are provided inside the turret for the gunner's electrically heated suit. A slip ring fastened to the turret mounting ring transmits electric power for operation.

(Continued on page 141)



TURRET—UPPER GUN

(Continued from page 140)

CHARACTERISTICS:

Turret diameter.....approximately 41 inches.
 Turret height.....approximately 60 inches.
 Weight.....approximately 466 pounds.
 Rotation in azimuth.....360 degrees.
 Elevation of guns.....85 degrees above horizontal.
 Operating voltage.....27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7450

TYPE DESIGNATION: A-3B

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-3C upper turret, A. E. Reference Number 52-7475.


SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.

NAVY

The Navy uses these turrets on airplanes procured from the Army.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Used on Airplanes	Army Type	Remarks
The Glenn L. Martin Company	250CE3A	R-312310	A-B	5400963143-3	11-45B-1	150A 9	165B	B-24 series	A-3B	Uses block type fire interrupter.
	250CE2A	R-314560	A-B	5400963144	11-45B-1	150A 7	165	B-26B	A-3A	Some turrets use block type fire interrupter. Others use profile type.
	250CE6	R-371300	A-B	5400963144	11-45BA-1	150A 23	165B	B-26B-1	A-3A	Uses profile type fire interrupter.
	250CE4	250CE40	A-B	5400963141	11-45BB-1	150A 22	212	B-26 series	A-3C	Uses profile type fire interrupter.
	250CE5	250CE50	A-B	5400963141-3	11-45BB-1	150A 11	212	B-24 series	A-3C	Uses profile type fire interrupter.
	250CE2	R-312285	A-B	5400963142	11-45B-1	150A 1	165	B-26A	A-3	Uses block type fire interrupter.
	250CE3	R-312300	A-B	5400963142	11-45B-1	150A 2	165	B-24	A-3	Uses block type fire interrupter.
	250CE7	250CE70	A	5400963149-3	11-45BB-1		212	B-34; B-37	A-3C	Uses profile type fire interrupter.
	250CE11	250CE110	A	5400963149-43	11-45BB-1		212	B-40	A-3C	Uses profile type fire interrupter.
	250CE8	R-371400	A-B	5400963149-5	11-45BC-1	150A 8	258	A-30	A-11	Uses profile type fire interrupter.
	250CE8A	R-371400	A-B	5400963149-5	11-45BD-1	150A 24	264	A-30	A-11	Uses block type fire interrupter.
	250CE10	250CE100	A	5400963149-7			281	A-20	A-11	Uses profile type fire interrupter.
	250CE1	R-266800	A-B	5400963145	11-45B-2	150A 32	165A	B-26	A-14	Uses block type fire interrupter.




TURRET—UPPER GUN

ARMY TYPE A-14 NAVY—SEE BELOW

NAMES: Upper gun turret
Martin upper gun turret
Deck turret—Martin

Turret—upper gun—Martin
Upper gun turret—local control (British)



DESCRIPTION: The Army type A-14 turret, which mounts two .50 caliber M2 machine guns, is supported on a mounting ring rigidly fastened to the airplane. It is electrically operated by two amplidyne drives; one for rotation of the turret, the other for movement of the guns in elevation and depression. In the event of power failure, the turret can be moved manually by the gunner.

The gunner, seated in a bucket-type seat with a hinged bottom, is provided with an adjustable foot rest. Armor plate provides for his protection. The target is sighted through a reflector type sight which moves with the guns. This sight is equipped with a sunshield, or glare eliminator, for sighting against the sun.

The guns, charged individually by manual chargers, are fired by pressing a trigger switch on the turret control handle. A safety switch on the same handle makes the turret electrically operable.

(Continued on page 147)

TURRET—UPPER GUN

(Continued from page 142)

CHARACTERISTICS:

Turret diameter.....approximately 41 inches.
 Turret height.....approximately 60 inches.
 Weight.....approximately 564 pounds.
 Rotation in azimuth.....360 degrees.
 Elevation of guns.....from 3 degrees below to 85 degrees above
 horizontal.
 Operating voltage.....27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7475

TYPE DESIGNATION: A-3C

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.


NAVY

The Navy uses these turrets on airplanes procured from the Army.


MODELS BELOW ARE INTERCHANGEABLE
 Models are used in services as noted in column 4
 A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Used on Airplanes	Army Type	Remarks
The Glenn L. Martin Company	250CE4	250CE40	A-B	5400963141	11-45BB-1	150A 22	212	B-26 series	A-3C	Uses profile type fire interrupter.
	250CE5	250CE50	A-B	5400963141-3	11-45BB-1	150A 11	212	B-24 series	A-3C	Uses profile type fire interrupter.
	250CE7	250CE70	A	5400963149-3	11-45BB-1		212	B-34; B-37	A-3C	Uses profile type fire interrupter.
	250CE11	250CE110	A	5400963149-43	11-45BB-1		212	B-40	A-3C	Uses profile type fire interrupter.
	250CE2	R-312285	A-B	5400963142	11-45B-1	150A 1	165	B-26A	A-3	Uses block type fire interrupter.
	250CE3	R-312300	A-B	5400963142	11-45B-1	150A 2	165	B-24	A-3	Uses block type fire interrupter.
	250CE2A	R-314560	A-B	5400963144	11-45B-1	150A 7	165	B-26B	A-3A	*
	250CE6	R-371300	A-B	5400963144	11-45BA-1	150A 23	165B	B-26B-1	A-3A	Uses profile type fire interrupter.
	250CE3A	R-312310	A-B	5400963143-3	11-45B-1	150A 9	165B	B-24 series	A-3B	Uses block type fire interrupter.
	250CE8	R-371400	A-B	5400963149-5	11-45BC-1	150A 8	258	A-30	A-11	Uses profile type fire interrupter.
	250CE8A	R-371400	A-B	5400963149-5	11-45BD-1	150A 24	264	A-30	A-11	Uses block type fire interrupter.
	250CE10	250CE100	A	5400963149-7			281	A-20	A-11	Uses profile type fire interrupter.
	250CE1	R-266800	A-B	5400963145	11-45B-2	150A 32	165A	B-26	A-14	Uses block type fire interrupter.

*Some turrets use block type fire interrupters; others use profile type fire interrupters.



TURRET—UPPER GUN
ARMY TYPE A-4 NAVY—SEE BELOW



NAMES: Upper gun turret
Deck turret—Bendix

Bendix upper gun turret
Upper turret—local control (British)

DESCRIPTION: The Army type A-4 upper turret, which mounts two .50 caliber M2 machine guns, is supported on a central column fastened to the floor of the airplane fuselage. It is electrically operated by two drive motors; one for rotation of the turret, the other for movement of the guns in elevation

(Continued on page 149)



TURRET—UPPER GUN

(Continued from page 138)

and depression. The power for the motors is supplied through two sets of relays, which interrupt the current flow and provide slow or fast operation. In the event of electrical failure, the turret can be moved by the gunner with a hand-crank.

The guns, charged simultaneously by individual hydraulic chargers, are fired by pressing a trigger switch on the turret control handle. A safety switch on the same handle makes the turret electrically operable.

The gunner is seated on a bicycle type seat within the turret, and sights the target through a non-fogging periscopic sight. The eyepiece of this sight remains fixed, while the periscope's prism moves with the guns.

Collector rings on the central column provide hydraulic, oxygen, and electrical connections to the turret.

CHARACTERISTICS:

Turret diameter	approximately 39 $\frac{1}{8}$ inches.
Turret height	approximately 85 $\frac{1}{8}$ inches.
Weight	approximately 525 pounds.
Rotation in azimuth	360 degrees.
Elevation of guns	87 degrees above horizontal.
Operating voltage	27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7500

TYPE DESIGNATION: A-4

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-9A, upper turret, A. E. Reference Number 52-7910.

SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.

NAVY

The Navy uses these turrets on airplanes procured from the Army.


MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	As Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Army Type	Remarks
Bendix Products Division	L	78001	A-B	5400963140		150A 5	78001A	A-4	
	N	80701	A-B	5400963035	11-45A-3	150A 20	ES0386	A-10	*


*Operated by amplidyne.



MACHINE GUN TURRETS ARMAMENT—GUNNERY



TURRET—UPPER GUN ARMY TYPE A-9 NAVY—SEE BELOW



NAMES: Upper gun turret
Deck turret—Bendix

Bendix upper gun turret
Upper turret—local control (British)

(Continued on page 151)



TURRET—UPPER GUN

(Continued from page 150)

DESCRIPTION: The Army type A-9 turret, which mounts two .50 caliber M2 machine guns, is supported on a central column fastened to the floor of the airplane fuselage. It is electrically operated by two amplidyne drives, one for rotation of the turret, the other for movement of the guns in elevation and depression. In the event of power failure, the turret can be moved manually by the gunner with a hand-crank.

The guns, charged simultaneously by individual hydraulic chargers, are fired by pressing a trigger switch on the turret control handle. A safety switch on the same handle makes the turret operable.

The gunner is seated on a bicycle-type seat within the turret and views the target through a non-fogging periscopic sight. The eyepiece of this sight remains fixed while the periscope's prism moves with the guns.

Collector rings on the central column provide hydraulic, oxygen, and electrical connections to the turret.

CHARACTERISTICS:

Turret diameter	approximately 39 $\frac{1}{8}$ inches.
Turret height	approximately 85 $\frac{1}{8}$ inches.
Weight	approximately 525 pounds.
Rotation in azimuth	360 degrees
Elevation of guns	84 degrees above horizontal.
Operating voltage	27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7900

TYPE DESIGNATION: A-9

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-9A, upper turret, A. E. Reference Number 52-7910.

SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.


NAVY

The Navy uses these turrets on airplanes procured from the Army.


MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Army Type	Remarks
Bendix Products Division	N	80701	A-B	5400963035	11-45A-3	150A 20	ES0386	A-9	
	A	82000	A-B	5400963064	11-45A-3	150A 30		A-9A	
	L	78001	A-B	5400963140		150A/5	78001A	A-4	*

*No amplidyne, uses electric motors



TURRET—UPPER GUN
ARMY TYPE A-9A NAVY—SEE BELOW



NAMES: Upper gun turret
Deck turret—Bendix

Bendix upper gun turret
Upper turret—local control (British)

(Continued on page 163)



TURRET—UPPER GUN

(Continued from page 152)

DESCRIPTION—The Army type A-9A upper turret, which mounts two .50 caliber, M2 machine guns, is supported on a central column fastened to the floor of the airplane fuselage. It is electrically operated by two amplidyne drives, one for rotation of the turret, the other for movement of the guns in elevation and depression. In the event of power failure, the turret can be moved manually by the gunner with a hand-crank.

The guns, charged mechanically by individual foot-operated chargers, are fired by pressing a trigger switch on the turret control handle. A safety switch on the same handle makes the turret electrically operable.

The gunner is seated on an adjustable, folding, bicycle-type seat, and views the target through a reflector sight. A clear-vision glass sighting panel in the dome prevents visual distortion.

Collector rings on the central column provide oxygen and electrical connections to the turret.

CHARACTERISTICS:

Turret diameter	approximately 39 $\frac{1}{16}$ inches.
Turret height	approximately 85 $\frac{1}{16}$ inches.
Weight	approximately 525 pounds.
Rotation in azimuth	360 degrees.
Elevation of guns	84 degrees above horizontal.
Operating voltage	27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7910

TYPE DESIGNATION: A-9A

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.


NAVY

The Navy uses these turrets on airplanes procured from the Army.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Army Type	Remarks
Bendix Products Division	A	82000	A-B	5400963175	11-45A-3	150A 30		A-9A	
	L	78001	A-B	5400963140		150A 5	78001A	A-4	*
	N	80701	A-B	5400963035	11-45A-3	150A 20	ES0386	A-9	

*No amplidyne. Electric motor driven.



TURRET—UPPER TRAINING
ARMY TYPE A-8

NAMES: Upper training turret
Crocker-Wheeler training turret

Training turret



(Continued on page 155)



TURRET—UPPER TRAINING

(Continued from page 154)

DESCRIPTION: The Army type A-8 turret, which mounts two .30 caliber M2 machine guns, is supported on a "T" structure fastened to the floor of the airplane fuselage. It is electrically operated by two Maxson electric drives, one for rotation of the turret, the other for the movement of the guns in elevation and depression.

The gunner, seated on an adjustable bicycle-type seat, has a fixed foot rest extending from the central column of the "T". He sights through a reflector type sight which is fixed to, and moves with, the guns.

The guns, charged individually by manual chargers, are fired by pressing a trigger switch on the turret control handle. This handle also has a safety switch to make the turret electrically operable.

Slip rings at the base of the "T" bring electric power into the turret for operation of the turret drives, gun sight, interphone, and other equipment. An outlet and controlling rheostat for the gunner's electrically-heated suit are located inside the turret.

This turret is used for training purposes only. When mounted in an airplane, only one gun is used, a camera being installed in the other gun position. The camera, operating from the same trigger as the gun, photographs the target to record the number of hits and the fire pattern.

CHARACTERISTICS:

Turret diameter	approximately 35 inches.
Turret height	approximately 79 $\frac{1}{2}$ inches.
Weight	approximately 335 pounds.
Rotation in azimuth	360 degrees.
Elevation of guns	90 degrees above horizontal.
Operating voltage	27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7700

TYPE DESIGNATION: A-8

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Alt Service Command Stock Number	Army Technical Order Number	Manufacturer's Specification
Crocker-Wheeler Manufacturing Company Division of Joshua Hendy Iron Works	*A-8	T-5500-N	A	5400963200	11-45F-1	EST-1002
National Mineral Company	*A-8	NMT-5500-N	A	5400963200	11-45F-1	EST-1002

Note: *AAI type.




TURRET—LOWER GUN

ARMY TYPE A-2 NAVY—SEE BELOW

NAMES: Lower gun turret
Lower ball turret—local control
Belly turret—ball type

Sperry lower ball turret
Turret—lower local control
Lower gun turret—local control (British)



(Continued on page 157)



TURRET—LOWER GUN

(Continued from page 156)

DESCRIPTION: The Army type A-2 lower gun turret, which mounts two .50 caliber, M2 machine guns, is supported by a framework suspended from a self-aligning bearing fastened inside the top of the fuselage. A Vickers electro-hydraulic unit enables the turret to rotate in any direction. In the event of power failure, the turret can be moved manually by the gunner.

The guns, which are fixed in relation to the turret, are charged individually by manual chargers, and are fired by pressing a button on the control handles.

The gunner is housed inside the spherical structure comprising the turret enclosure, and armor plate provides for his protection. He sights through an automatic compensating sight, and the turret, guns, sight, and gunner move as a unit while tracking the target.

Slip rings in the hangar assembly bring electrical power into the turret for operation of the Vickers unit, gun-sight, interphone, trouble-light, and other equipment. An outlet and controlling rheostat are provided inside the turret for the gunner's electrically heated suit.

CHARACTERISTICS:

Turret ring diameter	approximately 46 $\frac{1}{2}$ inches.
Turret height	approximately 101 inches.
Weight	approximately 850 pounds.
Rotation in azimuth	360 degrees.
Rotation in elevation	85 degrees from the vertical.
Operating voltage	27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7200

TYPE DESIGNATION: A-2

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, less guns, ammunition, and compensating sight.


NAVY

The Navy uses these turrets on airplanes procured from the Army.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Remarks
Sperry Gyroscope Company	*A-2	645796	A-B	5400963090	11-45C-1	150A 4	S-69808	
Emerson Electric Manufacturing Company	*A-2	205955M	A-B	5400963065	11-45C-1	150A 4	S-69808	
Briggs Manufacturing Company	*A-2	1300	A-B	5400963065	11-45C-1	150A 4	S-69808	
	*A-13	30000	A-B	5400963110		150A 31	BR-BT-7R	§

§Retractable turret. The ball of this turret is identical with Army type A-2 ball, but a conversion kit is required to convert the hangar assembly. Uses different fire interrupter.
Note: *AAF type.

**TURRET—RETRACTABLE LOWER GUN**

ARMY TYPE A-13 NAVY—SEE BELOW

NAMES: Retractable lower gun turret
Turret—lower gun—retractable—44 inch ball
Briggs retractable ball turret

Lower gun turret—local control—retractable
(British)
Lower ball local control turret—retractable

DESCRIPTION: The Army type A-13 turret, which mounts two .50 caliber M2 machine guns, is supported by a framework suspended from an hydraulic cylinder inside the top of the fuselage. The cylinder piston moves up and down through a 28-inch stroke to raise or lower the turret. In case of failure of the turret hydraulic system, two pins on the flange of the cylinder guide provide auxiliary means of

(Continued on page 159)



TURRET—RETRACTABLE LOWER GUN

(Continued from page 158)

retraction if fastened to the bomb hoist. A Vickers electro-hydraulic unit enables the turret to rotate in any direction. In the event of power failure, the turret can be moved manually by the gunner.

The guns, which are fixed in relation to the turret, are charged individually by manual chargers, and fired by pressing a button on the turret control handle.

The gunner is housed entirely inside the spherical structure comprising the turret enclosure, and armor plate provides for his protection. He sights through an automatic compensating sight and the turret, guns, sight, and gunner move as a unit while tracking the target.

Slip rings in the hangar assembly bring electrical power into the turret for operation of the Vickers unit, gunsight, interphone, trouble-light, and other equipment. An outlet and controlling rheostat inside the turret are provided for the gunner's electrically heated suit.

CHARACTERISTICS:

Turret ring diameter	approximately 47 $\frac{1}{4}$ inches.
Turret height	approximately 131 $\frac{3}{8}$ inches extended; 104 $\frac{1}{8}$ inches retracted.
Weight	approximately 780 pounds.
Rotation in azimuth	360 degrees.
Rotation in elevation	85 degrees from vertical.
Operating voltage	27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-8050

TYPE DESIGNATION: A-13

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, less guns, ammunition, and compensating sight.



NAVY

The Navy uses this turret on airplanes procured from the Army.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Remarks
Briggs Manufacturing Company	A-13	30000	A-B	5400963110		150A 31	BR-BT-7R	
	A-2	1300	A-B	5400963065	11-45C-1	150A 4	S-69808	§
Sperry Gyroscope Company	A-2	645796	A-B	5400963090	11-45C-1	150A 4	S-69808	§
Emerson Electric Manufacturing Company	A-2	205955M	A-B	5400963065	11-45C-1	150A 4	S-69808	§

Note: §The ball of this turret is identical with Army type A-13 but a conversion kit is required to convert the hangar assembly. Uses a different fire interrupter.
Note: *AAF type.


TURRET—LOWER GUN
ARMY TYPE A-5 NAVY—SEE BELOW


NAMES: Lower gun turret
Retractable lower gun turret—Bendix
Bendix lower gun turret

Power operated lower gun turret
Turret—lower gun—retractable

DESCRIPTION: The Army type A-5 turret, a retractable structure mounting two .50 caliber M2 machine guns, is supported from a central column by four spider arms. This turret is located beneath the belly of the fuselage. It is electrically operated by two drive motors, one for rotation of the turret, the other

(Continued on page 161)



TURRET—LOWER GUN

(Continued from page 160)

for movement of the guns in elevation and depression. The power for the motors is supplied through two sets of interrupter relays, which interrupt the current flow and provide slow or fast operation. Provision is made for manual operation in the event of electrical power failure. The motor drive normally providing power for horizontal movement is used to retract the turret.

The gunner is in a kneeling position while sighting on the target, and his chest is supported by an adjustable pad. He sights through a non-fogging periscopic sight. The eyepiece of the sight remains fixed while the periscope's prism moves with the guns throughout their range of elevation.

The guns, charged simultaneously by individual hydraulic gun chargers, are fired by pressing a trigger switch on the control handle. A safety switch on the same handle makes the turret electrically operable.

Collector rings on the central column provide hydraulic and electrical connections to the turret.

CHARACTERISTICS:

Turret diameter	approximately 39 $\frac{1}{2}$ inches.
Turret height	approximately 59 $\frac{3}{8}$ inches (with chest pad in lower position and turret extended).
Weight	approximately 497 pounds.
Rotation in azimuth	360 degrees.
Depression of guns	90 degrees below horizontal.
Operating voltage	24 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7100

TYPE DESIGNATION: A-5

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-10 lower turret, A. E. Reference Number 52-7950.

SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.

NAVY

The Navy uses these turrets on airplanes procured from the Army.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Army Type	Remarks
Bendix Products Division	J	76860	A-B	5400963070	11-45A-1	150A 6	76860-A	A-5	
	K	79800	A-B	5400963080	11-45A-1	150A 21	ES0385	A-10	*

*Operated by amplifiers



TURRET—LOWER GUN

(Continued from page 160)

for movement of the guns in elevation and depression. The power for the motors is supplied through two sets of interrupter relays, which interrupt the current flow and provide slow or fast operation. Provision is made for manual operation in the event of electrical power failure. The motor drive normally providing power for horizontal movement is used to retract the turret.

The gunner is in a kneeling position while sighting on the target, and his chest is supported by an adjustable pad. He sights through a non-fogging periscopic sight. The eyepiece of the sight remains fixed while the periscope's prism moves with the guns throughout their range of elevation.

The guns, charged simultaneously by individual hydraulic gun chargers, are fired by pressing a trigger switch on the control handle. A safety switch on the same handle makes the turret electrically operable.

Collector rings on the central column provide hydraulic and electrical connections to the turret.

CHARACTERISTICS:

Turret diameter	approximately 39 $\frac{1}{2}$ inches.
Turret height	approximately 59 $\frac{3}{8}$ inches (with chest pad in lower position and turret extended).
Weight	approximately 497 pounds.
Rotation in azimuth	360 degrees.
Depression of guns	90 degrees below horizontal.
Operating voltage	24 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7100

TYPE DESIGNATION: A-5

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type A-10 lower turret, A. E. Reference Number 52-7950.

SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.

NAVY

The Navy uses these turrets on airplanes procured from the Army.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British


Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Army Type	Remarks
Bendix Products Division	J	76860	A-B	5400963070	11-45A-1	150A 6	76860-A	A-5	
	K	79800	A-B	5400963080	11-45A-1	150A 21	ES0385	A-10	*

*Operated by amplifiers



TURRET—LOWER GUN

ARMY TYPE A-10 NAVY—SEE BELOW



NAMES: Lower gun turret
Lower turret — Bendix
Retractable lower gun turret

Bendix lower gun turret
Power operated lower gun turret
Turret — lower gun — retractable

DESCRIPTION: The Army type A-10 lower turret, a retractable structure mounting two .50 caliber, M2 machine guns, is supported from a central column by four spider arms. The turret is located beneath the belly of the fuselage. It is electrically operated by two amplidyne drives; one for rotation of the

(Continued on page 163)



TURRET—LOWER GUN

(Continued from page 162)

turret, the other for movement of the guns in elevation and depression. The motor drive normally providing power for horizontal movement is used to retract the turret.

The gunner is in a kneeling position while sighting the target, and his chest is supported by an adjustable pad. He aims through a non-fogging periscopic sight. The eyepiece of the sight remains fixed, while the periscope's prism moves with the guns throughout their range of elevation.

The guns, charged simultaneously by individual hydraulic gun chargers, are fired by pressing a trigger switch on the turret control handle. A safety switch on the same handle makes the turret operable.

Collector rings on the central column provide hydraulic and electrical connections to the turret.

CHARACTERISTICS:

Turret diameter	approximately 39 $\frac{1}{2}$ inches.
Turret height	approximately 59 $\frac{3}{8}$ inches (with chest pad in lower position and turret extended).
Weight	approximately 497 pounds.
Rotation in azimuth	360 degrees.
Depression of guns	88 degrees below horizontal.
Operating voltage	27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7950

TYPE DESIGNATION: A-10

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.


NAVY

The Navy uses these turrets on airplanes procured from the Army.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British


Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Army Type	Remarks
Bendix Products Division	K	79800	A-B	5400963080	11-45A-1	150A 21	ES0385	A-10	
	J	76860	A-B	5400963070	11-45A-1	150A 6	76860-A	A-5	*

*No amplicdynes. Electric motor driven.



TURRET—TAIL GUN

ARMY TYPE A-6 NAVY—SEE BELOW



NAMES: Tail gun turret
Consolidated tail turret

Turret—tail gun—Consolidated
Motor Products turret

(Continued on page 165)



TURRET—TAIL GUN

(Continued from page 164)

DESCRIPTION: The Army type A-6 turret, which mounts two .50 caliber, M2 machine guns, is located at the extreme rear of the fuselage. It rests on a circular track fastened to the airplane structure, and is rotated by two cables from an hydraulic drum in the base of the turret. An hydraulic jack elevates and depresses the guns. A separate electrical system for the turret furnishes power for operation of the hydraulic pump, the gun trigger mechanism, and sight illumination. In the event of power failure, the turret may be moved manually by the gunner.

The gunner, after entering the turret through double doors which open toward the fuselage, sits entirely within the armor plated turret enclosure. Bullet proof glass protects him while he sights the target through a reflector type sight that moves with the guns. These guns, charged individually by manual chargers, are fired by pressing triggers on the turret control handles. A safety switch on one handle makes the turret operable.

All hydraulic hose and electrical connections to the turret are flexible.

CHARACTERISTICS:

Turret diameter	approximately 40 inches.
Turret height	approximately 58 inches.
Weight	approximately 954 pounds.
Rotation in azimuth	122 degrees.
Elevation of guns	71 degrees above horizontal.
Depression of guns	40 degrees below horizontal.
Operating voltage	24 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7800

TYPE DESIGNATION: A-6

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.

NAVY

The Navy uses this turret on airplanes procured from the Army, and also procures them for installation on certain Navy aircraft. They are identified by the manufacturer's designation.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification
Motor Products Corporation	*A-6	32F5800-3	A-B	5400963033	11-45D-1	150A 10	32F5800
Southern Aircraft Corporation	*A-6	32F5800-3	A-B	5400963033	11-45D-1	150A 10	32F5800
		29F4824	N				

Note: *AAF type.



TURRET—NOSE GUN
ARMY TYPE A-15

NAMES: Nose gun turret
Emerson nose turret
Turret—Emerson

(Continued on page 167)



TURRET—NOSE GUN

(Continued from page 166)

DESCRIPTION: The Army type A-15 turret, which mounts two .50 caliber, M2 machine guns, is located in the nose of the airplane fuselage by means of a ring type mounting at the turret's base. It is electrically operated by two amplidyne drives, one for rotation of the turret, the other for movement of the guns in elevation and depression. Mechanical stops prevent turret rotation or movement of guns beyond predetermined limits.

The gunner, after entering the turret through double doors which open toward the fuselage, sits entirely within the armor plated turret enclosure. Bullet proof glass protects him while he sights the target through a reflector type sight. Both the bullet proof glass and the sight move with the guns. These guns, charged individually by manual chargers, are fired by pressing triggers on the turret control handles. A safety switch on one handle makes the turret electrically operable.

Flexible cables supply power and interphone connections to the turret, and an outlet and controlling rheostat are provided for the gunner's electrically heated suit.

CHARACTERISTICS:

Turret diameter.	approximately 42 inches.
Turret height	approximately 69 inches.
Weight.	approximately 1006 pounds.
Rotation in azimuth	150 degrees.
Elevation of guns.	60 degrees above horizontal.
Depression of guns	50 degrees below horizontal.
Operating voltage.	27.5 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.

ARMY

A. E. REFERENCE NUMBER: 52-7795
MANUFACTURER: Emerson Electric Manufacturing Company.
MANUFACTURER'S DRAWING NUMBER: 30500
MANUFACTURER'S SPECIFICATION NUMBER: AT-40N-127
TYPE DESIGNATION: A-15
A. S. C. STOCK NUMBER: 5400963103
TECHNICAL ORDER NUMBER: None
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.

NAVY

There is no Navy equivalent for the Army item.



TURRET—NOSE GUN

ARMY TYPE A-16

NAMES: Nose gun turret Chin turret
Bendix chin turret
Bendix nose gun turret
Turret—nose

DESCRIPTION: The Army type A-16 turret, a non-retractable structure mounting two .50 caliber, M2 machine guns, is supported from a central column by four spider arms. It is located below the nose of the airplane, and is electrically operated by two amplidyne drives, one for rotation of the turret, the other for movement of the guns in elevation and depression.

The gunner, seated inside the airplane and above the turret, sights the target through a reflector type sight, which moves with the guns. This sight is placed on a rotatable arm which is driven by a flexible shaft from the turret. Movement of this arm corresponds with the movement of the turret and the guns.

The guns are charged simultaneously by individual hydraulic gun chargers, and are fired by pressing trigger switches on the control handle. A safety switch on the same handle makes the turret electrically operable.


Collector rings on the central column provide hydraulic and electrical connections to the turret.

CHARACTERISTICS:

Turret diameter	approximately 39½ inches.
Turret height	approximately 36 inches.
Weight	approximately 412 pounds.
Rotation in azimuth	180 degrees.
Elevation of guns	30 degrees above horizontal.
Depression of guns	55 degrees below horizontal.
Operating voltage	24 volts direct current.

RELATIONSHIP OF PARTS:

A complete list of all turret equipment, whether government or contractor furnished, will be found in the turret manufacturer's model specification.



ARMY


A. E. REFERENCE NUMBER: 52-7350
MANUFACTURER: Bendix Products Division of Bendix Aviation Corporation.
MANUFACTURER'S MODEL IDENTIFICATION: D
MANUFACTURER'S DRAWING NUMBER: 82500
MANUFACTURER'S SPECIFICATION NUMBER: FI106
TYPE DESIGNATION: A-16
A. S. C. STOCK NUMBER: 5400963064
TECHNICAL ORDER NUMBER: 11-45AA-1
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit, less guns and ammunition.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 150A 26



UNIT—DOUBLE POWER HYDRAULIC

VICKERS MODEL AA-16801

NAMES: Double power hydraulic unit Power unit
 Turret double power unit Vickers unit

DESCRIPTION: This unit supplies motive power to Army types A-1 and A-1A locally controlled upper machine gun turrets. The power is developed hydraulically by an electrically driven piston type pump exerting pressure against the piston of a similar pump; the second pump is known as an hydraulic motor.

The entire unit consists of two transmissions, bolted to opposite ends of an electric drive motor. Each transmission contains one variable pressure pump and one hydraulic motor. Control of the pump's pressure, obtained by changing the angle between the cylinder of the pump and the master piston shaft, varies the speed of the transmission. When no pressure comes from the pump (zero degrees between cylinder and shaft) there is no movement of the hydraulic motor, and consequently no power is transmitted. The electric motor rotates at a constant speed and the transmissions provide smooth variable speed operation of the turret. One transmission is used to provide turret rotation, the other elevation and depression.

CHARACTERISTICS:

Dimensions	approximately 22½ by 7½ by 8 inches.
Weight	approximately 53 pounds.
Electric motor:	
Voltage	24 volts direct current.
Current	90 amperes.
Speed	4000 revolutions per minute.
Rating	2 horsepower.

RELATIONSHIP OF PARTS: Used with:

Army type A-1 and A-1A upper gun turrets, A. E. Reference Numbers 52-7600 and 52-7625.

ARMY

A. E. REFERENCE NUMBER: 52-8350
A. S. C. STOCK NUMBER: Refer to chart.
TECHNICAL ORDER NUMBER: Refer to chart.
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit.



NAVY

There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Ab Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Remarks
Vickers, Incorporated	AA-16801	56412	A-B	5400964512	11-45C-1	150C 2492		
	AA-16804	63404	A-B	5400964512	11-45C-1	150C 2353		*
Hobart Manufacturing Company	AA-16801	56412	A-B	5400964512	11-45C-1	150C 2492	4303	
	AA-16804	63404	A-B	5400964512	11-45C-1	150C 2353	4348	*

*Elevation transmission 90 degrees from that on model AA-16801. To effect interchangeability, unbolt and revolve 90 degrees.



UNIT—DOUBLE POWER HYDRAULIC

VICKERS MODEL AA-16804

NAMES: Double power hydraulic unit
Double power unit

Power unit
Vickers unit

DESCRIPTION: This unit supplies motive power to the Army types A-2 and A-13 locally controlled lower machine gun turrets. Power is developed hydraulically by an electrically driven piston type pump exerting pressure against the piston of a similar pump; the second pump is known as an hydraulic motor.

(Continued on page 171)



UNIT—DOUBLE POWER HYDRAULIC

(Continued from page 170)

The entire unit consists of two transmissions, bolted to opposite ends of an electric drive motor. Each transmission contains one variable pressure pump and one hydraulic motor. Control of the pump's pressure, obtained by changing the angle between the cylinder of the pump and the master piston shaft, varies the speed of the transmission. When no pressure comes from the pump (zero degrees between cylinder and shaft) there is no movement of the hydraulic motor, and consequently no power is transmitted. The electric motor rotates at a constant speed and the transmissions provide smooth variable speed operation of the turret. One transmission is used to provide turret rotation, the other elevation and depression.

This unit differs from model AA-16801 by having one transmission 90 degrees from its original position.

CHARACTERISTICS:

Dimensions approximately 22½ by 7½ by 8 inches.
 Weight approximately 53 pounds.
 Electric motor:
 Voltage 24 volts direct current.
 Current 90 amperes.
 Speed 4000 revolutions per minute.
 Rating 2 horsepower.

RELATIONSHIP OF PARTS: Used with:

Army types A-2 and A-13 lower ball turrets, A. E. Reference Numbers 52-7200 and 52-8050.

ARMY

A. E. REFERENCE NUMBER: 52:8375
 A. S. C. STOCK NUMBER: Refer to chart.
 TECHNICAL ORDER NUMBER: Refer to chart.
 PRODUCTION STATUS: Under procurement.
 SHIPPING DATA: Shipped as a complete unit.

NAVY


There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Manufacturer's Specification	Remarks
Vickers, Incorporated	AA-16804	63404	A-B	5400964512	11-45C-1	105C 2353		
	AA-16801	56412	A-B	5400964512	11-45C-1	105C 2494		"
Hobart Manufacturing Company	AA-16804	63404	A-B	5400964512	11-45C-1	105C 2353	4348	
	AA-16801	56412	A-B	5400964512	11-45C-1	105C 2494	4303	"

*Elevation transmission 90 degrees from that on model AA-16804. To effect interchangeability, unbolt and revolve 90 degrees.

FIRE CONTROL SYSTEMS ARMAMENT—GUNNERY



SYSTEM EQUIPMENT

- A 4" TURRETS
 - B 5" SIGHTING STATIONS
 - C 4" CONTROL BOXES
 - D 10" AMP-DYNES
 - E 4" DYNAMOTORS
 - F 5" AMPLIFIERS
 - G 5" COMPUTERS
 - H 2" DRIVE UNITS
 - I 1" COLLECTOR RING
 - J 1" ALTITUDE & AIR SPEED HANDSET
 - K 2" GUN SELECTORS
 - L 2" SWITCH BOXES
 - M 5" TURRET SAFETY SWITCHES
 - N 8" GUN CHARGERS
- TOTAL WEIGHT 2500 LBS.

G.E. B-29 CENTRAL STATION FIRE CONTROL SYSTEM



B-29 CENTRAL STATION FIRE CONTROL SYSTEM

The G. E. Model 2CFR55A1 central station fire control system is installed in the B-29 airplane. The armament used in this system consists of two upper and two lower turrets, each mounting two .50 caliber machine guns, and a tail mount carrying two .50 caliber machine guns and a 20-mm cannon. Each of these gun positions is controlled from one of five sighting stations. The sighting station located on the upper deck of the fuselage has control over both upper turrets, and the gunner in this station may fire either turret alone, or both at once. The gunner at the nose sighting station has control over the lower forward turret, and the gunner at the tail sighting station has control over the tail mount. There is a sighting station located in either side of the fuselage waist. The gunners at these positions decide between themselves which is to have primary control over the lower aft turret and secondary control over the lower forward turret or the tail mount. This means either gunner may take control over these other gun positions, but only when allowed by the gunner having primary control.

The gunner at any position is able to scan the sky through a plexiglas window, pick out the target, and track it by manually moving his sight. As the sight is moved the guns follow automatically and instantaneously.

The items of government furnished equipment which comprise this system are listed in the following pages:

A. E. Reference Number	Item	A. E. Reference Number	Item
52-6851	Servo-amplifier	52-6863	Altitude and airspeed hand-set
52-6852	Left blister auxiliary control box	52-3040	Amplidyne motor-generator
52-6853	Nose system control box	52-3045	Amplidyne motor-generator
52-6854	Right blister auxiliary control box	52-6864	Upper sight collector ring assembly
52-6855	Side blister system control box	52-6865	Left blister sighting station
52-6856	Side blister selector switch box	52-6866	Nose sighting station
52-6857	Tail system control box	52-6867	Right blister sighting station
52-6858	Upper blister system control box	52-6868	Tail sighting station
52-1720	Gun charger	52-6869	Upper ring sighting station
52-6859	Double parallax computer	52-6650	Tail cannon selector switch
52-6860	Single parallax computer	52-6870	Lower aft gun turret
52-6861	Tail gun mount azimuth drive	52-6871	Lower forward gun turret
52-6862	Tail gun mount elevation drive	52-6872	Upper aft gun turret
52-2580	Dynamotor	52-6873	Upper forward gun turret



← 12 $\frac{3}{8}$ " APPROX. →



SERVO—AMPLIFIER

GENERAL ELECTRIC COMPANY MODEL 2CV1C1

DESCRIPTION: The servo-amplifier, which may be located at any convenient point in the airplane, is a rectangular box containing vacuum tubes, transformers, condensers, and resistors.

This device amplifies a signal voltage from a selsyn receiver, and then rectifies it from alternating current to pulsating direct current, thereby making it suitable for exciting the field of an amplidyne motor generator.

This signal only occurs when there is misalignment between the sight and the guns, resulting in a small voltage passing between transformer and receiver selsyns. The amount of this voltage is proportionate to the amount of the misalignment.

The servo-amplifier is constantly supplied with power from the dynamotor. In this way it is always in readiness to respond to a signal.

CHARACTERISTICS:

Dimensions approximately 12 $\frac{3}{8}$ by 12 $\frac{3}{8}$ by 5 $\frac{1}{8}$ inches.

Weight approximately 18 pounds.

RELATIONSHIP OF PARTS: Used with:
B-29 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-6851
MANUFACTURER: General Electric Company
MANUFACTURER'S MODEL NUMBER: 2CV1C1
MANUFACTURER'S DRAWING NUMBER: T-8254157, Group 1
MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



BOX—LEFT BLISTER AUXILIARY CONTROL

GENERAL ELECTRIC COMPANY DRAWING NUMBER P-8242380, GROUP 2

NAME: Left blister auxiliary control box

DESCRIPTION: This auxiliary control box provides the gunner in the left side blister station with an ON-OFF switch for control over the 20-mm cannon in the tail mount. On the same panel are two indicator lights, to inform the gunner when he has primary control over the lower forward gun turret or the tail gun mount.

CHARACTERISTICS:

Dimensions	approximately $3\frac{1}{16}$ by $2\frac{3}{8}$ by $2\frac{3}{8}$ inches.
Weight	approximately 1 pound.


RELATIONSHIP OF PARTS: Used with:
B-29 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-6852
MANUFACTURER: General Electric Company.
MANUFACTURER'S DRAWING NUMBER: P-8242380, Group 2
MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

**BOX—SIDE BLISTER SYSTEM CONTROL**

GENERAL ELECTRIC COMPANY DRAWING NUMBER W-8258874, GROUP 1

NAME: Side blister system control box

DESCRIPTION: This control box is accessible to either gunner at the side blister sighting stations of the B-29 central station fire control system. It consists of power breakers, switches, and the camera, computer and gun safety switches.

The power breakers prevent overloading the amplidynes and dynamotor for the lower rear turret.

The power switches are of the single pole, double throw, ON-OFF type, and control alternating current from the dynamotor and power to the lower rear turret and tail gun mount.

The computer switches are the same type as the power switches. They control input to the right or left computer.

The gun safety switch, also of the ON-OFF type, provides fire and safe positions for guns in the lower rear turret.

CHARACTERISTICS:

Dimensions..... approximately 23 $\frac{5}{8}$ by 17 $\frac{1}{16}$ by 5 $\frac{1}{4}$ inches.
Weight..... approximately 40 pounds.

RELATIONSHIP OF PARTS: Used with:
B-29 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-6855

MANUFACTURER: General Electric Company.

MANUFACTURER'S DRAWING NUMBER: W-8258874, Group 1

MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



BOX—SIDE BLISTER SELECTOR SWITCH

GENERAL ELECTRIC COMPANY DRAWING NUMBER T-8252890, GROUP 1

NAME: Side blister selector switch box

DESCRIPTION: The side blister selector switch box, used in the B-29 central station fire control system, is accessible to the gunners at both side blister sighting stations. This box contains three manual two-position selector switches for determining which side blister sighting station shall have primary control of the lower aft gun turret, secondary control of the lower forward gun turret, and secondary control of the tail gun mount. These switches are all marked **LEFT** and **RIGHT**; indicating which side blister has control.

CHARACTERISTICS:

Dimensions..... approximately 13 $\frac{1}{4}$ by 5 $\frac{7}{8}$ by 3 $\frac{3}{8}$ inches.
Weight..... approximately 5 pounds.

RELATIONSHIP OF PARTS: Used with:
B-29 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-6856

MANUFACTURER: General Electric Company.

MANUFACTURER'S DRAWING NUMBER: T-8252890, Group 1


MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

**BOX—TAIL SYSTEM CONTROL**

GENERAL ELECTRIC COMPANY DRAWING NUMBER W-8258881, GROUP 1

NAME: Tail system control box

DESCRIPTION: This control box is used by the gunner at the tail sighting station of the B-29 central station fire control system. It consists of power breakers and switches, and the camera, computer, and gun safety switches.

The power breakers prevent overloading the amplidyne and dynamotor for the tail gun mount.

The power switches are of the single pole double throw ON-OFF type, and control alternating current from the dynamotor and power to the tail gun mount.

The computer switches are the same type as the power switches. They control input to the computer.

The gun safety switches, also of the ON-OFF type provide fire, safe and manual charge positions for the guns in the tail gun mount.

CHARACTERISTICS:

Dimensions.....approximately $21\frac{5}{8}$ by $15\frac{1}{4}$ by $4\frac{1}{8}$ inches.
Weight.....approximately 35 pounds.

RELATIONSHIP OF PARTS: Used with:
B-29 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-6857

MANUFACTURER: General Electric Company.

MANUFACTURER'S DRAWING NUMBER: W-8258881, Group 1


MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



BOX—UPPER BLISTER SYSTEM CONTROL

GENERAL ELECTRIC COMPANY DRAWING NUMBER W-8258865, GROUP 1

NAME: Upper blister system control box

DESCRIPTION: This control box is installed near the gunner at the upper ring sighting station of the B-29 central station fire control system. It contains power breakers and switches, and the camera, computer, and gun safety switches.

The power breakers prevent overloading the amplidyne and dynamotors for the upper forward and rear turrets.

The power switches, of the single pole double throw ON-OFF type, control the alternating current from the dynamotor and the power supply to the upper forward and rear turrets.

The computer switches are the same type as the power switches. They control electrical input to the computer.

The gun safety switches, also of the ON-OFF type, provide FIRE and SAFE positions for the guns in the upper forward and rear turrets.

CHARACTERISTICS:

Dimensions..... approximately 22 $\frac{3}{16}$ by 16 $\frac{1}{16}$ by 4 $\frac{1}{16}$ inches.

Weight..... approximately 35 pounds.

RELATIONSHIP OF PARTS: Used with:
B-29 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-6858

MANUFACTURER: General Electric Company.

MANUFACTURER'S DRAWING NUMBER: W-8258865, Group 1


MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



CHARGER—GUN

GENERAL ELECTRIC COMPANY DRAWING NUMBER T-8252878, GROUP 1

NAMES: Gun charger
Compressed air gun charger

CO₂ charger
Carbon Dioxide charger

DESCRIPTION: This gun charger is mounted on the side of a .50 caliber M2 machine gun used in the G. E. central station fire control systems. It is electrically controlled, so that when a firing key is closed, the gun fires. The charger automatically operates to cock or charge the gun in the event of a misfire. Five or six cocking operations are repeated in rapid succession, after which the charger will stop, indicating difficulty due to causes other than defective ammunition.

To actuate the gun bolt, a piston acts against a stud that extends outward from the side of the gun. This stud is carried by the gun bolt and projects through a guide slot into a cylinder. To operate the cylinder piston, compressed air, or gas, under a pressure of 1000 pounds per square inch, is admitted to the cylinder. The admission of the gas is controlled by a valve mechanism, which in turn is operated by an electromagnet known as the charging solenoid.

CHARACTERISTICS:

Dimensions.....approximately 16½ by 4¾ by 2¾ inches.
Weight.....approximately 10½ pounds.

RELATIONSHIP OF PARTS: Used with:

B-29 central station fire control system, P-61 central station fire control system, and A-26 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-1720

MANUFACTURER: General Electric Company.

MANUFACTURER'S DRAWING NUMBER: T-8252878, Group 1

MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1; GO-17400-B; and GO-17397-B.


A. S. C. STOCK NUMBER: 5900170000

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



COMPUTER—DOUBLE PARALLAX

GENERAL ELECTRIC COMPANY MODEL NUMBER 2CH1D1

NAME: Double parallax computer

DESCRIPTION: When a single sighting station controls two turrets, an additional parallax unit is required, to compensate for the fact that the two turrets are located at different points in the airplane.

This type of computer is used with each of the sighting stations for secondary control over an additional turret in the B-29 central station fire control system. It corrects for ballistics, parallax and lead, and permits an increase in both accuracy of fire and in the maximum range of accurate fire. This computer, attached to the left front side of a single parallax computer, changes the position of the second turret with respect to the position of the first turret, the first turret having been previously corrected by the single parallax computer with respect to the position of the sight by an angle equal to the correction necessary to cause the projective to hit the target at which it is aimed. These corrections are dependent upon the distance between the airplane and the target, the relative speeds of the two, and the altitude and air speed at which the airplane is flying.

CHARACTERISTICS:

Dimensions	approximately 23½ by 18½ by 18½ inches.
Weight	approximately 115 pounds.
Operating voltage	28 volts direct current.

RELATIONSHIP OF PARTS: Used with:


Single parallax computer, A. E. Reference Number 52-6860 in the B-29 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-6859
MANUFACTURER: General Electric Company.
MANUFACTURER'S MODEL NUMBER: 2CH1D1
MANUFACTURER'S DRAWING NUMBER: WW-8009120, Group 1
MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



COMPUTER—SINGLE PARALLAX

GENERAL ELECTRIC COMPANY MODEL NUMBER 2CH1C1

NAME: Single parallax computer

DESCRIPTION: This type of computer is used with each of the sighting stations, for controlling one turret in the B-29 central station fire control system. It corrects for ballistics, parallax and lead and permits an increase in both the accuracy of fire and the maximum range of accurate fire. This computer, located at a distance from the sighting station, changes the position of the turret with respect to the sight, by an angle equal to the correction necessary to cause the projectile to hit the target at which it is aimed. This correction is dependent upon the distance between the airplane and target, the relative speeds of the two, and the altitude and air speed of the airplane.

CHARACTERISTICS:

Dimensions approximately $23\frac{1}{2}$ by $18\frac{3}{8}$ by $10\frac{3}{8}$ inches.
 Weight approximately 90 pounds.
 Operating voltage 28 volts direct current.

RELATIONSHIP OF PARTS: Used with:

Altitude and airspeed handset, A. E. Reference Number 52-6863, in the B-29 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-6860
 MANUFACTURER: General Electric Company.
 MANUFACTURER'S MODEL NUMBER: 2CH1C1
 MANUFACTURER'S DRAWING NUMBER: WW-8009119, Group 1
 MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1
 PRODUCTION STATUS: Under procurement.
 SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



DRIVE—

TAIL GUN MOUNT AZIMUTH


GENERAL ELECTRIC COMPANY
DRAWING NUMBER W-8258810, GROUP 1

NAME: Tail gun mount azimuth drive

DESCRIPTION: In the B-29 central station fire control system, any movement of the tail sighting station is transmitted into a like movement of the tail mount guns.

The drive, used to horizontally move the tail gun mount, consists of a drive motor, two selsyn receivers and the necessary gearing.

Indications of misalignment between the selsyns on the mount and the selsyns on the sight are sent to the servo-amplifier, causing the amplidyne field in the motor generator to become energized. Power is then sent to the drive motor, which turns the gearing and rotates the mount. When the selsyns on the mount and the selsyns on the sight are once again aligned, the signal to the servo amplifier ceases and the amplidyne field is de-energized. This cuts off the power to the drive motor, stopping the mount.



CHARACTERISTICS:

Dimensions.....	approximately 14 $\frac{7}{16}$ by 5 $\frac{3}{16}$ by 12 $\frac{3}{4}$ inches.
Weight.....	approximately 50 pounds.
Motor.....	1.5 horsepower, G.E. model 5BC31NJ65.
Full load revolutions per minute.....	4000.
Field current.....	5.3 amperes.
Field voltage.....	28 volts direct current.
Field resistance.....	4.5 ohms.
Drive gear ratio.....	1250:1.

RELATIONSHIP OF PARTS: Used with:


Amplidyne motor-generator, G. E. model 5AM61NJ1C, A. E. Reference Number 52-3045, and selsyns, G. E. Model 2J1G1, A. E. Reference Number 52-4210, in the B-29 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-6861
MANUFACTURER: General Electric Company.
MANUFACTURER'S DRAWING NUMBER: W-8258810, Group 1.
MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit, including selsyns.

NAVY

There is no Navy equivalent for the Army item.



DRIVE—TAIL GUN MOUNT ELEVATION

GENERAL ELECTRIC COMPANY DRAWING NUMBER W-8258807, GROUP 1

NAME: Tail gun mount elevation drive

DESCRIPTION: In the B-29 central station fire control system, any movement of the tail sighting station is transmitted into a like movement of the tail mount guns.

The drive, used to elevate or depress the tail gun mount, consists of a drive motor two selsyn receivers and the necessary gearing.

Indications of misalignment between the selsyns on the mount and the selsyns on the sight are sent to the servo-amplifier, causing the amplidyne field in the motor-generator to become energized. Power is then sent to the drive motor, which turns the gearing and elevates or depresses the mount. When the selsyns on the mount and the selsyns on the sight are once again aligned, the signal to the servo amplifier ceases, and the amplidyne field is de-energized. This cuts off the power to the drive motor, stopping the mount.

CHARACTERISTICS:

Dimensions	approximately 18 ⁵ / ₈ by 12 ¹³ / ₁₆ by 14 ¹³ / ₁₆ inches.
Weight	approximately 50 pounds.
Motor	1.5 horsepower, G.E. model 5BC31NJ65.
Full load revolutions per minute	4000.
Field current	5.3 amperes.
Field voltage	28 volts direct current.
Field resistance	4.5 ohms.
Drive gear ratio	1163:1.

RELATIONSHIP OF PARTS: Used with:


Amplidyne motor-generator, G. E. model 5AM61NJ1C, A. E. Reference Number 52-3045, and selsyns G. E. model 2J1G1, A. E. Reference Number 52-4210, in the B-29 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-6862
MANUFACTURER: General Electric Company.
MANUFACTURER'S DRAWING NUMBER: W-8258807, Group 1
MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit, including selsyns.

NAVY

There is no Navy equivalent for the Army item.



DYNAMOTOR

GENERAL ELECTRIC MODEL 5D21NJ3A

NAMES:

DESCRIPTION: This dynamotor, a six pole, 8000 revolution per minute motor-generator, furnishes alternating current at 110 volts and 400 cycles per second, for the servo-amplifier and relays used in the B-29 and A-26 central station fire control systems. It consists of a 24 to 28 volt direct current shunt wound motor on a common shaft with a 110 volt single phase generator. The entire assembly is enclosed in a single housing. The motor operates from the airplane's power supply.

CHARACTERISTICS:

Dimensions.....	approximately 8 $\frac{15}{16}$ by 5 $\frac{1}{2}$ by 6 $\frac{1}{2}$ inches.
Weight.....	approximately 14 pounds.
Motor:	
Voltage.....	27 volts direct current.
Current.....	35 amperes.
Speed.....	8000 revolutions per minute.
Generator:	
Voltage.....	110 volts alternating current.
Current.....	4.4 amperes.
Rating.....	400 cycles per second single phase.


RELATIONSHIP OF PARTS: Used with:
B-29 and A-26 central station fire control systems.

ARMY

A. E. REFERENCE NUMBER: 52-2580
 MANUFACTURER: General Electric Company.
 MANUFACTURER'S MODEL NUMBER: 5D21NJ3A
 MANUFACTURER'S DRAWING NUMBER: TT-8117016, Group 1
 MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1; GO-17397-B
 PRODUCTION STATUS: Under procurement.
 SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



MOTOR-GENERATOR—AMPLIDYNE REMOTE CONTROL

GENERAL ELECTRIC COMPANY MODEL 5AM31NJ9

NAMES: Amplidyne remote control motor-generator Amplidyne Motor generator

DESCRIPTION: This type amplidyne motor-generator, used to supply current for the operation of remotely controlled machine gun turrets, consists essentially of a direct current electric motor and a direct current output generator mounted on the same shaft. In spite of the fact that the motor operates constantly to turn the shaft, there is no output from the generator unless the generator field is excited. This field requires only a small current to produce full generator output voltage. Minute variations in the field current instantaneously produce large variations in the generator's output. When the turret's guns and sight are in exact alignment no current is transmitted to the field; thus no output to the turret drive motor takes place even though the generator armature is turning. When the sight and guns are not in alignment, current is transmitted to the field and the generator produces voltage to cause the turret drive motor to align the guns with the sight.

Two amplidyne motor-generators and two turret drive motors are required for each turret; one of each for movement of the guns in elevation and depression and the others for rotation of the turret.

CHARACTERISTICS:

Dimensions	approximately 12 by 7 $\frac{3}{8}$ by 6 inches.
Weight	approximately 29 pounds.
Revolutions per minute	8300.
Motor input:	
Voltage	27 volts, direct current
Current	44 amperes
Winding	Compound.
Generator output:	
Voltage	60 volts, direct current
Current	8.8 amperes
Power	530 watts
Winding	amplidyne.

RELATIONSHIP OF PARTS: Used in:

B-29 central station fire control system, P-61 central station fire control system and A-26 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-3040

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Manufacturer's Specification
General Electric Company	5AM31NJ9	P-8111135 outline TT-5818156 assembly	A	5900466500	OST-1B
Marathon Electric Manufacturing Corporation	5AM31NJ9	P-8111135 outline TT-5818156 assembly	A	5900466500	OST-1B



STATION—SIGHTING

GENERAL ELECTRIC COMPANY MODEL 2CSD1C1

NAMES: Sighting station
Periscopic sighting station

DESCRIPTION: The gunner at the periscopic sighting station in the A-26 airplane can see targets above or below the airplane, but he cannot see both at the same time.

The sight itself is a double-end periscope, having a rotating eyepiece located just below the top mounting flange. This eyepiece transfers the line of sight into the tube of the periscope either up or down, depending upon the area to be scanned. The gunner needs only to aim his sight at the target, and the selection of the line of sight is made automatically within the sighting station. A changeover mirror is rotated to change the line of sight from the upper periscope head to the lower head, or vice versa. This mirror is turned by a changeover motor whenever the line of sight intersects the fuselage, thus allowing the gunner to follow his target without pausing to shift the line of sight when the target moves above or below him.

The selsyn transmitters, indicating horizontal motion of the sight, are located near the bottom end of the periscope tube. The selsyns indicating vertical movement are located just behind the gunner's control grips. A firing trigger is incorporated in one of these grips.

A collector ring assembly, located near the base of this sighting station, enables the sight to be rotated 360 degrees without twisting the power cables. This supplies electric power while the sight is rotated.

CHARACTERISTICS:

Dimensions.....approximately 77½ by 17½ by 24 inches
Weight.....approximately 135 pounds
Required voltage 28 volts direct current for lamp
 110 volts alternating current for selsyns
Range.....360 degrees in azimuth
 90 degrees in elevation
 90 degrees in depression
Field of view at
any one time...70 degree cone
Lamp.....Kollsman 71-A-O

RELATIONSHIP OF PARTS: Used with:
A-26 central station fire control system.


ARMY

A. E. REFERENCE NUMBER: 52-6703
MANUFACTURER: General Electric Company
MANUFACTURER'S MODEL NUMBER: 2CSD1C1
MANUFACTURER'S DRAWING NUMBER: W-8009100, Group 1
MANUFACTURER'S SPECIFICATION NUMBER: GO-17397-B
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit, including lamp and selsyns.

NAVY


There is no Navy equivalent for the Army item.





TURRET—LOWER GUN
GENERAL ELECTRIC COMPANY MODEL 2CGD50LRC1

NAME: Lower gun turret



(Continued on page 223)



TURRET—LOWER GUN

(Continued from page 222)

DESCRIPTION: This remotely controlled turret, housing two .50 caliber M2 machine guns, is supported, in the A-26 airplane, by a mounting ring and saddle assembly. It is electrically operated by two drive motors, each powered by an amplidyne motor-generator; one drive motor for horizontal rotation of the turret, the other for movement of the guns in elevation and depression. Two ammunition cases, each with a capacity of approximately 560 rounds of .50 caliber ammunition, are mounted above the guns. A collector unit with twenty-five slip rings is mounted on the axis of rotation of the turret to furnish electrical power to the various units in it.

When not in use, the turret is turned so the guns are horizontal and pointed aft. It is latched in this position to prevent accidental movement, which might result in an increase in drag.

CHARACTERISTICS:

Dome diameter	approximately 40 $\frac{5}{8}$ inches
Ring diameter	approximately 38 inches
Height to ring	approximately 28 $\frac{1}{2}$ inches
Height overall	approximately 42 $\frac{1}{2}$ inches
Weight	approximately 275 pounds
Rotation in azimuth	360 degrees
Movement in depression	95 degrees

RELATIONSHIP OF PARTS: Used with:

Turret drive motor, A. E. Reference Number 52-3065; Amplidyne motor-generator, A. E. Reference Number 52-3040; Gun charger, A. E. Reference Number 52-1720; and Selsyns, A. E. Reference Number 52-4210.

ARMY

A. E. REFERENCE NUMBER: 52-6704

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.


NAVY

There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British


Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Manufacturer's Specification	Used on Airplanes	Remarks
General Electric Company	2CGD50LRC1	WW-8019523	A	GO-17397-B	A-26	
	2CGD50LRC5	WW-8009114, Group 1	A	GO-18393-B-1	B-29 aft	"
	2CGD50LRC4	WW-8009113, Group 1	A	GO-18393-B-1	B-29 fore	"

*Uses different contour follower and fire interrupter.



TURRET—UPPER GUN
GENERAL ELECTRIC COMPANY MODEL 2CGD50URC1

NAME: Upper gun turret



(Continued on page 225)



TURRET—UPPER GUN

(Continued from page 224)

DESCRIPTION: This remotely controlled turret, housing two .50 caliber M2 machine guns, is supported, in the A-26 airplane, by a mounting ring and saddle assembly. It is electrically operated by two drive motors, each powered by an amplidyne motor-generator; one drive motor for horizontal rotation of the turret, the other for movement of the guns in elevation and depression. Two ammunition cases, each with a capacity of approximately 560 rounds of .50 caliber ammunition, are mounted below the guns. A collector unit with twenty-five slip rings is mounted on the axis of rotation of the turret, to furnish electrical power to the various units in it.

When not in use, the turret is turned so the guns are horizontal and pointed forward. It is latched in this position, and may be fired by the pilot when he aims the airplane at a target.

CHARACTERISTICS:

Dome diameter	approximately 40 $\frac{1}{2}$ inches
Ring diameter	approximately 38 inches
Height to ring	approximately 28 $\frac{1}{2}$ inches
Height overall	approximately 41 $\frac{1}{2}$ inches
Weight	approximately 275 pounds
Rotation in azimuth	360 degrees
Movement in elevation	-5 degrees to +90 degrees

RELATIONSHIP OF PARTS: Used with:

Turret drive motor, A. E. Reference Number 52-3065; Amplidyne motor-generator, A. E. Reference Number 52-3040; Gun charger, A. E. Reference Number 52-1720; and Selsyn, A. E. Reference Number 52-4210.

ARMY

A. E. REFERENCE NUMBER: 52-6705

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.


NAVY

There is no Navy equivalent for the Army item.

ALL MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Manufacturer's Specification	Used in Airplanes	Remarks
General Electric Company	2CGD50URC1	WW-8019524	A	GO-17397-B	A-26	
	2CGD50URC3	WW-8009111 Group 1	A	GO-18393-B-1	B-29 fore	"
	2CGD50URC4	WW-8009112 Group 1	A	GO-18393-B-1	B-29 aft	"

*Uses different contour follower and fire interrupter.

**CHARGER—GUN****GENERAL ELECTRIC COMPANY DRAWING NUMBER T-8252878, GROUP 1**

NAMES: Gun charger
Compressed air gun charger

CO₂ charger
Carbon Dioxide charger

DESCRIPTION: This gun charger is mounted on the side of a .50 caliber M2 machine gun used in the G. E. central station fire control systems. It is electrically controlled, so that when a firing key is closed, the gun fires. The charger automatically operates to cock or charge the gun in the event of a misfire. Five or six cocking operations are repeated in rapid succession, after which the charger will stop, indicating difficulty due to causes other than defective ammunition.

To actuate the gun bolt, a piston acts against a stud that extends outward from the side of the gun. This stud is carried by the gun bolt, and projects through a guide slot into a cylinder. To operate the cylinder piston, compressed air, or gas, under a pressure of 1000 pounds per square inch, is admitted to the cylinder. The admission of the gas is controlled by a valve mechanism, which in turn is operated by an electromagnet known as the charging solenoid.

CHARACTERISTICS:

Dimensions..... approximately 16½ by 4¾ by 2¾ inches.
Weight..... approximately 10½ pounds.

RELATIONSHIP OF PARTS: Used with:

B-29 central station fire control system, P-61 central station fire control system, and A-26 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-1720

MANUFACTURER: General Electric Company.

MANUFACTURER'S DRAWING NUMBER: T-8252878, Group 1

MANUFACTURER'S SPECIFICATION NUMBER: GO-18393-B-1; GO-17400-B; and GO-17397-B.


A. S. C. STOCK NUMBER: 5900170000

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



MOTOR—TURRET DRIVE
GENERAL ELECTRIC COMPANY MODEL 5BA50LJ2A

NAMES: Turret drive motor
Drive motor

Universal turret drive motor

DESCRIPTION: This $\frac{1}{2}$ horsepower universal turret drive motor is of the four-pole, two-brush type, with a separately excited field. When used to rotate a turret (azimuth drive), it is connected to a 533 to 1 reduction gear train. When used to elevate or depress a two gun turret gun carriage, (elevation drive) it is connected to an 800 to 1 reduction gear; for a four gun turret gun carriage, it is connected to a 600 to 1 reduction gear. The motor is bolted to the turret, and the extended armature shaft engages the drive pinion of the gear train used in the reduction mechanism. This motor is equipped with sealed type ball bearings containing enough low temperature lubricant to last throughout normal operational life. One amplidyne motor-generator is required to furnish power for the operation of each turret drive motor.

CHARACTERISTICS:

Dimensions.....	approximately 7 $\frac{3}{4}$ by 5 $\frac{5}{8}$ by 4 $\frac{1}{4}$ inches
Weight.....	approximately 8 pounds
Type.....	$\frac{1}{2}$ horsepower direct current
Full load revolutions per minute.....	4000
Field current.....	2.3 amperes
Field voltage.....	24 volts, direct current
Field resistance.....	9.4 ohms

RELATIONSHIP OF PARTS: Used with:

Amplidyne motor generator G. E. model 5AM31NJ9, A. E. Reference Number 52-3040 in Army type B-29 central station fire control system, Army type P-61 central station fire control system, and Army type A-26 central station fire control system.

ARMY

A. E. REFERENCE NUMBER: 52-3065

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: This unit is normally a component part of the turrets used in the fire control systems but may be shipped as a separate unit when required.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Manufacturer's Specification	Remarks
General Electric Company	5BA50LJ2A	TT-8117000	A	OST-1B	GE model 5BA50LJ2A supersedes and is interchangeable with GE model 5BA50LJ2.
Electric Vacuum Cleaner Company	5BA50LJ2A	TT-8117000	A	OST-1B	

(RESTRICTED)



BOMB ARMING CONTROLS ARMAMENT—BOMBING

(RESTRICTED)

ARMAMENT—BOMBING



BOMBING EQUIPMENT

Digitized by Google

Original from
CORNELL UNIVERSITY



ADAPTER—BOX
BRITISH TYPE A

NAMES: Box adapter
Bomb box adapter

Universal bomb carrier adapter box
Box, adapter and terminal

DESCRIPTION: The British type A box adapter consists of a rectangular shaped junction box with a built-in 5 hole socket, and an extension cable with a 5 pin plug attached. This adapter is used to enable installation of incendiary or small bomb boxes in the universal bomb carrier, and to permit systematic electrical release of these boxes.

CHARACTERISTICS:

Dimensions approximately $5\frac{1}{8}$ by $2\frac{1}{4}$ by $1\frac{3}{8}$ inches (without socket)
Dimensions approximately $1\frac{3}{4}$ by $2\frac{1}{4}$ inches (socket only)

INSTALLATION PECULIARITIES: This adapter is equipped with a built-in socket, British Reference Number 5D 526, and a four foot extension cable with a 5 pin plug, British Reference Number 5D/517. It is inserted between the carrier and the airplane socket.

RELATIONSHIP OF PARTS: Used with:

Universal bomb carrier, A. E. Reference Numbers 64-197, 64-198 and 64-199, and 5-way bomb socket, A. E. Reference Number 64-4195.

ARMY

A. E. REFERENCE NUMBER: 64-110

MANUFACTURER: Guardian Electric Company

MANUFACTURER'S DRAWING NUMBER: 20388

MANUFACTURER'S SPECIFICATION NUMBER: G32693

A. S. C. STOCK NUMBER: 6400008420

PRODUCTION STATUS: Not under procurement for initial installation.

SHIPPING DATA: Shipped as a complete unit, including extension cable and plug.

NAVY

There is no Navy equivalent for this item.

BRITISH

REFERENCE NUMBER: 5D/610



PANEL—AUTOPILOT CONTROL

ARMY TYPE A-6A NAVY—SEE BELOW

NAMES: Autopilot control panel
Control box
Control panel

Pilot's control box
Pilot's control panel
Turn type remote control unit (British)

DESCRIPTION: The autopilot control panel is a part of the automatic pilot, and is mounted in the pilot's compartment. It contains all the controls necessary for the operation of the automatic pilot when used in conjunction with a bombsight or as a navigational aid.

The assembly incorporates a turn control, by means of which coordinated turns can be made, and a turn control transfer switch, which permits operation of a remotely located turn control.

Six toggle switches located below the turn control activate the complete automatic pilot, including the directional stabilizer. The master and the stabilizer servo switch are connected by a bar which moves both ON and OFF together, and prevents the other switches from being used before the automatic pilot is in operation. Movement of the bar to the OFF position operates all switches simultaneously, disconnecting the automatic pilot.

Six tell-tale lights, two for each axis of control, are located at the top of the panel. When a light is illuminated, it indicates a condition of unbalance in an axis of control. During proper operation of the pilot all lights are extinguished.

Adjusting knobs for the centering, sensitivity, ratio and turn compensation for the three axis of control are located on the face of the panel.

CHARACTERISTICS: Dimensions approximately 8 by 8 by $4\frac{1}{16}$ inches
Weight approximately 5 $\frac{1}{16}$ pounds
Illumination None
Markings Fluorescent—radioactive

RELATIONSHIP OF PARTS: Part of the Army type C-1 automatic pilot, A. E. Reference Number 64-2300

ARMY

A. E. REFERENCE NUMBER: 64-195

SPECIFICATIONS:

General C-24825

Detail C-24861

MANUFACTURER: Minneapolis Honeywell
Regulator Company, part number G1047
outline drawing number DR2155.

TYPE DESIGNATION: A-6A

A. S. C. STOCK NUMBER: 6400092800

TECHNICAL ORDER NUMBER: 11-60-1

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: A part of Mark 2
Modification 1 Stabilized Bombing Ap-
proach Equipment


**AVIATION ORDNANCE STOCK LIST
NUMBER:** 2-S-335

**NAVAL ORDNANCE PAMPHLET NUM-
BER:** 639

PROCUREMENT STATUS: Under procure-
ment.

BRITISH

REFERENCE NUMBER: 106J/699



CARRIER—UNIVERSAL BOMB

ARMY TYPE NUMBER 1 MARK III BRITISH NUMBER 1 MARK III

NAMES: Universal bomb carrier
British bomb carrier

DESCRIPTION: The Number 1 Mark III universal bomb carrier is a British designed device for carrying and releasing bombs having one or three suspension lugs. The carrier is electrically controlled, and provides selective arming of the bombs.

Major parts of the bomb carrier are two fusing units, a bomb hook, release unit, crutch assemblies (sway bracing), and a junction box with a male plug.

The fusing units are provided to enable fusing of both, or either, the nose and tail of a bomb.

CHARACTERISTICS:

Weight	approximately 17 pounds
Dimensions	approximately 46 $\frac{1}{16}$ by 7 $\frac{3}{4}$ by 10 $\frac{1}{4}$ inches
Power supply	24 volts, direct current
Capacity	1000 pounds

RELATIONSHIP OF PARTS: Used with:

5-way bomb socket, type A, A. E. Reference Number 64-4195, and box adapter, A. E. Reference Number 64-110.

ARMY


A. E. REFERENCE NUMBER: 64-198
MANUFACTURER'S DRAWING NUMBER: Mills Novelty Company BR-719-CSP
TYPE DESIGNATION: Number 1 Mark III
A. S. C. STOCK NUMBER: 6400162010
TECHNICAL ORDER NUMBER: 11-5-43
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for this item.

BRITISH

BRITISH REFERENCE NUMBER: 111A/41



TYPICAL BOMB RELEASE SYSTEM



BOMB ARMING CONTROLS

Bomb arming controls allow bombs to be dropped either in safe or in armed condition. Bombs are dropped safe when their release over friendly territory is necessary.

The control is operated by the bombardier's fuse switch. When the bombardier places the switch OFF, the bombs are safe and will not normally explode upon impact. When the switch is ON, the bombs are armed and explode upon impact.

The bomb arming or fusing wire of the bomb is placed between ball ended retainers on the bomb arming control which is installed on the bomb rack. One of these retainers is stationary and the other, under spring tension, is movable.

To release a bomb in an armed condition, the electrical circuit is energized by turning the bombardier's fuse switch ON. As the circuit is energized, a pin moves into a hole in the center of the ball ended retainers, thereby locking the arming wire in place. When the bomb is dropped, the arming wire is pulled from the bomb and allows the bomb to explode upon impact.

To release a bomb in a safe condition, the bombardier places the fuse switch OFF. This de-energizes the electrical circuit, allowing the arming wire to pull out from between the retainers as the bomb falls.



BOMB ARMING CONTROLS ARMAMENT—BOMBING



CONTROL—BOMB ARMING

TYPE AN-A-1 FORMER ARMY TYPE A-1 FORMER NAVY TYPE A-1

NAMES: Bomb arming control
Auxiliary arming mechanism
Bomb arming control box

Fusing unit
Selective fusing control
Bomb fusing control

DESCRIPTION: The type AN-A-1 bomb arming control is a box-shaped control used to arm the bomb as it is released from the shackle or rack. The control operates on a 24 to 28 1/2 volt direct current supply.

CHARACTERISTICS:

Weight approximately 3 1/2 pound
Dimensions approximately 1 1/2 by 3 by 4 inches
Electrical connector plug AN3106-10S-2S

INSTALLATION PECULIARITIES: A slide mount is supplied as an integral part of the type AN-A-1 bomb arming control. The purpose of this mount is to provide mounting attachment when used with the British universal bomb carrier, or on an airplane equipped with slide mounting rails.

ARMY

A. E. REFERENCE NUMBER: 64-200

SPECIFICATIONS:

Detail 93-24753
Superseded 24753

A. A. F. DRAWING NUMBER: H42B6598

TYPE DESIGNATION: AN-A-1

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped with electrical connector plug AN3106-10S-2S in a single container.

NAVY

TYPE DESIGNATION: AN-A-1

BUREAU OF ORDNANCE DRAWING NUMBER: 328446


AVIATION ORDNANCE STOCK LIST NUMBER: Refer to chart

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	AAF Type and Navy Type	Aviation Ordnance Stock List Number	Remarks
J. P. Seeburg Company	*A-1	BA-106000	A-N-B	6400217000		105D 194	AN-A-1	3-C-1805 (formerly 3-B-1969)	
P. R. Mallory & Company, Incorporated	SF-6	C-134624 B-134163	A-N-B	6400217000	11-5-33	105D 99	AN-A-1	3-C-1805 (formerly 3-B-1969)	
	SF-4	B-134163	N				Navy Type SF-4	3-B-1970	†
Magnavox Corporation	14D26G1	14D26G1	A-N-B	6400217050	11-5-47	105D 195	AN-A-2	3-C-1810	†

*A slide or bomb arming control mount must be used to provide for complete interchangeability.
Note: *AAF and Navy type.



CONTROL—BOMB ARMING

TYPE AN-A-2 FORMER ARMY TYPE A-2

NAMES: Bomb arming control
Auxiliary arming mechanism
Bomb arming control box

Fusing unit
Selective fusing control
Bomb fusing control

DESCRIPTION: The type AN-A-2 bomb arming control is a cylindrically shaped control used to arm the bomb as it is released from the shackle or rack. The control operates on a 24 to 28½ volt direct current supply.

CHARACTERISTICS:

Weight	approximately 1½ pound
Dimensions	approximately 1½ by 1¼ by 4 inches
Electrical connector plug	AN3106-10S-2S

RELATIONSHIP OF PARTS: When used with British Universal Bomb Carrier or on an airplane equipped with slide mounting rails, this unit must be equipped with a bomb arming control mount, Army type A-1, A. E. Reference Number 64-2270.

ARMY

A. E. REFERENCE NUMBER: 64-220

SPECIFICATIONS:

Detail	93-24828
Superseded	24828

A. A. F. DRAWING NUMBER: 43B9887

TYPE DESIGNATION: AN-A-2

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped complete with electrical connector plug AN3106-10S-2S in a single container.

NAVY

TYPE DESIGNATION: AN-A-2

BUREAU OF ORDNANCE DRAWING NUMBER: 388363


AVIATION ORDNANCE STOCK LIST NUMBER: Refer to column 9 of the chart.

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	AAF Type and Navy Type	Aviation Ordnance Stock List Number	Remarks
Magnavox Corporation	14D26G1	14D26G1	A-N-B	6400217050	11-5-47	105D 195	AN-A-2	3-C-1810	
J. P. Seeburg Company	A-1	BA-106000	A-N-B	6400217000		105D 194	AN-A-1	3-C-1805 (formerly 3-B-1969)	"
P. R. Mallory & Company, Incorporated	SF-6	C-134624 B-134163	A-N-B	6400217000	11-5-33	105D 99	AN-A-1	3-C-1805 (formerly 3-B-1969)	"
	SF-4	B-134163	N				Navy Type SF-4	3-B-1970	

*Contains slide for attaching to mounting rails.



CONTROL—BOMB ARMING

ARMY TYPE B-2

NAMES: Bomb arming control
Auxiliary arming mechanism
Bomb arming control box

Fusing unit
Selective fusing control
Bomb fusing control

DESCRIPTION: The type B-2 bomb arming control is a cylindrically-shaped control, used to arm the bomb as it is released from the shackle or rack. The control operates on a 12 to 14½ volt direct current supply.

CHARACTERISTICS:

Weight approximately 1½ pound
Dimensions approximately 1½ by 2 by 4 inches
Electrical connector plug AN3106-10S-2S

RELATIONSHIP OF PARTS: When used with British universal bomb carrier or on an airplane equipped with slide mounting rails, this unit must be equipped with an Army type A-1 bomb arming control mount, A. E. Reference Number 64-2270.

ARMY

A. E. REFERENCE NUMBER: 64-275

SPECIFICATIONS:

Detail 93-24829
Superseded 24829

A. A. F. DRAWING NUMBER: 43B11958

TYPE DESIGNATION: B-2

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped complete with electrical connector plug AN3106-10S-2S in a single container.

NAVY

The Navy does not use this item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	AAF Type	Navy Type	Navy Bureau of Ordnance Drawing Number	Aviation Ordnance Stock List Number
Magnavox Corporation	14D26G4	14D26G4	A	6400217100	B-2			
P. R. Mallory & Co., Inc.	SF-10	Outline B-134163	N			SF-10	328446	3-B-1977



BOMB RELEASE INTERVAL CONTROL

Bomb release interval controls permit the release of a uniformly spaced pattern or train of bombs, assuring one or more hits when crossing a target.

The bomb release interval control determines the time interval between release of successive bombs to give the desired ground spacing. To accomplish this, the ground speed is determined and set on the ground speed dial to correspond to the desired spacing between bombs.

A select-train switch is provided to allow bombs to be dropped selectively or in train. One bomb is released with each operation of the switch when in the select position, and a uniformly spaced pattern of bombs is released when the switch is in the train position.

The counter, or bombs to be released control, may be set manually, either forward or backward, according to the number of bombs to be released in each train. Resetting of this control may be accomplished at any time, provided at least one minute elapses between the time of resetting and the time of release of bombs.


Bomb release interval controls are equipped with a signal light which indicates that the bomb release circuit is ready for operation. The light goes on when the select-train switch is in the select position, and in the train position only when the number of bombs to be released has been determined and the dial set. Bomb release interval controls with fluorescent markings have adjustable housing assemblies so that the signal light may be blacked out under ultra-violet light.

All controls are calibrated directly so that it is not necessary to refer to charts or to make calculations. They are marked in miles per hour or knots, and are available with either fluorescent or standard non-luminous markings.

For installation, refer to diagram on page 234.



BOMB RELEASE INTERVAL CONTROLS ARMAMENT—BOMBING



CONTROL—BOMB RELEASE INTERVAL ARMY TYPE B-2

NAMES: Bomb release interval control
Interval control

Bomb release control
Intervalometer (Navy)

DESCRIPTION: The type B-2 bomb release interval control operates on a 24 to 28½ volt direct current supply. The ground speed of the airplane is determined, and set on the ground speed dial opposite the desired spacing between bomb hits. The control has a fixed intensity amber signal light and dull white non-luminous markings.

CHARACTERISTICS:

Weight	approximately 5½ pounds
Dimensions	approximately 9½ by 6 by 4½ inches
Electrical connector	Cannon GK-M5-32S, Bulletin K
Ground speed dial range	100 to 500 miles per hour
Bomb spacing dial range	7 to 400 feet
Bombs to be released dial range	2 to 20 bombs per second

ARMY

A. E. REFERENCE NUMBER: 64-600

SPECIFICATIONS:

Detail	93-24630-A
Superseded	24630

A. A. F. DRAWING NUMBER: 41D1831

TYPE DESIGNATION: B-2

A. S. C. STOCK NUMBER: Refer to chart.

TECHINICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation, superseded by Army type B-2A,

A. E. Reference Number 64-800.

SHIPPING DATA: Shipped as a complete unit.

NAVY

The Navy does not use the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	AAF Type and Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
P. R. Mallory & Co., Inc.	*B-2	Outline C-134558	A-B	6400217520	11-5-29	105D 30	Aluminum case.
	*B-2A	Outline C-134558	A-B	6400217550	11-5-29	105D 84	Aluminum case.
		Outline C-134729					Steel case.
		Assembly C-134584					Aluminum case.
		Assembly C-134643					Steel case.
		Parts list B-134204					Steel case.
J. P. Seaburg Co.	*B-2A	BR-105C00	A-B	6400217550	11-5-14 11-1-36	105D 84	

*AAF type.



CONTROL—BOMB RELEASE INTERVAL

ARMY TYPE B-2A

NAMES: Bomb release interval control
Interval control

Bomb release control
Intervalometer (Navy)

DESCRIPTION: The type B-2A bomb release interval control operates on a 24 to 28½ volt direct current supply. The ground speed of the airplane is determined, and set on the ground speed dial opposite the desired spacing between bomb hits. The control uses a filament lamp with amber lens, and the light intensity is adjusted by rotating the lamp housing. Markings are fluorescent, and are visible under external and ultra-violet light.

CHARACTERISTICS:

Weight	approximately 6½ pounds
Dimensions	approximately 9½ by 6 by 4½ inches
Electrical connector	Cannon GK-M5-32S, Bulletin K
Ground speed dial range	100 to 500 miles per hour
Bomb spacing dial range	7 to 750 feet
Bombs to be released dial range	1 to 20 bombs per second.

ARMY

A. E. REFERENCE NUMBER: 64-800

SPECIFICATIONS:

Detail	93-24630-A (amended)
Superseded	93-24630

A. A. F. DRAWING NUMBER: 41D10802

TYPE DESIGNATION: B-2A

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by type AN-B-3.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: B-2A

AVIATION ORDNANCE STOCK LIST NUMBER: 3-C-1875

PROCUREMENT STATUS: Not under procurement for initial installation.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	AAF Type and Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
P. R. Mallory & Co., Inc.	*B-2A	Outline C-134558	A-B	6400217550	11-5-29	105D/84	Aluminum case.
		Outline C-134729					Steel case.
		Assembly C-134584					Aluminum case.
		Assembly C-134643					Steel case.
		Parts list B-134204					Steel case.
J. P. Seeburg Co.	*B-2A	BR-105000	A-B	6400217550	11-5-14 11-1-36	105D/84	

Note: *AAF type

**CONTROL—BOMB RELEASE INTERVAL****TYPE AN-B-3 FORMER ARMY TYPE B-3****NAMES:** Bomb release interval control
Interval controlBomb release control
Intervalometer (Navy and British type)

DESCRIPTION: The type AN-B-3 bomb release interval control operates on a 24 to 28½ volt direct current supply. The ground speed of the airplane is determined, and set on the ground speed dial opposite the desired spacing between bomb hits. The control uses a filament lamp with amber lens, and the light intensity is adjusted by rotating the lamp housing. Markings are fluorescent, and are visible under external and ultra-violet light.

CHARACTERISTICS:

Weight	approximately 6 pounds
Dimensions	approximately 9½ by 6 by 4½ inches
Electrical connector	AN3102-14S-7P
Ground speed dial range	100 to 500 miles per hour
Opposite face of ground speed dial range	90 to 460 knots. (Navy use)
Bomb spacing dial range	7 to 750 feet
Bombs to be released dial range	1 to 20 bombs per second

ARMY**A. E. REFERENCE NUMBER:** 64-825**SPECIFICATIONS:**

Detail	93-24717
Superseded	24717

A. A. F. DRAWING NUMBER: 42D3116**TYPE DESIGNATION NUMBER:** AN-B-3**A. S. C. STOCK NUMBER:** Refer to chart.**TECHINICAL ORDER NUMBER:** Refer to chart.**PRODUCTION STATUS:** Under procurement.**SHIPPING DATA:** shipped as a complete unit.**NAVY****TYPE DESIGNATION:** AN-B-3**AVIATION ORDNANCE STOCK LIST NUMBER:** 3-C-1880 (formerly 3-I-495)**PROCUREMENT STATUS:** Not under procurement for initial installation, superseded by Navy type K-2.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	A-Army Service Command Stock Number	Army Technical Order Number	British Reference Number	AAF Type	Navy Type	Remarks
P. R. Mallory & Co., Inc.	*AN-B-3	Outline C-134558	A-N-B	6400217700	11-5-29	105D, 94	AN-B-3	AN-B-3	Aluminum case.
		Outline C-134729							Steel case.
	†K-2	Outline C-134558	N-B			105D, 31		K-2	Aluminum case.†
		Outline C-134729							Steel case.†
J. P. Seaburg Co.	*AN-B-3	BR-105100	A-N	6400217700			AN-B-3	AN-B-3	

†NOTE: Graduated in knots only. The range of the ground speed dial is 90 to 460 knots for the unit in the steel case and 100 to 450 knots for the one in the aluminum case. The bomb spacing dial range is 7 to 400 feet, and the bombs to be released dial range is 2 to 20 bombs per second. The type K-2 and type AN-B-3 are interchangeable electrically and installationally.

Note: *AAF type; †Navy type.



CONTROL—PILOT DIRECTOR INDICATOR

ARMY TYPE A-1

NAMES: Pilot director indicator control
P. D. I. control

DESCRIPTION: The Army type A-1 pilot director indicator control provides the bombardier with a means of indicating to the pilot, through the pilot director indicator, changes to be made in the heading or direction of the airplane to complete a bombing run. The control consists of a selector switch, mounted in a cylindrical container, with markings indicating zero, right and left. Movement of the control knob by the bombardier causes the pointer on the pilot director indicator in the pilot's cockpit to move accordingly. When the airplane is on the desired course the bombardier releases the control knob, and it is returned to the zero position by spring action.

CHARACTERISTICS:

Dimensions	approximately 3 $\frac{1}{4}$ by 3 $\frac{1}{4}$ by 2 $\frac{1}{16}$ inches
Weight	approximately $\frac{1}{2}$ pound
Illumination	none
Markings	white enamel
Voltage	24 volts direct current

RELATIONSHIP OF PARTS: Used with:

Pilot director indicator, A. E. Reference Numbers 64-2255, or 64-2257 when the airplane does not have an Army type C-1 automatic pilot.

ARMY

A. E. REFERENCE NUMBER: 64-835

SPECIFICATIONS:

Detail

24841

MANUFACTURER: P. R. Mallory Company, Incorporated.

MANUFACTURER'S DRAWING NUMBER	Outline	B-134405
	Part	C-134815

TYPE DESIGNATION: A-1

A. S. C. STOCK NUMBER: 6400219325

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



COVER—ELECTRICALLY HEATED BOMBSIGHT

ARMY TYPE A-1 NAVY MARK 1

NAMES: Electrically heated bombsight cover
Bombsight blanket (Navy)
Bombsight cover
Electrically heated bombsight blanket

DESCRIPTION: The Army type A-1 electrically heated bombsight cover is used as a protective coat to retain the heat produced by the bombsight and to supply heat to the bombsight in low temperatures.

The cover is of sufficient size to cover both the bombsight and the stabilizer, and is secured about the stabilizer base with a draw cord and clamp.

The cover is made of woolen batting quilted to cotton fabric. The electrical heating wires are sewed to the inner cotton fabric.

Automatic thermostatic control is provided in the electrical circuit to prevent overheating. The thermostat is encased in a metal tube which is attached to the inner lining of the bombsight cover.

The power supply cable is approximately sixty inches long, and connects to the aircraft electrical circuit by a male plug.



CHARACTERISTICS:

Weight	approximately 6 pounds
Navy type electrical connector	AN3106-16-11P
Army type electrical connector	Twist lock plug, Hubbel part number 7542 or 7545
Maximum external temperature range	Minus 60 to plus 170 degrees fahrenheit (Minus 51 to plus 77 degrees centigrade)
Minimum heating requirement	Maintains plus 15 degrees fahrenheit (Minus 9.4 degrees centigrade) at external temperature of minus 60 degrees fahrenheit (minus 51 degrees centigrade)

RELATIONSHIP OF PARTS: Used with:

Army type M-series bombsight, and stabilizer
Navy Mark 15, modification 5 and 7 bombsight, and stabilizer

ARMY

A. E. REFERENCE NUMBER: 64-850

MANUFACTURER: General Electric Company

MANUFACTURER'S PART NUMBER: G. E. catalog number PC 15A6

SPECIFICATIONS:

Detail	40453-A
Superseded	40453

A. A. F. DRAWING NUMBER: 42M15384

TYPE DESIGNATION: A-1

A. S. C. STOCK NUMBER: 6400225915

TECHNICAL ORDER NUMBER: 11-30-1 and 11-30-9

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

SHIPPING WEIGHT: approximately 7 pounds.

SHIPPING CARTON DIMENSIONS: approximately 22¾ by 20 by 4¾ inches.

NAVY

TYPE DESIGNATION: Mark 1

AVIATION ORDNANCE STOCK LIST NUMBER: 2-B-1900

ORDNANCE TECHNICAL INSTRUCTIONS NUMBER: V-4-43

PROCUREMENT STATUS: Under procurement.

INTERCHANGEABILITY: To effect interchangeability between Army and Navy types, the proper electrical connector must be used.



COVER—ELECTRICALLY HEATED BOMBSIGHT

ARMY TYPE A-2

NAMES: Electrically heated bombsight cover
Bombsight blanket
Bombsight cover
Electrically heated bombsight blanket

DESCRIPTION: The Army type A-2 electrically heated bombsight cover is used as a protective coat, to retain the heat produced by the bombsight and to supply heat to the bombsight in low temperatures.

The cover is made of woolen batting quilted to cotton fabric. The electrical heating wires are sewed to the inner cotton fabric.

Automatic thermostatic control is provided in the electrical circuit to prevent overheating. The thermostat is encased in a metal tube which is attached to the inner lining of the bombsight cover.

The cover is secured about the bombsight with snap fasteners.

The power supply cable is approximately sixty inches long, and connects to the aircraft electrical circuit by a male plug.



CHARACTERISTICS:

Weight	approximately 7 pounds
Electrical connector	twist lock plug, Hubbel part number 7542 or 7545
Maximum external temperature range	minus 60 to plus 170 degrees fahrenheit (minus 51 to plus 77 degrees centigrade)
Minimum heating requirements	maintains plus 15 degrees fahrenheit (minus 9.4 degrees centigrade) at external temperature of minus 60 degrees fahrenheit (minus 51 degrees centigrade)

RELATIONSHIP OF PARTS: Used with:
Army type S-1 bombsight

ARMY

A. E. REFERENCE NUMBER: 64-852

SPECIFICATIONS:

Detail40630

MANUFACTURER: General Electric Company

MANUFACTURER'S PART NUMBER: G. E. catalog number PC 16A1

TYPE DESIGNATION: A-2

A. S. C. STOCK NUMBER: 6400225912

TECHNICAL ORDER NUMBER: 11-30-10

PRODUCTION STATUS: Under procurement

SHIPPING DATA: Shipped as a complete unit

SHIPPING WEIGHT: approximately 9 pounds

SHIPPING CARTON DIMENSIONS: approximately 16 by 16 by 6 inches

NAVY

There is no Navy equivalent for the Army item.

BRITISH

REFERENCE NUMBER: 109/43



COVER — ELECTRICALLY HEATED AUTOMATIC PILOT

GENERAL ELECTRIC CATALOG NUMBER PK 1A1

NAMES: Electrically heated automatic pilot cover

Electrically heated cover

A. F. C. E. cover

Electrically heated automatic pilot blanket

Electrically heated A. F. C. E. cover

DESCRIPTION: The electrically heated automatic pilot cover for the Army type C-1 automatic pilot consists of three type A-3 covers for the servo units and one type A-4 cover for the vertical gyro control unit.

The covers provide a protective coat to retain heat produced by the automatic pilot and to supply heat to the automatic pilot units for low temperature operation.

The covers are made of woolen batting quilted to cotton fabric. The electrical heating wires are sewed to the inner cotton fabric.

Automatic thermostatic control is provided in the electrical circuit to prevent overheating. The thermostat is encased in a metal tube which is attached to the inner lining of the cover.

A power supply cable on each cover is connected to the aircraft electrical circuit by a male plug.

CHARACTERISTICS:

Electrical connector	Twist lock plug, Hubbel part number 7542 or 7545
Maximum external temperature range	Minus 60 to plus 170 degrees fahrenheit (minus 51 to plus 77 degrees centigrade)
Minimum heating requirement	Maintains plus 15 degrees fahrenheit (minus 9.4 degrees centigrade) at external temperature of minus 60 degrees fahrenheit (minus 51 degrees centigrade)

RELATIONSHIP OF PARTS: Used with:

Servo unit of Army type C-1 automatic pilot and vertical gyro control unit of Army type C-1 automatic pilot.

ARMY

A. E. REFERENCE NUMBER: 64-855

SPECIFICATIONS:

Detail 40631 for type A-3 servo unit cover, 40633 for type A-4 vertical gyro control cover

MANUFACTURER: General Electric Company

MANUFACTURER'S PART NUMBER: G. E. catalog number PK 1A1

TYPE DESIGNATION: A-3 for servo unit cover, A-4 for vertical gyro control cover

A. S. C. STOCK NUMBER: 6400225911

TECHNICAL ORDER NUMBER: 11-30-11

PRODUCTION STATUS: Under procurement

SHIPPING DATA: Shipped as a complete unit, consisting of 3 electrically heated covers, type A-3 for servo units and 1 electrically heated cover type A-4 for vertical gyro control unit.

SHIPPING WEIGHT: approximately 16 pounds

SHIPPING CARTON DIMENSIONS: approximately 22 by 12 by 17 inches.

NAVY

There is no Navy equivalent for the Army item.



TORPEDO DIRECTORS

The function of the torpedo director is to determine the proper course upon which to set an airplane before launching a torpedo toward the desired target to assure interception of the target. The torpedo itself must be set for a straight run to permit accurate calculation. The factors to be considered in making calculations are the torpedo speed, the target speed, and the approach angle. Of these factors, only the torpedo speed is known, and consequently the target speed and approach angle must be estimated. The factors are then set upon the torpedo director controls and the airplane turned through the approach angle until the target appears in the sight, whereupon the torpedo is launched.

The various types of torpedo directors differ in general appearance and construction since some models employ an optical illuminated sight and other models are equipped with a non-optical sighting bar. All types perform identical functions and utilize similar steps for estimations and calculations.

In order to insure that the calculations performed will be satisfactory to complete the torpedoing mission, predetermined altitude, launching speed and torpedo range must be adhered to.



DIRECTOR—TORPEDO

MARK 28 MODIFICATION 2

NAMES: Torpedo director
Director assembly—torpedo

DESCRIPTION: The Mark 28 Modification 2 torpedo director is shaped in the form of a drum, and is provided with six scales to permit calculation of sight alignment for six different torpedo speeds. Target speed is estimated over a calibrated range. The sight angle scale is graduated in two sections, each ranging from 0° to 180°. The target direction angle is estimated, and the estimated angle is set on a movable pointer. The resultant angle of these calculations enables the pilot to change the course of the airplane to the proper position for launching a torpedo.



CHARACTERISTICS:

Weight..... approximately 4½ pounds
Outline dimensions..... approximately 8½ by 8½ by 8½ inches

INSTALLATION PECULIARITIES: A sun guard must be used with this director, to prevent the plastic pointer from warping. This guard is removed prior to operation of the director.

ARMY

A. E. REFERENCE NUMBER: 64-900

TYPE DESIGNATION: Mark 28 Modification 2.

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type B-2.

A. E. Reference Number 64-950.

SHIPPING DATA: Shipped as a complete unit, including a mounting bracket.

NAVY

TYPE DESIGNATION: Mark 28 Modification 2.

BUREAU OF ORDNANCE DRAWING NUMBER: 275122

AVIATION ORDNANCE STOCK LIST: 2-D-155

ORDNANCE DATA NUMBERS: 3786 and 4410

ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Under procurement


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
A. C. Spark Plug Division of General Motors	Mark 28 Modification 2	1590752	A-N-B	6402242425	11-50-1 11-50-2	109/40
Douglas Aircraft Corporation	Mark 28 Modification 2	1590752	A-N-B	6402242425	11-50-1 11-50-2	109/40

Above items are completely interchangeable with Mark 28 Torpedo Director. The only difference is the two directors is that the Mark 28 director has three torpedo speed scales, and the Mark 28 Modification 2 director has six torpedo speed scales.



DIRECTOR—TORPEDO

ARMY TYPE B-2

NAMES: Torpedo director

Director assembly—torpedo

DESCRIPTION: The Army type B-2 torpedo director is an optical, illuminated sighting device used on torpedo carrying airplanes. It is mounted on a square bar forward of the pilot's or co-pilot's station, and is adjustable over the length of the mounting bar. Calculations are made by means of vector arms which are adjusted through graduated dials.

In emergencies, this director may be used as an auxiliary gun-sight for the airplane's fixed guns by adjusting the director to a position parallel to the center line of the airplane, and in alignment with the line of fire.

CHARACTERISTICS:

Weight	approximately 2 $\frac{3}{4}$ pounds
Dimensions	approximately 10 $\frac{1}{2}$ by 7 $\frac{1}{4}$ by 7 $\frac{1}{2}$ inches
Electrical connector	AN3102-8S-1P
Electrical cable length	approximately 9 inches
Lamp bulb	Lamp, trade number 1666, I.F., 28 volts 21-21 C.P. S-8 I.F. bulb D.C. bay. base

ARMY

A. E. REFERENCE NUMBER: 64-950

SPECIFICATIONS:

Detail R-24789

A. A. F. DRAWING NUMBER: 43G7095

SUPERSEDED DRAWING NUMBER: 42G16373

TYPE DESIGNATION: B-2

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit including electrical cable and connector.

NAVY

TYPE DESIGNATION: B-2

AVIATION ORDNANCE STOCK LIST NUMBER: 2-D-176

PROCUREMENT STATUS: Procured from Army.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
J. H. Keeney & Co.	*B-2	**43G7095	A-N-B	6400242430	11-50-3	109/44
Douglas Aircraft Co.	RCL-2	5147380	A-B	6400242430	11-50-3	109/44

The above torpedo directors are interchangeable as complete units, but the optical systems are not interchangeable.
Note: *AAF type; **AAF drawing.

RELEASE HANDLES ARMAMENT—BOMBING



NAMES: Bomb release handle
Bomb release handle assembly

Tee-grip bomb release handle

DESCRIPTION: The type A-3 bomb release handle is used to release bombs and droppable cargo. Its application is restricted to the mechanical release of one bomb rack or multiple racks in salvo.

The handle is composed of a tee-grip, flexible spring, and a two hole mounting bracket.

Actuation of the bomb rack is accomplished by a flexible cable, one end of which is attached to the release handle and the other end to the bomb release mechanism.

CHARACTERISTICS:

Weight.....approximately $1\frac{1}{2}$ pound
Dimensions.....approximately $6\frac{1}{4}$ by $2\frac{1}{8}$ by 3 inches

INSTALLATION PECULIARITIES: A $\frac{1}{16}$ inch cable, specification number 48-22, is attached at the time of installation in the airplane.

ARMY

A. E. REFERENCE NUMBER: 64-1400

SPECIFICATIONS:

Detail.....93-24542
Superseded.....24542

A. A. F. DRAWING NUMBER: 0159268

TYPE DESIGNATION: A-3

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation, superseded by Army type A-3A, A. E. Reference Number 64-1600, and Army type A-3B, A. E. Reference Number 64-1610.

SHIPPING DATA: Shipped as a complete unit, disassembled.

NAVY

TYPE DESIGNATION: A-3

BUREAU OF ORDNANCE DRAWING NUMBER: 155892 and 155981

AVIATION ORDNANCE STOCK LIST NUMBER: 3-H-635


NAVY PUBLICATION: Ordnance Pamphlet Number 865

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Husband Aircraft Specialties, Incorporated	*A-3	**0159268	A-N-B	6400312100	111A 30
National Mineral Company	*A-3	**0159268	A-N-B	6400312100	111A 30
	*A-3A	**41810395	A-B	6400309950	111A 59
	*A-3B	**43811390	A-B	6400309975	111A 51
Union Steel Products Company	*A-3	‡155982	N	6400312100	111A 30

Note: *AAF type; **AAF drawing; ‡Bureau of Ordnance Drawing.



HANDLE—BOMB AND FLARE RELEASE

ARMY TYPE A-3A

NAMES: Bomb and flare release handle
Bomb and flare release handle assembly
Ball-grip bomb and flare release handle

DESCRIPTION: The Army type A-3A bomb and flare release handle is used to release bombs, flares or droppable cargo. Its application is restricted to the mechanical release of one bomb rack, or multiple racks in salvo.

The release handle is composed of a ball-grip, flexible spring, and a two hole mounting bracket.

Actuation of the bomb rack is accomplished by a flexible cable, one end of which is attached to the release handle and the other end to the bomb release mechanism.

CHARACTERISTICS:

Weight approximately $\frac{1}{2}$ pound
Dimensions approximately $7\frac{1}{8}$ by $3\frac{1}{4}$ by 2 inches

INSTALLATION PECULIARITIES: A $\frac{1}{16}$ inch cable, specification number AN-RR-C-43, is attached at the time of installation in the airplane.

ARMY

A. E. REFERENCE NUMBER: 64-1600

SPECIFICATIONS:

Detail 93-24542-A
Superseded 93-24542

A. A. F. DRAWING NUMBER: 41B10395

TYPE DESIGNATION: A-3A

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation, superseded by Army type A-3B.

A. E. Reference Number 64-1610.

SHIPPING DATA: Shipped as a complete unit, disassembled.

NAVY


There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
National Mineral Company	*A-3A	**41B10395	A-B	6400309950	111A 59
	*A-3	**0159268	A-N-B	6400312100	111A 30
	*A-3B	**43B11390	A-B	6400309975	111A 51
Husband Aircraft Specialties, Incorporated	*A-3	**0159268	A-N-B	6400312100	111A 30

*AAF type; **AAF drawing.

RELEASE HANDLES ARMAMENT—BOMBING



HANDLE—BOMB AND FLARE RELEASE **ARMY TYPE A-3B**

NAMES: Bomb and flare release handle
Bomb and flare release handle assembly

Ball-grip bomb and flare release handle

DESCRIPTION: The Army type A-3B bomb and flare release handle is used to release bombs, flares or droppable cargo. Its application is restricted to the mechanical release of one bomb rack or multiple racks in salvo.

The release handle is composed of a ball-grip and a tubular section set at an angle and welded to a two hole mounting bracket.

Actuation of the bomb rack is accomplished by a flexible cable, one end of which is attached to the release handle and the other end to the bomb release mechanism.

CHARACTERISTICS:

Weight approximately $\frac{3}{4}$ pound
Dimensions approximately $7\frac{1}{8}$ by $3\frac{1}{8}$ by 2 inches

INSTALLATION PECULIARITIES: A $\frac{1}{16}$ inch cable, specification number AN-RR-C-43, is attached at the time of installation in the airplane.

ARMY

A. E. REFERENCE NUMBER: 64-1610

SPECIFICATIONS:

Detail 93-24542B
Superseded 93-24542

A. A. F. DRAWING NUMBER: 43B11390

TYPE DESIGNATION: A-3B

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, disassembled.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
National Mineral Company	*A-3B	**43B11390	A-B	6400309975	111A/51
	*A-3A	**41B10395	A-B	6400309950	111A/59
	*A-3	**0159268	A-N-B	6400312100	111A/30
Husband Aircraft Specialties, Incorporated	*A-3	**0159268	A-N-B	6400312100	111A/30

Note: *AAF type; **AAF drawing.

**HANDLE—BOMB RELEASE**

ARMY TYPE L-21A NAVY TYPE L-21A

NAMES: Bomb release handle
Bomb release handle assembly
Bomb rack handle

DESCRIPTION: The type L-21A bomb release handle is used for the manual release of bombs and flares. Provision is made for release of bombs in either SAFE or ARMED condition.

When the release handle is used in a completely mechanical bomb release circuit, bombs can be released in salvo only. When the release handle is used to control electrical bomb release circuits, the handle must be placed in either the selective or salvo position before the release of bombs is accomplished by the bombardier's electrical release switch.

CHARACTERISTICS:

Dimensions..... approximately 8⁵/₈ by 8³/₈ by 3⁷/₈ inches
Weight..... approximately 1¹/₂ pounds

INSTALLATION PECULIARITIES: The type L-21A bomb release handle is normally used for left hand installation. For right hand installation, the sectors and lever must be reversed as shown on Army drawing number 38B5990.

ARMY

A. E. REFERENCE NUMBER: 64-1800

SPECIFICATIONS:

Detail..... 93-24563A
Superseded..... 93-24563

A. A. F. DRAWING NUMBER: 38D5989

TYPE DESIGNATION: L-21A

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: L-21A

BUREAU OF ORDNANCE DRAWING NUMBER: 308078

AVIATION ORDNANCE STOCK LIST NUMBER: 3-H-645


PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Arro Tool and Engineering Company	*L-21A	**38D5989	A-N-B	6400313900	111A/35
Guardian Electric Manufacturing Company	*L-21A	20933	A-N-B	6400313900	111A/35
Aero Supply Manufacturing Company, Incorporated	L-21A	308078	N	6400313900	111A/35

Note: *AAF type; **AAF drawing.



HANDLE—BOMB RELEASE

MARK 4 MODIFICATION 2

NAMES: Bomb release handle
Bomb rack release handle

Bomb release handle assembly

DESCRIPTION: The Mark 4 Modification 2 bomb release handle provides selective manual release of bombs in a left wing rack, a right wing rack, or salvo of the entire bomb load. A supplementary handle provides for controlling the arming of bombs which can be dropped in either SAFE or ARMED condition.

The bomb release handle consists of a metallic case which has a release handle extending from the top and a separate arming handle located on the lower sector of the case. The handles activate levers to which the bomb rack actuating cables are attached.

The handles, which are attached to the release lever and arming lever, may be reversed for either right or left hand installation.

The handle is installed on the airplane structure within reach of the operator.

CHARACTERISTICS:

Dimensions approximately 10½ by 6 by 3½ inches
Weight approximately 2¼ pounds

RELATIONSHIP OF PARTS: Used with:

Type AN-Mark 51 Modification 7 bomb racks, A. E. Reference Numbers 64-2349, 64-2350, and 64-2351.

ARMY

A. E. REFERENCE NUMBER: 64-1900

TYPE DESIGNATION: Mark 4 Modification 2

A. S. C. STOCK NUMBER: 6400311700

TECHNICAL ORDER NUMBER: 11-1-44

PRODUCTION STATUS: Under procurement from the Navy Department for Army use.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: Mark 4 Modification 2

BUREAU OF ORDNANCE DRAWING NUMBER: 108611, 375602 and 179000

AVIATION ORDNANCE STOCK LIST NUMBER: 3-H-627

PROCUREMENT STATUS: Under procurement.


BRITISH

BRITISH REFERENCE NUMBER: 111A/52



HEAD—PILOT'S BOMBSIGHT

ARMY TYPE A-1



NAMES: Pilot's bombsight head Variable bombing reflector
Low altitude bombsight Variable reflector

DESCRIPTION: The Army type A-1 pilot's bombsight head is used on a fixed gun sight body for directing bombs from extremely low altitudes, and to direct the firing of fixed guns.

The head is mounted on the gun sight directly in front of the pilot, with the center of the reflector at eye level. Adjustment is provided for bombing from various altitudes and speeds by varying the reflector angle. Variation is controlled by a graduated dial which allows a sight range from zero deflection down until the line of sight touches the airplane nose. Provision is made for adjusting the head for personal factors, which are determined by experience for the individual pilot's requirements. The pilot's bombsight head is composed of the following parts, whose functions are as indicated: Adjustable gun lock cam—to stop and lock the head in gunnery position. Adjusting dial—reading in degrees. Adjustable bombing cams—enables quick selection of position of adjusting dial. Latch—to release cams. Reflector frame—carries reflector. Sliding inner dial plate—for personal factor adjustment.

CHARACTERISTICS:

Dimensions approximately 6 $\frac{3}{8}$ by 5 by 5 $\frac{7}{8}$ inches
Weight approximately 1 $\frac{1}{2}$ pounds

INSTALLATION PECULIARITIES: When used with Army type N-6 fixed gun sight, A. E. Reference Number 52-4500 or Army type N-6A fixed gun sight, A. E. Reference Number 52-4525, a pilot's bombsight adapter ring, A. E. Reference Number 64-2001, must be supplied.

RELATIONSHIP OF PARTS: Used with:

Army type N-3A fixed gun sight, A. E. Reference Number 52-4400, Army type N-3B fixed gun sight, A. E. Reference Number 52-4425, Army type N-6 fixed gun sight, A. E. Reference Number 52-4500, or Army type N-6A fixed gun sight, A. E. Reference Number 52-4525.

ARMY

A. E. REFERENCE NUMBER: 64-2000
A. A. F. DRAWING NUMBER: 43D12264
TYPE DESIGNATION: A-1
A. S. C. STOCK NUMBER: Refer to chart.
TECHNICAL ORDER NUMBER: Refer to chart.
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number
American Gage Company	*A-1	**43D12264	A	6400322880	11-30-12
	*A-2	**43D19996	A		11-30-12
S. F. Bowser & Co., Inc.	*A-1	**43D12264	A	6400322880	11-30-12
	*A-2	**43D19996	A		11-30-12

*AAF type; **AAF drawing.



RING—PILOT'S BOMBSIGHT ADAPTER

ARMY PART NUMBER 43B15328

NAMES: Pilot's bombsight adapter ring
Pilot's bombsight head adapter ring

Adapter ring

DESCRIPTION: The pilot's bombsight adapter ring is used as a bushing to afford stable mounting of the Army type A-1 or A-2 pilot's bombsight head on a fixed gun sight when the outside diameter of the gun sight body is too small to provide a close fit with the inside diameter of the pilot's bombsight head. The adapter ring is cylindrical in shape and has two mounting holes in the flange, one diametrically opposite the other. The flange is notched to prevent interference with the gun sight when installation is made.

CHARACTERISTICS:

Dimensions approximately $3\frac{5}{8}$ by $2\frac{7}{8}$ by $1\frac{5}{16}$ inches
Weight approximately 1 $\frac{1}{6}$ pound

RELATIONSHIP OF PARTS: Used with:

Army type N-6 fixed gun sight, A. E. Reference Number 52-4500, or Army type N-6A fixed gun sight, A. E. Reference Number 52-4525, and Army type A-1 pilot's bombsight head, A. E. Reference Number 64-2000, or Army type A-2 pilot's bombsight head, A. E. Reference Number 64-2005.

ARMY

A. E. REFERENCE NUMBER: 64-2001

A. A. F. DRAWING NUMBER: 43B15328

TECHNICAL ORDER NUMBER: 11-30-12

PRODUCTION STATUS: Not under procurement for initial installation. This ring will be procured only when necessary to adapt the pilot's bombsight head to Army type N-6 or N-6A gun sight.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



HEAD—PILOT'S BOMBSIGHT

ARMY TYPE A-2

NAMES: Pilot's bombsight head
Low altitude bombsight
Variable bombing reflector
Variable reflector

DESCRIPTION: The Army type A-2 pilot's bombsight head is used on a fixed gun sight body for directing bombs from extremely low altitudes, and to direct the firing of fixed guns. The head is mounted on the gun sight directly in front of the pilot, with the center of the reflector at eye level. Adjustment is provided for bombing from various altitudes and speeds by varying the reflector angle. Variation is controlled by a graduated dial, which allows a sight range from zero deflection down until the line of sight touches the airplane nose. Provision is made for adjusting the head for personal factors, which are determined by experience for the individual pilot's requirements. The pilot's bombsight head is composed of the following parts, whose functions are as indicated: Adjustable gun lock cam—to stop and lock the head in gunnery position. Adjusting dial—reading in degrees. Adjustable bombing cams—enables quick selection of position of adjusting dial. Latch—to release cams. Reflector frame—carries reflector. Sliding inner dial plate—for personal factor adjustment. The A-2 pilot's bombsight head employs a different dial and latch, and is more durable and flexible than the A-1 pilot's bombsight head.



CHARACTERISTICS:

Dimensions..... approximately 5½ by 5¼ by 5 inches
Weight..... approximately 1¼ pounds

INSTALLATION PECULIARITIES: When used with Army type N-6 fixed gun sight, A. E. Reference Number 52-4500 or Army type N-6A fixed gun sight, A. E. Reference Number 52-4525, a pilot's bombsight adapter ring, A. E. Reference Number 64-2001, must be supplied.

RELATIONSHIP OF PARTS: Used with:

Army type N-3A fixed gun sight, A. E. Reference Number 52-4400 and Army type N-3B fixed gun sight, A. E. Reference Number 52-4425.

ARMY

A. E. REFERENCE NUMBER: 64-2005
A. A. F. DRAWING NUMBER: 43D19996
TYPE DESIGNATION: A-2
TECHNICAL ORDER NUMBER: Refer to chart.
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE Models are used in services as noted in column 4 A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number
American Gage Company	*A-2	**43D19996	A		11-30-12
	*A-1	**43D12264	A	6400322880	11-30-12
S. F. Bowser & Co., Inc.	*A-2	**43D19996	A		11-30-12
	*A-1	**43D12264	A	6400322880	11-30-12

Note: *AAF type, **AAF drawing.



HOIST—PORTABLE BOMB TYPE AN-MARK 7 MODIFICATION 1

NAMES: Portable bomb hoist
Adjustable bomb hoist

Bomb adjustable hoist
Bomb portable hoist

DESCRIPTION: The AN-Mark 7 Modification 1 portable bomb hoist provides a means for hoisting bombs to their proper bomb racks. This hand-held crank operated bomb hoist is used for loading operations on fighter, attack and light bombardment airplanes, and has a normal lifting capacity of 1000 pounds.

The complete bomb hoist is composed of a cable drum, an extension tube, cable pulley, hoist attachment fitting, hand grip and a gear-operating crank. The hoist attachment fitting is hooked to a hoist bracket on the airplane structure or on the bomb rack, and transmits the load of the bomb to the airplane structure and acts as a pivot for movement of the hoist for convenience of the operator. An internal ratchet prevents the bomb cable from slipping when the handle is released.

Some form of adapter such as trunnion bands or the Army type A-2 bomb hoist sling must be provided for hoisting bombs not equipped with a hoisting lug.

CHARACTERISTICS:

Weight	approximately 41 pounds
Dimensions	approximately 49 by 13¼ by 13¼ inches
Normal lifting capacity	1000 pounds
Maximum emergency capacity	1600 pounds
Distance of total lift	102 inches

RELATIONSHIP OF PARTS: Used with:

Bomb trunnion bands, M1 to M6 inclusive or Army type A-2 bomb hoist sling, A. E. Reference Number 64-4150.

(Continued on page 269)



HOIST—PORTABLE BOMB

(Continued from page 258)

ARMY

A. E. REFERENCE NUMBER: 64-2250

A. A. F. DRAWING NUMBER: H42B16115

TYPE DESIGNATION: AN-Mark 7 Modification 1

A. S. C. STOCK NUMBER: 6400324800

TECHNICAL ORDER NUMBER: 11-5-49

PRODUCTION STATUS: Under procurement from the Navy Department for Army use.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: AN-Mark 7 Modification 1

BUREAU OF ORDNANCE DRAWING NUMBER: Assembly 300173B, Outline 300172

AVIATION ORDNANCE STOCK LIST NUMBER: 3-H-1035

ORDNANCE PAMPHLET NUMBER: 949 and 865

ORDNANCE CIRCULAR LETTER NUMBER: V 14-42

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE


Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
The Manley Manufacturing Division of American Chain & Cable Company, Inc.	AN-Mark 7 Modification 1	Assembly 300173B	A-N-B	6400324800	11-5-49	111A/46
		Outline 300172				
Sullivan Machine Company	AN-Mark 7 Modification 1	Assembly 300173B	A-N-B	6400324800	11-5-49	111A/46
		Outline 300172				
Food Machinery Corporation	AN-Mark 7 Modification 1	Assembly 300173B	A-N-B	6400324800	11-5-49	111A/46
		Outline 300172				

NOTE: The AN-Mark 7, Modification 1 supersedes and is interchangeable with Navy Mark 7 and Mark 2, Modification 1 portable bomb hoists.
*Army-Navy Type.

BOMB HOISTS ARMAMENT—BOMBING



HOIST—BOMB

ARMY TYPE C-3

NAMES: Bomb hoist

Bomb hoist assembly

DESCRIPTION: The Army type C-3 bomb hoist provides a means for hoisting demolition bombs of all sizes up to and including 2000 pounds to their proper stations on the bomb rack. This hand operated bomb hoist may also be used for hoisting cargo, provided the total weight does not exceed 2000 pounds. The complete hoist is composed of a right hand and a left hand windlass assembly, two bomb hoist handle assemblies and one each of the following size slings: 300 pound; 500 to 600 pound; 1000 to 1100 pound; and 2000 pound. The Army type A-2 bomb hoist sling may be included as a part of this bomb hoist.

Each windlass assembly is equipped with a brake to prevent the bomb cable from slipping when pressure on the handle is relaxed. The handles may be attached to either side of the windlass and are provided with three box sockets to allow for increased leverage as required with increased bomb weights.

CHARACTERISTICS:

Weight approximately 68½ pounds
Dimensions approximately 21½ by 11¼ by 9½ inches.

RELATIONSHIP OF PARTS: Used with:

Army type A-1 bomb hoist sling, A. E. Reference Number 64-4100 or Army type A-2 bomb hoist sling, A. E. Reference Number 64-4150

INSTALLATION PECULIARITIES: Either windlass may be converted to a right or left hand unit by rewinding the hoisting cable about the windlass drum in the opposite direction.

ARMY

A. E. REFERENCE NUMBER: 64-2200

SPECIFICATIONS:

Detail 93-24583
Superseded 24583

A. A. F. DRAWING NUMBER: (Hoist Assembly) 36H5311; (Packing Case Assembly) 37K4961

TYPE DESIGNATION: C-3

A. S. C. STOCK NUMBER: Refer to chart

TECHNICAL ORDER NUMBER: Refer to chart

PRODUCTION STATUS: Under procurement

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE


Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
The Taylor Machine Company	*C-3	**36H5311	A-B	6400325200	11-5-26	104G 28	See note.
Sparks-Withington Company	*C-3	A-16759	A-B	6400325200	11-5-26	104G 28	See note.

NOTE. Early models of the Army type C-3 bomb hoist did not contain a brake assembly. Army part number 40A6792.

*AAF type; **AAF drawing.



MOUNT—GRENADE

ARMY TYPE A-1

NAMES: Grenade mount
Grenade mount assembly

Hand grenade mount
Incendiary grenade mount

DESCRIPTION: The Army type A-1 grenade mount is composed of two spring steel clamps riveted to a steel base.

The grenade mount is attached to the airplane structure within reach of the pilot, and is used to carry one incendiary grenade.

CHARACTERISTICS:

Weight.....approximately 4/5 pound
Dimensions.....approximately 6 1/4 by 2 5/8 by 2 5/8 inches

RELATIONSHIP OF PARTS: Used with:
One AN-M14 incendiary grenade.

ARMY

A. E. REFERENCE NUMBER: 64-2265

SPECIFICATIONS:

Detail.....93-24840
Superseded.....24840

MANUFACTURER: Airolite Co.

A. A. F. DRAWING NUMBER: 43D10279

TYPE DESIGNATION: A-1


A. S. C. STOCK NUMBER: 6400469150

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



MOUNT—BOMB ARMING CONTROL ARMY TYPE A-1

NAMES: Bomb arming control mount
Bomb fusing control box slide

Bomb arming control mount assembly

DESCRIPTION: The type A-1 bomb arming control mount is used to attach bomb arming controls to bomb racks equipped with slide mounting rails. The mount is fastened to the control with two screws and a movable bracket which is under spring tension. The assembly is then installed in the mounting rails.

CHARACTERISTICS:

Weight approximately $\frac{3}{16}$ pound
Dimensions approximately $2\frac{1}{2}$ by $1\frac{3}{8}$ by $\frac{1}{8}$ inches

RELATIONSHIP OF PARTS: Used with:

Type AN-A-2 bomb arming control, A. E. Reference Number 64-220, and Army type B-2 bomb arming control, A. E. Reference Number 64-275, when mounting to slide mounting rails.

ARMY

A. E. REFERENCE NUMBER: 64-2270

SPECIFICATIONS:

Detail 24830

MANUFACTURER'S DRAWING NUMBER: Magnavox Corporation 14D27G1

A. A. F. DRAWING NUMBER: 43A9886

TYPE DESIGNATION: A-1

A. S. C. STOCK NUMBER: 6400467850


TECHNICAL ORDER NUMBER: 11-5-33


PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.





MOUNT—BOMBSIGHT

ARMY TYPE B-7

NAMES: Bombsight mount
Anti-vibration bombsight mount

Bombsight mount assembly
Bombsight shock mount

DESCRIPTION: The M-series bombsight and stabilizer are retained in their proper location upon the airplane by the Army type B-7 bombsight mount.

This device is so built that two mechanical regulators control leveling of the bombsight both fore and aft and laterally.

The B-7 bombsight mount is attached to a bracket in the bombardier's compartment in the airplane by three bolts, and is equipped with rubber shock absorbers, which protect the bombsight from damage by shock or vibration.

CHARACTERISTICS:

Weight approximately 9¾ pounds
Dimensions approximately 9 by 12 by 14 inches

RELATIONSHIP OF PARTS: Used with:
Army type M-series bombsights.

ARMY

A. E. REFERENCE NUMBER: 64-2272

SPECIFICATIONS:

Detail 24809

MANUFACTURER'S DRAWING NUMBER: Lovell Manufacturing Company, E11779

A. A. F. DRAWING NUMBER: 42J11779

TYPE DESIGNATION: B-7

A. S. C. STOCK NUMBER: 6400468850

PRODUCTION STATUS: Under procurement


SHIPPING DATA: shipped as a complete unit.

NAVY

The Navy does not use the Army item.



PILOT DIRECTOR INDICATORS ARMAMENT—BOMBING



INDICATOR—PILOT DIRECTOR

ARMY—SEE BELOW NAVY MARK 15, MOD. 5

NAMES: Pilot director indicator
Bombsight pilot director indicator
P. D. I.

DESCRIPTION: The pilot director indicator is an indicating type meter with 4 graduation marks to the right and left of a center zero, and it is mounted on the pilot's instrument panel.

The pointer fluctuates right or left in response to signals originating in the automatic pilot's directional stabilizer; this indicates to the pilot the course change desired by the bombardier. Movement of the airplane in the desired direction returns the pointer to the zero position.

This indicator operates on a 26 volt electrical circuit, and has a two pin electrical receptacle. A mating electrical plug, AN3106-12S-3S, was supplied with early models of this indicator to facilitate installation in the airplane.

CHARACTERISTICS:

Dimensions.....	approximately 3 $\frac{1}{4}$ " by 3 $\frac{1}{4}$ " by 3 $\frac{3}{8}$ " inches
Weight.....	approximately 1 $\frac{1}{2}$ pounds
Illumination.....	none
Markings.....	fluorescent
Voltage.....	26 volts direct current
Electrical Receptacle.....	AN3102-12S-3P

RELATIONSHIP OF PARTS: Used with:

Army type C-1 automatic pilot, A. E. Reference Number 64-2300. When installed on an airplane not equipped with an Army type C-1 automatic pilot, it is used with Army type A-1 pilot director indicator control, A. E. Reference Number 64-835.

(Continued on page 265)

INDICATOR—PILOT DIRECTOR

(Continued from page 264)

ARMY

A. E. REFERENCE NUMBER: 64-2255

SPECIFICATIONS:

General C-24825

Detail C-24863

TECHNICAL ORDER NUMBER: 11-60AA-1

PRODUCTION STATUS: Under procurement

SHIPPING DATA: Shipped as a complete unit including electrical connector plug AN3106-12S-3S for early models only.

NAVY

TYPE DESIGNATION: Mark 15, Mod. 5

BUREAU OF ORDNANCE DRAWING NUMBER: 300206 (Installation Drawing)

AVIATION ORDNANCE STOCK LIST NUMBER: 2-I-115

PROCUREMENT STATUS: Under procurement.


MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	A. E. Reference Number	Navy Type	Bureau of Ordnance Drawing Number	Remarks
O. B. McClintock Company	MD3071 (2 pole)	PDI 100 (26 volt)	A-N-B	6400374920	11-60AA-1	109 45	64-2255	MK 15, Mod. 5	300206	Electrical receptacle: AN3102-12S-3P (2 pin)
	MD3071 (4 pole)	PDI 100 (26 volt)	A-N	6400374900			64-2257	MK 15, Mod. 3	300206	Electrical receptacle: Cannon WK-4-32S (4 pin)
Roller-Smith Company		‡265673 (modified)	A-N-B	6400374920	11-60AA-1	109 45	64-2255	MK 15, Mod. 5	300206	Electrical receptacle: AN3102-12S-3P (2 pin)

NOTE: These models may be made interchangeable by substituting the proper electrical connector. ‡Bureau of Ordnance Drawing.



PILOT DIRECTOR INDICATORS ARMAMENT—BOMBING



INDICATOR—PILOT DIRECTOR NAVY MARK 15, MOD. 3

NAMES: Pilot director indicator
Bombsight pilot director indicator
P. D. I.

DESCRIPTION: The pilot director indicator is an indicating type meter with 4 graduation marks to the right and left of a center zero, and it is mounted on the pilot's instrument panel.

The pointer fluctuates right or left in response to signals originating in the automatic pilot's directional stabilizer. This indicates to the pilot the course change desired by the bombardier. Movement of the airplane in the desired direction returns the pointer to the zero position.

This indicator operates on a 26 volt electrical circuit. It has a four pin electrical connector, although only two pins are utilized electrically.

CHARACTERISTICS:

Dimensions.....	approximately 3 $\frac{1}{4}$ " by 3 $\frac{1}{4}$ " by 3 $\frac{1}{2}$ " inches
Weight.....	approximately 1 $\frac{1}{8}$ pounds
Illumination.....	none
Markings.....	fluorescent
Voltage.....	26 volts direct current
Receptacle.....	Cannon WK-4-32S

RELATIONSHIP OF PARTS: Used with:

Army type C-1 automatic pilot, A. E. Reference Number 64-2300. When installed on an airplane not equipped with Army type C-1 automatic pilot, it is used with Army type A-1 pilot director indicator control, A. E. Reference Number 64-835.

(Continued on page 267)

INDICATOR—PILOT DIRECTOR

(Continued from page 266)

ARMY

A. E. REFERENCE NUMBER: 64-2257

SPECIFICATIONS:

General C-24825
 Detail C-24580-D
 Superseded C-24580-C

A. S. C. STOCK NUMBER: 6400374900

PRODUCTION STATUS: Not under procurement for initial installation.
 Superseded by pilot director indicator, A. E.
 Reference Number 64-2255

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: Mark 15, Mod. 3

BUREAU OF ORDNANCE DRAWING NUMBER: 300206 (Installation Drawing)

AVIATION ORDNANCE STOCK LIST NUMBER: 2-1-105

PROCUREMENT STATUS: Not under procurement for initial installation. Superseded by Mark 15,
 Mod. 5.

MODELS BELOW ARE INTERCHANGEABLE
 Models are used in services as noted in column 4
 A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	A. E. Reference Number	Navy Type	Bureau of Ordnance Drawing Number	Remarks
O. B. McClintock Company	MD3071 (4 pole)	PDI 100 (26 volt)	A-N	6400374900			64-2257	MK 15, Mod. 3	300206	Electrical receptacle: Cannon WK-4-32S (4 pin)
	MD3071 (2 pole)	PDI 100 (26 volt)	A-N-B	6400374920	11-60AA-1	109, 45	64-2255	MK 15, Mod. 5	300206	Electrical receptacle: AN3102-12S-3P (2 pin)
Roller-Smith Company		265673 (modified)	A-N-B	6400374920	11-60AA-1	109 45	64-2255	MK 15, Mod. 5	300206	Electrical receptacle: AN3102-12S-3P (2 pin)

NOTE: These models may be made interchangeable by substituting the proper electrical connector.
 ‡Bureau of Ordnance Drawing.

AUTOMATIC PILOT ARMAMENT—BOMBING




PILOT—AUTOMATIC

ARMY TYPE C-1 NAVY MARK 2, MODIFICATION 1

The automatic pilot is used to automatically control the airplane during normal flight or on bombing runs. The diagram below shows the approximate location of the component units in the airplane.

The pilot's control panel and the turn control are not used with the automatic pilot when an autopilot control panel is specified.



COMPONENT ITEMS

- | | |
|--|--|
| <ul style="list-style-type: none"> 1 Stabilizer-Directional 2 Panel-Directional 3 Lock-Directional arm 4 Panel-Pilot's control 5 Control-Turn 6 Panel-Autopilot control AER No. 64-195 | <ul style="list-style-type: none"> 7 Indicator-Pilot director AER No. 64-2255 8 Control-Vertical gyro 9 Amplifier 10 Inverter-Rotary 11 Motor-Servo |
|--|--|

ARMY

A. E. REFERENCE NUMBER: (complete pilot) 64-2300

SPECIFICATION:

General C-24825

TECHNICAL ORDER NUMBER: 11-60-1 and 11-60AA-1

A. S. C. STOCK NUMBER: 6400507995

NAVY

NAME: Stabilized Bombing Approach Equipment (SBAE)

TYPE DESIGNATION: Mark 2 Modification 1

AVIATION ORDNANCE STOCK LIST NUMBER: (complete pilot) 2-S-335

NAVAL ORDNANCE PAMPHLET NUMBER: 639.

BRITISH

REFERENCE NUMBERS: see individual items.

MANUFACTURER

Minneapolis Honeywell Regulator Company.

(Continued on page 269)

PILOT—AUTOMATIC

(Continued from page 268)

DIRECTIONAL STABILIZER

The directional stabilizer contains the stabilizer gyro which controls the movement of the airplane in azimuth and the pilot director indicator potentiometer and brush which operate the pilot director indicator located on the pilot's instrument panel.

The directional arm and the directional arm lock are attached to this unit.

Dimensions, approximately $11\frac{1}{2}$ by $12\frac{1}{8}$ by $12\frac{3}{4}$ inches.
 Weight, approximately 39 $\frac{1}{4}$ pounds.
 Army Air Force specification C-24827
 A. S. C. stock number 6400963750
 British reference number 106J 758
 Manufacturer's drawing and part number G1048
 Production status: Under procurement.



AUTOPILOT CONTROL PANEL

For detailed description of this item refer to A. E. Reference Number 64-195, page 232 of this index.

PILOT DIRECTOR INDICATOR

For detailed description of this item refer to A. E. Reference Number 64-2255, page 264 of this index.

VERTICAL GYRO CONTROL

The vertical gyro control unit is the vertical reference of the airplane with respect to the earth's surface. It provides reference for the lateral and longitudinal control of the airplane.

The unit consists of a gyroscope rotor secured to a spindle on which is mounted the armature of a shunt-wound motor. The rotor provides the motivating force for the gyro, operating it at high speed.

Dimensions, approximately 7 $\frac{1}{2}$ by $10\frac{1}{2}$ by $8\frac{1}{4}$ inches.
 Weight, approximately 18 $\frac{1}{4}$ pounds.
 Army Air Force specification C-24858
 A. S. C. stock number 6400304650
 British reference number 106J/694
 Manufacturer's drawing and part number G1021A
 Manufacturer's outline drawing number DR2002
 Production status: Under procurement.



AMPLIFIER

The amplifier consists of electronic tubes, relays, chokes, and a transformer for the power supply of the tubes. These units are mounted on a removable rack which slides into its case on two guides.

Dimensions, approximately 7 $\frac{1}{2}$ by 9 $\frac{3}{4}$ by 8 $\frac{1}{4}$ inches.
 Weight, approximately 12 $\frac{1}{4}$ pounds.
 Army Air Force specification C-24859
 A. S. C. Stock number 6400009400
 British reference number 106J 700
 Manufacturer's drawing and part number G1024A
 Manufacturer's outline drawing number DR2000
 Production status: Under procurement.



(Continued on page 270)



PILOT—AUTOMATIC

(Continued from page 269)

ROTARY INVERTER



The rotary inverter provides the alternating current required to operate the automatic pilot.

This rotary inverter consists of a direct current motor with its armature windings tapped at two opposite points, and connected to two collector rings insulated from the armature. Direct current is supplied to the motor commutator through carbon brushes; the alternating current is drawn from the collector rings by carbon brushes. A choke coil, three condensers, and a connector plug (AN3102-14S-5P) are included in the base. The construction of the base permits the inverter to be turned 180 degrees for connection or mounting convenience.

The inverter receives the 24 to 28 volt direct current provided by the airplane's generator and supplies 19 volt alternating current for operating the pilot. The starting current drawn is 23 amperes and running current is 2.5 amperes.


Dimensions, approximately	5 $\frac{5}{8}$ by 5 $\frac{3}{4}$ by 6 $\frac{3}{4}$ inches.
Weight, approximately	10 $\frac{1}{4}$ pounds.
Army Air Force specification	C-24862
A. S. C. Stock number	6400219650
British reference number	106J 693
Manufacturer's drawing and part number	G1025A
Manufacturer's outline drawing number	DR2001
Production status: Under procurement.	

SERVO MOTOR

The servo motor consists of an assembly containing a 1/20 horsepower direct current motor. This motor operates a system of gears, brakes, clutches, solenoids, and a limit switch to drive a cable drum. The drum can accommodate 24 to 26 inches of cable travel while driving over a range of four and one half inches.

Three servo motors are used on each aircraft; the motors are connected by cable to control the plane's rudder, elevator and ailerons.

Dimensions, approximately	6 $\frac{1}{4}$ by 9 $\frac{1}{2}$ by 10 $\frac{1}{2}$ inches.
Weight, approximately	23 $\frac{3}{4}$ pounds.
Army Air Force specification	C-24860
A. S. C. stock number	6400464500
British reference number	106J 696
Manufacturer's drawing and part number	G1020
Manufacturer's outline drawing number	DR2003
Production status: Under procurement.	



DIRECTIONAL PANEL

The directional panel is mounted on the directional stabilizer. It consists of two potentiometers with pick-up contacts or brushes, a flight gyro roller cutout switch, and a dash pot with linkage.

Dimensions, approximately	5 $\frac{1}{4}$ by 8 $\frac{1}{4}$ by 3 $\frac{3}{4}$ inches.
Weight, approximately	3 $\frac{1}{4}$ pounds.
Army Air Force specification	C-24796
A. S. C. Stock number	6400496523
British reference number	106J 695
Manufacturer's drawing and part number	G1005A
Manufacturer's outline drawing number	DR2004
Production status: Under procurement.	



(Continued on page 271)



PILOT—AUTOMATIC

(Continued from page 270)

DIRECTIONAL ARM LOCK

The directional arm lock consists of a solenoid, drawing approximately 0.4 amperes of current actuated by a series of levers. It is mounted on the directional stabilizer.

Rotation of the turn control knob from the center, or zero, position energizes the solenoid and actuates the levers to lock the gyro secondary clutch in a neutral position. When the control knob is returned to the zero position, the clutch is released and the airplane resumes straight flight on the new course.

Dimensions, approximately	7 $\frac{3}{8}$ " by 5 $\frac{1}{2}$ " by 1 $\frac{1}{4}$ " inches.
Weight, approximately	1 $\frac{1}{4}$ pounds.
Army Air Force specification	C-24827
A. S. C. Stock number	6400430925
British reference number	106J 759
Manufacturer's drawing and part number	G1029A2
Manufacturer's outline drawing number	DR2033

Production status: Under procurement.



PILOT'S CONTROL PANEL

The pilot's control panel contains the controls necessary for the operation of the automatic pilot except the pilot's turn control, which is mounted separately, and the limit switches of the servos, which are attached to individual units. It is mounted in the pilot's compartment.

It contains toggle switches at the top of the panel, to control the following units:

- Master (for complete control)
- Pilot director indicator
- Aileron servo, (brake clutch solenoid only)
- Rudder servo, (brake clutch solenoid only)
- Elevator servo, (brake clutch solenoid only)
- Directional stabilizer
- Stabilizer servo

The master and directional stabilizer switches are connected by a bar which moves both switches ON and OFF together, and prevents the other switches from being used before the automatic pilot is in operation. Movement of the bar to the OFF position operates all switches simultaneously, with the exception of the pilot director indicator and the stabilizer servo switches.

Adjusting knobs for the centering, sensitivity, ratio and turn compensation for the three axes of control are also located on the face of the panel.

Dimensions, approximately	10 $\frac{1}{8}$ " by 6" by 4 $\frac{3}{8}$ " inches.
Weight, approximately	5 $\frac{3}{4}$ pounds.
Army Air Force specification	C-24861
A. S. C. stock number	6400091560
British reference number	106J 698
Manufacturer's drawing and part number	G1023A

Production status: Not under procurement for initial installation. Superseded by Autopilot Control Panel.


TURN CONTROL

The turn control provides the pilot with a means of turning the airplane at an angle of bank (up to 40 degrees), and returning it to straight flight by means of the automatic pilot. It is mounted in the pilot's compartment.

Dimensions, approximately	3 $\frac{3}{8}$ " by 2 $\frac{1}{2}$ " by 4 $\frac{1}{4}$ " inches.
Weight, approximately	1 pound
Army Air Force specification	C-24864
A. S. C. stock number	6400372100
British reference number	106J 697
Manufacturer's drawing and part number	G1027A
Manufacturer's outline drawing number	DR2031

Production status: Not under procurement for initial installation. Superseded by Autopilot Control Panel.



**RACK—BOMB****TYPE AN-MARK 51 MODIFICATION 7****NAMES:** Bomb rack

Bomb rack assembly

DESCRIPTION: This type bomb rack is a combination electrical and mechanical unit, designed to be adapted to all types of dive bombers having a 24 volt electrical system. Installation may be made either in the lower wing surface or in the bomb bay compartment. Arming and releasing controls are actuated by the energizing of solenoids or, in emergency, by mechanical means. Two solenoids, located in the forward part of the bomb rack, actuate the arming of the bomb nose and tail fuses, and a solenoid located toward the rear operates the release mechanism.

CHARACTERISTICS:

Weight	approximately 11 1/4 pounds
Dimensions	approximately 23 1/2 by 2 3/8 by 5 1/4 inches
Maximum capacity	1600 pounds
Electrical connector	AND10427-14S-5P insert arrangement
Electrical connector mates with	AN3108-14S-5S, or AN3106-14S-5S
Distance between suspension lugs	14 inches

RELATIONSHIP OF PARTS: Used with:

Navy Mark 4 Modification 2 bomb release handle. . . A. E. Reference Number 64-1900

INSTALLATION PECULIARITIES: To facilitate installation, the Mark 51 Modification 7 bomb rack may be ordered by designating the required installation position in the airplane. Arrangement of parts for the different positions are as follows:

CENTER—A. E. REFERENCE NUMBER 64-2349

Electrical receptacle assembly on left sideplate

No hoist bracket

Smoke screen tank terminal on left sideplate forward

LEFT—A. E. REFERENCE NUMBER 64-2350

Electrical receptacle assembly on right sideplate

Hoist bracket on left sideplate

Smoke screen tank terminal on left sideplate forward

RIGHT—A. E. REFERENCE NUMBER 64-2351

Electrical receptacle assembly on left sideplate

Hoist bracket on right sideplate

Smoke screen tank terminal on left sideplate forward

ARMY

A. E. REFERENCE NUMBER: 64-2349 (Center), 64-2350 (Left), 64-2351 (Right)

A. A. F. DRAWING NUMBER: 43B7513

TYPE DESIGNATION: AN-Mark 51 Modification 7

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement. Supersedes and is interchangeable with Mark 51 Modification 5.

SHIPPING DATA: Shipped as a complete unit.

(Continued on page 279)



RACK—BOMB

(Continued from page 272)

NAVY

TYPE DESIGNATION: AN-Mark 51 Modification 7

BUREAU OF ORDNANCE DRAWING NUMBER: 328759

AVIATION ORDNANCE STOCK LIST NUMBER: 3-R-176-70 (Center), 3-R-176-73 (Left), 3-R-176-75 (Right)

ORDNANCE PAMPHLET NUMBER: 865A and 925


ORDNANCE CIRCULAR LETTER NUMBER: V 10 43

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
International Register Company	AN-Mark 51 Modification 7	**4387513	A-N-B	6400624115	11-5-7	111A/53
Pallak Manufacturing Company	AN-Mark 51 Modification 7	41C430	A-N-B	6400624115	11-5-7	111A/53

NOTE: Above information is applicable regardless of arrangement of parts.
**AAF drawing.



RACK—BOMB

ARMY TYPE MARK 43 MODIFICATION 1

NAVY MARK 43 MODIFICATION 1

NAMES: Bomb rack
Miniature bomb rack

Bomb rack assembly

DESCRIPTION: The Mark 43, Modification 1 bomb rack is a light, torpedo-shaped cylinder, with enclosed operating mechanism. The bomb rack has five compartments, each of which will hold one three-pound practice bomb. The doors are closed upon loading. The bombs are held in place by spring loaded ejectors, and are released from the compartments upon opening of the compartment doors by movement of the bomb release handle at the bombardier's station. Bombs used in this bomb rack are always in an armed condition and explode upon impact. This bomb rack was developed especially for practice dive bombing at speed up to 345 miles per hour.

CHARACTERISTICS:

Weight	approximately 13 $\frac{3}{4}$ pounds
Dimensions	approximately 38 $\frac{1}{4}$ by 7 $\frac{1}{4}$ by 4 $\frac{1}{4}$ inches
Distance between suspension lugs	22 $\frac{1}{4}$ inches
Capacity	5 miniature practice bombs

RELATIONSHIP OF PARTS: Used with:

Navy, Mark 4 Modification 2 bomb release handle, A. E. Reference Number 64-1900.

ARMY

A. E. REFERENCE NUMBER: 64-2340

TYPE DESIGNATION: Mark 43 Modification 1.

A. S. C. STOCK NUMBER: 6400621515

TECHNICAL ORDER NUMBER: 11-5-18

PRODUCTION STATUS: Under procurement from the Navy Department for Army use.

SHIPPING DATA: Shipped as a complete unit.


NAVY

TYPE DESIGNATION: Mark 43 Modification 1

BUREAU OF ORDNANCE DRAWING NUMBER: 182990

AVIATION ORDNANCE STOCK LIST NUMBER: 3-R-167

PROCUREMENT STATUS: Under procurement.

**RACK—BOMB****ARMY TYPE N-5**

NAMES: Bomb rack
Bomb rack assembly

Wing bomb rack
External bomb rack

DESCRIPTION: The type N-5 bomb rack is installed externally, usually in the wing position of light bombardment or fighter airplanes. Each bomb rack will support three thirty-pound fragmentation bombs, or three twenty-pound practice bombs. Bombs may be dropped individually, or in salvo, from this rack.

Front and rear away bracing must be provided to prevent movement of the bombs during flight.

The bomb rack is activated by a 12 volt solenoid which forms a part of this rack.

CHARACTERISTICS:

Weight	approximately 8 pounds
Dimensions	approximately 2 $\frac{1}{4}$ by 6 by 17 $\frac{1}{4}$ inches
Maximum capacity	three 30 pound bombs
Electrical connector	Army drawing number 35A2539

RELATIONSHIP OF PARTS: Used with:

Army type L-21A bomb release handle, A. E. Reference Number 64-1800, for mechanical release, or AN3022-2 toggle switch, A. E. Reference Number 52-6650 and Army type B-5 control stick switch, A. E. Reference Number 52-6600, for electrical release.

ARMY

A. E. REFERENCE NUMBER: 64-2400

SPECIFICATIONS:

Detail	98-24626
Superseded	24626

MANUFACTURER: Banner Die Tool and Stamping Company

MANUFACTURER'S DRAWING NUMBER: 39G4407

A. A. F. DRAWING NUMBER: 39G4407

TYPE DESIGNATION: N-5


A. S. C. STOCK NUMBER: 6400621600

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by Army type Q-2 bomb rack, A. E. Reference Number 64-2600, since 12 volt systems are no longer used in bombardment or fighter airplanes.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.



RACK—BOMB ARMY TYPE Q-2

NAMES: Bomb rack
Bomb rack assembly

External bomb rack
Wing bomb rack

DESCRIPTION: The type Q-2 bomb rack is installed externally, usually in the wing position, of light bombardment or fighter airplanes. Each bomb rack will support three thirty-pound fragmentation bombs, or three twenty-pound practice bombs. Bombs may be dropped individually, or in salvo, from this rack.

Front and rear sway bracing must be provided, to prevent movement of the bombs during flight. The bomb rack is activated by a 24 volt solenoid, which forms a part of this rack.

CHARACTERISTICS:

Weight	approximately 7¾ pounds
Dimensions	approximately 19 by 2½ by 6 inches
Maximum capacity	three 30 pound bombs
Electrical connector	Army drawing number 35A2539
Power supply	24 volt, direct current

RELATIONSHIP OF PARTS: Used with:

Army type L-21A bomb release handle, A. E. Reference Number 64-1800, for mechanical release, or AN3022-2 toggle switch, A. E. Reference Number 52-6650 and Army type B-5 control stick switch, A. E. Reference Number 52-6600, for electrical release.

ARMY

A. E. REFERENCE NUMBER: 64-2600

SPECIFICATIONS:

Detail	93-24628
Superseded	24628

MANUFACTURER'S DRAWING NUMBER: Banner Die Tool and Stamping Company: 39G4427

A. A. F. DRAWING NUMBER: 39G4427

TYPE DESIGNATION: Q-2

A. S. C. STOCK NUMBER: 6400621750

PRODUCTION STATUS: Under procurement

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

BRITISH

BRITISH REFERENCE NUMBER: 111A/36.

**RECEPTACLE—BOMB RELEASE****ARMY TYPE A-1 NAVY MARK 1**

NAMES: Bomb release receptacle
Bomb release receptacle assembly

Auxiliary switch box

DESCRIPTION: The Army type A-1 bomb release receptacle is a three contact socket. It is installed in the electrical circuit of the airplane, and mates with the corresponding connector on the bomb rack release.

CHARACTERISTICS:

Power supply	12 or 24 volts, direct current
Dimensions	approximately $1 \frac{3}{4}$ by $1 \frac{3}{4}$ by $1 \frac{1}{4}$ inches
Weight	approximately 1/10 pound

RELATIONSHIP OF PARTS: Used with: Bomb rack release;

A. E. Reference Number	Army Type	
64-3000	A-2	left hand release
64-3200	A-2	right hand release
64-3425	A-3	right hand release
64-3430	A-4	left hand release
64-3431	A-4	right hand release

ARMY

A. E. REFERENCE NUMBER: 64-2900

SPECIFICATIONS:

Detail 24843

MANUFACTURER'S DRAWING NUMBER: P. R. Mallory and Company, Incorporated B-134375

A. A. F. DRAWING NUMBER: 43B11200

TYPE DESIGNATION: A-1

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit

NAVY

TYPE DESIGNATION: Mark 1

BUREAU OF ORDNANCE DRAWING NUMBER: 388366

AVIATION ORDNANCE STOCK LIST NUMBER: 3-B-1901


PROCUREMENT STATUS: Under procurement.

INTERCHANGEABILITY: The Navy Mark 1 is identical to the Army type A-1, except that it includes waterproof packing.

BRITISH

BRITISH REFERENCE NUMBER: 105D 95

BOMB RELEASES ARMAMENT—BOMBING



RELEASE—BOMB RACK LEFT HAND ARMY TYPE A-2

NAMES: Bomb rack left hand release
Bomb rack release
Bomb rack release assembly

Bomb shackle release mechanism
Bomb shackle release
Left hand bomb rack release

DESCRIPTION: The type A-2 bomb rack left hand release electrically or mechanically actuates the bomb shackle.

Electrical operation is accomplished by energizing the solenoid within the bomb rack release. When the solenoid is energized, the arming and releasing levers, which are placed in a cocked position under spring tension, are released, thereby actuating the bomb shackle.

If the electrical system is rendered inoperative, mechanical operation may be accomplished by any one of three methods. The release lever may be pried over with a screw driver or similar implement so that the bomb may be released from the shackle. Turning of a slotted screw on the face of the release also releases the bomb in an armed condition. An external coupling known as the salvo coupling may also be used to release the bomb in a safe condition.

Two dowel pins align the release, which is then fastened by two snap fasteners to the bomb rack.

CHARACTERISTICS:

Dimensions	approximately 7 1/8 by 3 1/2 by 5 1/2 inches
Weight	approximately 2 1/2 pounds
Electrical connector	three-pin connector in accordance with figure 5, specification 93-24699-A
Power supply	24 volts direct current

RELATIONSHIP OF PARTS: Used with:

Army type A-1 bomb release receptacle. A. E. Reference Number 64-2900

ARMY

A. E. REFERENCE NUMBER: 64-3000

SPECIFICATIONS:

Detail	93-24699-A
Superseded	93-24699

A. A. F. DRAWING NUMBER: 41G1742

TYPE DESIGNATION: A-2

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.


ARMY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Crosley Corporation	WP-70L	D-210530	A-B	6400634700	11-5-28	111A 31	
P. R. Mallory & Company, Incorporated	*A-2	C-134588	A-B	6400634700	11-5-46	111A 31	Aluminum case.
	*A-2	C-134732	A-B	6400634700	11-5-46	111A 31	Steel case.
J. P. Seeburg Company	*A-2	SR105801	A-B	6400634700		111A 31	
Sparks-Withington Company	*A-2	C-57-57	A-B	6400634700	11-5-38	111A 31	

Note: *AAF type.

**RELEASE—BOMB RACK RIGHT HAND****ARMY TYPE A-2**

NAMES: Bomb rack right hand release
Bomb rack release
Bomb rack release assembly

Bomb shackle release mechanism
Bomb shackle release
Right hand bomb rack release

DESCRIPTION: The type A-2 bomb rack right hand release electrically or mechanically actuates the bomb shackle.

Electrical operation is accomplished by energizing the solenoid within the bomb rack release. When the solenoid is energized, the arming and releasing levers, which are placed in a cocked position under spring tension, are released, thereby actuating the bomb shackle.

If the electrical system is rendered inoperative, mechanical operation may be accomplished by any one of three methods. The release lever may be pried over with a screw driver or similar implement so that the bomb may be released from the shackle. Turning of a slotted screw on the face of the release also releases the bomb in an armed condition. An external coupling known as the salvo coupling may also be used to release the bomb in a safe condition.

Two dowel pins align the release, which is then fastened by two snap fasteners to the bomb rack.

CHARACTERISTICS:

Dimensions approximately 7 5/8 by 3 1/4 by 5 1/2 inches
Weight approximately 2 1/2 pounds
Electrical connector three-pin connector in accordance with figure 5, specification 93-24699-A
Power supply 24 volts direct current

RELATIONSHIP OF PARTS: Used with:

Army type A-1 bomb release receptacle A. E. Reference Number 64-2900

ARMY

A. E. REFERENCE NUMBER: 64-3200

SPECIFICATIONS:

Detail 93-24699-A
Superseded 93-24699

A. A. F. DRAWING NUMBER: 41G1742-1

TYPE DESIGNATION: A-2

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.


NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Crosley Corporation	WP-70R	D-210607	A-B	6400634720	11-5-28	111A/32	
P. R. Mallory & Company, Incorporated	*A-2	C-134588	A-B	6400634720	11-5-46	111A/32	Aluminum case.
	*A-2	C-134732	A-B	6400634720	11-5-46	111A/32	Steel case.
J. P. Seeburg Company	*A-2	SR105800	A-B	6400634720		111A/32	
Sparks-Withington Company	*A-2	C-57-56	A-B	6400634720	11-5-38	111A/32	

Note: *AAF type.

**RELEASE—BOMB RACK RIGHT HAND****ARMY TYPE A-3 NAVY TYPE A-3**

NAMES: Bomb rack right hand release
Bomb rack release
Bomb rack release assembly

Bomb shackle release mechanism
Right hand bomb rack release
Bomb shackle release

DESCRIPTION: The type A-3 bomb rack right hand release electrically or mechanically actuates the bomb shackle.

Electrical operation is accomplished by energizing the solenoid within the bomb rack release. When the solenoid is energized, the arming and releasing levers, which are placed in a cocked position under spring tension, are released, thereby actuating the bomb shackle.

If the electrical system is rendered inoperative, mechanical operation may be accomplished by any one of three methods. The release lever may be pried over with a screw driver or similar implement so that the bomb may be released from the shackle. Turning of a slotted screw on the face of the release also releases the bomb in an armed condition. An external coupling known as the salvo coupling may also be used to release the bomb in a safe condition.

Two dowel pins align the release, which is then fastened by two snap fasteners to the bomb rack.

CHARACTERISTICS:

Dimensions	approximately 7 $\frac{3}{4}$ by 3 $\frac{1}{4}$ by 5 $\frac{1}{2}$ inches
Weight	approximately 2 $\frac{1}{4}$ pounds
Electrical connector	three-pin connector in accordance with specification 93-24742
Power supply	12 volt direct current

RELATIONSHIP OF PARTS: Used with:

Army type A-1 bomb release receptacle A. E. Reference Number 64-2900

ARMY

A. E. REFERENCE NUMBER: 64-3425

SPECIFICATIONS:

Detail	93-24742
Superseded	24742

A. A. F. DRAWING NUMBER: H42G4872

TYPE DESIGNATION: A-3

A. S. C. STOCK NUMBER: 6400634780

TECHNICAL ORDER NUMBER: 11-5-30

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: A-3

AVIATION ORDNANCE STOCK LIST NUMBER: 3-R-519-25

PROCUREMENT STATUS: Not under procurement for initial installation.

BRITISH


REFERENCE NUMBER: 111A 40

MANUFACTURER: P. R. Mallory & Company, Incorporated

MANUFACTURER'S DRAWING NUMBER: C-134600 (assembly) and C-134727 (outline)

SHACKLE—BOMB

The bomb shackle supports bombs or cargo in the bomb bay compartment of the airplane, or externally in adapters located in the wing section.



TYPICAL BOMB INSTALLATION


In operation, the shackle is actuated remotely by the bombardier's arming and releasing handle, or the electrical release controls, or by the pilot's emergency release handle.

Sequence of operation in most type shackles is started by an impulse from the bombardier's arming and releasing handle, or the electrical release controls, or the pilot's emergency release handle to the bomb rack release, which in turn actuates the bomb shackle, or the impulse goes direct to the shackles' built-in arming and releasing mechanism for activation.

The shackle release lever has two positions, namely: "lock" and "release." When the release lever is in the "lock" position, a pawl in the releasing mechanism engages a stop in the connecting link, thereby preventing the opening of the carrying hooks. When the release lever is thrown to the release position, the pawl is disengaged, allowing the weight of the bomb to open the carrying hooks.

The arming lever has two positions, namely: "safe" and "armed." When the arming lever is in the safe or normal position the arming wire is retained in a slot by the arming hook which is held across the slot opening by a spring. Upon release of a bomb, the arming hook is withdrawn from the slot and the arming wire loop is free to slip out, permitting the bomb to drop safe. When the arming lever is moved to the armed position, it locks the arming hook so that the arming wire loop cannot be withdrawn from the slot. Thus, upon release of a bomb, the arming wire is pulled from the bomb fuse, arming the bomb.

BOMB SHACKLES ARMAMENT—BOMBING



SHACKLE—BOMB **ARMY TYPE B-7 NAVY TYPE B-7**

NAMES: Bomb shackle Bomb shackle assembly Bomb shackle 1100 pounds

DESCRIPTION: The Army type B-7 bomb shackle is a device normally used for carrying and releasing bombs. It is equipped with two bomb-carrying hooks, one releasing lever, one arming hook, and one arming lever. The shackles are usually installed in vertical tiers in the bomb bay compartment, and are free to swing out of the path of bombs from above; they may be installed in adapters in the wing section. These shackles are also used to carry and release droppable fuel tanks or parachute delivered cargo.

CHARACTERISTICS:

Weight.....approximately 3 pounds
 Dimensions.....approximately 16 $\frac{13}{64}$ by 4 $\frac{1}{4}$ by $\frac{3}{4}$ inches
 Distance between suspension lugs.....14 $\frac{37}{64}$ inches
 Distance between bomb carrying hooks.....14 inches
 Carrying capacity.....1100 pounds

RELATIONSHIP OF PARTS: Used with bomb rack release:

A. E. Reference Number	Type
64-3000	A-2 left hand release
64-3200	A-2 right hand release
64-3425	A-3 right hand release
64-3430	A-4 left hand release
64-3431	A-4 right hand release

ARMY

A. E. REFERENCE NUMBER: 64-3600

SPECIFICATIONS:

Detail.....93-24557
 Superseded.....24557

A. A. F. DRAWING NUMBER: 33D5226

TYPE DESIGNATION: B-7

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation, superseded by Army type B-10, A. E. Reference Number 64-3725.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: B-7

BUREAU OF ORDNANCE DRAWING NUMBER: Refer to chart.

AVIATION ORDNANCE STOCK LIST NUMBER: Refer to chart.

PROCUREMENT STATUS: Not under procurement. Superseded by Navy Mark 5 Mod. 1.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	At Service Command Stock Number	Army Technical Order Number	British Reference Number	Bureau of Ordnance Drawing Number	Aviation Ordnance Stock List Number
Banner Die Tool and Stamping Company	*B-7	**33D5226	A-N-B	6400694500	11-5-27	111A 1	169516	3-S-1904
Crosley Corporation	WP-80	D210438	A-N-B	6400694500	11-5-27	111A 1	169516	3-S-1904
Spriesch Tool and Manufacturing Company	*B-7	**33D5226	A-N-B	6400694500	11-5-27	111A 1	169516	3-S-1904
Gibson Refrigerator Company	*B-7	**33D5226	A-N-B	6400694500	11-5-27	111A 1	169516	3-S-1904

Note. *AAF type; **AAF drawing.



SHACKLE—BOMB

TYPE AN-B-9 FORMER ARMY TYPE B-9

NAMES: Bomb shackle
Bomb shackle assembly

Bomb shackle 1000 pounds

DESCRIPTION: The type AN-B-9 bomb shackle is a device for carrying and releasing bombs. It is equipped with a single bomb-carrying hook, located approximately midway between the ends of the shackle. Located at each end is a sway bracing assembly which contains an adjustable rod, a knurled nut, and two contact clips which are adjusted to fit and steady the bomb. An arming hook is located adjacent to the bomb-carrying hook. The shackle is designed to carry bombs which have one suspension lug located at the center of gravity. It may be used to carry two-lug bombs by using bomb adapter bands.

CHARACTERISTICS:

Weight approximately 6 1/4 pounds
 Dimensions approximately 16 1/4 by 6 1/4 by 1 1/8 inches
 Distance between suspension lugs 14 1/8 inches
 Carrying capacity 1000 pounds
 Single carrying hook located in the center of the shackle.

RELATIONSHIP OF PARTS: Used with bomb rack release:

A. E. Reference Number	Type
64-3000	A2 left hand release
64-3200	A-2 right hand release
64-3425	A-3 right hand release
64-3430	A-4 left hand release
64-3431	A-4 right hand release

ARMY

A. E. REFERENCE NUMBER: 64-3700

SPECIFICATIONS:

Detail 93-24749
 Superseded 24749

A. A. F. DRAWING NUMBER: 42D7307

TYPE DESIGNATION: AN-B-9

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: AN-B-9

BUREAU OF ORDNANCE DRAWING NUMBER: 309888

AVIATION ORDNANCE STOCK LIST NUMBER: 3-S-1905

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Airtemp, Division of Chrysler Corporation	*AN-B-9	**42D7307	A-N-B	6400694550	11-5-35	111A/34
Ainsworth Manufacturing Corporation	*AN-B-9	**AG-300	A-N-B	6500694550	11-5-35	111A/34
Spiesch Tool and Manufacturing Corporation	*AN-B-9	**42D7307	A-N-B	6400694550	11-5-35	111A/34

Note: *Army-Navy type; **AAF drawing.

**SHACKLE—BOMB****TYPE AN-B-10 FORMER ARMY TYPE B-10**

NAMES: Bomb shackle
Bomb shackle assembly

Bomb shackle 1600 pounds

DESCRIPTION: The type AN-B-10 bomb shackle is a device normally used for carrying and releasing bombs. It is equipped with two bomb-carrying hooks, one arming hook, one releasing lever, and one arming lever. The shackles are usually installed in the bomb bay compartment, but may be installed in adapters in the wing section. These shackles are also used to carry and release droppable fuel tanks or parachute delivered cargo.

CHARACTERISTICS:

Dimensions..... approximately 16 $\frac{13}{64}$ by 4 $\frac{1}{4}$ by $\frac{5}{8}$ inches
 Weight..... approximately 3 pounds
 Distance between suspension lugs..... 14 $\frac{5}{8}$ inches
 Distance between bomb carrying hooks..... 14 inches
 Carrying capacity..... 1600 pounds

RELATIONSHIP OF PARTS: Used with bomb rack release:

A. E. Reference Number	Type
64-3000	A-2 left hand release
64-3200	A-2 right hand release
64-3425	A-3 right hand release
64-3430	A-4 left hand release
64-3431	A-4 right hand release

ARMY

A. E. REFERENCE NUMBER: 64-3725

SPECIFICATIONS:

Detail..... 24832

A. A. F. DRAWING NUMBER: 43D10157

TYPE DESIGNATION: AN-B-10

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: The Navy identifies this type as AN-B-10 and procures it under Army drawings and specifications.

AVIATION ORDNANCE STOCK LIST NUMBER: 3-S-1906


MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference Number
Airtemp Division of Chrysler Corporation	*AN-B-10	**43D10157	A-N-B	6400695100	111A/44
Ainsworth Manufacturing Corporation	*AN-B-10	AG-500	A-N-B	6400695100	111A/44
Pallak Manufacturing Company	P-6A	411011	A-N-B	6400695100	111A/44
Spriess Tool and Manufacturing Company	*AN-B-10	**43D10157	A-N-B	6400695100	111A/44
Gibson Refrigerator Company	*AN-B-10	**43D10157	A-N-B	6400695100	111A/44

Note: *Army-Navy type; **AAF drawing.



BOMB SHACKLES ARMAMENT—BOMBING



SHACKLE—BOMB ARMY TYPE D-3

NAMES: Bomb shackle
Bomb rack

Bomb shackle assembly
Bomb shackle 2000 pounds

DESCRIPTION: The Army type D-3 bomb shackle is a device for carrying and releasing bombs. It incorporates a built-in arming control to enable the release of bombs in either safe or armed condition. The chief parts of the shackle are the frame assembly, two carrying hooks, releasing mechanism, arming mechanism, and releasing solenoid.

CHARACTERISTICS:

Dimensions..... approximately 42 by 7 $\frac{1}{4}$ by 7 $\frac{1}{2}$ inches
Weight..... approximately 25 pounds
Distance between carrying hooks..... 30 inches
Carrying capacity..... 2000 pounds
Power supply..... 12 volt, direct current

ARMY

A. E. REFERENCE NUMBER: 64-3750

SPECIFICATIONS:

Detail..... 93-24555-A
Superseded..... 93-24555

A. A. F. DRAWING NUMBER: 33K2512

TYPE DESIGNATION: D-3

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation, superseded by Army type D-5,
A. E. Reference Number 64-3800.

SHIPPING DATA: Shipped as a complete unit.

NAVY


There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Av Service Command Stock Number	Army Technical Order Number	British Reference Number	Remarks
Pollak Manufacturing Company	*D-3	**33K2512	A-B	6400695100	11-5-13	111A/2	
Oneida Limited	*D-5	300	A-B	6400695160	11-5-13	111A/27	See note.
Ainsworth Manufacturing Corporation	*D-5	AG-200	A-B	6400695160	11-5-13	111A/27	See note.
Union Chain Company	*D-5	**39K3828	A-B	6400695160	11-5-13	111A/27	See note.

NOTE: Army type D-5 bomb shackles may be made interchangeable with Army type D-3 bomb shackles by replacing the 24 volt solenoid, Army part number 39B3829, with 12 volt solenoid, Army part number 33B2523.
Note: *AAF type, **AAF drawing.

BOMB SHACKLES ARMAMENT—BOMBING



SHACKLE—BOMB

ARMY TYPE D-5

NAMES: Bomb shackle
Bomb rack

Bomb shackle assembly
Bomb shackle 2000 pounds

DESCRIPTION: The Army type D-5 bomb shackle is a device for carrying and releasing bombs. It incorporates a built-in arming control, to enable the release of bombs in either safe or armed condition.

The chief parts of the shackle are the frame assembly, two bomb carrying hooks, releasing mechanism, arming mechanism and releasing solenoid.

CHARACTERISTICS:

Dimensions	approximately 42 by 7 $\frac{1}{8}$ by 7 $\frac{1}{2}$ inches
Weight	approximately 25 pounds
Distance between carrying hooks	30 inches
Carrying capacity	2000 pounds
Power supply	24 volt, direct current

ARMY

A. E. REFERENCE NUMBER: 64-3800

SPECIFICATIONS:

Detail	93-24622
Superseded	24622

A. A. F. DRAWING NUMBER: 39K3828

TYPE DESIGNATION: D-5

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation, superseded by Army type D-6,
A. E. Reference Number 64-4000

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4


A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Oneida Limited	*D-5	300	A-B	6400695160	11-5-13	111A 27
Ainsworth Manufacturing Corporation	*D-5	AG-200	A-B	6400695160	11-5-13	111A 27
Union Chain Company	*D-5	**39K3823	A-B	6400695160	11-5-13	111A 27
Pallak Manufacturing Company	*D-3	**33K2512	A-B	6400695100	11-5-13	111A 2

The Army type D-5 bomb shackle, and may be made interchangeable by replacing the 12 volt solenoid, Army part number 3382523 with a 24 volt solenoid, Army part number 3983829.

Note: *AAF type; **AAF drawing.

BOMB SHACKLES ARMAMENT—BOMBING



SHACKLE—BOMB

ARMY TYPE D-5

NAMES: Bomb shackle
Bomb rack

Bomb shackle assembly
Bomb shackle 2000 pounds

DESCRIPTION: The Army type D-5 bomb shackle is a device for carrying and releasing bombs. It incorporates a built-in arming control, to enable the release of bombs in either safe or armed condition.

The chief parts of the shackle are the frame assembly, two bomb carrying hooks, releasing mechanism, arming mechanism and releasing solenoid.

CHARACTERISTICS:

Dimensions	approximately 42 by 7 $\frac{1}{8}$ by 7 $\frac{1}{2}$ inches
Weight	approximately 25 pounds
Distance between carrying hooks	30 inches
Carrying capacity	2000 pounds
Power supply	24 volt, direct current

ARMY

A. E. REFERENCE NUMBER: 64-3800

SPECIFICATIONS:

Detail	93-24622
Superseded	24622

A. A. F. DRAWING NUMBER: 39K3828

TYPE DESIGNATION: D-5

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Not under procurement for initial installation, superseded by Army type D-6,
A. E. Reference Number 64-4000

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Oneida Limited	*D-5	300	A-B	6400695160	11-5-13	111A 27
Ainsworth Manufacturing Corporation	*D-5	AG-200	A-B	6400695160	11-5-13	111A 27
Union Chain Company	*D-5	**39K3823	A-B	6400695160	11-5-13	111A 27
Pallak Manufacturing Company	*D-3	**33K2512	A-B	6400695100	11-5-13	111A 2

The Army type D-5 bomb shackle, and may be made interchangeable by replacing the 12 volt solenoid, Army part number 3382523 with a 24 volt solenoid, Army part number 3983829.

Note: *AAF type; **AAF drawing.



SHACKLE—BOMB

ARMY TYPE D-6 NAVY TYPE D-6

NAMES: Bomb shackle
Bomb shackle assembly

Bomb shackle 2000 pounds

DESCRIPTION: The type D-6 bomb shackle is a device for carrying and releasing bombs. It is equipped with two bomb-carrying hooks, one releasing lever, one arming lever, and one arming hook.

CHARACTERISTICS:

Dimensions	approximately 33 $\frac{1}{8}$ by 6 $\frac{1}{4}$ by 1 $\frac{3}{16}$ inches
Weight	approximately 9 $\frac{7}{8}$ pounds
Distance between suspension lugs	30 inches
Distance between carrying hooks	30 inches
Carrying capacity	2000 pounds

RELATIONSHIP OF PARTS: Used with bomb rack release:

A. E. Reference Number	Type
64-3000	A-2 left hand release
64-3200	A-2 right hand release
64-3425	A-3 right hand release
64-3430	A-4 left hand release
64-3431	A-4 right hand release

ARMY

A. E. REFERENCE NUMBER: 64-4000

SPECIFICATIONS:

Detail	93-24694
Superseded	24694

A. A. F. DRAWING NUMBER: 41E4555

TYPE DESIGNATION: D-6

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: D-6

BUREAU OF ORDNANCE DRAWING NUMBER: 307276


AVIATION ORDNANCE STOCK LIST NUMBER: 3-S-1908

PROCUREMENT STATUS: Under procurement.

MODELS BELOW ARE INTERCHANGEABLE
Models are used in services as noted in column 4
A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Pallak Manufacturing Company	"D-6	400429	A-N-B	6400695165	11-5-10	111A 29
	"D-4	"37E5013	A-B	6400695150	11-5-10	111A 33
Ainsworth Manufacturing Corporation	"D-6	AG-100	A-N-B	6400695165	11-5-10	111A 29

Note: "Aaf type, "AAF drawing.



SHACKLE—BOMB

ARMY TYPE D-7

NAMES: Bomb shackle
Bomb shackle assembly

Bomb shackle 4000 pounds

DESCRIPTION: The Army type D-7 bomb shackle is a device for carrying and releasing bombs. It is equipped with two bomb-carrying hooks, one arming lever, and one releasing lever.

The D-7 shackle was designed principally for installation in the bomb bay compartment, but installation can be made externally by equipping the airplane with especially constructed adapters, which vary with each type of airplane.

CHARACTERISTICS:

Weight	approximately 12 1/2 pounds
Dimensions	approximately 33 1/8 by 7 1/4 by 1 3/8 inches
Distance between suspension lugs	30 inches
Distance between carrying hooks	30 inches
Carrying capacity	4000 pounds

RELATIONSHIP OF PARTS: Used with bomb rack release:

A. E. Reference Number	Type
64-3000	A-2 left hand release
64-3200	A-2 right hand release
64-3425	A-3 right hand release
64-3430	A-4 left hand release
64-3431	A-4 right hand release

ARMY

A. E. REFERENCE NUMBER: 64-4050

SPECIFICATIONS:

Detail	93-24748
Superseded	24748

A. A. F. DRAWING NUMBER: 42E7219

TYPE DESIGNATION: D-7

A. S. C. STOCK NUMBER: Refer to chart.

TECHNICAL ORDER NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.


MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	Army Technical Order Number	British Reference Number
Pollak Manufacturing Company	P-56	410429	A-B	6400695167	11-5-10	111A/45
Ainsworth Manufacturing Corporation	*D-7	AG-700	A-B	6400695167	11-5-10	111A/45

Note: *AAF type.



OVERALL LENGTH... APPROX. 65"

SLING—BOMB HOIST

ARMY TYPE A-1

NAMES: Bomb hoist sling
Bomb hoist sling assembly

Heavy bomb hoist

DESCRIPTION: The Army type A-1 bomb hoist sling is used with Army type bomb hoists to load bombs on bombardment airplanes. Two slings are required for each bomb.

The sling is made of nylon webbing stitched with nylon thread. Two yoke assemblies, one located at each end of the webbed fabric, are used to attach the sling to the hoist.

CHARACTERISTICS:

Weight	approximately 3 ⁵ / ₈ pounds
Dimensions	approximately 65 by 6 ¹ / ₄ by 3 ¹ / ₄ inches
Lifting capacity (two slings)	4000 pounds

RELATIONSHIP OF PARTS: Used with:

Army type C-3 bomb hoist assembly A. E. Reference Number 64-2200

ARMY

A. E. REFERENCE NUMBER: 64-4100

SPECIFICATIONS:

Detail	93-24731
Superseded	24731

MANUFACTURER: Taylor Machine Company.

A. A. F. DRAWING NUMBER: 42G2343

ARMY PART NUMBER: 42G2343-5

TYPE DESIGNATION: A-1

A. S. C. STOCK NUMBER: 6400743850

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, two slings to a carton.

NAVY

There is no Navy equivalent for the Army item.



OVERALL LENGTH...APPROX. 78"

SLING—BOMB HOIST

ARMY TYPE A-2

NAMES: Bomb hoist sling
Bomb hoist sling assembly

Bomb sling
Chain-type bomb hoist sling

DESCRIPTION: The Army type A-2 bomb hoist sling is used with Army type bomb hoists to load bombs on bombardment airplanes. The sling is a double strand rollerless chain, and is attached to the hoist by two hook assemblies. The sling is adjustable over a wide range to accommodate various size bombs. Two slings are required to hoist a 4000 pound bomb.

CHARACTERISTICS:

Weight	approximately 10 pounds
Dimensions	approximately 78 $\frac{1}{8}$ by 1 $\frac{3}{4}$ by $\frac{3}{4}$ inches
Lifting capacity	2000 pounds

RELATIONSHIP OF PARTS: Used with:

Army type C-3 bomb hoist A. E. Reference Number 64-2200

ARMY

A. E. REFERENCE NUMBER: 64-4150

SPECIFICATIONS:

Detail 24781

MANUFACTURER: Diamond Chain Company

A. A. F. DRAWING NUMBER: 42D6433

TYPE DESIGNATION: A-2


A. S. C. STOCK NUMBER: 6400743875


PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit, two slings to a carton; or shipped as a component part of the Army type C-3 bomb hoist.

NAVY

There is no Navy equivalent for the Army item.





SOCKET—5-WAY BOMB

BRITISH TYPE A

NAMES: 5 way bomb socket
Bomb socket

Bomb carrier receptacle
Plug container assembly

DESCRIPTION: The type A, 5-way bomb socket is a receptacle used for electrical connection between the airplane electrical circuit and British electrical bombing equipment. The socket is protected from the weather by a hinged cover under spring tension, which covers the five contacts when the socket is not in use.

Mounting is accomplished by two screws, which secure the socket to the airplane structure.

CHARACTERISTICS:

Weight.....approximately $\frac{3}{16}$ pound
Dimensions.....approximately $2\frac{1}{16}$ by $1\frac{1}{16}$ by $1\frac{1}{16}$ inches

RELATIONSHIP OF PARTS: Used with:

Number 1 Mark 3 universal bomb carrier.....A. E. Reference Number 64-198

ARMY

A. E. REFERENCE NUMBER: 64-4195

A. S. C. STOCK NUMBER: Refer to chart.

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for this item.

MODELS BELOW ARE INTERCHANGEABLE

Models are used in services as noted in column 4

A-Army, N-Navy, B-British

Manufacturer	Manufacturer's Model Identification	Manufacturer's Drawing Number	Used By	Air Service Command Stock Number	British Reference		Remarks
					British Stores Reference Number	American Stores Reference Number	
Victor Adding Machine Company	V-34	50050	A-B	6400745150	5D/525	105D/22	
Crouse Hinds Company	A		A-B		5D/525	105D/22	Brass.
	A		A-B		5D/529	105D/16	See note.

NOTE: Light alloy, British Reference Number 5D/529 absolute and superseded by British Reference Number 105D/22.



TACHOMETER— BOMBSIGHT DISC SPEED

**JAEGER WATCH COMPANY, INC.
PART NUMBERS 4050A AND 4050**

NAMES: Bombsight disc speed tachometer
Handheld tachometer
Disc speed indicator
Portable tachometer—1000 R.P.M.
BS. Mk. XV disc speed indicator

DESCRIPTION: The bombsight disc speed tachometer is a hand-held tachometer used by bombardiers, and in bombsight repair shops, to check the bombsight disc speed. This tachometer is furnished in a velvet-lined leather case, complete with one soft rubber convex drive tip, one instruction sheet and one calibration sheet. One tachometer is normally supplied with each bombsight, and may be stowed in a pocket of the electrically heated bombsight cover when not in use.



CHARACTERISTICS:

Weight.....	approximately 1 pound
Dimensions.....	approximately 3 by 4 $\frac{1}{8}$ by 1 $\frac{1}{4}$ inches (in case)
Dial speed range.....	0 to 1000 revolutions per minute
Markings.....	fluorescent paint, inorganic, natural radium color.

RELATIONSHIP OF PARTS: Used with:
Army M-Series bomb sight assembly
Navy Mark 15-Series bomb sight assembly.

ARMY


A. E. REFERENCE NUMBER: 64-4400
MANUFACTURER: Jaeger Watch Company, Inc.
MANUFACTURER'S PART NUMBER: 4050A
A. S. C. STOCK NUMBER: 6400908000
TECHNICAL ORDER NUMBER: 17-1-44
PRODUCTION STATUS: Under procurement
SHIPPING DATA: Shipped as a complete unit.

NAVY

SPECIFICATIONS:
General.....18T22 (Modified)
AVIATION ORDNANCE STOCK LIST NUMBER: 2-T-20
PROCUREMENT STATUS: Under procurement.
MANUFACTURER'S PART NUMBER: 4050




ARMAMENT



ORDNANCE EQUIPMENT





DESTRUCTOR, AN-M3

FORMER NAVY TYPE M3

NAMES: Detonator
Electrical Detonator

Electrical Destructor

DESCRIPTION: The AN-M3 destructor is used to destroy certain radio equipment in order to prevent its falling into enemy hands. It consists of a cylindrical housing with a two pin electrical socket fastened to one end. The housing contains two electric detonators and a two-gram explosive charge. The electrical circuit is completed by a switch accessible to the pilot, or by an inertia switch which closes in the event of a crash landing. Current passing through the detonator causes the explosive charge to ignite, and the housing to explode. The force of this explosion is sufficient to destroy the internal parts of the equipment in which it is located, but other equipment in the airplane will not be damaged. The destructor is mounted in an adapter, which forms a part of the equipment with which it is to be used.

CHARACTERISTICS:

Weight.....approximately $\frac{3}{8}$ pound
Dimensions.....approximately $1\frac{3}{8}$ by $1\frac{3}{8}$ by 6 inches.

RELATIONSHIP OF PARTS: Used in conjunction with aircraft radio equipment.

ARMY

A. E. REFERENCE NUMBER: 93-725
TYPE DESIGNATION: AN-M3
PRODUCTION STATUS: Under procurement
SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: AN-M3
BUREAU OF ORDNANCE DRAWING NUMBER: 344428
PROCUREMENT STATUS: Under procurement.

ORDNANCE

MODEL: AN-M3
STANDARD NOMENCLATURE LIST NUMBER: R-7
WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-1900
WAR DEPARTMENT TECHNICAL BULLETIN NUMBER: 1900-12

SUPPLIED BY


Ordnance Office, War Department.

USED BY

Army and Navy.

BRITISH

REFERENCE NUMBER: 112D. 8.



GUN, AUTOMATIC, 37-MM, M4

NAMES: 37-mm automatic gun
Cannon—37-mm

Gun—aircraft 37-mm
Airplane automatic 37-mm gun

DESCRIPTION: The M4, 37-mm automatic gun is an aircraft weapon of the long recoil type. The feed and ejector mechanism are operated by the movement of the recoiling portion of the gun. Recoil and counter-recoil are hydraulically controlled by means of a piston connected to the recoiling parts and a cylinder mounted on the stationary trunnion block assembly.

The gun will fire in any position, since all parts operate independently of gravity. It may be fired manually, or by remote control through a solenoid mounted at the rear of the gun. It is used in both fixed and flexible installations, but it is not designed to be synchronized with the airplane engine. In fixed installations, the gun may be mounted to fire through the propeller shaft, or it may be mounted to fire outside the arc of propeller rotation.

Ammunition may be fed to the gun from a rigid clip holding five cartridges, a fifteen round magazine, or an endless belt magazine. The endless belt magazine contains thirty rounds of ammunition, and is used more frequently than either of the other feed mechanisms.

CHARACTERISTICS:

Weight	approximately 213 pounds
Dimensions	approximately 89 $\frac{5}{8}$ by 18 $\frac{7}{8}$ by 6 $\frac{1}{8}$ inches
Rate of fire	125 to 150 rounds per minute
Muzzle velocity	2000 feet per second, approximately

RELATIONSHIP OF PARTS: Used with:

Type M6, 37-mm endless belt magazine, A. E. Reference Number 93-3100, or Type M7, 37-mm endless belt magazine, A. E. Reference Number 93-3110, or Type M2, 37-mm 15 round magazine, A. E. Reference Number 93-2100.

ARMY

A. E. REFERENCE NUMBER: 93-1280
A. A. F. DRAWING NUMBER: H42G4769
SUPERSEDED DRAWING
NUMBER: H39G5561
TYPE DESIGNATION: M4
TECHNICAL ORDER
NUMBER: 11-1-15, 11-1-17 and 11-1-18
PRODUCTION STATUS: Under
procurement
SHIPPING DATA: Shipped as a complete
unit.

NAVY

There is no Navy equivalent for the Army item.

ORDNANCE

MODEL: M4
ORDNANCE DRAWING NUMBER: 51-92
and D69446 (Mounting Dimensions)
STANDARD NOMENCLATURE LIST
NUMBER: A-46
WAR DEPARTMENT TECHNICAL
MANUAL NUMBER: 9-240
9-1240

BRITISH


REFERENCE NUMBER: 107M/1

SUPPLIED BY

Ordnance Office, War Department

USED BY

Army and British.



GUN, AIRCRAFT, AUTOMATIC, 20-MM, M1 AND AN-M2 ALL TYPES

NAMES: 20-mm aircraft automatic gun
Aircraft automatic 20-mm cannon
Automatic 20-mm cannon

Hispano-Suiza cannon
20-mm cannon
Gun—automatic 20-mm cannon

DESCRIPTION: The 20-mm aircraft automatic gun is an air-cooled aircraft weapon, the mechanism of which is operated by a combination of gas pressure and recoil. When used as a fixed gun, it can be mounted to fire through the propeller hub, or it may be mounted in the fuselage or wing to fire outside the arc of propeller rotation. When used as a flexible gun, it must be supported in a flexible or turret-type mount. Ammunition is fed from either a drum-type magazine or a continuous feed belt. The gun consists of a one-piece barrel screwed into a receiver at its breech end. The rifling of the barrel begins just ahead of the cartridge chamber, and imparts rotation to the projectile, which causes it to maintain its direction and prevents it from tumbling.

Firing is accomplished, in most cases, by means of an electrical solenoid. However, provision may be made to permit manual firing with a remote control cable, which is attached to the gun by means of a bowden control attachment. The 20-mm automatic gun does not lend itself to a synchronized installation due to the design of its bolt and firing mechanism.

The term "basic gun" used as pertaining to 20-mm guns in this index, describes a 20-mm aircraft automatic gun, M1 or AN-M2, without a gun charger, solenoid, recoil adapter, or muzzle brake. The basic M1 and AN-M2 guns are identical with respect to function and installation. The only difference between the two models is in the dimensions of some of the receiver parts. The AN-M2 receiver is 0.2 inches longer, and the M1 receiver slide has a head flange which overlaps the bottom face and receiver slide bolts, which are locked by locking wire. The shoulders on the bottom faces of the receiver slides serve as further means of identifying the M1 gun.

The M1 automatic 20-mm gun, A. E. Reference Number 93-1300, is a type of aircraft cannon formerly supplied for installation on combat airplanes. It is equipped with an M7 recoil adapter, muzzle brake and accessory mounting parts. The AN-M2 aircraft automatic 20-mm gun, A. E. Reference Number 93-1350, is another type of aircraft cannon formerly supplied for installation on combat airplanes. It is equipped with an M7 recoil adapter, muzzle brake and accessory mounting parts. To facilitate installation in various types of aircraft, the 20-mm aircraft automatic gun is identified by the Army Air Forces according to distribution types, as shown on the accompanying chart.

CHARACTERISTICS:

Dimensions.....	approximately 100 by 5 $\frac{3}{8}$ by 6 inches
Weight:	
M1.....	approximately 108 pounds
AN-M2.....	approximately 112 $\frac{1}{2}$ pounds
Rate of fire.....	600 to 700 rounds per minute
Maximum allowable recoil.....	1.181 inches
Minimum recoil.....	0.787 inches

RELATIONSHIP OF PARTS: When fired electrically, this gun is equipped with an AN-M1 electric trigger (Army type G-17 solenoid), A. E. Reference Number 52-6380. Ammunition is supplied by means of M1 60 round magazine, A. E. Reference Number 93-3050, or M1 20-mm feed mechanism, A. E. Reference Numbers 93-3200 and 93-3205.

(Continued on pages 298 and 299)

DISTRIBUTION TYPES

(Continued from page 297)

A. E. REF. No.	NAME	TYPE	REMARKS	USED BY
93-1351	Gun, Automatic, 20-mm, M1 or Gun, Aircraft, Automatic, AN-M2	A	Complete with:	A
			Adapter.....	
			Trigger Mechanism.....	
93-1352	Gun, Automatic, 20-mm, M1 or Gun, Aircraft, Automatic, AN-M2	B	Complete with:	A
			Adapter.....	
			Trigger Mechanism.....	
93-1353	Gun, Automatic, 20-mm, M1 or Gun, Aircraft, Automatic, AN-M2	C	Complete with:	A
			Adapter.....	
			Trigger Mechanism.....	
93-1354	Gun, Automatic, 20-mm, M1 or Gun, Aircraft, Automatic, AN-M2	D	Complete with:	A
			Adapter.....	
			Trigger Mechanism.....	
93-1355	Gun, Aircraft, Automatic, 20-mm, AN-M2	E	Complete with:	A-N
			Adapter.....	
			Trigger Mechanism.....	
93-1356	Gun, Automatic, 20-mm, M1	F	Complete with:	A-B
			Adapter.....	
			Trigger Mechanism.....	
93-1357	Gun, Aircraft, Automatic, 20-mm, AN-M2	G	Complete with:	A
			Adapter.....	
			Trigger Mechanism.....	

(Continued on page 299)

(RESTRICTED)

AUTOMATIC GUNS
ARMAMENT—ORDNANCE



GUN, AIRCRAFT, AUTOMATIC, 20-MM, M1 AND AN-M2

(Continued from page 297)

ARMY

A. A. F. DRAWING NUMBER:

M1..... H41J5074 (general drawing)

AN-M2..... H41J9229 (general drawing)

TECHNICAL ORDER NUMBER: 11-1-16

PRODUCTION STATUS: Types A to G, A. E. Reference Numbers 93-1351 to 93-1357 inclusive, are under procurement. A. E. Reference Numbers 93-1300 and 93-1350, are not under procurement for initial installation.

SHIPPING DATA: Shipped as a complete unit, in accordance with distribution types shown on the opposite page.

NAVY

BU. ORD. DRAWING NUMBER:

M1..... 296508 (general drawing)

AN-M2..... 296509 (general drawing)

AVIATION ORDNANCE STOCK LIST NUMBER:

M1..... 1-G-5642

AN-M2..... 1-G-5544

AN-M2, Type E..... 1-G-5599

ORDNANCE PAMPHLET NUMBER: 215, 823 and 865

PROCUREMENT STATUS: Type E, Aviation Ordnance Stock List Number 1-G-5599, is under procurement. Aviation Ordnance Stock List Number 1-G-5642 and 1-G-5544 are not under procurement for initial installation.

ORDNANCE

ORDNANCE DRAWING NUMBER:

M1..... 51-105-4 (general drawing)

AN-M2..... 51-107-4 (general drawing)

STANDARD NOMENCLATURE LIST NUMBER: A-47

**WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-227 (General Information)
9-1227 (Maintenance)**

BRITISH

BRITISH REFERENCE NUMBER:


AN-M2..... 107G/5

M1, Type F..... 107G/279

PROCUREMENT STATUS: Type F, British Reference Number 107G/279 is under procurement. British Reference Number 107G 5 is not under procurement for initial installation.

INTERCHANGEABILITY

All types may be made interchangeable by substituting the required adapter, muzzle brake, trigger mechanism, and charger.



ADAPTER, 20-MM, AN-M1

FORMER ARMY TYPE M1 FORMER NAVY TYPE M1

NAMES: 20-mm adapter assembly Recoil absorption adapter
 Adapter assembly—20-mm recoil absorption Ring spring cartridge—20-mm gun adapter
 Adapter, gun mount AG 20-mm (M-1 and M-2) Edgewater 20-mm recoil adapter

DESCRIPTION: The 20-mm, AN-M1 adapter assembly is used to absorb the recoil force of the 20-mm gun, and to limit the recoil travel. If recoil travel is too long, it will damage the gun, and if too short, it will deprive the feed mechanism of its power.

For proper operation, the adapter must be mounted on the barrel of the gun near the muzzle. An extension and spacer sleeve provide means of attaching the adapter to the gun mounting. Spacer sleeves of several lengths are furnished, to facilitate installation and attachment.

CHARACTERISTICS:

Dimensions.....approximately 33½ by 3 by 3 inches assembled
 Weight.....approximately 11¾ pounds
 Adapter type.....ring spring cartridge

RELATIONSHIP OF PARTS: Used with:

20-mm automatic gun type M1 or type AN-M2. One end of the adapter is fastened to the barrel of the gun, and the other to the gun mount.

(Continued on page 301)



ADAPTER, 20-MM, AN-M1

(Continued from page 300)

ARMY

A. E. REFERENCE NUMBER: 93-200

A. A. F. DRAWING NUMBER: H41D10198

TYPE DESIGNATION: AN-M1

TECHNICAL ORDER NUMBER: 11-1-16

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: The adapter assembly is shipped as a complete unit which contains the various components necessary for installation.

NAVY

TYPE DESIGNATION: AN-M1

BUREAU OF ORDNANCE DRAWING NUMBER: 328544

AVIATION ORDNANCE STOCK LIST NUMBER: 1-A-56

ORDNANCE DATA NUMBER: 4447

ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Under procurement.

ORDNANCE

MODEL: AN-M1

ORDNANCE DRAWING NUMBER: D36592

STANDARD NOMENCLATURE LIST NUMBER: A-47

WAR DEPT. TECHNICAL MANUAL NUMBER: 9-227

BRITISH

REFERENCE NUMBER: 150J/56


INTERCHANGEABILITY

The addition of the rear mounting extension makes the type AN-M1 completely interchangeable with type AN-M6.

SUPPLIED BY: Ordnance office, War Department.

USED BY

Army, Navy, and British.



ADAPTER, 20-MM, AN-M6

FORMER ARMY TYPE M6

NAMES: 20-mm. adapter

Adapter assembly—20-mm recoil absorption

Adapter, gun mount, AG 20-mm (M-1 and M-2)

Recoil absorption adapter

Ring spring cartridge—20-mm gun adapter

Edgewater 20-mm recoil adapter

DESCRIPTION: The 20-mm. AN-M6 adapter assembly is used to absorb the recoil force of the 20-mm gun, and to limit the recoil travel. If recoil travel is too long, it will damage the gun, and if too short, it will deprive the feed mechanism of its power.

For proper operation, the adapter must be mounted on the barrel of the gun near the muzzle. An extension and spacer sleeve provide means of attaching the adapter to the gun mounting. Spacer sleeves of several lengths are furnished, to facilitate installation and attachment.

The AN-M6 adapter assembly contains a rear mounting extension, which distinguishes it from the AN-M1 adapter assembly. The two assemblies are identical in all other respects.

CHARACTERISTICS:

Dimensions.....	approximately 41½ by 3 by 8 inches assembled
Weight.....	approximately 14½ pounds
Adapter type.....	ring spring cartridge

(Continued on page 303)

**ADAPTER, 20-MM, AN-M6***(Continued from page 302)*

RELATIONSHIP OF PARTS: The type AN-M6 adapter is used with the automatic 20-mm guns, type M1 and AN-M2. One end of the adapter is fastened to the barrel of the gun, and the other to the gun mount.

ARMY

A. E. REFERENCE NUMBER: 93-250

A. A. F. DRAWING NUMBER: H41D10198

TYPE DESIGNATION: AN-M6

TECHNICAL ORDER NUMBER: 11-1-16

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: The adapter assembly is shipped as a complete unit which contains the various components necessary for installation.

NAVY

TYPE DESIGNATION: AN-M1 with rear mounting extension.

BUREAU OF ORDNANCE DRAWING NUMBER: 328544

F. S. S. C. NUMBER: 1-A-56

ORDNANCE DATA NUMBER: 4447

PROCUREMENT STATUS: Under procurement.

ORDNANCE

MODEL: AN-M6

ORDNANCE DRAWING NUMBER: D36593

STANDARD NOMENCLATURE LIST NUMBER: A-47

WAR DEPT. TECHNICAL MANUAL NUMBER: 9-227

INTERCHANGEABILITY

The omission of the rear mounting extension makes the type AN-M6 completely interchangeable with AN-M1.

SUPPLIED BY

Ordnance office, War Department.

USED BY

Army and Navy.



AIRCRAFT MACHINE GUNS

Aircraft machine guns are used offensively or defensively against enemy aircraft or ground objectives, and are fired from fixed, flexible, or turret installations.

The caliber .30 and .50 Browning aircraft machine guns are recoil-operated, belt-fed, and air-cooled. Upon depressing the trigger, the gun operation becomes fully automatic, and it will continue to fire within the limit of the ammunition supply or until the trigger is released. Firing is accomplished manually by depressing the trigger, or electrically by a solenoid which is operated from a gun switch. The recoil of the gun supplies the power necessary to extract ammunition from the belt, feed it into the chamber, cock and fire the gun, eject the empty cartridge case, and move the next round into the feedway. Charging the gun for initial firing, or following stoppages, is performed manually, by retracting the handle of the slide group assembly, or remotely, by operating the control valve of a pneumatic or hydraulic gun charger.

These guns may be fed from the left or right side, and may be converted to either feed by reversing a few minor parts. A disintegrating metallic link belt is normally used to supply ammunition to the guns. The belt separates into individual links upon the removal of the loaded cartridge.

Guns may be mounted in the fuselage or in the wings, and require the use of gun mounts or adapters, depending upon the individual installation. When mounted to fire through the propeller arc, the gun must be equipped with a synchronizer, to prevent damage to the propeller.

(Continued on page 305)




AIRCRAFT MACHINE GUNS

(Continued from page 304)

INSTALLATION TYPES


CALIBER .30

BROWNING AIRCRAFT MACHINE GUN




FIXED MACHINE GUN

(Including fixed back plate and operating slide group assembly)



FLEXIBLE, WITH FIXED BACK PLATE, MACHINE GUN


(Including fixed back plate and retracting slide group assembly.) Used in turret installations.



FLEXIBLE MACHINE GUN


(Including flexible back plate and retracting slide group assembly)

CALIBER .50




FIXED MACHINE GUN

(Including fixed back plate and operating slide group assembly)




FLEXIBLE, WITH FIXED BACK PLATE, MACHINE GUN

(Including fixed back plate and retracting slide group assembly.) Used in turret installations.



FLEXIBLE MACHINE GUN

(Including flexible back plate and retracting slide group assembly)



GUN MACHINE, CALIBER .30, BROWNING, M2, AIRCRAFT, FIXED

NAMES: Browning machine gun, caliber .30, M2, aircraft, fixed
Browning aircraft fixed machine gun, caliber .30
Machine gun, .30 caliber—Browning aircraft—fixed
Gun—machine .30 caliber—Browning aircraft—fixed

DESCRIPTION: The M2 caliber .30 Browning aircraft fixed machine gun is used in installations requiring the gun to be fired in one direction only from a fixed position in the wings or fuselage.

This gun is a caliber .30 aircraft machine gun equipped with an operating slide group assembly, which may be mounted to either side of the gun for charging. A cable may be attached to the operating slide group assembly to permit its operation in remote installations. The fixed gun referred to in this description does not contain a trigger bar or trigger bar pin, since firing is accomplished remotely through the use of an electrical solenoid and firing switch.

CHARACTERISTICS:

Weight	approximately 21½ pounds
Outline dimensions	approximately 39¾ by 5¼ by 3¼ inches
Rate of fire	1350 rounds per minute
Muzzle velocity	approximately 2700 feet per second

RELATIONSHIP OF PARTS: The gun is attached to the airplane by any fixed .30 caliber gun mount or gun mount adapter.

ARMY

A. E. REFERENCE NUMBER: 93-1420
A. A. F. DRAWING NUMBER: H39G5331
TYPE DESIGNATION: M2
TECHNICAL ORDER NUMBER: 11-1-28
PRODUCTION STATUS: Under procurement
SHIPPING DATA: Shipped complete with operating slide group assembly.

NAVY

TYPE DESIGNATION: M2
BUREAU OF ORDNANCE DRAWING NUMBER: 204675
AVIATION ORDNANCE STOCK LIST NUMBER: 1-G-5606
ORDNANCE PAMPHLET NUMBER: 714, 398, 865
PROCUREMENT STATUS: Under procurement

ORDNANCE

MODEL: M2
ORDNANCE DRAWING NUMBER: 51-57-3
51-57-3A (List of Parts)
STANDARD NOMENCLATURE LIST NUMBER: A-28
WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-205
9-1205

BRITISH

REFERENCE NUMBER: 107L/391

INTERCHANGEABILITY

May be converted to either a flexible or flexible with fixed back plate machine gun by substituting the proper back plate and slide group assembly.

SUPPLIED BY

Ordnance Office, War Department.

USED BY

Army, Navy, and British.

NAMES: Browning machine gun, caliber .30, M2, aircraft, flexible with fixed back plate
Browning aircraft, flexible with fixed back plate machine gun, caliber .30
Gun—machine .30 caliber—Browning aircraft—flexible with fixed back plate

DESCRIPTION: The M2 caliber .30 Browning aircraft flexible machine gun, with fixed back plate, is used in installations which require flexibility of movement but which do not require hand grips on the guns. Such installations are found in power operated gun turrets or in gun mount adapters which are themselves equipped with hand grips.

This gun is a caliber .30 aircraft machine gun which contains a fixed back plate, and is equipped with a retracting slide group assembly which may be mounted to either side of the gun for charging.

Weight	approximately 21 $\frac{1}{2}$ pounds
Dimensions	approximately 39 $\frac{3}{4}$ by 5 $\frac{1}{2}$ by 5 $\frac{1}{4}$ inches
Rate of fire	1350 rounds per minute
Muzzle velocity	2700 feet per second

RELATIONSHIP OF PARTS: The gun is attached to the airplane by any flexible .30 caliber gun mount adapter which is provided with hand grips, or is installed in a .30 caliber gun turret.

A. E. REFERENCE NUMBER: 93-1440
A. A. F. DRAWING NUMBER: H39G5331
TYPE DESIGNATION: M2
TECHNICAL ORDER NUMBER: 11-1-28
PRODUCTION STATUS: Under procurement
SHIPPING DATA: Shipped as a complete unit.

TYPE DESIGNATION: M2
F. S. S. C. NUMBER: 1-G-5612
ORDNANCE PAMPHLET NUMBER: 714 and 398
PROCUREMENT STATUS: Under procurement

MODEL: M2
ORDNANCE DRAWING NUMBER: 51-122-1
51-122-1A (List of Drawings)
STANDARD NOMENCLATURE LIST NUMBER: A-28
WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-205 and 9-1205

REFERENCE NUMBER: 107L 390

May be converted to either a fixed or a flexible machine gun by substituting the proper back plate and slide group assembly.

Ordinance Office, War Department.

Army, Navy, and British.



NAMES: Browning aircraft flexible machine gun caliber .30
Gun-machine .30 caliber—Browning aircraft flexible
Gun, caliber .30, BAM-30 (M-2) flexible
Machine Gun, caliber .30, Browning, M2, aircraft, flexible
Flexible machine gun, caliber .30, Browning, M2, aircraft flexible

This gun is a caliber, .30 aircraft machine gun, equipped with a retracting slide group assembly which is mounted to either side of the gun for charging, and it has a flexible back plate. The flexible back plate differs from the fixed back plate by the addition of two spade grips with an external trigger.

Weight	approximately 23 pounds
Dimensions	approximately 39" by 5½ by 6⅞ inches
Rate of fire	1350 rounds per minute
Muzzle velocity	approximately 2700 feet per second

ARMY

A. E. REFERENCE NUMBER: 93-1520
A. A. F. DRAWING NUMBER: H39G5331
TYPE DESIGNATION: M2
TECHNICAL ORDER NUMBER: 11-1-28
PRODUCTION STATUS: Under procurement
SHIPPING DATA: Shipped as a complete unit.

TYPE DESIGNATION: M2
N. A. F. DRAWING NUMBER: 204674
AVIATION ORDNANCE STOCK LIST NUMBER: 1-G-5611
ORDNANCE PAMPHLET NUMBER: 714 and 398
PROCUREMENT STATUS: Under procurement.

MODEL: M2
ORDNANCE DRAWING NUMBER: 61-76-1
51-76-1A (List of Parts)
STANDARD NOMENCLATURE LIST NUMBER: A-28
WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-205 and 9-1205.

REFERENCE NUMBER: 107L/392

May be converted to either a fixed or flexible with fixed back plate machine gun by substituting the proper back plate and slide group assembly.

Ordinance Office, War Department.

Army, Navy and British.



GUN, MACHINE, CALIBER .50, BROWNING, M2, AIRCRAFT, BASIC

NAMES: Browning machine gun, caliber .50, M2, aircraft, basic
Gun, machine .50 caliber—Browning aircraft—basic
Gun, caliber .50, BAM—50 (M2) basic

DESCRIPTION: The M2 caliber .50 Browning aircraft basic machine gun is the model from which all installation types are derived. It is a Browning aircraft machine gun without a slide group assembly, but with a fixed back plate, and an internal trigger bar and trigger bar pin assembly.

The basic gun may be converted to a fixed gun by the addition of an operating slide group assembly, and a solenoid to permit remote firing. It may be converted to a flexible gun by substituting a flexible back plate for the fixed back plate and by adding a retracting slide group assembly. When used in turret installations, the basic gun is equipped with a retracting slide group assembly.

CHARACTERISTICS:

Weight	approximately 60¾ pounds
Dimensions	approximately 56½ by 5¾ by 3¾ inches
Rate of fire	700 to 850 rounds per minute
Muzzle velocity	approximately 2800 feet per second

RELATIONSHIP OF PARTS: Used with:

Operating slide group assembly, A. E. Reference Number 93-1100, or retracting slide group assembly, A. E. Reference Number 93-1125.

ARMY

A. E. REFERENCE NUMBER: 93-1560
A. A. F. DRAWING NUMBER: H39G5332
TYPE DESIGNATION: M2
TECHNICAL ORDER NUMBER: 11-1-28 and 11-1-8
PRODUCTION STATUS: Under procurement
SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: M2
BUREAU OF ORDNANCE DRAWING NUMBER: 297034
AVIATION ORDNANCE STOCK LIST NUMBER: 1-G-5636
ORDNANCE PAMPHLET NUMBER: 215, 548 and 716
ORDNANCE CIRCULAR LETTER NUMBER: V-34
PROCUREMENT STATUS: Under procurement.

ORDNANCE

MODEL: M2
ORDNANCE DRAWING NUMBER: 51-82-1
51-82-1A (List of Drawings)
STANDARD NOMENCLATURE LIST NUMBER: A-38
WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-225 and 9-1225

BRITISH

REFERENCE NUMBER: 107K 482

INTERCHANGEABILITY


May be mounted in either a fixed, flexible, or turret installation by substituting the proper back plate, and supplying the proper slide group assembly, solenoid, and adapter.

SUPPLIED BY

Ordnance Office, War Department.

USED BY

Army, Navy, and British.



SLIDE, OPERATING GROUP ASSEMBLY

ORDNANCE DRAWING D28200

NAMES: Group assembly—operating slide
Operating slide group assembly

Slide, operating, BAM .50 (M-2), group
assembly

DESCRIPTION: The operating slide group assembly is used for manually charging fixed guns by retracting the breech mechanism. It is also used for unloading the gun, and for correction of stoppages in firing. If the gun is mounted in the wing, or in the fuselage, out of reach of the gunner, a remote control cable may be attached so that the slide can be operated from the cockpit.

This assembly is a lever and slide arrangement equipped with a metal handle and may be mounted on either side of the gun. The slide group assembly engages the bolt stud and retracts it to the rear, to perform initial charging. Upon firing, the bolt stud and breech mechanism operate independently of the slide group assembly.

CHARACTERISTICS:

Dimensions.....approximately 21½ by 6 by 1¾ inches
Weightapproximately 1½ pounds

RELATIONSHIP OF PARTS: The operating slide group assembly is used on M2 .50 caliber Browning fixed machine guns, and is secured to the side plate of the gun by two guide bearings.

ARMY

A. E. REFERENCE NUMBER: 93-1100
TECHNICAL ORDER NUMBER: 11-1-8
PRODUCTION STATUS: Under procurement
SHIPPING DATA: Shipped complete with bolt stud and mounting attachments.

NAVY

BUREAU OF ORDNANCE DRAWING NUMBER: 169790
AVIATION ORDNANCE STOCK LIST NUMBER: 1-S-9423
ORDNANCE PAMPHLET NUMBER: 716 and 865
PROCUREMENT STATUS: Under procurement.

ORDNANCE

ORDNANCE DRAWING NUMBER: D28200
STANDARD NOMENCLATURE LIST NUMBER: A-38
WAR DEPT. TECHNICAL MANUAL NUMBER: 9-225 and 1-409

BRITISH


REFERENCE NUMBER: 107K/119

SUPPLIED BY

Ordnance office, War Department.

USED BY

Army, Navy, and British.



SLIDE, RETRACTING, GROUP ASSEMBLY

ORDNANCE DRAWING D28300A

NAMES: Group assembly—retracting slide
Retracting slide group assembly

Slide, retracting, BAM 50 (M-2) group
assembly

DESCRIPTION: The retracting slide group assembly provides a means of charging flexible guns by hand retraction of the breech mechanism. It is also used for loading or unloading the gun, and to clear firing stoppages.

It is a lever and slide arrangement which can be mounted on the left or right hand side of the gun. The force needed to start the charging cycle is furnished through the crank-like wooden hand grip. This grip is connected to the bolt stud in such a way that the bolt stud, and consequently the breech mechanism, operate independently of the handle and the slide group assembly upon firing.

The wooden handle may be removed, and a cable can be attached to the lever, for remote operation.

CHARACTERISTICS:

Dimensions approximately 12 by 4½ by 5¼ inches
Weight approximately 2½ pounds

RELATIONSHIP OF PARTS: The retracting slide group assembly is used on all M2 .50 caliber Browning flexible machine guns.

ARMY

A. E. REFERENCE NUMBER: 93-1125
A. A. F. DRAWING NUMBER: H39B5344
TECHNICAL ORDER NUMBER: 11-1-8
PRODUCTION STATUS: Under procurement
SHIPPING DATA: Shipped complete with bolt stud, and mounting attachments.

NAVY

BUREAU OF ORDNANCE DRAWING NUMBER: 307245
AVIATION ORDNANCE STOCK LIST NUMBER: 1-S-9428
ORDNANCE CIRCULAR LETTER NUMBER: 12-42
ORDNANCE PAMPHLET NUMBER: 716 and 865
PROCUREMENT STATUS: Under procurement.

ORDNANCE

ORDNANCE DRAWING NUMBER: D28300A
STANDARD NOMENCLATURE LIST NUMBER: A-38
WAR DEPT. TECHNICAL MANUAL NUMBER: 9-225 and 1-409

BRITISH


REFERENCE NUMBER: 107K 225

SUPPLIED BY

Ordnance office, War Department.

USED BY

Army, Navy, and British.



MAGAZINE, 15 ROUND, 37-MM, M2

NAMES: 37-mm, 15 round magazine M2
15 round articulated link belt magazine

15 round 37-mm ammunition box

DESCRIPTION: The type M2 15 round 37-mm magazine is used only where limited space for ammunition storage is available. This magazine incorporates a 15 link articulated belt, which passes through the feed box and falls into a suitable container placed near the gun.

CHARACTERISTICS:

Weight.....approximately 12½ pounds
Dimensions.....approximately 11½ by 8½ by 10¼ inches

RELATIONSHIP OF PARTS: The 15 round, 37-mm magazine is held to the left hand side of the feed box of the type M-4, 37-mm aircraft gun (A. E. Reference Number 93-1280) by the action of two spring held latches which are provided with quick release buttons.

ARMY

A. E. REFERENCE NUMBER: 93-2100
A. A. F. DRAWING NUMBER: H39G5584
TYPE DESIGNATION: M2
TECHNICAL ORDER NUMBER: 11-1-15, 11-1-17, 11-1-18
PRODUCTION STATUS: Not under procurement for initial installation.
SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

ORDNANCE

MODEL: M2
ORDNANCE DRAWING NUMBER: D36321
STANDARD NOMENCLATURE LIST NUMBER: A-46
WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-240

BRITISH

REFERENCE NUMBER: 107M/52

SUPPLIED BY

Ordnance Office, War Department.

USED BY

Army.



MAGAZINE, 60 RD, 20-MM, M1

NAMES: 20-mm 60 rd magazine
60 round magazine

Drum type magazine

DESCRIPTION: The M1, 20-mm 60 round magazine is a drum shaped ammunition box which is quickly attachable to the magazine slides of the 20-mm automatic gun. It consists of a cylindrical casing, which houses a driving spring and feeder assembly. The magazine is operated by spring tension. Initial tension is applied during assembly, and additional tension is added subsequently by the loading operations. The feeder arm acts under the spring tension to move each successive round of ammunition to the proper position for loading into the gun. A series of holes in the rear plate provide visual indication of the rounds of ammunition remaining in the magazine.

CHARACTERISTICS:

Dimensions.....approximately 9 $\frac{3}{8}$ by 12 $\frac{5}{16}$ by 12 $\frac{5}{16}$ inches
Weight.....approximately 20 $\frac{3}{4}$ pounds

RELATIONSHIP OF PARTS: This magazine is mounted on the magazine slide of the M1 automatic 20-mm gun, or the AN-M2 aircraft automatic 20-mm gun.

ARMY

A. E. REFERENCE NUMBER: 93-3050
A. A. F. DRAWING NUMBER: H42G2391
TYPE DESIGNATION: M1
TECHNICAL ORDER NUMBER: 11-1-16
PRODUCTION STATUS: Under procurement
SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

ORDNANCE


MODEL: M1
ORDNANCE DRAWING NUMBER: D36339
STANDARD NOMENCLATURE LIST NUMBER: A-47
WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-227

SUPPLIED BY

Ordnance Office, War Department.

USED BY

Army.



MAGAZINE, ENDLESS BELT, 37-MM, M6

NAMES: 37-mm endless belt magazine, M6

30 round endless belt magazine

DESCRIPTION: The M-6, 37-mm endless belt magazine is made up of an endless belt of 33 links which hold 30 rounds of ammunition within a horse collar shaped frame. This magazine was designed to fit within the nose contours of the airplane.

The magazine is constructed in two sections to facilitate installation on the cannon. A removable plate provides access to the endless belt for loading operations. The lower ends of the magazine are rigidly fastened to opposite sides of the feed box to provide support for the magazine.

CHARACTERISTICS:

Dimensions	approximately 26 $\frac{1}{2}$ by 18 $\frac{3}{8}$ by 10 $\frac{3}{8}$ inches
Weight	approximately 35 pounds
Capacity	30 rounds of 37-mm ammunition

RELATIONSHIP OF PARTS: Used with:

Type M4 37-mm aircraft gun, A. E. Reference Number 93-1280.

ARMY

A. E. REFERENCE NUMBER: 93-3100
 A. A. F. DRAWING NUMBER: H42G2521
 TYPE DESCRIPTION: M6
 TECHNICAL ORDER
 NUMBER: 11-1-17 and 11-1-18
 PRODUCTION STATUS: Under
 procurement
 SHIPPING DATA: Shipped as a complete
 unit.

NAVY

There is no Navy equivalent for the Army item.

ORDNANCE

MODEL: M6
 ORDNANCE DRAWING
 NUMBER: D36488
 STANDARD NOMENCLATURE
 LIST NUMBER: A-46
 WAR DEPT. TECHNICAL MANUAL
 NUMBER: 9-240

SUPPLIED BY

Ordnance Office, War Department.

USED BY

Army.

**MAGAZINE, ENDLESS
BELT, 37-MM, M7**

NAMES: 37-mm endless belt magazine
30 round magazine

DESCRIPTION: The M7 37-mm endless belt magazine is made up of an endless belt of 34 links, which holds 31 rounds of ammunition within a horse collar shaped frame. The frame of the magazine is not symmetrical about the center line of the gun, since the hinged portion of the top is offset nine degrees to permit the gun to be tilted through this angle. This magazine was designed to fit within the nose contours of the airplane, and was formerly known as experimental model T14.



The magazine is constructed in two sections to facilitate installation on the gun. A removable plate provides access to the endless belt for loading. The lower ends of the magazine are rigidly fastened to opposite sides of the gun feed box to provide support for the magazine.

CHARACTERISTICS:

Dimensions	approximately 26 $\frac{1}{8}$ by 18 $\frac{3}{8}$ by 10 $\frac{1}{8}$ inches
Weight	approximately 35 pounds
Capacity	31 rounds (maximum)

RELATIONSHIP OF PARTS: Used with:

Type M4 37-mm automatic gun, A. E. Reference Number 93-1280.

ARMY

A. E. REFERENCE NUMBER: 93-3110

TYPE DESIGNATION: M7

SUPERSEDED TYPE: T14

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for the Army item.

ORDNANCE

MODEL: M7

COLT'S PATENT FIREARMS MFG. CO.

DRAWING NUMBER: E. S. A-1738

SUPPLIED BY

Ordnance Office, War Department.

USED BY

Army.



GUN ACCESSORIES ARMAMENT—ORDNANCE

MECHANISM, FEED, LEFT HAND, 20-MM, AN-M1


FORMER ARMY TYPE M1 FORMER NAVY TYPE M1

NAMES: 20-mm left hand feed mechanism
Mechanism—feed 20-mm—left hand
20-mm ammunition feeder
20-mm belt feed mechanism
Feed mechanism—20-mm L.H.

DESCRIPTION: The AN-M1 20-mm left hand feed mechanism is designed to pull belted ammunition into the mechanism housing, separate and eject the links, and feed the unbelted rounds of ammunition into the gun.

The feed mechanism derives power for its operation from the recoil of the gun, and from a driving spring which rotates the shaft. This spring is initially wound to a suitable tension and this tension is maintained by the recoil of the gun which actuates a rack and pinion, and ratchet assembly. There is an assembly of sprockets on the shaft, which engages the rounds in the belt and aligns the links.

The front casting is constructed to act as a cam, pushing the rounds to the rear and freeing them of the links.



Parts for the left and right hand feed are of the same shape and dimensions, but differ in that their positions are reversed in the mechanism. Many parts of the two are interchangeable, but the mechanisms as complete units, are not interchangeable.

CHARACTERISTICS:

Dimensions.....	approximately 11 1/4 by 7 1/8 by 7 3/4 inches
Weight.....	approximately 18 1/2 pounds
Operates on gun recoil.....	7 10 inch (minimum)
Rate of feeding.....	approximately 600 rounds per minute

RELATIONSHIP OF PARTS: Used with:

Type M1 automatic 20 mm gun or type AN M2 aircraft automatic 20 mm gun.

ARMY

A. E. REFERENCE NUMBER: 93-3200
A. A. F. DRAWING NUMBER: H41H5144
TYPE DESIGNATION: AN-M1
TECHNICAL ORDER NUMBER: 11-1-16
PRODUCTION STATUS: Under
procurement
SHIPPING DATA: Shipped as a complete
unit with guide and bracket, Ordnance
drawing numbers A25940 and B163511A,
respectively.

NAVY

TYPE DESIGNATION: AN-M1
BUREAU OF ORDNANCE DRAWING
NUMBER: 309302
AVIATION ORDNANCE STOCK LIST
NUMBER: 1-F-121
ORDNANCE PAMPHLET NUMBER: 865
PROCUREMENT STATUS: Under
procurement.

ORDNANCE

MODEL: AN-M1
ORDNANCE DRAWING
NUMBER: D36371
STANDARD NOMENCLATURE LIST
NUMBER: A-47
WAR DEPT. TECHNICAL MANUAL
NUMBER: 9-227

BRITISH


REFERENCE NUMBER: 107G 80

SUPPLIED BY

Ordnance Office, War Department.

USED BY

Army, Navy, and British.



MECHANISM, FEED, RIGHT HAND 20-MM, AN-M1

FORMER ARMY TYPE M1 FORMER NAVY TYPE M1

NAMES: 20-mm Right hand feed mechanism
20-mm Ammunition feeder
20-mm belt feed mechanism
Mechanism—feed 20-mm—right hand
Feed mechanism—20-mm, R.H.

DESCRIPTION: The AN-M1 20-mm right hand feed mechanism is designed to pull belted ammunition into the mechanism housing, separate and eject the links and feed the unbelted rounds of ammunition into the gun.

The feed mechanism derives power for its operation from the recoil of the gun, and from a driving spring which rotates the shaft. This spring is initially wound to a suitable tension and this tension is maintained by the recoil of the gun, which actuates a rack and pinion, and ratchet assembly. There is an assembly of sprockets on the shaft which engages the rounds in the belt and aligns the links.

The front casting is constructed to act as a cam, pushing the rounds to the rear and freeing them of the links.

Parts for the left and right hand feed are of the same shape and dimensions, but differ in that their positions are reversed in the mechanism. Many parts of the two are interchangeable, but the mechanisms as complete units, are not interchangeable.

CHARACTERISTICS:

Dimensions	approximately 11 $\frac{1}{4}$ by 7 $\frac{1}{8}$ by 7 $\frac{3}{4}$ inches
Weight	approximately 18 $\frac{1}{2}$ pounds
Operates on gun recoil	7-10 inch (minimum)
Rate of feeding	approximately 600 rounds per minute

RELATIONSHIP OF PARTS: Used with:

Type M1 automatic 20-mm gun, or type AN-M2 aircraft automatic 20-mm gun.

ARMY

A. E. REFERENCE NUMBER: 93-3205
A. A. F. DRAWING NUMBER: H41H5144
TYPE DESIGNATION: AN-M1
TECHNICAL ORDER NUMBER: 11-1-16
PRODUCTION STATUS: Under procurement

SHIPPING DATA: Shipped as a complete unit with guide and bracket, ordnance drawing numbers A25940 and B163511A, respectively.

NAVY

TYPE DESIGNATION: AN-M1
BUREAU OF ORDNANCE
DRAWING NUMBER: 309301 and 309294
AVIATION ORDNANCE STOCK
LIST NUMBER: 1-F-122
ORDNANCE PAMPHLET
NUMBER: 865
PROCUREMENT STATUS: Under procurement.

ORDNANCE

MODEL: AN-M1
ORDNANCE DRAWING
NUMBER: D36370
STANDARD NOMENCLATURE
LIST NUMBER: A-47
WAR DEPARTMENT TECHNICAL
MANUAL NUMBER: 9-227

BRITISH

REFERENCE NUMBER: 107G 86

SUPPLIED BY


Ordnance Office, War Department.

USED BY

Army, Navy, and British.



GUN MOUNTS ARMAMENT—ORDNANCE



MOUNT, GUN, AIRPLANE, 75-MM, M6

NAMES: 75-mm airplane gun mount
Mount—75-mm gun
Mount assembly—75-mm cannon

Gun mount, 75-mm airplane
75-mm mount

DESCRIPTION: The M6 75-mm gun mount contains the M4 75-mm gun and all attachments required to adapt this gun to aircraft use. The mount is equipped with a combination hydraulic and spring recoil absorbing mechanism and a muzzle cover. This cover opens automatically upon completion of the loading operation. It prevents firing gases from being blown back into the airplane, and facilitates loading the gun during flight. The muzzle cover, however, is not required in all installations.

Firing is accomplished remotely, from the pilot's compartment, by means of a solenoid operated firing mechanism. Ammunition is loaded manually and ejected through an automatic ejector mechanism.

CHARACTERISTICS:

Weight.....	approximately 1297 pounds
Dimensions.....	approximately 140 $\frac{1}{4}$ by 15 $\frac{1}{4}$ by 19 inches
Muzzle velocity.....	1550 to 2050 feet per second

ARMY

A. E. REFERENCE NUMBER: 93-4000

TYPE DESIGNATION: M6

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit consisting of the following major items: 75-mm gun, M4; cradle; recoil mechanism; firing mechanism with solenoid; ejector mechanism; and loading tray. A muzzle cover is supplied when required.

NAVY

There is no Navy equivalent for the Army item.

ORDNANCE

MODEL: M6

ORDNANCE DRAWING NUMBER: 18-9-1 (M6 Mount) and 52-243-1 (M4 Gun)

STANDARD NOMENCLATURE LIST NUMBER: C-47

ROCK ISLAND ARSENAL NOTES NUMBER: R1A-AM-3

SUPPLIED BY

Ordnance Office, War Department

USED BY

Army



TOOL ROLLS ARMAMENT—ORDNANCE



ROLL, TOOL ARMORER'S W/CONTENTS, COMPLETE

ORDNANCE SNL NUMBER A-28

NAMES: Armorer's tool roll complete w contents
Armorer's tool kit

Tool roll
.30 caliber tool roll

DESCRIPTION: The caliber .30 armorer's tool roll consists of a canvas container provided with pockets to accommodate the tools making up this complete kit. These tools are for use by the airplane armorer in cleaning, lubricating, and maintaining the caliber .30 aircraft machine guns. The tools are rolled into a compact carrying unit when not in use. The following tools are included with this roll:

QUANTITY	NAME	ORDNANCE DRAWING OR PIECE MARK NO.
2	Brush, chamber cleaning, M6	B108828
10	Brush, cleaning, cal. .30, M2	C4035
1	Case, cleaning rod, M1	C6573
1	Drift, brass, stght., $\frac{3}{8}$ rd. x 4	TCGX2D
1	Extractor, ruptured cartridge, Mk. IV	C3854
1	Gage, headspace and timing, cal. .30, BMG	A196229
1	Hammer, brass, dble-bell-face, 3 oz.	TAFX2A
1	Oiler, oval, 3 oz., w/cap and chain	C59737
1	Pliers, side-cutting, paral-jaw, 6 in.	THBX1A
1	Punch, center, 4 in.	TCDX1A
1	Punch, drive pin, .03 in. pt.	TCFX2A
1	Punch, drive pin, .05 in. pt.	TCFX2C
1	Punch, drive pin, .08 in. x $\frac{3}{4}$ pt.	TCFX2F
1	Reflector, barrel, cal. .30	B147001
1	Rod, cleaning, jointed, cal. .30, M1	D8237
1	Screw driver, comm., normal duty, 3 in. blade	TGAX1A
1	Stone, sharp., unmounted, artificial, fine, tri., 4 x $\frac{7}{16}$	B147160
1	Tool, carbon removing, cal. .30 M4	C64302
1	Tool, combination, cal. .30, M2	B131314
1	*Tool, release	C3856

*Not carried with original issue. Must be ordered separately.

(Continued on page 321)

**ROLL, TOOL ARMORER'S
W/CONTENTS, COMPLETE***(Continued from page 320)***CHARACTERISTICS:**

Weight approximately 10 pounds
Dimensions approximately 20 by 15 by 3 inches (unrolled)
..... approximately 15 by 6 by 6 inches (rolled)

RELATIONSHIP OF PARTS: Used with:

Type M2 caliber .30 Browning aircraft fixed machine gun, A. E. Reference Number 93-1420.
Type M2 caliber .30 Browning aircraft flexible with fixed back plate machine gun, A. E. Reference Number 93-1440.
Type M2 caliber .30 Browning aircraft flexible machine gun, A. E. Reference Number 93-1520.

ARMY

A. E. REFERENCE NUMBER: 93-6575
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit.

NAVY

AVIATION ORDNANCE STOCK LIST NUMBER: 1-R-5025
ORDNANCE PAMPHLET NUMBER: 714 and 865A
PROCUREMENT STATUS: Under procurement.

ORDNANCE

ORDNANCE DRAWING NUMBER: D1888 (empty roll only)
STANDARD NOMENCLATURE LIST NUMBER: A-28
WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-205 and 9-1205

BRITISH

REFERENCE NUMBER: 108D 89

INTERCHANGEABILITY

The tools supplied in this assembly are interchangeable with tools formerly issued for maintenance of the caliber .30 machine guns in the combination .30 and .50 caliber armorer's tool roll.

SUPPLIED BY


Ordnance Office, War Department

USED BY

Army, Navy, British



TOOL ROLLS ARMAMENT—ORDNANCE



ROLL, TOOL, ARMORER'S W/CONTENTS, COMPLETE

ORDNANCE SNL NUMBER A-38

NAMES: Armorer's tool roll complete w contents
Armorer's tool kit

Tool roll
.50 caliber tool roll

DESCRIPTION: The caliber .50 armorer's tool roll consists of a canvas container provided with pockets to accommodate the tools making up this complete kit. These tools are for use by the airplane armorer in cleaning, lubricating, and maintaining the caliber .50 aircraft machine guns. The tools are rolled into a compact carrying unit when not in use. The following tools are included with this roll:

QUANTITY	NAME	ORDNANCE DRAWING OR PIECE MARK NO.
2	Brush, chamber cleaning, M6	B108828
10	Brush, cleaning, cal. .50, M4	C4037
1	Case, cleaning rod, cal. .50, M15	C64274
1	Drift, brass, stght., $\frac{3}{8}$ rd. x 4	TCGX2D
1	Gage, headspace and timing, cal. .50, BMG	A196228
1	Hammer, brass, dble-bell-face, 3 oz.	TAFX2A
1	*Oiler, filling, oil buffer	B8514
1	Oiler, oval, 3 oz., w cap and chain	C59737
1	Pliers, side-cutting, paral-jaw., 6 in.	THBX1A
1	Punch, center, 4 in.	TCDX1A
1	Punch, drive pin, .03 in. pt.	TCFX2A
1	Punch, drive pin, .05 in. pt.	TCFX2C
1	Punch, drive pin, .08 x $\frac{3}{4}$ pt.	TCFX2F
1	Reflector, barrel, cal. .50	C64255
1	Rod, cleaning, jointed, cal. .50, M7	D35441
1	Screw driver, comm., normal duty, 3 in. blade	TGAX1A
1	Stone, sharp., unmounted, artificial, fine, tri., 4 x $\frac{3}{8}$	B147160
1	*Tool, release	C3856
1	*Wrench, combination, cal. .50, M2	D28242

*Not included in original issue. Must be ordered separately.

(Continued on page 523)

**ROLL, TOOL, ARMORER'S
W/CONTENTS, COMPLETE***(Continued from page 322)***CHARACTERISTICS:**

Weight	approximately 10 pounds
Dimensions	approximately 20 by 15 by 3 inches (unrolled)
	approximately 15 by 6 by 6 inches (rolled)

RELATIONSHIP OF PARTS: Used with:

Type M2 caliber .50 Browning aircraft basic machine gun, A. E. Reference Number 93-1560.

Type M2 caliber .50 Browning aircraft flexible machine gun, A. E. Reference Number 93-1590.

ARMY

A. E. REFERENCE NUMBER: 93-6577

TECHNICAL ORDER NUMBER: 11-1-8

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Shipped as a complete unit.

NAVY

AVIATION ORDNANCE STOCK LIST NUMBER: 1-R-5039

ORDNANCE PAMPHLET NUMBER: 716 and 865A

PROCUREMENT STATUS: Under procurement.

ORDNANCE

ORDNANCE DRAWING NUMBER: D1888 (empty roll only)

STANDARD NOMENCLATURE LIST NUMBER: A-38

WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-225, 9-1225

BRITISH

REFERENCE NUMBER: 108D 90

INTERCHANGEABILITY

The tools supplied in this assembly are interchangeable with tools formerly issued for maintenance of the caliber .50 machine guns in the combination .30 and .50 caliber armorer's tool roll.

SUPPLIED BY

Ordnance Office, War Department.

USED BY

Army, Navy, British



PYROTECHNIC PROJECTORS AND SIGNALS


The use of pyrotechnic signals permits communication between airplanes in flight, and between airplanes and ground stations. Predetermined signals are arranged prior to each flight or troop movement to maintain radio silence and minimize the possibility of interception of messages by the enemy. They are also used as distress or emergency signals. Signalling with pyrotechnics is accomplished by use of pistols or dischargers.

Pyrotechnic pistols may be hand-fired directly from the airplane, or from a mount fastened to the fuselage. Pistols may be breech loaded or muzzle loaded. After each firing of single-loading pistols, the empty cartridge must be removed by hand and the pistol reloaded. Double-action pistols are cocked and fired by a single movement of the trigger.

Multi-barrel dischargers contain several cartridges, which are fired without reloading until all cartridges are used. This type of discharger is operated remotely by means of a cable which, by a pull on the remote controller handle, revolves the barrel, cocks the discharger, and fires the cartridge.

Signals are of two general types, although they vary in size, shape, and construction. Igniting discharges vary in color, intensity, and pattern. One type has an aluminum case with a groove machined around its head. It is identified by markings on the case and top. The other type has a paper and brass case like a shotgun shell, and is identified by markings on the case and top. The following tables list the characteristics of the most common signals supplied by the Ordnance Department for use in airplane pyrotechnic projectors:

SIGNALS, AIRCRAFT: RIMLESS TYPE



NAME	MODEL	IDENTIFICATION TOP
Signal, aircraft white star, parachute	M10	WP
Signal, aircraft red star, parachute	M11	RP
Signal, aircraft red star, cluster	M14	RS
Signal, aircraft white star, blinker, parachute	M15	WB
Signal, aircraft green star, blinker, parachute	M16	GB

AAF Drawing H41DI0594 Covers
Signals M11, M14, M15, and M16.


Continued on page 325

PYROTECHNIC PROJECTORS AND SIGNALS

(Continued from page 324)

SIGNALS, AIRCRAFT: RIMLESS TYPE


(Single and Double Star)



NAME	MODEL	IDENTIFICATION TOP
Signal, aircraft, double star, red-red	AN-M28	RR
Signal, aircraft, double star, yellow-yellow	AN-M29	YY
Signal, aircraft, double star, green-green	AN-M30	GG
Signal, aircraft, double star, red-yellow	AN-M31	RY
Signal, aircraft, double star, red-green	AN-M32	RG
Signal, aircraft, double star, green-yellow	AN-M33	GY
Signal, aircraft, single star, red	AN-M34	R
Signal, aircraft, single star, yellow	AN-M35	Y
Signal, aircraft, single star, green	AN-M36	G

AAF Drawing H42B10457 Covers
Signals AN-M28 to AN-M36.


SIGNALS, AIRCRAFT: CARTRIDGE TYPE



NAME	MODEL	IDENTIFICATION TOP
Signal, aircraft, double star, red-red	AN-M37	red-red
Signal, aircraft, double star, yellow-yellow	AN-M38	yellow-yellow
Signal, aircraft, double star, green-green	AN-M39	green-green
Signal, aircraft, double star, red-yellow	AN-M40	red-yellow
Signal, aircraft, double star, red-green	AN-M41	red-green
Signal, aircraft, double star, yellow-green	AN-M42	yellow-green
Signal, aircraft, single star, red	AN-M43	red
Signal, aircraft, single star, yellow	AN-M44	yellow
Signal, aircraft, single star, green	AN-M45	green


AAF Drawing H42B10457 Covers
Signals AN-M37 to AN-M45.

FLARE, AIRCRAFT PARACHUTE: RIMLESS TYPE



NAME	MODEL
Flare, aircraft parachute	M9
Flare, aircraft parachute	M9A1

AAF Drawing H41D10594 Covers
Flare M9 and M9A1



DISCHARGER, PYROTECHNIC, AN-M5

FORMER ARMY TYPE M5 FORMER NAVY TYPE M5

NAMES: Molin type discharger Pyrotechnic projector
Molin type projector Pyrotechnic discharger
Pyrotechnic discharger AN-M5 and remote controller M2

DESCRIPTION: The AN-M5 pyrotechnic discharger is a double-action, multi-barrel discharger used to project pyrotechnic signals from an airplane in flight. This discharger is fastened to the fuselage, and is operated by means of a cable attached to the remote controller, Ordnance model M2. It is loaded with six signal cartridges, and movement of the remote controller performs the functions of rotating the barrel and cocking and firing the discharger. The signals used are cartridge types AN-M37 to AN-M45 inclusive, or British 1½ inch cartridges.

CHARACTERISTICS:

Dimensions approximately 9 by 7 by 6½ inches
Weight approximately 9½ pounds
Finish glossy black

RELATIONSHIP OF PARTS:

The type AN-M5 pyrotechnic discharger is installed in the airplane fuselage, and is operated by means of a cable connected to the type M2 remote controller.

ARMY

A. E. REFERENCE NUMBER: 93-800

A. A. F. DRAWING NUMBER: H42B10947

TYPE DESIGNATION: AN-M5

PRODUCTION STATUS: Not under procurement for initial installation. Superseded by AN-M8 pyrotechnic pistol.

SHIPPING DATA: The type AN-M5 pyrotechnic discharger, including control cable and the type M2 remote controller, comprise the complete shipping unit.

NAVY

TYPE DESIGNATION: AN-M5

BUREAU OF ORDNANCE DRAWING NUMBER: 333089

AVIATION ORDNANCE STOCK LIST NUMBER: 2-D-180

ORDNANCE CIRCULAR LETTER NUMBER: V 12-42

ORDNANCE PAMPHLET NUMBER: 562 and 865

PROCUREMENT STATUS: Not under procurement for initial installation.

ORDNANCE

MODEL: AN-M5

ORDNANCE DRAWING NUMBER: 42-39

STANDARD NOMENCLATURE LIST NUMBER: B-34

WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-290

SUPPLIED BY

Ordnance Office, War Department

USED BY

Army and Navy



PISTOL, PYROTECHNIC, M2

NAMES: Pyrotechnic pistol
Pyrotechnic signal pistol
Signal pistol


DESCRIPTION: The type M2 pyrotechnic pistol is a double-action single-loading pistol, used to project pyrotechnic signals from an airplane in flight. It is hand-fired from a window or other opening in the fuselage. The signals are rimless barrel types M14, M15, M16, and M28 to M36 inclusive, which permit muzzle-loading. It may also be used to fire M9 and M9A1 parachute flares and M10 and M11 parachute signals.

CHARACTERISTICS:

Dimensions: approximately $7\frac{5}{16}$ by $5\frac{1}{16}$ by $1\frac{13}{16}$ inches
Weight: approximately 3-1/10 pounds

RELATIONSHIP OF PARTS:

For stowage in the airplane, the type M2 pyrotechnic pistol is usually inserted in the type A-1 pyrotechnic pistol holder, A. E. Reference Number 52-2825, which is snap-fastened to the airplane structure.



ARMY

A. E. REFERENCE NUMBER: 93-6000
A. A. F. DRAWING NUMBER: H41D10594
TYPE DESIGNATION: M2
TECHNICAL ORDER NUMBER: 11-15-9
PRODUCTION STATUS: Under procurement.
SHIPPING DATA: Shipped as a complete unit.

NAVY

TYPE DESIGNATION: M2
BUREAU OF ORDNANCE DRAWING NUMBER: 281829
AVIATION ORDNANCE STOCK LIST NUMBER: 2-P-3495
ORDNANCE CIRCULAR LETTER NUMBER: V 11-42
ORDNANCE PAMPHLET NUMBER: 865
AVIATION ORDNANCE PAMPHLET NUMBER: 981-1
TECHNICAL BULLETIN NUMBER: 290-1
PROCUREMENT STATUS: Not under procurement for initial installation. Superseded by type AN-M8 pyrotechnic pistol.

ORDNANCE

MODEL: M2
ORDNANCE DRAWING NUMBER: D10305
STANDARD NOMENCLATURE LIST NUMBER: B-18
WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-290

SUPPLIED BY

Ordnance Office, War Department

USED BY

Army and Navy



PYROTECHNIC PROJECTORS ARMAMENT—ORDNANCE



PISTOL, SIGNAL BRITISH NUMBER 4, MARK 1

NAMES: Signal pistol
Pyrotechnic pistol

British signal pistol

DESCRIPTION: The Number 4, Mark 1 signal pistol is a British pistol used to project pyrotechnic signals from an aircraft while in flight. It is a double-action, signal-loading pistol, fired from a mounting sleeve fastened to the airplane fuselage. The signals used are British $1\frac{1}{2}$ inch cartridges, A. E. Reference Numbers 93-400 to 93-650 inclusive, or Army Ordnance signals, AN-M37 to AN-M45, inclusive. This pistol differs from the Army type AN-M8 in the length of the barrel and general construction; however, both pistols fire the same signals, and are functionally interchangeable when installed in their own mounting.

CHARACTERISTICS:

Weight.....approximately 4 pounds
Dimensions.....approximately 6 by 6 by 2 inches

RELATIONSHIP OF PARTS:

The Number 4, Mark 1 signal pistol is inserted in the Number 2, Mark 1 mounting sleeve for firing. When not in use, the insert hole in the mounting sleeve is covered with the Number 2, Mark 1 aperture disc.

ARMY

A. E. REFERENCE NUMBER: 93-6500

TYPE DESIGNATION: Number 4, Mark 1

PRODUCTION STATUS: Under procurement for installation on airplanes procured for British use.

SHIPPING DATA: Shipped as a complete unit.

NAVY

There is no Navy equivalent for this item.

BRITISH

REFERENCE NUMBER: 7B/810

TYPE DESIGNATION: Number 4, Mark 1

DISC, APERTURE BRITISH NUMBER 2, MARK 1

NAMES: Aperture disc
Cover

Pistol mount cover

(Continued on page 329)



DISC, APERTURE

BRITISH NUMBER 2, MARK 1

(Continued from page 328)

DESCRIPTION: The Number 2, Mark 1 disc aperture is a small circular cover used to seal the opening in the Number 2, Mark 1 mounting sleeve when the signal pistol is removed. The purpose of this disc is to keep out dust and rain, and to seal the fuselage of the airplane against the escape of heat.

CHARACTERISTICS:

Weight approximately $\frac{1}{8}$ pound
Dimensions approximately $2\frac{1}{2}$ by $2\frac{1}{2}$ by 1 inches

RELATIONSHIP OF PARTS: Used with:

The Number 2, Mark 1 mounting sleeve A. E. Reference Number 93-6502

ARMY

A. E. REFERENCE NUMBER: 93-6501

TYPE DESIGNATION: Number 2, Mark 1

PRODUCTION STATUS: Under procurement for installation on airplanes procured for British use.

SHIPPING DATA: Shipped as a complete unit. Usually included in the same carton with the Number 4, Mark 1 signal pistol.

NAVY

There is no Navy equivalent for this item.

BRITISH

REFERENCE NUMBER: 7B 812

TYPE DESIGNATION: Number 2, Mark 1

SLEEVE, MOUNTING

BRITISH NUMBER 2, MARK 1

NAMES: Mounting sleeve
Mount

Pistol mount

DESCRIPTION: The Number 2, Mark 1 mounting sleeve is a cylindrical mount with a slotted insert hole and a four hole mounting flange. This sleeve is installed in the airplane fuselage to provide a mount for holding the Number 4, Mark 1 signal pistol when the latter is being fired.

CHARACTERISTICS:

Weight approximately $\frac{1}{4}$ pound
Dimensions approximately $3\frac{3}{4}$ by $3\frac{3}{4}$ by 2 inches

RELATIONSHIP OF PARTS: Used with:

The Number 2, Mark 1 disc aperture, A. E. Reference Number 93-6501 and the Number 4, Mark 1 signal pistol, A. E. Reference Number 93-6500.

ARMY

A. E. REFERENCE NUMBER: 93-6502

TYPE DESIGNATION: Number 2, Mark 1

PRODUCTION STATUS: Under procurement for installation on airplanes procured for British use.

SHIPPING DATA: Shipped as a complete unit. Usually included in the same carton with the Number 4, Mark 1 signal pistol.


NAVY

There is no Navy equivalent for this item.

BRITISH

REFERENCE NUMBER: 7B 811

TYPE DESIGNATION: Number 2, Mark 1



PISTOL, PYROTECHNIC, AN-M8, W/MOUNT

FORMER ARMY TYPE M8 FORMER NAVY TYPE M8

NAMES: Pyrotechnic pistol
Pyrotechnic signal pistol

Signal pistol
Flare pistol

DESCRIPTION: The type AN-M8 pyrotechnic pistol is a double-action, single-loading pistol, used to project pyrotechnic signals from an airplane in flight. This pistol has a seamless tube barrel hinged to the frame of the handle, which is released by a breech lock to permit breech-loading. The barrel is secured to the type M1 mount by means of a mount latch. The standard signals used are cartridge type, AN-M37 to AN-M45 inclusive, 1½ inch British cartridges, or parachute flares type M9A1. However, provisions is made to permit firing of old style signals M10, M11, M14, M15, M16, and M28 to M36 inclusive. This pistol is normally fired from the type M1 mount, which is fastened to the airplane structure, and acts as a recoil absorbing adapter; however, it may be hand-fired without a mount.

CHARACTERISTICS:

Dimensions.....approximately 10¼ by 8¾ by 3¾ inches
Weight.....approximately 3-2 5 pounds

RELATIONSHIP OF PARTS:

The type AN-M8 pyrotechnic pistol is inserted in the type M1 mount for firing.

ARMY

A. E. REFERENCE NUMBER: 93-6100

A. A. F. DRAWING NUMBER: H42B10666

TYPE DESIGNATION: AN-M8

TECHNICAL ORDER NUMBER: 11-15-1

PRODUCTION STATUS: Under procurement.

SHIPPING DATA: Complete shipping unit is composed of type AN-M8 pyrotechnic pistol and type M1 mount with cover.

NAVY

TYPE DESIGNATION: AN-M8

BUREAU OF ORDNANCE DRAWING NUMBER: 247642

AVIATION ORDNANCE STOCK LIST NUMBER: 2-P-3499

ORDNANCE CIRCULAR LETTER NUMBER: V 35-42

ORDNANCE PAMPHLET NUMBER: 865

PROCUREMENT STATUS: Under procurement.

ORDNANCE

MODEL: AN-M8

ORDNANCE DRAWING NUMBER: 42-44

STANDARD NOMENCLATURE LIST NUMBER: B-33

WAR DEPARTMENT TECHNICAL MANUAL NUMBER: 9-290

SUPPLIED BY

Ordnance Office, War Department

USED BY

Army and Navy

(RESTRICTED)



(RESTRICTED)



(RESTRICTED)

